State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-17-22
Relating to Certification of New Motor Vehicles

AMERICAN MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 39018, 39600, 39601, 43101, and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That American Motors Corporation exhaust emission control systems for 1976 model-year passenger cars are certified for the engine family described below:

Engine Family: I-2C
Engine: 258 CID
Transmission: 3 speed automatic
Exhaust Emission Control Systems: Air Injection, Exhaust Gas Recirculation, Oxidation Catalyst

Model: Pacer

BE IT FURTHER RESOLVED: That this certification is contingent upon American Motors Corporation affixing a permanent catalyst overheat warning label on the driver's sun-visor of all catalyst-equipped vehicles. This label must be approved by the Executive Officer.

BE IT FURTHER RESOLVED: That this certification is also contingent upon American Motors Corporation listing in the owner's manual the operating cautions associated with a catalyst-equipped vehicle. This listing must be approved by the Executive Officer.

The following are the recommended values to be listed on the window decal required by California Assembly-Line Test Procedures for 1976 model vehicles:

Engine Family	Hydrocarbons Grams per Mile	Carbon Monoxide Grams per Mile	Nitrogen Oxides Grams per Mile
I-2C	0.4	7.3	1.6

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 3 day of March, 1976.

G. C. Hass

G. C. Hass, Chief
Division of Vehicle Emissions Control

AIR RESOURCES BOARD
SUPPLEMENTAL INFORMATION
1976 MODEL YEAR

[x] PASSENGER CARS [ ] LIGHT-DUTY TRUCKS

MANUFACTURER: AMERICAN MOTORS CORPORATION

EXECUTIVE ORDER NO. A- 17-22

Engine Family	Vehicle Models (If coded see attachment)	Engine CID	Trans.	Inertia Weight	Distributor Type	Distributor Mfgr. Part No.	Fuel System Type	Fuel System Mfgr. Part No.	Emission Control System Type	Emission Control System OC TR Part No. Service*	Emission Control System EGR Part No. Service*	Tune-up Specifications Idle RPM	Tune-up Specifications Basic Timing	Tune-up Specifications Idle Mixture
I-2C	Pacer	258	A-3 3.08 axle ratio	3500	EI, C,V	Prestolite IDJ-4002-E which is 3227331	1-2V	Carter 8067	AI EGR OC	3224569 (AC 6498929)	Rochester 17050471, Red dot.	700 ± 100 in "drive"	8° ± 2° BTDC @ 500 RPM with transmission in "drive", distributor vacuum line disconnected.	25 RPM lean drop

Abbreviations:

Distributor
C - Centrifugal Advance
V - Vacuum Advance
VR - Vacuum Retard
HEI- High Energy Ignition
EI - Electronic Ignition

Exhaust Emission Control System
AI - Air Injection
EFI- Electronic Fuel Injection
EGR- Exhaust Gas Recirculation
EM - Engine Modifications
CAI- Catalyst Air Injection
EFE- Early Fuel Evaporation
FI - Fuel Injection
OC - Oxidation Catalyst
RC - Reduction Catalyst
TR - Thermal Reactor
ESAC-Electronic Spark Advance Control
PAI -Pulse Air Injection

*Service
I - Inspect, repair/replace as needed
R - Replace