

Ambient Air Quality Standards

Pollutant	Averaging Time	California Standards ¹		Federal Standards ²			
		Concentration ³	Method ⁴	Primary ^{3,5}	Secondary ^{3,6}	Method ⁷	
Ozone (O ₃)	1 Hour	0.09 ppm (180 µg/m ³)	Ultraviolet Photometry	0.12 ppm (235 µg/m ³) ⁸	Same as Primary Standard	Ethylene Chemiluminescence	
	8 Hour	—		0.08 ppm (157 µg/m ³)			
Respirable Particulate Matter (PM ₁₀)	Annual Geometric Mean	30 µg/m ³	Size Selective Inlet Sampler ARB Method P (8/22/85)	—	Same as Primary Standard	Inertial Separation and Gravimetric Analysis	
	24 Hour	50 µg/m ³		150 µg/m ³			
	Annual Arithmetic Mean	—		50 µg/m ³			
Fine Particulate Matter (PM _{2.5})	24 Hour	No Separate State Standard		65 µg/m ³	Same as Primary Standard	Inertial Separation and Gravimetric Analysis	
	Annual Arithmetic Mean			15 µg/m ³			
Carbon Monoxide (CO)	8 Hour	9.0 ppm (10 mg/m ³)	Non-dispersive Infrared Photometry (NDIR)	9 ppm (10 mg/m ³)	None	Non-dispersive Infrared Photometry (NDIR)	
	1 Hour	20 ppm (23 mg/m ³)		35 ppm (40 mg/m ³)			
	8 Hour (Lake Tahoe)	6 ppm (7 mg/m ³)		—			
Nitrogen Dioxide (NO ₂)	Annual Arithmetic Mean	—	Gas Phase Chemiluminescence	0.053 ppm (100 µg/m ³)	Same as Primary Standard	Gas Phase Chemiluminescence	
	1 Hour	0.25 ppm (470 µg/m ³)		—			
Lead	30 days average	1.5 µg/m ³	AIHL Method 54 (12/74) Atomic Absorption	—	Same as Primary Standard	High Volume Sampler and Atomic Absorption	
	Calendar Quarter	—		1.5 µg/m ³			
Sulfur Dioxide (SO ₂)	Annual Arithmetic Mean	—	Fluorescence	0.030 ppm (80 µg/m ³)	—	Pararosaniline	
	24 Hour	0.04 ppm (105 µg/m ³)		0.14 ppm (365 µg/m ³)			
	3 Hour	—		—			0.5 ppm (1300 µg/m ³)
	1 Hour	0.25 ppm (655 µg/m ³)		—			—
Visibility Reducing Particles	8 Hour (10 am to 6 pm, PST)	In sufficient amount to produce an extinction coefficient of 0.23 per kilometer—visibility of ten miles or more (0.07—30 miles or more for Lake Tahoe) due to particles when the relative humidity is less than 70 percent. Method: ARB Method V (8/18/89).		No Federal Standards			
Sulfates	24 Hour	25 µg/m ³	Turbidimetric Barium Sulfate-AIHL Method 61 (2/76)				
Hydrogen Sulfide	1 Hour	0.03 ppm (42 µg/m ³)	Cadmium Hydroxide STRactan				

See footnotes on next page...

1. California standards for ozone, carbon monoxide (except Lake Tahoe), sulfur dioxide (1 and 24 hour), nitrogen dioxide, suspended particulate matter—PM₁₀, and visibility reducing particles, are values that are not to be exceeded. All others are not to be equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the California Code of Regulations.

In addition, Section 70200.5 lists vinyl chloride (chloroethene) under “Ambient Air Quality Standards for Hazardous Substances.” In 1978, the California Air Resources Board (ARB) adopted the vinyl chloride standard of 0.010 ppm (26 µg/m³) averaged over a 24-hour period and measured by gas chromatography. The standard notes that vinyl chloride is a “known human and animal carcinogen” and that “low-level effects are undefined, but are potentially serious. Level is not a threshold level and does not necessarily protect against harm. Level specified is lowest level at which violation can be reliably detected by the method specified. Ambient concentrations at or above the standard constitute an endangerment to the health of the public.”

In 1990, the ARB identified vinyl chloride as a Toxic Air Contaminant and determined that there was not sufficient available scientific evidence to support the identification of a threshold exposure level. This action allows the implementation of health-protective control measures at levels below the 0.010 ppm ambient concentration specified in the 1978 standard.

2. National standards (other than ozone, particulate matter, and those based on annual averages or annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest eight hour concentration in a year, averaged over three years, is equal to or less than the standard. For PM₁₀, the 24 hour standard is attained when 99 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. For PM_{2.5}, the 24 hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact U.S. EPA for further clarification and current federal policies.
3. Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of 25°C and a reference pressure of 760 mm of mercury. Most measurements of air quality are to be corrected to a reference temperature of 25°C and a reference pressure of 760 mm of mercury (1,013.2 millibar); ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
4. Any equivalent procedure which can be shown to the satisfaction of the ARB to give equivalent results at or near the level of the air quality standard may be used.
5. National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.
6. National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
7. Reference method as described by the EPA. An “equivalent method” of measurement may be used but must have a “consistent relationship to the reference method” and must be approved by the EPA.
8. New federal 8-hour ozone and fine particulate matter standards were promulgated by U.S. EPA on July 18, 1997. The federal 1-hour ozone standard continues to apply in areas that violated the standard. Contact U.S. EPA for further clarification and current federal policies.