| California Environmental Protection Agency AIR RESOURCES BOARD | FERRARI S.p.A. | EXECUTIVE ORDER A-040-0063 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles |
|---|---|---|

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:**
That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | TEST GROUP | VEHICLE TYPE | EXHAUST EMISSION STANDARD CATEGORY | USEFUL LIFE (miles) | | INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use) | | FUEL TYPE |
|---|---|---|---|---|---|---|---|---|
| | | | | EXH / ORVR | EVAP | EXH | EVAP | |
| 2005 | 5FEXV05.7LEV | Passenger Car | Low Emission Vehicle (LEV) | 100K | 100K | * | * | Gasoline (Indolene) |

| No. | ECS & SPECIAL FEATURES | EVAPORATIVE FAMILY (EVAF) | DISPLACEMENT (L) |
|---|---|---|---|
| 1 | 4WU-TWC,2TWC, 4HO2S(2), SFI, AIR, OBD(P) | 5FEXR0203575 | 5.7 |
| * | * | * | |
| * | * | * | |
| * | * | * | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

**BE IT FURTHER RESOLVED:**
That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50$^0$ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

**BE IT FURTHER RESOLVED:**
That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 26TH day of August 2004.

Raphael Susnowitz
for Allen Lyons, Chief
Mobile Source Operations Division

| California Environmental Protection Agency AIR RESOURCES BOARD | FERRARI S.p.A. | EXECUTIVE ORDER A-040-0063 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles |
|---|---|---|

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure

| NMOG FLEET AVERAGE [g/mi] | | NMOG @ RAF=* CH4 RAF = * | | NMOG or NMHC STD [g/mi] | CO [g/mi] | | NOx [g/mi] | | HCHO [mg/mi] | | PM [g/mi] | | Hwy NOx [g/mi] | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CERT | STD | NMOG CERT [g/mi] | NMHC CERT [g/mi] | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD |
| 0.075 | 0.075 | | | | | | | | | | | | | |
| [redacted] | @ 50K | 0.067 | * | 0.075 | 0.2 | 3.4 | 0.1 | 0.2 | 1.0 | 15. | * | * | 0.1 | 0.3 |
| [redacted] | @ UL | 0.086 | * | 0.090 | 0.3 | 4.2 | 0.1 | 0.3 | 1.0 | 18. | * | * | 0.1 | 0.4 |
| [redacted] | @ 50°F & 4K | 0.070 | * | 0.150 | 0.8 | 3.4 | 0.03 | 0.2 | 1.0 | 30. | * | * | * | * |

| CO [g/mi] @ 20°F & 50K | | [redacted] | NMHC+NOx [g/mi] (composite) | | CO [g/mi] (composite) | | NMHC+NOx [g/mi] [US06] | | CO [g/mi] [US06] | | NMHC+NOx [g/mi] [SC03] | | CO [g/mi] [SC03] | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD |
| CERT | 4.7 | SFTP @ 4000 miles | * | * | * | * | 0.05 | 0.14 | 0.8 | 8.0 | 0.05 | 0.20 | 0.02 | 2.7 |
| STD | 10.0 | SFTP @ * miles | * | * | * | * | * | * | * | * | * | * | * | * |

| Evaporative Family | 3-Days Diurnal + Hot Soak (grams/test) @ UL | | 2-Days Diurnal + Hot Soak (grams/test) @ UL | | Running Loss (grams/mile) @ UL | | On-Board Refueling Vapor Recovery (grams/gallon) @ UL | |
|---|---|---|---|---|---|---|---|---|
| | CERT | STD | CERT | STD | CERT | STD | CERT | STD |
| 5FEXR0203575 | 0.9 | 2.0 | 0.7 | 2.5 | 0.002 | 0.05 | 0.12 | 0.20 |
| * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * |

* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; DGI=direct gasoline fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel;

## 2005 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE | MODEL | EVAPORATIVE FAMILY | ECS NO. | ENGINE SIZE (L) | INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use) | | PHASE-IN STD. | OBD II |
|---|---|---|---|---|---|---|---|---|
| | | | | | EXH | EVAP | | |
| FERRARI | 612 Scaglietti | 5FEXR0203575 | 1 | 5.7 | * | * | SFTP | Partial |
| FERRARI | 575 M Maranello | 5FEXR0203575 | 1 | 5.7 | * | * | SFTP | Partial |