

[Note: Amendments are shown in underline to indicate additions and ~~strikeout~~ to indicate deletions.]

## **Proposed Amendments to the Regulation for Reducing the Ozone Formed from Aerosol Coating Product Emissions**

### **SUBCHAPTER 8.5. CONSUMER PRODUCTS**

**Amend title 17, California Code of Regulations, sections 94520-94528 to read as follows:**

#### **Article 3. Aerosol Coating Products**

##### **§ 94520.     **Applicability.****

This article shall apply to any person who sells, supplies, offers for sale, applies, or manufactures any aerosol coating products for use in the ~~s~~State of California, except as provided in section 94523. This means that any aerosol coating product sold, supplied, offered for sale, applied, or manufactured in California must comply with the provisions of this article unless specifically exempted as set forth in section 94523.

NOTE: Authority cited: Sections 39600, 39601 and 41712, Health and Safety Code.  
Reference: Sections 39002, 39600, 40000 and 41712, Health and Safety Code.

##### **§ 94521.     **Definitions.****

- (a) For the purpose of this article, the following definitions apply:
- (1) “Adhesive” means a product used to bond one surface to another by attachment.
  - (2) “Aerosol Coating Product” means a pressurized coating product containing pigments or resins that dispenses product ingredients by means of a propellant, and is packaged in a disposable can for hand-held application, or for use in specialized equipment for ground traffic/marketing applications.
  - (3) ~~“Anti-Static Spray” means a product used to prevent or inhibit the accumulation of static electricity.~~ “Anti-Static Product” means a product that is designed and labeled to eliminate, prevent, or inhibit the accumulation of static electricity.
  - (4) “Art Fixative or Sealant” means a clear ~~coating~~ “Aerosol Coating Product,” including art varnish, workable art fixative, and ceramic coating, which is designed and labeled exclusively for application to paintings, pencil, chalk, or pastel drawings, ceramic art pieces, or other closely related art uses, in order to

provide a final protective coating or to fix preliminary stages of artwork while providing a workable surface for subsequent revisions.

- (5) “ASTM” means ~~the American Society for Testing and Materials.~~ ASTM International.
- (6) “Auto Body Primer” means an ~~automotive primer or primer surfacer coating~~ “Aerosol Coating Product” designed and labeled exclusively to be applied to a vehicle body substrate ~~for the purposes of~~ to provide corrosion resistance ~~and or~~ to building a repair area to a condition in which, after drying, it can be sanded to a smooth surface.
- (7) “Automotive Bumper and Trim Product” means ~~a product~~ an “Aerosol Coating Product,” including adhesion promoters and chip sealants, designed and labeled exclusively to repair and refinish automotive bumpers and automotive plastic trim parts.
- (8) ~~“Automotive Underbody Coating” means flexible coating which contains asphalt or rubber and is designed and labeled exclusively for use on the underbody of motor vehicles to resist rust, abrasion and vibration, and to deaden sound.~~
- (9) “Aviation Propeller Coating” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively to provide abrasion resistance and corrosion protection for aircraft propellers.
- (10) “Aviation or Marine Primer” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively to meet federal specification TT-P-1757.
- (11) “Base Reactive Organic Gas Mixture” (Base ROG Mixture) means the mixture of reactive organic gases utilized in deriving the MIR scale.
- (12) “Belt Dressing” means a product applied ~~on auto~~ to vehicular fan belts, water pump belting, power transmission belting, ~~and or~~ and or industrial and farm machinery belting to prevent slipping, ~~and or~~ and or to extend belt life.
- (13) “Cleaner” means a product designed and labeled primarily to remove soil or other contaminants from surfaces.
- (14) “Clear Coating” means ~~a coating~~ an “Aerosol Coating Product” which is colorless, containing resins but no pigments except flattening agents, and is designed ~~and or~~ and or labeled to form a transparent or translucent solid film.
- (15) “Coating Solids” means the nonvolatile portion of an ~~a~~ “Aerosol eCoating pProduct,” consisting of the film forming ingredients, including pigments and resins.

- (16) “Commercial Application” means the use of aerosol coating products in the production of goods, or the providing of services for profit, including touch-up and repair.
- (17) “Corrosion Resistant Brass, Bronze, or Copper Coating” means a clear coating “Aerosol Coating Product” designed and labeled exclusively to prevent tarnish and corrosion of uncoated brass, bronze, or copper metal surfaces.
- (18) “Distributor” means any person to whom an ~~a~~ “Aerosol Coating Product” is sold or supplied for the purposes of resale or distribution in commerce, except that manufacturers, retailers, and consumers are not distributors.
- (19) “Dye” means a product containing no resins which is used to color a surface or object without building a film.
- (20) “Electrical/~~Electronic/Conformal~~ Coating” means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively ~~as such, which is used exclusively to coat electrical or electronic components or devices such as wire windings on electric motors to provide insulation and or protection from corrosion, chemicals, dust, debris, handling, or temperature extremes.~~
- (21) “Enamel” means a coating which cures by chemical cross-linking of its base resin and is not resoluble in its original solvent.
- (22) “Engine Paint” means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively to coat engines and their components.
- ~~(XX) “Exact Match Finish” means a coating which meets all of the following criteria: (A) the product is labeled with the manufacturer’s name for which they were formulated; and (B) the product is labeled with one of the following: (1.) the original equipment manufacturer’s (O.E.M.) color code number; (2.) the color name; or (3.) other designation identifying the specific O.E.M. color to the purchaser.~~
- (23) “Exact Match Finish, Engine Paint” means ~~a coating an~~ “Aerosol Coating Product” which meets ~~the definition of “Exact Match Finish” and all of the following criteria: (A) the product is designed and labeled exclusively to exactly match the color of an original, factory-applied engine paint; ; (B) the product is labeled with the manufacturer’s name for which they were formulated; and (C) the product is labeled with one of the following: (1.) the original equipment manufacturer’s (O.E.M.) color code number; (2.) the color name; or (3.) other designation identifying the specific O.E.M. color to the purchaser.~~
- (24) “Exact Match Finish, Automotive” means ~~a topcoat an~~ “Aerosol Coating Product” which meets the definition of “Exact Match Finish” and all of the following criteria:

- ~~(A) the product is designed and labeled exclusively to exactly match the color of an original, factory-applied automotive coating during the touch-up of automobile finishes; (B) the product is labeled with the manufacturer's name for which they were formulated; and (C) the product is labeled with one of the following: (1.) the original equipment manufacturer's (O.E.M.) color code number; (2.) the color name; or (3.) other designation identifying the specific O.E.M. color to the purchaser. Notwithstanding the foregoing, automotive clear coatings designed and labeled exclusively for use over automotive exact match finishes to replicate the original factory applied finish shall be considered to be automotive exact match finishes.~~
- (25) “Exact Match Finish, Industrial” means a coating an “Aerosol Coating Product” which meets the definition of “Exact Match Finish” and all of the following criteria: ~~(A) the product is designed and labeled exclusively to exactly match the color of an original, factory-applied industrial coating during the touch-up of manufactured products; (B) the product is labeled with the manufacturer's name for which they were formulated; and (C) the product is labeled with one of the following: (1.) the original equipment manufacturer's (O.E.M.) color code number; (2.) the color name; or (3.) other designation identifying the specific O.E.M. color to the purchaser.~~
- (26) “Executive Officer” means the Executive Officer of the Air Resources Board, or her or his delegate.
- (xx) “Extender” means an ingredient added to an “Aerosol Coating Product” to increase coverage or enhance durability.
- (27) “Flat Paint Products” means a coating an “Aerosol Coating Product” which, when fully dry, registers specular gloss less than or equal to 15 on an 85° gloss meter, or less than or equal to 5 on a 60° gloss meter, or which is labeled as a flat coating.
- (28) “Flatting Agent” means a compound added to a coating to reduce the gloss of the coating without adding color to the coating.
- (xx) “Flexible Coating” means an “Aerosol Coating Product” designed and labeled exclusively to dampen noise, reduce vibration, provide resistance to dust, chemicals, corrosion, chipping and abrasion, impart a protective coating to prevent water intrusion and rust formation, insulate against extreme temperatures, or otherwise to provide a flexible coating to protect surfaces. “Flexible Coating” includes, but is not limited to, rubberized, mastic, or asphaltic products. “Flexible Coating” does not include “Undercoating” as defined in section 94508(a).
- (29) “Floral Coating Spray” means a coating an “Aerosol Coating Product” designed and labeled exclusively for use on fresh flowers, dried flowers, or other items in a

floral arrangement for the purposes of coloring, preserving or protecting their appearance.

- (30) “Fluorescent Coating” means ~~a coating~~ an “Aerosol Coating Product” labeled as ~~such a fluorescent coating~~, which converts absorbed incident light energy into emitted light of a different hue.
- (xx) “Fragrance” means a substance or complex mixture of aroma chemicals, natural essential oils, and other functional components with a combined vapor pressure not in excess of 2 mm of Hg at 20°C, the sole purpose of which is to impart an odor or scent, or to counteract a malodor.
- (31) “Glass Coating” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively for use on glass or other transparent material to create a soft, translucent light effect, or to create a tinted or darkened color while retaining transparency.
- (32) “Ground Traffic/Marking Coating” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively to be applied to dirt, gravel, grass, concrete, asphalt, warehouse floors, or parking lots. ~~Such Ground traffic/markings~~ coatings must be in a container equipped with a valve and sprayhead designed to direct the spray toward the surface when the can is held in an inverted vertical position.
- (33) “High Temperature Coating” means a high performance “Aerosol Coating Product” designed and labeled exclusively for application to substrates exposed continuously or intermittently to temperatures above 204°C (400°F) coating, excluding engine paint, which is designed and labeled exclusively for use on substrates which will, in normal use, be subjected to temperatures in excess of 400°F. “High Temperature Coating” does not include “Engine Paint.”
- (34) “Hobby/Model/Craft Coating” means ~~a coating~~ an “Aerosol Coating Product” which is designed and labeled exclusively for hobby applications and is sold in aerosol containers of 6 ounces by weight or less.
- (35) “Ingredient” means a component of an ~~“aerosol coating product.”~~
- (36) “Ink” means a fluid or viscous substance used in the printing industry to produce letters, symbols or illustrations, but not to coat an entire surface.
- (xx) “Impurity” means an individual chemical compound present in a raw material which is incorporated into the final aerosol coating product formulation and the compound is present in the raw material below the following amounts:
- (A) any carcinogen, as defined in 29 Code of Federal Regulations, section 1910.1200(d)(4), must be present in an amount less than 0.1 percent by weight.

(B) any other compound must be present in an amount less than 1.0 percent by weight.

- (37) “Lacquer” means a thermoplastic film-forming material dissolved in organic solvent, which dries primarily by solvent evaporation, and is resoluble in its original solvent.
- (38) “Layout Fluid” (or toolmaker's ink) means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively to be sprayed on metal, glass or plastic, to provide a glare-free surface on which to scribe designs, patterns or engineering guide lines prior to shaping the piece.
- (39) “Leather ~~p~~Preservative or ~~e~~Cleaner” means a leather treatment material applied exclusively to clean or preserve leather.
- (40) “Lubricant” means a ~~product substance such as oil, petroleum distillates, grease, graphite, silicone, lithium, etc. that is used to~~ reduces friction, heat, noise, or wear when applied between surfaces between moving parts, or loosens rusted or immovable parts of mechanisms.
- (41) “Manufacturer” means any person who imports, manufactures, assembles, produces, packages, repackages, or relabels a consumer product.
- (42) “Marine Spar Varnish” means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively to provide a protective sealant for marine wood products.
- (43) “Maskant” means ~~a coating an~~ “Aerosol Coating Product” applied directly to a component to protect surface areas when chemical milling, anodizing, aging, bonding, plating, etching, or performing other chemical operations on the surface of the component.
- (44) “Maximum Incremental Reactivity” (MIR) means the maximum change in weight of ozone formed by adding a compound to the “Base ROG Mixture” per weight of compound added, expressed to hundredths of a gram (g O<sub>3</sub>/g ROC). MIR values for individual compounds and hydrocarbon solvents are specified in sections 94700 and 94701, Title 17, California Code of Regulations.
- (45) “Metallic Coating” means ~~a topcoat~~ an “Aerosol Coating Product” which contains at least 0.5 percent by weight elemental metallic pigment in the formulation, including propellant, and is labeled as “metallic<sub>1</sub>”; or with the name of a specific metallic finish such as “gold<sub>1</sub>”; “silver<sub>1</sub>”; or “bronze.”
- (46) “Mold Release” means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively to be applied to molds to prevent products from sticking to the surfaces of the mold.

- (47) “Multi-Component Kit” means ~~a spray paint~~ an “Aerosol Coating Product” system which requires the application of more than one component (e.g. foundation coat and top coat), where both components are sold together in one package.
- (48) “Nonflat Paint Product” means ~~a coating~~ an “Aerosol Coating Product” which, when fully dry, registers a specular gloss greater than 15 on an 85° gloss meter or greater than 5 five on a 60° gloss meter, or which is labeled as a nonflat coating.
- (49) “Ozone” means a colorless gas with a pungent odor, having the molecular form O<sub>3</sub>.
- (50) ~~“Percent VOC By Weight” means the ratio of the weight of VOC to the total weight of the product contents expressed as follows:~~

$$\text{Percent VOC By Weight} = (W_{\text{VOC}} / W_{\text{total}}) \times 100$$

Where:

- (A) ~~for products containing no water and no volatile compounds exempt from the definition of VOC: W<sub>VOC</sub> = the weight of volatile compounds;~~
- (B) ~~for products containing water or exempt compounds: W<sub>VOC</sub> = the weight of volatile compounds, less water, and less compounds exempt from the VOC definition in this section 94521; and~~
- (C) ~~W<sub>total</sub> = the total weight of the product contents.~~
- (51) “Photograph Coating” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively to be applied to finished photographs to allow corrective retouching, protection of the image, changes in gloss level, or to cover fingerprints.
- (xx) “Pigment” means a finely ground natural or synthetic insoluble material added to a coating to provide color, opacity, or corrosion inhibition to a coating film.
- (xx) “Plasticizer” means an ingredient added to the resin to aid in flexibility.
- (52) “Pleasure Craft” means privately owned vessels used for noncommercial purposes.
- (53) “Pleasure Craft Finish Primer/Surfacer/Undercoater” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively to be applied prior to the application of a ~~p~~“Pleasure eCraft tTopcoat” for the purpose of corrosion resistance ~~and~~ or adhesion of the topcoat, and which promotes a uniform surface by filling in surface imperfections.

- (54) “Pleasure Craft Topcoat” means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively to be applied to a ~~“Pleasure eCraft”~~ as a final coat above the waterline and below the waterline when stored out of water. ~~This category~~ “Pleasure Craft Topcoat” does not include ~~“Clear eCoatings.”~~
- (55) “Polyolefin Adhesion Promoter” means ~~a coating an~~ “Aerosol Coating Product” designed and labeled exclusively to be applied to a polyolefin or polyolefin copolymer surface of ~~automotive~~ vehicular body parts, bumpers, or trim parts to provide a bond between the surface and subsequent coats.
- (56) “Primer” means ~~a coating an~~ “Aerosol Coating Product” labeled as ~~such a primer~~, which is designed to be applied to a surface to provide a bond between that surface and subsequent coats.
- (57) “Product-Weighted MIR” (PWMIR) means the sum of all weighted-MIR for all ingredients in ~~an~~ “Aerosol Coating Product” ~~subject to this article~~. The PWMIR is the total product reactivity expressed to hundredths of a gram of ozone formed per gram of product (excluding container and packaging) and calculated according to the following equations:
- (a) Weighted MIR (Wtd-MIR) ingredient = MIR x Weight fraction ingredient,  
and,
- (b) Product Weighted MIR = (Wtd-MIR)<sub>1</sub> + (Wtd-MIR)<sub>2</sub> + ... + (Wtd-MIR)<sub>n</sub>  
where,
- MIR = ingredient MIR, as specified in section 94522(h);
- Wtd-MIR = MIR of each ingredient in a product multiplied by the weight fraction of that ingredient, as shown in (a);
- 1,2,3,...,n = each ingredient in the product up to the total n ingredients in the product.
- (58) “Propellant” means a liquefied or compressed gas that is used in whole or in part, ~~such as a cosolvent~~, to expel a liquid or any other material from the same self-pressurized container or from a separate container.
- (59) “Reactivity Limit” means the maximum ozone forming potential of ingredients ~~“product-weighted MIR” product~~ (excluding container and packaging) allowed in an aerosol coating product ~~that is subject to the limits specified in section 94522(a)(3) for a specific category~~, expressed as g O<sub>3</sub>/g product.

- (60) “Reactive Organic Compound (ROC)” means any compound containing at least one atom of carbon and that has the potential, once emitted, to contribute to ozone formation in the troposphere.
- ~~(xx) “Resin” means the film-forming ingredients in an “Aerosol Coating Product.”  
Examples of resin ingredients include acrylic, alkyd, enamel, epoxy, polyurethane, polyvinyl chloride, silicone, and styrene.~~
- (61) “Responsible Party” means the company, firm, or establishment which is listed on the product’s label. If the label lists two companies, firms or establishments, the responsible party is the party which the product was “manufactured for” or “distributed by”, as noted on the label.
- (62) “Retailer” means any person who sells, supplies, or offers aerosol coating products for sale directly to consumers.
- (63) “Retail Outlet” means any establishment where consumer products are sold, supplied, or offered for sale, directly to consumers.
- (64) “Rust Converter” means ~~a product~~ an “Aerosol Coating Product” designed and labeled exclusively to convert rust to an inert material and which contains a minimum acid content of 0.5 percent by weight, and a maximum coating solids content of 0.5 percent by weight.
- (65) “Shellac Sealer” means a clear or pigmented ~~coating~~ “Aerosol Coating Product” formulated solely with the resinous secretion of the lac beetle (*Laccifer lacca*), thinned with alcohol, and formulated to dry by evaporation without a chemical reaction.
- (66) “Slip-Resistant/Non-Slip Grip Coating” means ~~a coating~~ an “Aerosol Coating Product” (A) designed and labeled exclusively as such a slip-resistant coating, which is formulated with synthetic grit and used as a safety coating or (B) labeled exclusively as a non-slip grip coating designed to reduce or prevent slipping.
- (67) “~~Spatter Coating/Multicolor/Stucco Coating~~” means ~~a coating~~ an “Aerosol Coating Product” (A) labeled exclusively as such a spatter/multicolor coating wherein to provide spots, globules, or spatters of contrasting colors on or within the surface of a contrasting or similar background or (B) labeled exclusively as a stucco coating to apply to a plaster finish typically made from a mixture of Portland cement, sand, and lime.
- ~~(68) “Stain” means a coating which is designed and labeled to change the color of a surface but not conceal the surface.~~
- ~~(xx) “Uniform Finish Coating” means an “Aerosol Coating Product” designed and labeled exclusively for application to the area adjacent to a spot repair for the~~

purpose of blending the spot repair's color or clear coating to match the appearance of an adjacent area's existing coating. For the purpose of this article, "Spot Repair" means repair of an area of less than 1 square foot (929 square centimeters). "Uniform Finish Coating" includes products labeled as Edge Blenders.

- (69) "Upper-Limit Kinetic Reactivity" (ULKR) means the maximum percentage of the emitted ROC which has reacted. For this article, the ULKR is one hundred percent and is used to calculate the ULMIR.
- (70) "Upper-Limit Mechanistic Reactivity" (ULMR) means the maximum gram(s) of ozone formed per gram of ~~reactive organic compound (ROC)~~-reacting. The ULMR is used to calculate the ULMIR.
- (71) "Upper-Limit MIR" (ULMIR) means the upper-limit kinetic reactivity (ULKR) multiplied by the upper-limit mechanistic reactivity (ULMR), as calculated using the following equation:

$$\text{ULMIR} = \text{Upper Limit KR} \times \text{Upper Limit MR.}$$

The units for ULMIR are g O<sub>3</sub>/g ROC.

- (72) "~~Vinyl/Fabric/Leather/Plastic/Polycarbonate Coating~~" means ~~a coating an~~ "Aerosol Coating Product" (A) designed and labeled exclusively to coat vinyl, fabric, leather, plastic, or polycarbonate substrates or (B) designed and labeled exclusively to repel water from fabric or leather substrates. "Vinyl/Fabric/Leather/Plastic/Polycarbonate Coating" does not include "Fabric Protectant" as defined in section 94508(a).

- ~~(73) "Volatile Organic Compound (VOC)" means any compound containing at least one atom of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, and excluding the following:~~

- ~~(A) methane,  
methylene chloride (dichloromethane),  
1,1,1-trichloroethane (methyl chloroform),  
trichlorofluoromethane (CFC-11),  
dichlorodifluoromethane (CFC-12),  
1,1,2-trichloro-1,2,2-trifluoroethane (CFC-113),  
1,2-dichloro-1,1,2,2-tetrafluoroethane (CFC-114),  
chloropentafluoroethane (CFC-115),  
chlorodifluoromethane (HCFC-22),  
1,1,1-trifluoro-2,2-dichloroethane (HCFC-123),  
1,1-dichloro-1-fluoroethane (HCFC-141b),  
1-chloro-1,1-difluoroethane (HCFC-142b),~~

~~2-chloro-1,1,1,2-tetrafluoroethane (HCFC-124),  
trifluoromethane (HFC-23),  
1,1,2,2-tetrafluoroethane (HFC-134),  
1,1,1,2-tetrafluoroethane (HFC-134a),  
pentafluoroethane (HFC-125),  
1,1,1-trifluoroethane (HFC-143a),  
1,1-difluoroethane (HFC-152a),  
cyclic, branched, or linear completely methylated siloxanes,  
the following classes of perfluorocarbons:~~

- ~~1. cyclic, branched, or linear, completely fluorinated alkanes;~~
- ~~2. cyclic, branched, or linear, completely fluorinated ethers with no unsaturations;~~
- ~~3. cyclic, branched, or linear, completely fluorinated tertiary amines with no unsaturations; and~~
- ~~4. sulfur containing perfluorocarbons with no unsaturations and with the sulfur bonds to carbon and fluorine, and~~

~~(B) the following low-reactive organic compounds which have been exempted by the U.S. EPA:~~

~~acetone,  
ethane,  
methyl acetate  
parachlorobenzotrifluoride (1-chloro-4-trifluoromethyl benzene),  
perchloroethylene (tetrachloroethylene).~~

(74) “Webbing/Veiling Coating” means a coating an “Aerosol Coating Product” designed and labeled exclusively to provide a stranded to or spider webbed appearance when applied.

(75) “Weight Fraction” means the weight of an ingredient divided by the total net weight of the product, expressed to thousandths of a gram of ingredient per gram of product (excluding container and packaging). The weight fraction is calculated according to the following equation:

$$\text{Weight Fraction} = \frac{\text{Weight of the Ingredient}}{\text{Total Product Net Weight (excluding container and packaging)}}$$

(76) “Weld-Through Primer” means a coating an “Aerosol Coating Product” designed and labeled exclusively to provide a bridging or conducting effect for corrosion protection following welding.

(77) “Wood Stain” means a coating an “Aerosol Coating Product” which is formulated designed and labeled exclusively as a wood stain and is used to change the color of a wood surface but not conceal the surface.

- (78) “Wood Touch-Up/Repair/Restoration Coating” means ~~a coating~~ an “Aerosol Coating Product” designed and labeled exclusively to provide an exact color or sheen match on finished wood products.
- (79) “Working Day” means any day between Monday through Friday, inclusive, except for days that are federal holidays.

NOTE: Authority cited: Sections 39600, 39601 and 41712, Health and Safety Code. Reference: Sections 39002, 39600, 40000 and 41712, Health and Safety Code.

**§ 94522. Reactivity Limits and Requirements for Aerosol Coating Products.**

- ~~(a)(1) Compliance with Limits. Aerosol coating products manufactured beginning June 1, 2002, for the general coating categories and beginning January 1, 2003, for the specialty coating categories shall comply with the reactivity requirements specified in 94522(a)(3). Aerosol coating products manufactured before the effective dates of the reactivity limits specified in section 94522(a)(3) shall comply with the VOC requirements specified in section 94522(a)(2), except for products that are labeled by the manufacturer with the applicable reactivity limit, as provided in section 94524(b)(1)(B). If an aerosol coating product is so labeled, then the product shall comply with the reactivity requirements specified in section 94522(a)(3), regardless of the date on which the product was manufactured.~~
- ~~(a)(2) VOC Limits for Aerosol Coating Products. Except as provided in sections 94522(a)(1), 94523 (Exemptions), 94525 (Variances), 94540 through 94555 (Alternative Control Plan), and 94567(a)(1) (Hairspray Credit Program), Title 17, California Code of Regulations, no person shall sell, supply, offer for sale, apply, or manufacture for use in California, any aerosol coating product which, at the time of sale, use, or manufacture, contains volatile organic compounds in excess of the limits specified in the following Table of Standards after the specified effective dates.~~

**Table of Standards**

**Percent Volatile Organic Compounds by Weight<sup>1</sup>**

Aerosol Coating Category	1/8/96
<b>General Coatings</b>	
Clear Coatings	67.0
Flat Paint Products	60.0
Fluorescent Coatings	75.0
Metallic Coatings	80.0

Nonflat Paint Products	65.0
Primers	60.0

**Specialty Coatings**

Art Fixatives or Sealants	95.0
Auto Body Primers	80.0
Automotive Bumper and Trim Products	95.0
Aviation or Marine Primers	80.0
Aviation Propeller Coatings	84.0
Corrosion Resistant Brass, — Bronze, or Copper Coatings	92.0
Aerosol Coating Category	1/8/96

**Specialty Coatings (continued)**

Exact Match Finishes:

— Engine Enamel	80.0
— Automotive	88.0
— Industrial	88.0
Floral Sprays	95.0
Glass Coatings	95.0
Ground Traffic/Marking Coatings	66.0
High Temperature Coatings	80.0
Hobby/Model/Craft Coatings:	
— Enamel	80.0
— Lacquer	88.0
— Clear or Metallic	95.0
Marine Spar Varnishes	85.0
Photograph Coatings	95.0
Pleasure Craft Finish Primers, — Surfacers or Undercoaters	75.0
Pleasure Craft Topcoats	80.0
Shellac Sealers:	
— Clear	88.0
— Pigmented	75.0
Slip-Resistant Coatings	80.0
Spatter/Multicolor Coatings	80.0
Vinyl/Fabric/Leather/Polycarbonate Coatings	95.0
Webbing/Veil Coatings	90.0
Weld-Through Primers	75.0
Wood Stains	95.0
Wood Touch-Up, Repair — or Restoration Coatings	95.0

=====

<sup>4</sup> ~~As specified in section 94522(c), for aerosol coating products containing methylene chloride, the VOC standards specified in this subsection (a)(2) shall apply to the combined percent VOC and methylene chloride by weight.~~

~~(a)(3)(4) Reactivity Limits for Aerosol Coating Products.~~

(1) Except as provided in section 94523, any “Aerosol Coating Product” shall comply with the applicable general coating limit specified in section 94522(a)(2) unless the “Aerosol Coating Product” meets all the requirements for a specialty coating that is defined in section 94521.

~~(2) (A) Except as provided in sections 94522(a)(1), 94523 (Exemptions) and 94525 (Variances), Title 17, California Code of Regulations, no person shall sell, supply, offer for sale, apply, or manufacture for use in California, any aerosol coating product “Aerosol Coating Product” which, at the time of sale, use, or manufacture, contains reactive organic compounds that have a PWMIR in excess of exceeds the limits specified in the following Table of Reactivity Limits after the specified effective date.~~

**Table of Reactivity Limits**

**Product-Weighted MIR in Grams Ozone per Gram Product  
(g O3 / g product)**

**Aerosol Coating Category**

<b>General Coatings</b>	<b>06/01/2002</b>	<b><u>01/01/2016</u></b>
Clear Coatings	1.50	<u>0.80</u>
Flat Paint Products	1.20	<u>0.80</u>
Fluorescent Coatings-	1.75	<u>0.80</u>
Metallic Coatings	1.90	<u>1.20</u>
Nonflat Paint Products	1.40	<u>0.80</u>
Primers-	1.20	<u>0.60</u>
<b><u>Specialty Coatings (A)</u></b>	<b><u>01/01/2003</u></b>	<b><u>01/01/2016</u></b>
<u>Auto Body Primer</u>	<u>1.55</u>	<u>0.95</u>
<u>Exact Match Finish:</u>		<u>0.90</u>
<u>Engine Paint</u>	<u>1.70</u>	<u>0.90</u>
<u>Automotive</u>	<u>1.50</u>	<u>0.90</u>
<u>Industrial</u>	<u>2.05</u>	<u>0.90</u>
<u>Ground Traffic/Marking Coating</u>	<u>1.20</u>	<u>0.80</u>
<u>Electrical/Electronic/Conformal Coating</u>		<u>2.00</u>
<u>Flexible Coating</u>		<u>1.60</u>

<u>Mold Release</u>	<u>1.10</u>
<u>Uniform Finish Coating</u>	<u>1.30</u>

<b>Specialty Coatings (B)</b>	<b>01/01/2003</b>	<b><u>01/01/2015</u></b>
Art Fixatives or Sealants	1.80	<u>1.75</u>
<del>Auto Body Primers</del>	<del>1.55</del>	
Automotive Bumper <u>and Trim Product</u> <del>and Trim Products</del>	1.75	<u>1.70</u>
Aviation or Marine Primers	2.00	<u>1.25</u>
Aviation Propeller Coatings	2.50	<u>1.40</u>
Corrosion Resistant Brass, Bronze, or Copper Coatings	1.80	<u>1.80</u>
<del>Exact Match Finishes:</del>		
<del>Engine Enamel</del>	<del>1.70</del>	
<del>Automotive</del>	<del>1.50</del>	
<del>Industrial</del>	<del>2.05</del>	
Floral <u>Sprays Coating</u>	1.70	<u>0.85</u>
Glass Coatings	1.40	<u>1.35</u>
<del>Ground Traffic/Marking Coatings</del>	<del>1.20</del>	
High Temperature Coatings	1.85	<u>1.85</u>
Hobby/Model/Craft Coatings:		
Enamel	1.45	<u>1.35</u>
Lacquer	2.70	<u>1.50</u>
Clear or Metallic	1.60	<u>1.60</u>
Marine Spar Varnishes	0.90	<u>0.90</u>
Photograph Coatings	1.00	<u>0.75</u>
<del>Pleasure Craft Finish Primers, /</del>		
<del>Surfacers or /Undercoaters</del>	1.05	<u>0.90</u>
Pleasure Craft Topcoats	0.60	<u>0.60</u>
Polyolefin Adhesion Promoters	2.50	<u>2.50</u>
Shellac Sealers:		<u>1.00</u>
Clear	1.00	
Pigmented	0.95	
Slip-Resistant/ <u>Non-Slip Grip</u> Coatings	2.45	<u>2.10</u>
Spatter/Multicolor/ <u>Stucco</u> Coatings	1.05	<u>1.05</u>
Vinyl/Fabric/Leather/ <u>Plastic</u> /Polycarbonate Coatings	1.55	<u>1.45</u>
Webbing/ <u>Veiling</u> Coatings	0.85	<u>0.75</u>
Weld-Through Primers-	1.00	<u>1.00</u>
Wood Stains	1.40	<u>0.90</u>
Wood Touch-Up, /Repair/Restoration Coating <del>or Restoration Coatings</del>	1.50	<u>1.45</u>

(a)(4b) If an aerosol coating product is subject to both a general coating limit and a specialty coating limit, as listed in section 94522(a)(2) ~~or (a)(3)~~, and the product meets all the criteria of the applicable specialty coating category as defined in

section 94521, then the specialty coating limit shall apply instead of the general coating limit.

(a)(5c) Notwithstanding the provisions of sections 94522(a)(4) or 94524(a), high-temperature coatings that contain at least 0.5 percent by weight of an elemental metallic pigment in the formulation, including propellant, shall be subject to the limit specified for metallic coatings.

(a)(6d) The Alternative Control Plan Regulation (sections 94540-94555) ~~may not be used for~~ does not apply to aerosol coating products subject to the reactivity limits specified in section 94522(a)(3).

(be) *Sell-Through of Products* ~~Subject to the VOC Limits Specified in Section 94522(a)(2).~~

~~Notwithstanding the provisions of section 94522(a)(1) and (a)(3), an aerosol coating product manufactured prior to each of the effective dates specified for that product in section 94522(a)(3) may be sold, supplied, offered for sale, or applied for up to three years after each of the specified effective dates, provided that the product complies with the limit specified in section 94522(a)(2). This subsection (b) does not apply to any product which does not display on the product container or package the date on which the product was manufactured, or a code indicating such date. (c)~~

(1) Notwithstanding the provisions of sections 94522(a), an aerosol coating product manufactured prior to each of the effective dates specified for that product in the Table of Reactivity Limits may be sold, supplied, offered for sale, or applied for up to three years after each of the specified effective dates. This subsection (e) does not apply to:

(A) any aerosol coating product that does not display on the product container or package the date on which the product was manufactured, or a code indicating such date, or

(B) any aerosol coating product on which the manufacturer has used a code indicating the date of manufacture that is different than the code specified in section 94524(b)(2)(B), but an explanation of the code has not been filed with the ARB Executive Officer by the deadlines specified in section 94524(b)(2)(E)1. or section 94524(b)(2)(E)2. or

(C) Products contained in multi-unit packages, as specified below:

1. Subsection (e)(1) does not apply to any individual aerosol coating product unit contained within a multi-unit package that is produced or assembled after January 1, 2015, where the multi-unit package does not display the date(s) or date-code(s) of the individual product units, or display the date of

assembly, such that the displayed information is not readily observable without irreversibly disassembling any portion of the container or packaging.

2. For the purposes of this section, “date of assembly” means the date that the individual product units are assembled into the finished multi-unit package.
3. For multi-unit packages that display the “date of assembly” instead of the date(s) or date-code(s) of the individual product units, the “date of assembly” shall be the “date of manufacture” for all of the product units contained within the multi-unit package. In other words, all of the product units shall be deemed to have been manufactured on the date these units are assembled into the multi-unit package, even if the individual product units show different date(s) or date-code(s).

(2) Notification for products sold during the sell-through period. Any person who sells or supplies an aerosol coating subject to the Table of Reactivity Limits in section 94522(a) must notify the purchaser of the product in writing of the date on which the sell-through period for that product will end, provided, however, that this notification must be given only if all of the following conditions are met:

- (A) the product is being sold or supplied to a distributor or retailer;
- (B) the sell-through period for the product will expire 6 months or less from the date the product is sold or supplied;
- (C) the product does not comply with the lowest PWMIR limit that applies on the date the sell-through period ends;

~~(e) Products Containing Prohibition on use of Methylene Chloride, Perchloroethylene, or Trichloroethylene.~~

- ~~(1) Requirements for Products Subject to the VOC Limits Specified in Section 94522(a)(2).~~

~~For any aerosol coating product containing methylene chloride, the VOC standards specified in section 94522(a)(2) shall apply to the combined percent by weight of both volatile organic compounds, and methylene chloride, calculated as follows:~~

~~(Percent by weight VOC + Percent by weight methylene chloride) must be less than or equal to the applicable VOC standard~~

- ~~(2) Requirements for Products Subject to the Reactivity Limits Specified in Section 94522(a)(3).~~

~~(A1) For any aerosol coating product subject to the reactivity limits specified in section 94522(a)(3), no person shall sell, supply, offer for sale, apply, or manufacture for use in California any aerosol coating product which contains methylene chloride, perchloroethylene, or trichloroethylene.~~

~~(B2) The requirements of section 94522(~~ef~~)(21) shall not apply to any aerosol coating product containing methylene chloride, perchloroethylene, or trichloroethylene that is present as an impurity in a combined amount equal to or less than 0.01% by weight of the product.~~

~~(dg) *Products Containing Perchloroethylene or Prohibition on use of Ozone Depleting Substances.*~~

~~(1) Requirements for Products Subject to the VOC Limits Specified in Section 94522(a)(2).~~

~~For any aerosol coating product subject to the VOC limits specified in section 94522(a)(2), no person shall sell, supply, offer for sale, apply, or manufacture for use in California any aerosol coating product which contains perchloroethylene, or an ozone depleting substance identified by the United States Environmental Protection Agency in the Code of Federal Regulations, 40 CFR Part 82, Subpart A, under Appendices A and B, July 1, 1998. The requirements of this section 94522(d)(1) shall not apply to (A) any existing product formulation that complies with the Table of Standards and was sold in California during calendar year 1992, or (B) any product formulation that was sold in California during calendar year 1992 that is reformulated to meet the Table of Standards, as long as the content of perchloroethylene, or ozone depleting substances, as identified in this section 94522(d), in the reformulated product does not increase.~~

~~(2) Requirements for Products Subject to the Reactivity Limits Specified in Section 94522(a)(3).~~

~~(A) — Perchloroethylene~~

~~For any aerosol coating product subject to the reactivity limits specified in section 94522(a)(3), no person shall sell, supply, offer for sale, apply, or manufacture for use in California any aerosol coating product which contains perchloroethylene.~~

~~(B) — Ozone Depleting Substances~~

~~(1) For any aerosol coating product subject to the reactivity limits specified in section 94522(a)(3), no person shall sell, supply, offer for sale, apply, or manufacture for use in California any aerosol coating product which~~

~~contains an ozone depleting substance identified by the United States Environmental Protection Agency in the Code of Federal Regulations, 40 CFR Part 82, Subpart A, under Appendices A and B, July 1, 1998. The requirements of this section 94522(d)(2) shall not apply to (1.) any existing product formulation containing an ozone depleting substance that complies with the Table of Limits and was sold in California during calendar year 1997, or (2.) any product formulation containing an ozone depleting substance that was sold in California during calendar year 1997 that is reformulated to meet the Table of Limits, as long as the content of ozone depleting substances, as identified in this section 94522(d)(2), in the reformulated product does not increase.~~

- (32) The requirements of section 94522(dg)(1) and (d)(2) shall not apply to any aerosol coating product containing perchloroethylene, or an ozone depleting substance as identified in section 94522(dg)(1) or (d)(2), that are is present as impurities an "Impurity" in a combined amount equal to or less than 0.01% by weight of the product.

(eh) *Multicomponent Kits.*

- ~~(1) Requirements for Products Subject to the VOC Limits Specified in Section 94522(a)(2).~~

~~No person shall sell, supply, offer for sale, apply, or manufacture for use in California any multi-component kit, as defined in section 94521, in which the total weight of VOC and methylene chloride contained in the multi-component kit  $(\text{Total VOC} + \text{MC})_{\text{actual}}$  is greater than the total weight of VOC and methylene chloride that would be allowed in the multi-component kit if each component product in the kit had separately met the applicable VOC standards  $(\text{Total VOC} + \text{MC})_{\text{standard}}$  as calculated below:~~

$$\text{(Total VOC + MC)}_{\text{actual}} = (\text{VOC}_1 \times W_1) + (\text{MC}_1 \times W_1) + (\text{VOC}_2 \times W_2) + (\text{MC}_2 \times W_2) + (\text{VOC}_n \times W_n) + (\text{MC}_n \times W_n)$$

$$\text{(Total VOC + MC)}_{\text{standard}} = (\text{STD}_1 \times W_1) + (\text{STD}_2 \times W_2) + (\text{STD}_n \times W_n)$$

Where:

~~VOC = the percent by weight VOC of the component product~~

~~MC = the percent by weight methylene chloride of the component product~~

~~STD = the VOC standard specified in section 94522(a) which applies to the component product~~

~~W = the weight of the product contents (excluding container)~~

~~Subscript 1 denotes the first component product in the kit~~

~~Subscript 2 denotes the second component product in the kit~~

~~Subscript n denotes any additional component product~~

~~(2) Requirements for Products Subject to the Reactivity Limits Specified in Section 94522(a)(3).~~

No person shall sell, supply, offer for sale, apply, or manufacture for use in California any multi-component kit, as defined in section 94521, in which the Kit PWMIR is greater than the Total Reactivity Limit. The Total Reactivity Limit represents the limit that would be allowed in the multi-component kit if each component product in the kit had separately met the applicable Reactivity Limit. The Kit PWMIR and Total Reactivity Limit are calculated as in equations (1), (2), and (3) below:

$$(1) \quad \text{Kit PWMIR} = (\text{PWMIR}_{(1)} \times W_1) + (\text{PWMIR}_{(2)} \times W_2) + \dots + (\text{PWMIR}_{(n)} \times W_n)$$

$$(2) \quad \text{Total Reactivity Limit} = (\text{RL}_1 \times W_1) + (\text{RL}_2 \times W_2) + \dots + (\text{RL}_n \times W_n)$$

$$(3) \quad \text{Kit PWMIR} \leq \text{Total Reactivity Limit}$$

Where:

W = the weight of the product contents (excluding container)

RL = the Reactivity Limit specified in section 94522(a)(3)

Subscript 1 denotes the first component product in the kit

Subscript 2 denotes the second component product in the kit

Subscript n denotes any additional component product

- ~~(f)~~ *Products Assembled by Adding Bulk Paint to Aerosol Containers of Propellant.* No person shall sell, supply, offer for sale, apply, or manufacture for use in the state of California any aerosol coating product assembled by adding bulk paint to aerosol containers of propellant, unless such products comply with the VOC standards specified in section 94522(a)(2), or with the reactivity limits specified in section 94522(a)(3) for products subject to those limits.

~~(g) Requirements for Lacquer Aerosol Coating Products Subject to the VOC Limits Specified in Section 94522(a)(2).~~

~~(1) Notwithstanding the provisions of Section 94522(a)(2), lacquer aerosol coating products may be sold, supplied, offered for sale, applied, or manufactured for use in California with a combined VOC and methylene chloride content of up to 80 percent by weight until January 1, 1998.~~

~~(2) On or after January 1, 1998, all lacquer aerosol coating products sold, supplied, offered for sale, applied, or manufactured for use in California shall comply with the provisions of section 94522(a)(2), except that lacquer aerosol coating products manufactured prior to January 1, 1998~~

~~may be sold, supplied, offered for sale, or applied until January 1, 2001, as long as the product displays on the product container or package the date on which the product was manufactured or a code indicating such date.~~

~~(3) This subsection (g) does not apply to: (A) any lacquer coating product not clearly labeled as such, or (B) any lacquer coating product which is sold, supplied, offered for sale, applied, or manufactured for use in the Bay Area Air Quality Management District (BAAQMD) and is subject to BAAQMD Rule 8-49, or (C) any lacquer coating product that meets the definition of "clear coating" specified in section 94521.~~

(hj) *Assignment of Maximum Incremental Reactivity (MIR) Values.*

(1) All ingredients in an amount equal to or exceeding 0.1 percent by weight shall be used to calculate the PWMIR.

(42) In order to calculate the PWMIR of an a "Aerosol eCoating pProducts" as specified in section 94521(a)(~~57xx~~), the MIR values of product ingredients are assigned as follows:

(A) Any ingredient which does not contain carbon is assigned a MIR value of 0.0.

(B) Any aerosol coating solid, including but not limited to resins, pigments, fillers, plasticizers, and extenders "Coating Solids," "Extenders," "Fragrance" in an amount of up to 0.25 percent by weight, and "Plasticizer" ingredients are assigned a MIR value of 0.0.

(C) For any ROC not covered under (42)(A) and (42)(B) of this subsection (hj), each ROC is assigned the MIR value set forth in Subchapter 8.6, Article 1, sections 94700 and 94701, Title 17, California Code of Regulations.

(D) If a ROC is not listed in section 94700, Title 17, California Code of Regulations, but an isomer(s) of the ROC is listed, then the MIR value for the isomer shall be used. If more than one isomer is listed, the listed MIR value for the isomer with the highest MIR value shall be used.

~~(DE) Except as provided in subsection (hj)(34), only ROCs listed in sections 94700 and 94701, Title 17, California Code of Regulations, can be used to comply with the reactivity limits specified in section 94522(a)(3) if a ROC is not listed in section 94700 or 94701, Title 17, California Code of Regulations, the MIR value for 1,2,3-~~

trimethyl benzene shall be used to determine the weighted MIR of the ROC to calculate the PWMIR.

- (F) “Fragrance” present in an aerosol coating in an amount exceeding 0.25 percent by weight shall use the MIR value for terpinolene to determine the weighted MIR of the “Fragrance” to calculate the PWMIR.
- (E) ~~All individual compounds in an amount equal to or exceeding 0.1 percent shall be considered ingredients in calculating the PWMIR. Such individual compounds shall be considered ingredients whether or not they are reported by the manufacturer pursuant to section 94526(b).~~
- (23) (A) For products manufactured before [date]: The MIR values dated July 18, 2001, shall be used to calculate the PWMIR for aerosol coating products, and these MIR values shall not be changed until June 1, 2007.
- For products manufactured on or after [date]: The MIR values dated October 2, 2010, shall be used to calculate the PWMIR for aerosol coating products, and these MIR values shall not be changed until at least [date].
- (B) ~~If a new ROC is added to section 94700 or 94701, ROC may be used in aerosol coating products, and the value specified in (2)(D) or (E) the MIR value for the new ROC may be used instead of the value specified in section 94522(j)(2)(D) or (E) to calculate the PWMIR after the effective date of the MIR value.~~
- (34) The MIR value for any aromatic hydrocarbon solvent with a boiling range different from the ranges specified in section 94701(b) shall be assigned as follows:
- (A) if the solvent dry point is lower than or equal to 420 degrees F, the MIR value specified in section 94701(b) for bin 23 shall be used.
- (B) if the solvent initial boiling point is higher than 420 degrees F, the MIR value specified in section 94701(b) for bin 24 shall be used.

NOTE: Authority cited: Section 39600, 39601 and 41712, Health and Safety Code.  
Reference: Sections 39002, 39600, 40000 and 41712, Health and Safety Code.

### **§ 94523. Exemptions.**

- (a) ~~(1) For products manufactured before December 31, 2008: This article shall not~~

~~–apply to aerosol lubricants, mold releases, automotive underbody coatings,  
–electrical coatings, cleaners, belt dressings, anti-static sprays, layout fluids and  
–removers, adhesives, maskants, rust converters, dyes, inks, cosmetics or any  
–other products used on the human body, and leather preservatives or cleaners.~~

(2) ~~For products manufactured on or after December 31, 2008: This article shall not apply to products that meet the definitions for aerosol “Adhesive,” “Anti-Static Product,” “Lubricant,” s mold releases, automotive underbody coatings, undercoatings, electrical coatings, e“Cleaners,” bBelt dressings,” anti-static sprays, l“Layout fluids and removers,” adhesives, m“Maskants,” r“Rust converters,” d“Dyes, i“Inks,” other products used on the human body, l“Leather preservatives or cleaners.” This article also does not apply to products applied to vehicle tires, “Rubber/Vinyl Protectants,” “Undercoating,” as defined in section 94508, and or “Fabric Protectants” as defined in section 94508(a).~~

- (b) This article shall not apply to any aerosol coating product manufactured in California for shipment and use outside of California.
- (c) The provisions of this article shall not apply to a manufacturer, distributor, or responsible party who sells, supplies, or offers for sale in California an aerosol coating product that does not comply with the limits specified in section 94522(a)(2<sup>1</sup>) or (a)(3), as long as the manufacturer, distributor, or responsible party can demonstrate both that the aerosol coating product is intended for shipment and use outside of California, and that the manufacturer, distributor, or responsible party has taken reasonable prudent precautions to assure that the aerosol coating product is not distributed to California. This subsection (c) does not apply to aerosol coating products that are sold, supplied, or offered for sale by any person to retail outlets in California.
- (d) The requirements in sections 94522(a)(2) and (a)(3) prohibiting the application of aerosol coating products that exceed the limits specified in the sections 94522(a)(2) or (a)(3) shall apply only to commercial application of aerosol coating products.

NOTE: Authority cited: Section 39600, 39601 and 41712, Health and Safety Code.  
Reference: Sections 39002, 39600, 40000 and 41712, Health and Safety Code.

#### **§ 94524. Administrative Requirements.**

- (a) *Most Restrictive Limit.*

Except as otherwise provided in section 94522(ab)(4), if anywhere on the container of any aerosol coating product subject to the specified limits in section 94522(a)(2) or (a)(3), or on any sticker or label affixed thereto, or in any sales or advertising literature, any representation is made that the product may be used as, or is suitable for use as a product for which a lower limit is specified, then the lowest applicable limit shall apply.

(b) *Labeling Requirements.*

(1) Both the manufacturer and ~~r~~Responsible ~~p~~Party for each aerosol coating product subject to this article shall ensure that all the products clearly displays the following information on each product container which is manufactured ~~90 days or later~~ on or after the effective date of this article:

~~(A) Products subject to the VOC limits specified in section 94522(a)(2) shall display:~~

- ~~1. the applicable VOC standard for the product that is specified in section 94522(a)(2), expressed as a percentage by weight unless the product is included in an alternative control plan approved by the Executive Officer, as provided in Article 4, Section 94540-94555, Title 17, California Code of Regulations, and the product exceeds the applicable VOC standard;~~
- ~~2. if the product is included in an alternative control plan approved by the Executive Officer, and the product exceeds the applicable VOC standard specified in section 94522(a)(2), the product shall be labeled with the term "ACP" or "ACP product";~~
- ~~3. the aerosol coating category as defined in section 94521, or an abbreviation of the coating category; and~~
- ~~4. the day, month, and year on which the product was manufactured, or a code indicating such date.~~

~~(B) Products subject to the reactivity limits specified in section 94522(a)(3) shall display:~~

- ~~1(A). the applicable ~~r~~Reactivity ~~l~~Limit for the product that is specified in section 94522(a)(3);~~
- ~~2(B). the aerosol coating category as defined in section 94521, or an abbreviation of the coating category; and~~
- ~~3. the day, month, and year on which the product was Manufactured or a code indicating such date.~~

(2) Product Dating Requirements

(A) In addition to the labeling requirements specified in section 94524(b)(1), each

manufacturer of an aerosol coating product subject to section 94522 shall clearly display on each aerosol coating product container or package, the day, month, and year on which the product was manufactured, or a code indicating such date.

Codes that represent a sequential batch number or that otherwise cannot be attributed to a specific day, month, and year, do not satisfy this requirement.

(B) A manufacturer who uses the following code to indicate the date of manufacture shall not be subject to the requirements of section 94524(b)(2)(E), if the code is represented separately from other codes on the product container so that it is easily recognizable:

YY DDD = year year day day day

Where: “YY” = two digits representing the year in which the product was manufactured, and

“DDD” = three digits representing the day of the year on which the product was manufactured, with “001” representing the first day of the year, “002” representing the second day of the year, and so forth (i.e. the “Julian date”).

(C) The date of manufacture or code indicating the date of manufacture shall be displayed on each aerosol coating product container or package no later than twelve months prior to the effective date of the applicable standard specified in section 94522(a).

(D) Products Sold in Multi-unit Packages.

1. Products sold, supplied, or offered for sale in multi-unit packages are not required to comply with subsection (b)(2)(E)3.
2. If a multi-unit package does not comply with subsection (b)(2)(E)3., the “sell-through” provisions of section 94522(e) shall not apply to the individual product units contained within the multi-unit package. In other words, if any multi-unit package produced or assembled after January 1, 2015, does not display the date(s) or date-code(s) of the product units, such that the displayed information is readily observable without irreversibly disassembling any portion of the container or packaging, the individual product units shall be subject to the Reactivity Limit in effect when the multi-unit package is sold, supplied, or offered for sale, regardless of the date on which the product units were manufactured.
3. A multi-unit package may comply with subsection (b)(2)(E)3. by displaying the date of assembly instead of the date(s) or date-code(s) of the individual

product units, so long as the date of assembly is readily observable without irreversibly disassembling any portion of the container or packaging. The “date of assembly” means the date that the individual product units are assembled into the finished multi-unit package. If the date of assembly is displayed instead of the individual date(s) or date-code(s), the “date of assembly” shall be the “date of manufacture” for all of the product units contained within the multi-unit package. In other words, all of the product units shall be deemed to have been manufactured on the date these units are assembled into the multi-unit package, even if the individual product units show different date(s) or date-code(s), and the “date of assembly” shall be “date of manufacture” of each product unit for the purposes of applying the “sell-through” provisions of section 94522(e).

(E) Additional Product Dating Requirements

1. If a manufacturer uses a code indicating the date of manufacture, for any aerosol coating product subject to section 94522 an explanation of the code must be filed with the Executive Officer of the ARB no later than twelve months prior to use of the code or abbreviation. Thereafter, manufacturers using a code must file an explanation of the code with the Executive Officer on an annual basis, beginning January 1, 2015.

The explanation of the code must be received by the Executive Officer on or before January 31<sup>st</sup> of each year, with the first explanation due on or before January 31, 2015.

2. If a manufacturer changes any code indicating the date of manufacture for any aerosol coating product subject to subsection (b)(2)(E)1., an explanation of the modified code must be received by the Executive Officer before any products displaying the modified code are sold, supplied, or offered for sale in California.
3. Except as provided (b)(2)(D), ~~T~~the information required in section 94524(b)(1) and (b)(2), shall be displayed on the product container such that it is readily observable without removing or disassembling any portion of the product container or packaging. For the purposes of this subsection, information may be displayed on the bottom of a container as long as it is clearly legible without removing any product packaging.
- ~~(3)~~ 4. No person shall remove, alter, conceal, or deface the information required in section 94524(b)(1) prior to final sale of the product. No person shall erase, alter, deface, or otherwise remove or make illegible any date or code indicating the date of manufacture from any regulated product container without the express authorization of the manufacturer.
- ~~(4)~~ For any aerosol coating product subject to section 94522(a), if the

~~manufacturer or responsible party uses a code indicating the date of manufacture or an abbreviation of the coating category as defined in section 94521, an explanation of the code or abbreviation must be filed with the Executive Officer prior to the use of the code or abbreviation.~~

5. Codes indicating the date of manufacture are public information and shall not be claimed as confidential.

(c) *Reporting Requirements.*

- (1) Any ~~r~~Responsible ~~p~~Party for an aerosol coating product subject to this article which is sold, supplied, or offered for sale in California, must supply the Executive Officer of the Air Resources Board with the following information within 90 days of the effective date of this article: the company name, mailing address, contact person, email address, and the telephone number of the contact person.

For ~~a~~ ~~r~~Responsible ~~p~~Parties who ~~do~~ does not manufacture their own aerosol coating products, the ~~r~~Responsible ~~p~~Party shall also supply the information specified in this subsection (~~e~~C)(1) for those manufacturers which produce products for the ~~r~~Responsible ~~p~~Party.

The responsible party shall also notify the Executive Officer within 90 days of any change in the information supplied to the Executive Officer pursuant to this subsection (~~e~~C)(1).

- (2) Upon 90 days written notice, each manufacturer or ~~r~~Responsible ~~p~~Party subject to this article shall submit to the Executive Officer a written report with all of the following information for each product they manufacture under their name or another company's name:
- (A) the brand name of the product;
  - (B) ~~upon request~~, a copy of the product label;
  - (C) the owner of the trademark or brand names;
  - (D) the product category as defined in section 94521;
  - (E) the annual California sales in pounds per year and the method used to calculate California annual sales;
  - (F) ~~product formulation data~~;
  - (G) the weight fraction of each ROC present in amount greater than or equal to 0.1 percent by weight along with its corresponding MIR value as specified in sections 94700 or 94701;
  - (H) the weight fraction of ingredients listed in 94522(j)(2)(A) and 94522(j)(2)(B).
  - (I) The weight fraction of any other ingredient that is not an "Impurity".

~~1. for products subject to the VOC limits specified in section~~

~~94522(a)(2), the percent by weight VOC, water, solids, propellant, and any compounds exempt from the definition of VOC as specified in section 94521;~~

- ~~2. for products subject to the reactivity limits specified in section 94522(a)(3), the PWMIR and the weight fraction of all ingredients including: water, solids, each ROC, and any compounds assigned a MIR value of zero as specified in sections 94522(h), 94700, or 94701 [Each ROC must be reported as an ingredient if it is present in an amount greater than or equal to 0.1 percent by weight of the final aerosol coatings formulation. If an individual ROC is present in an amount less than 0.1 percent by weight, then it does not need to be reported as an ingredient. In addition, an impurity that meets the following definition does not need to be reported as an ingredient.~~

~~For the purpose of this section, an “impurity” means an individual chemical compound present in a raw material which is incorporated into the final aerosol coatings formulation, if the compound is present below the following amounts in the raw material:~~

- ~~(i) for individual compounds that are carcinogens, as defined in 29 CFR section 1910.1200(d)(4), each compound must be present in an amount less than 0.1 percent by weight in order to be considered an “impurity.”~~
  - ~~(ii) for all other compounds present in a raw material, a compound must be present in an amount less than 1 percent by weight in order to be considered an “impurity”];~~
- ~~(G) an identification of each product brand name as a “household,” “industrial,” or “both” product; and~~
- ~~(HJ) any other information necessary to determine the emissions or the product-weighted MIR from an aAerosol eCoating pProducts.~~

~~The information requested in this section (c)(2) may be supplied as an average for a group of aerosol coating products within the same coating category when the products do not vary in VOC content by more than two percent (by weight), and the coatings are based on the same resin type, or the products are color variations of the same product (even if the coatings vary by more than 2 percent in VOC content).~~

~~(3) Upon written request, the responsible party for aerosol coating products subject to this article shall supply the Executive Officer with a list of all exempt compounds contained in any aerosol coating product within 15 working days.~~

(d) *Treatment of Confidential Information.*

All information submitted by manufacturers pursuant to section 94524 and 94526 shall be handled in accordance with the procedures specified in Title 17, California Code of Regulations, sections 91000-91022.

~~(e) **Special Reporting Requirements for Perchloroethylene-Containing Aerosol Coatings.**~~

~~(1) The requirements of this subsection shall apply to all responsible parties for perchloroethylene-containing aerosol coatings sold or offered for sale in California on or after January 1, 1996. For the purposes of this subsection, "perchloroethylene-containing aerosol coating" means any aerosol coating that is required to comply with any limit specified in section 94522(a)(2) or (a)(3) and contains 1.0 percent or more by weight (exclusive of the container or packaging) of perchloroethylene (tetrachloroethylene).~~

~~(2) Reporting Requirements to Establish Baseline. On or before March 1, 1997, or 60 days after the effective date of this subsection (e) (whichever date occurs later), all responsible parties for perchloroethylene-containing aerosol coatings shall report to the Executive Officer the following information for each product:~~

~~(A) the product brand name and a copy of the product label with legible usage instructions;~~

~~(B) the product category to which the aerosol coating belongs;~~

~~(C) the total amount of the aerosol coating sold in California between January 1, 1996 and December 31, 1996, to the nearest pound (exclusive of the container or packaging), and the method used for calculating the California sales;~~

~~(D) the weight percent, to the nearest 0.10 percent, of perchloroethylene in the aerosol coating.~~

~~(3) Annual Reporting Requirements. On or before March 1, 1998, March 1, 1999, March 1, 2000, March 1, 2001, and March 1, 2002, all responsible parties subject to the requirements of this subsection shall provide to the Executive Officer an update which reports, for the previous calendar year,~~

~~any changes in the annual California sales, perchloroethylene content, or any other information provided pursuant to subsections (e)(2)(A) through (e)(2)(D). After March 1, 2002, responsible parties are not required to submit this information unless specifically requested to do so by the Executive Officer.~~

~~(4) Upon request, the Executive Officer shall make the information submitted pursuant to this subsection available to publicly-owned treatment works in California, in accordance with the procedures for handling of confidential information specified in Title 17, California Code of Regulations, sections 91000-91022.~~

~~(A) On or before July 1, 2002, the Executive Officer shall evaluate the information, along with data on influent and effluent levels of perchloroethylene as reported by publicly-owned treatment works and any other relevant information, to determine if it is likely that publicly-owned treatment works are experiencing increased levels of perchloroethylene, relative to 1996 levels, that can be attributed to aerosol coatings which contain perchloroethylene.~~

~~(B) If the Executive Officer determines that it is likely that increased perchloroethylene levels at the publicly-owned treatment works are caused by increased levels of perchloroethylene in aerosol coatings subject to this regulation, then the Executive Officer shall, in conjunction with the publicly-owned treatment works, implement measures which are feasible, appropriate, and necessary for reducing perchloroethylene levels at the publicly-owned treatment works.~~

NOTE: Authority cited: Section 39600, 39601, 41511 and 41712, Health and Safety Code.  
Reference: Sections 39002, 39600, 40000, 41511 and 41712, Health and Safety Code.

### **§ 94525.     **Variances.****

(a) Any person who cannot comply with the requirements set forth in §section 94522, because of extraordinary reasons beyond the person's reasonable control may apply in writing to the Executive Officer for a variance. The variance application shall set forth:

- (1) the specific grounds upon which the variance is sought;
- (2) the proposed date(s) by which compliance with the provisions of §section 94522 will be achieved, and
- (3) a compliance report reasonably detailing the method(s) by which compliance will be achieved.

- (b) Upon receipt of a variance application containing the information required in subsection (a), the Executive Officer shall hold a public hearing to determine whether, under what conditions, and to what extent, a variance from the requirements in Section 94522 is necessary and will be permitted. A hearing shall be initiated no later than 75 working days after receipt of a variance application. Notice of the time and place of the hearing shall be sent to the applicant by certified mail not less than 30 days prior to the hearing. Notice of the hearing shall also be submitted for publication in the California Regulatory Notice Register and sent to every person who requests such notice, not less than 30 days prior to the hearing. The notice shall state that the parties may, but need not be, represented by counsel at the hearing. At least 30 days prior to the hearing, the variance application shall be made available to the public for inspection. Information submitted to the Executive Officer by a variance applicant may be claimed as confidential, and such information shall be handled in accordance with the procedures specified in Title 17, California Code of Regulations, Sections 91000-91022. The Executive Officer may consider such confidential information in reaching a decision on a variance application. Interested members of the public shall be allowed a reasonable opportunity to testify at the hearing and their testimony shall be considered.
- (c) No variance shall be granted unless all of the following findings are made:
- (1) that, because of reasons beyond the reasonable control of the applicant, requiring compliance with Section 94522 would result in extraordinary economic hardship.
  - (2) that the public interest in mitigating the extraordinary hardship to the applicant by issuing the variance outweighs the public interest in avoiding any increased emissions of air contaminants which would result from issuing the variance.
  - (3) that the compliance report proposed by the applicant can reasonably be implemented, and will achieve compliance as expeditiously as possible.
- (d) Any variance order shall specify a final compliance date by which the requirements of Section 94522 will be achieved. Any variance order shall contain a condition that specifies increments of progress necessary to assure timely compliance, and such other conditions that the Executive Officer, in consideration of the testimony received at the hearing, finds necessary to carry out the purposes of Division 26 of the Health and Safety Code.
- (e) A variance shall cease to be effective upon failure of the party to whom the variance was granted to comply with any term or condition of the variance.
- (f) Upon the application of any person, the Executive Officer may review, and for good cause, modify or revoke a variance from the requirements of Section

94522 after holding a public hearing in accordance with the provisions of subsection 94525(b).

NOTE: Authority cited: Sections 39600, 39601 and 41712, Health and Safety Code.  
Reference: Sections 39002, 39600, 40000 and 41712, Health and Safety Code.

**§ 94526. Test Methods and Compliance Verification.**

(a) *Test Methods*

Compliance with the requirements of this article shall be determined by using the following test methods, which are incorporated by reference herein. Alternative test methods which are shown to accurately determine the ~~VOC Content~~ PWMIR, ingredient name and weight percent of each ingredient, ~~exempt compound content~~, metal content, specular gloss, or acid content may also be used after approval in writing by the Executive Officer:

~~(a) Testing for Products Subject to the VOC Limits Specified in Section 94522(a)(2).~~

~~(1) VOC Content. The VOC content of all aerosol coating products subject to the provisions of this article shall be determined by the procedures set forth in "Air Resources Board Method 310, Determination of Volatile Organic Compounds (VOC) in Consumer Products and Reactive Organic Compounds in Aerosol Coating Products", adopted September 25, 1997 and as last amended on May 5, 2005.~~

~~(2) In sections 3.5 and 3.7 of Air Resources Board (ARB) Method 310, a process is specified for the "Initial Determination of VOC Content" and the "Final Determination of VOC Content". This process is an integral part of testing procedure set forth in ARB Method 310, and is reproduced below:~~

~~Sections 3.5 and 3.7 of Air Resources Board Method 310~~

~~3.5 Initial Determination of VOC Content. The Executive Officer will determine the VOC content pursuant to section 3.2 and 3.3. Only those components with concentrations equal to or greater than 0.1 percent by weight will be reported.~~

~~3.5.1 Using the appropriate formula specified in section 4.0, the Executive Officer will make an initial determination of whether the product meets the applicable VOC standards specified in ARB regulations. If initial results show that the products does not meet the applicable VOC standards, the~~

~~Executive Officer may perform additional testing to confirm the initial results.~~

~~3.5.2 If the results obtained under section 3.5.1 show that the products does not meet the applicable VOC standards, the Executive Officer will request the product manufacturer or responsible party to supply product formulation data. The manufacturer or responsible party shall supply the requested information. Information submitted to the ARB Executive Officer may be claimed as confidential; such information will be handled in accordance with the confidentiality procedures specified in Title 17, California Code of Regulations, sections 91000 to 91022.~~

~~3.5.3 If the information supplied by the manufacturer or responsible party shows that the product does not meet the applicable VOC standards, then the Executive Officer will take appropriate enforcement action.~~

~~3.5.4 If the manufacturer or responsible party fails to provide formulation data as specified in section 3.5.2, the initial determination of VOC content under this section 3.5 shall determine if the product is in compliance with the applicable VOC standards. This determination may be used to establish a violation of ARB regulations.~~

~~3.7 *Final Determination of VOC Content.* If a product's compliance status is not satisfactorily resolved under section 3.5 and 3.6, the Executive Officer will conduct further analyses and testing as necessary to verify the formulation data.~~

~~3.7.1 If the accuracy of the supplied formulation data is verified and the product sample is determined to meet the applicable VOC standards, then no enforcement action for violation of the VOC standards will be taken.~~

~~3.7.2 If the Executive Officer is unable to verify the accuracy of the supplied formulation data, then the Executive Officer will request the product manufacturer or responsible party to supply information to explain the discrepancy.~~

~~3.7.3 If there exists a discrepancy that cannot be resolved between the results of Method 310 and the supplied formulation data, then the results of Method 310 shall take precedence over the supplied formulation data. The results of Method 310 shall then determine if the product is in~~

~~compliance with the applicable VOC standards, and may be used to establish a violation of ARB regulations.~~

~~(b) Testing for Products Subject to the Reactivity Limits Specified in Section 94522(a)(3).~~

~~(1) The ingredients and the amount of each ingredient of all aerosol coating products subject to the provisions of this article shall be determined by the procedures set forth in "Air Resources Board Method 310, Determination of Volatile Organic Compounds (VOC) in Consumer Products and Reactive Organic Compounds (ROC) in Aerosol Coating Products," (Method 310) adopted September 25, 1997 and as last amended on May 5, 2005 [effective date] which is incorporated herein by reference. Only those components with concentrations equal to or greater than 0.1 percent by weight will be reported.~~

~~(2) Upon written notification from the Executive Officer, the aerosol coating manufacturer shall have 10 working days to provide to the Executive Officer the following information for products selected for testing:~~

~~(A) the product category as defined in section 94521(a);~~

~~(B) the PWMIR;~~

~~(C) the weight fraction of all ingredients including: water, solids, each ROC, and any compounds assigned a MIR value of zero as specified in sections 94522(h), 94700, or 94701. [Each ROC must be reported as an ingredient if it is present in an amount greater than or equal to 0.1 percent by weight of the final aerosol coatings formulation. If an individual ROC is present in an amount less than 0.1 percent by weight, then it does not need to be reported as an ingredient. In addition, an impurity that meets the following definition does not need to be reported as an ingredient~~

~~For the purpose of this section, an "impurity" means an individual chemical compound present in a raw material which is incorporated into the final aerosol coatings formulation, if the compound is present below the following amounts in the raw material:~~

~~(i) for individual compounds that are carcinogens, as defined in 29 CFR section 1910.1200(d)(4), each compound must be present in an amount less than 0.1 percent by weight in order to be considered an "impurity."~~

~~(ii) for all other compounds present in a raw material, a~~

~~compound must be present in an amount less than 1 percent by weight in order to be considered an "impurity";~~

~~(D) any other information necessary to determine the PWMIR of the aerosol coating products to be tested.~~

~~(3) Final determination of the PWMIR of the aerosol coatings shall be determined using the information obtained from section 94526(b)(1) and (2).~~

~~(c) Exempt Compounds from Products Subject to the VOC Limits Specified in Section 94522(a)(2). Compounds exempt from the definition of VOC shall be analyzed according to the test methods listed below:~~

~~(1) the exempt compound content of aerosol coating products shall be determined by "Air Resources Board Method 310, Determination of Volatile Organic Compounds (VOC) in Consumer Products," adopted September 25, 1997 and as last amended on May 5, 2005, which is incorporated herein by reference.~~

~~(2) the following classes of compounds will be analyzed as exempt compounds only if manufacturers specify which individual compounds are used in the product formulations and identify the test methods, which prior to such analysis, have been approved by the Executive Officer of the ARB, and can be used to quantify the amounts of each exempt compound: cyclic, branched, or linear, completely fluorinated alkanes; cyclic, branched, or linear, completely fluorinated ethers with no unsaturations; cyclic, branched, or linear, completely fluorinated tertiary amines with no unsaturations; and sulfur-containing perfluorocarbons with no unsaturations and with sulfur bonds only to carbon and fluorine.~~

~~(d2) Metal Content. The metal content of metallic aerosol coating products shall be determined by South Coast Air Quality Management District (SCAQMD) Test Method 318-95 "Determination of Weight Percent Elemental Metal in Coatings by X-ray Diffraction" July 1996, which is incorporated herein by reference.~~

~~(e3) Specular Gloss. Specular gloss of flat and nonflat coatings shall be determined by ASTM Method D-523-89, March 31, 1989, which is incorporated herein by reference.~~

~~(f4) Acid Content. The acid content of rust converters shall be determined by ASTM Method D-1613-96, "Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products, May 10, 1996, which is incorporated~~

herein by reference.

- (g5) Lacquers. Lacquer aerosol coating products shall be identified according to the procedures specified in ASTM Method D-5043-90, "Standard Test Methods for Field Identification of Coatings," April 27, 1990, which is incorporated herein by reference.

(b) Compliance Verification

(1) Upon written notification from the Executive Officer, the Responsible Party shall have 20 working days to provide to the Executive Officer the exact product formulation and any other information necessary to determine compliance for products selected for testing:

(A) For the purpose of this subsection, formulation means the exact weight fraction of all ingredients including: water, "Coating Solids," each ROC, "Plasticizer," "Extender," and any compounds assigned an MIR value of zero as specified in section 94522(j).

(1) Each ROC must be reported as an ingredient if it is present in an amount greater than or equal to 0.1 percent by weight of the final aerosol coatings formulation. If an individual ROC is present in an amount less than 0.1 percent by weight, then it does not need to be reported as an ingredient.

(2) A MSDS does not constitute a product's formulation.

(B) the product category as defined in section 94521(a);

(C) the PWMIR of the "Aerosol Coating Product";

(D) any other information necessary to determine the PWMIR of the aerosol coating product to be tested;

(E) Failure to provide the required information within 20 working days or providing incomplete or inaccurate formulation data are violations and subject to penalties.

(2) The Responsible Party must supply the contact person, mailing address, email address, and phone number for the party who is to be contacted to provide the information specified in (b)( 1)

(3) The information specified in (b)(2) shall be supplied before January 1, 2015, and anytime thereafter that the information changes.

(34) Final determination of the PWMIR of the a "Aerosol eCoatings Product" shall be determined using the information obtained from section 94526(ba)(1) and (2).

(A) If an aerosol coating product contains one or more Hydrocarbon Solvent(s), the following MIR values shall be used to determine the weighted MIR for each Hydrocarbon Solvent fraction:

Table 94526(b)(4)(A)

<u>Hydrocarbon Solvent Fraction</u>	<u>MIR Value (October 2, 2010)</u>
<b><u>Alkanes</u></b>	
<u>Alkane(s) containing 5 carbons</u>	<u>1.45</u>
<u>Alkane(s) containing 6 carbons</u>	<u>1.27</u>
<u>Alkane(s) containing 7 carbons</u>	<u>1.41</u>
<u>Alkane(s) containing 8 carbons</u>	<u>1.27</u>
<u>Alkane(s) containing 9 carbons</u>	<u>1.09</u>
<u>Alkane(s) containing 10 carbons</u>	<u>0.90</u>
<u>Alkane(s) containing 11+ carbons</u>	<u>tbd</u>
<b><u>Aromatic Compounds</u></b>	
<u>Xylene isomers, Ethyl benzene</u>	<u>7.64</u>
<u>Aromatics containing 9 carbons</u>	<u>7.99</u>
<u>Aromatics containing C10+carbons</u>	<u>tbd</u>

(B) If there exists a discrepancy that cannot be resolved between the results of Method 310 and the supplied formulation data, then the results of Method 310 shall take precedence over the supplied formulation data. The results of Method 310 shall then determine if the product is in compliance with the applicable limits, and may be used to establish a violation of this article.

NOTE: Authority cited: Sections 39600, 39601, 39607, 41511 and 41712, Health and Safety Code. Reference: Sections 39002, 39600, 39607, 40000, 41511 and 41712, Health and Safety Code.

**§ 94527. Severability.**

Each part of this article shall be deemed severable, and in the event that any part of this article is held to be invalid, the remainder of this article shall continue in full force and effect.

NOTE: Authority cited: Sections 39600, 39601 and 41712, Health and Safety Code.  
Reference: Sections 39002, 39600, 40000 and 41712, Health and Safety Code.

**§ 94528. Federal Enforceability.**

For purposes of federal enforceability of this article, the United States Environmental Protection Agency is not subject to approval determinations made by the Executive Officer under sections 94525 and 94526. Within 180 days of a request from a person who has been granted a variance under Section 94525, a variance meeting the requirements of the Clean Air Act shall be submitted by the Executive Officer to the Environmental Protection Agency for inclusion in the applicable implementation plan approved or promulgated by the Environmental Protection Agency pursuant to §section 110 of the Clean Air Act, 42 U.S.C., Section 7410.

NOTE: Authority cited: Sections 39600, 39601, 39602 and 41712, Health and Safety Code. Reference: Sections 39002, 39600, 39602, 40000 and 41712, Health and Safety Code.