

PRELIMINARY DRAFT - February 20, 1997

**AUTOMOTIVE RUBBING OR POLISHING COMPOUND**

---

---

**Preliminary Draft VOC Limit: (Semisolid): 3.0% by weight  
(All other forms) 13.0% by weight**

**I. Product Definition:**

"Automotive Rubbing or Polishing Compound" means a product designed and labeled primarily to remove oxidation, old paint, scratches or "swirl marks" from the painted surfaces of motor vehicles without leaving a protective barrier.

**II. Typical Formulations of Complying Products (Category 200):**

*Disclaimer: The following sample formulations for complying products are not intended to be complete formulations. Air Resources Board staff realize that consumer product formulations are often complex mixtures that require extensive testing to optimize. The sample formulations are intended to illustrate the approximate proportions of compounds that may be used to formulate a consumer product that meets the draft volatile organic compound limits for the Mid-term Measures.*

A. Semisolid Products

1. Water-based Formulation:

<b>Wt. %</b>	<b>Ingredient</b>
66	Water
2	VOC's
11	LVP VOC's
21	Inorganics

\* As seen in our 1995 Mid-term Measures Survey

**PRELIMINARY DRAFT - February 20, 1997**

**AUTOMOTIVE RUBBING OR POLISHING COMPOUND**

---

---

**Preliminary Draft VOC Limit: (Semisolid): 3.0% by weight  
(All other forms) 13.0% by weight**

B. All other product forms

1. Water-based Formulation:\*

<b>Wt. %</b>	<b>Ingredient</b>
33-80	Water
0-13	VOC's
0-12	LVP VOC's
11-44	Inorganics

\* As seen in our 1995 Mid-term Measures Survey