

**RULE 4653 - ADHESIVES**

*(Adopted March 17, 1994)(Amended April 13, 1995; March 19, 1998; December 14, 2000; December 20, 2001; September 20, 2007)*

1.0 Purpose

The purpose of this rule is to reduce emissions of volatile organic compounds (VOCs) from the application of adhesive products, the organic solvent cleaning, and the storage and disposal of solvents and waste solvent materials associated with such applications.

2.0 Applicability

This rule is applicable to any person who supplies, sells, offers for sale, or applies any adhesive product used within the District. This rule is also applicable to any person who supplies, sells, offers for sale, or applies any solvent associated with the use of adhesive product within the District.

3.0 Definitions

The following definitions apply for the purpose of this rule.

3.1 ABS Welding Adhesive: any adhesive that is intended by the manufacturer to weld acrylonitrile butadiene styrene (ABS) plastic. ABS is made by reacting monomers of acrylonitrile, butadiene, and styrene and is normally identified with ABS marking.

3.2 Adhesive: any material used to bond two surfaces together by attachment.

3.3 Adhesive Primers: any material applied to a substrate prior to the application of an adhesive to provide a bonding surface.

3.4 Adhesive Products: adhesives and adhesive primers.

3.5 Aerosol Spray Adhesive: a mixture of rubber, resin, liquids and gaseous solvents and propellants packaged in a disposable nonrefillable container for hand-held application.

3.6 APCO: as defined in Rule 1020 (Definitions).

3.7 Application Equipment: a device, including, but not limited to, a spray gun, brush, and roller, used to apply adhesives, coatings, or inks.

3.8 ARB: California Air Resources Board.

3.9 Architectural: pertaining to stationary structures including buildings, houses, and mobile homes, and their appurtenances.

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 3.10 ASTM: American Society for Testing and Materials.
- 3.11 Bench Scale Project: a project (other than at a research and development facility) that is operated on a small scale, such as one capable of being located on a laboratory bench top.
- 3.12 Ceramic Tile Installation Adhesive: any adhesive that is intended by the manufacturer to be used for installation of ceramic tiles.
- 3.13 CFR: Code of Federal Regulations.
- 3.14 Coating: a material applied onto or impregnated into a substrate for protective, decorative, or functional purposes. Such materials include, but are not limited to, paints, varnishes, sealers, and stains.
- 3.15 Contact Adhesive: any adhesive that is intended by the manufacturer to adhere to itself instantaneously upon contact. This adhesive is applied to both adherends and allowed to become dry, which develops a bond when the adherends are brought together without sustained pressure.
- 3.16 Contact Adhesive - Specialty: contact adhesives that are intended by the manufacturer to be used for the bonding of nonporous substrates to each other, the bonding of decorative laminate in postforming applications, the bonding of decorative laminate to metal, melamine-covered board, or curved surfaces, or the bonding of any substrate to metal, rubber, rigid plastic, or wood veneer not exceeding 1/16 inch in thickness.
- 3.17 CPVC Welding Adhesive: any adhesive intended by the manufacturer for the welding of CPVC (chlorinated polyvinyl chloride) plastic. CPVC is a polymer of the monomer that contains 67 percent chlorine and is normally identified with a CPVC marking.
- 3.18 Cured Adhesive, Cured Coating, or Cured Ink: an adhesive, coating, or ink that is dry to the touch.
- 3.19 EPA: United States Environmental Protection Agency.
- 3.20 Exempt Compounds: compounds identified as exempt under the definition of VOC, in Rule 1020 (Definitions).
- 3.21 Flexible Vinyl: a nonrigid polyvinyl chloride plastic with at least five percent, by weight of plasticizer content. A plasticizer is a material, such as a high boiling point organic solvent, that is incorporated into an adhesive to increase its flexibility, workability, or distensibility, and may be determined using the latest version of ASTM Method E260 or from product formulation data.

SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 3.22 Floor Covering Installation: installation of wood flooring, carpet, floor tile, or artificial grass. Floor covering installation does not include ceramic tile installation or perimeter bonded sheet flooring installation.
- 3.23 Grams of VOC per Liter of Adhesive Product, Excluding Water and Exempt Compounds: the weight of VOC per combined volume of VOC and coating solids, calculated using the following equation:

$$\begin{array}{l} \text{Grams of VOC per Liter of} \\ \text{Adhesive Product, Excluding} \\ \text{Water and Exempt Compounds} \end{array} = \frac{W_s - W_w - W_{ec}}{V_m - V_w - V_{ec}}$$

Where:

- W<sub>s</sub> = weight of volatile compounds, in grams
- W<sub>w</sub> = weight of water, in grams
- W<sub>ec</sub> = weight of exempt compounds, in grams
- V<sub>m</sub> = volume of material, in liters
- V<sub>w</sub> = volume of water, in liters
- V<sub>ec</sub> = volume of exempt compounds, in liters

- 3.24 Grams of VOC per Liter of Material: the weight of VOC per volume of material, calculated using the following equation:

$$\text{Grams of VOC per Liter of Material} = (W_s - W_w - W_{ec}) / V_m$$

Where:

- W<sub>s</sub> = weight of all volatile compounds, in grams
- W<sub>w</sub> = weight of water, in grams
- W<sub>ec</sub> = weight of exempt compounds, in grams
- V<sub>m</sub> = volume of the material, in liters

- 3.25 High Precision Optics: optical elements used in electro-optical devices which are designed to sense, detect, or transmit light energy, including specific wavelengths of light energy and changes in light energy levels.
- 3.26 High-Volume, Low-Pressure (HVLP) Spray Equipment: equipment used to apply materials by means of a spray gun which is designed and intended to be operated, and which is operated, between 0.1 and 10.0 psig of air atomizing pressure, measured dynamically at the center of the air cap and the air horns.
- 3.27 Liquid Leak: a visible solvent leak from a container at a rate of more than three drops per minute, or a visible liquid mist.
- 3.28 Low-Solids Adhesive Product: any adhesive or adhesive primer that contains less than 120 grams of solids per liter of material.

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 3.29 Maintenance Cleaning: the cleaning of tools, forms, molds, jigs, machinery, and equipment (except coating application equipment, ink application equipment, or adhesive application equipment), and the cleaning of work areas where maintenance or manufacturing occurs.
- 3.30 Manufacturing Process: the process of making goods or articles by hand or by machine.
- 3.31 Multipurpose Construction: the installation or repair of construction materials including, but not limited to, drywall, subfloor, panelling, baseboards, fiberglass, ceiling tiles, and ceiling panels.
- 3.32 Non-Absorbent Container: a container made of non-porous material that does not allow the migration of solvents through it.
- 3.33 Non-Atomized Solvent Flow: solvents in the form of a liquid stream without the introduction of any propellant.
- 3.34 Non-Leaking Container: a container without a liquid leak.
- 3.35 Normal Business Hours: Monday through Friday, 8:00 am to 5:00 pm.
- 3.36 Organic Solvent: the same as "Solvent."
- 3.37 Organic Solvent Cleaning: an activity, or operation, or process, (including surface preparation, cleanup, or wipe cleaning), performed outside of a degreaser, that uses organic solvent to remove uncured adhesives, uncured coatings, uncured inks or other contaminants, including, but not limited to, dirt, soil, oil, lubricants, coolants, moisture, fingerprints, and grease, from parts, products, tools, machinery, application equipment and general work areas. Cleaning spray equipment used for the application of coatings, adhesives, or ink, is also considered to be organic solvent cleaning.
- 3.38 Percent VOC by Weight: the ratio of the weight of the VOC to the weight of the material, expressed as a percentage.
- 3.39 Perimeter Bonded Sheet Flooring Installation: the installation of sheet flooring with vinyl backing onto a nonporous substrate using an adhesive designed to be applied only to a strip of up to four inches wide around the perimeter of the sheet flooring.
- 3.40 Plastic Cement Welding Adhesive: adhesives composed of resins and solvents that are used to dissolve plastic surfaces to form a bond between mating surfaces.
- 3.41 Plastic Cement Welding Primer: any primer intended by the manufacturer to prepare plastic substrates prior to welding.

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 3.42 Plastic Foam: a foam constructed of plastic material.
- 3.43 Porous Materials: materials with surfaces permeable to liquids. Examples of porous materials include paper, and cardboard.
- 3.44 Pre-formed Rubber Products: any rubber product which has undergone a vulcanization process and is in its final state for further use and is not intended to be vulcanized any further.
- 3.45 Propellant: any gas, including air, in a pressure container for expelling the contents when the pressure is released.
- 3.46 PVC Welding Adhesive: any adhesive intended by the manufacturer to weld polyvinyl chloride (PVC) plastic. PVC plastic is a polymer of the chlorinated vinyl monomer that contains 57 percent chlorine and which is normally identified with a PVC marking.
- 3.47 Repair Cleaning: a solvent cleaning operation or activity carried out during a repair process.
- 3.48 Repair Process: the process of returning a damaged object or an object not operating properly to good condition.
- 3.49 Research and Development: a facility or portion thereof used to further the development of useful materials, devices, systems, or methods, including, but not limited to, design, development, and improvement of prototypes and processes. Research and development does not include the manufacturing process itself.
- 3.50 Rubber: any natural or manmade rubber substrate, including but not limited to styrene-butadiene rubber (SBR), polychloroprene (neoprene), butyl rubber, nitrile rubber, chlorosulfonated polyethylene (CSM), and ethylene propylene diene terpolymer (EPDM).
- 3.51 Rubber Stock Sheets: any cured, uncured or partially cured rubber sheets which are not in their final state of intended use.
- 3.52 Rubber Vulcanization Adhesive/Primer: any adhesive product designed to bond rubber to metal, rubber, or polyester or nylon fabrics during the following vulcanization processes:
  - 3.52.1 Molded vulcanization: the application of heat and pressure to uncured rubber in a mold;
  - 3.52.2 Sheet-applied Vulcanization: the application of heat after rubber stock sheets have been adhered to the walls of tanks, tankers, elbow joints, protective earthquake building pads, or rail cars; or the application of heat

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

after one or more layers of rubber stock sheets have been built-up to form a rubber product;

- 3.52.3 Cold vulcanization: the chemical reaction of an adhesive with rubber stock sheets that are adhered to earthmoving equipment, other high impact/abrasion devices, or industrial belting devices, without the application of heat or pressure.
- 3.53 SCAQMD: South Coast Air Quality Management District.
- 3.54 Scientific Instruments: instruments (including the components, assemblies, and subassemblies used in their manufacture) and associated accessories and reagents which are used for the detection, measurement, analysis, separation, synthesis, or sequencing of various compounds.
- 3.55 Single-ply Roof Material Installation: the use of adhesive products to apply one layer of roofing membrane.
- 3.56 Solvent: as defined in Rule 4663 (Organic Solvent Cleaning, Storage, and Disposal).
- 3.57 Solvent Flushing: the use of a solvent to remove uncured adhesives, uncured inks, uncured coatings, or contaminants from the internal surfaces and passages of equipment by flushing solvent, by a non-atomized solvent flow, through the equipment.
- 3.58 Solvent Welding: is the softening of the surfaces of two substrates by wetting them with solvents and/or adhesives, and joining them together with a chemical and/or physical reaction(s) to form a fused union.
- 3.59 Staple and Nail Manufacturing Adhesive: any adhesive that is intended by the manufacturer to bond industrial staples into a clip or to be applied to industrial nails to produce collated nails.
- 3.60 Stationary Source: as defined in Rule 2201 (New and Modified Stationary Source Review Rule).
- 3.61 Stripping: the use of solvent to remove material such as cured adhesives, cured inks, cured or dried paint, cured or dried paint residue or temporary protective coating.
- 3.62 Structural Glazing: the use of adhesives to bond glass, ceramic, metal, stone, or composite panels to the exterior of a building.

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 3.63 Surface Preparation: the removal of contaminants from a surface prior to the application of coatings, inks, or adhesives or before proceeding to the next step of a manufacturing process.
- 3.64 Surface Preparation Solvent: any VOC containing material used to remove dirt, oil, and other contaminants. This surface cleaning is typically done prior to the application of an adhesive product.
- 3.65 Thinner: a solvent that is used to dilute coatings to reduce viscosity, color strength, and solids, or to modify drying conditions.
- 3.66 Tire Repair: the repair of a hole, tear, fissure, or blemish in a tire casing by grinding or gouging, applying adhesive or sealant product and filling the hole or crevice with rubber.
- 3.67 Ultraviolet Ink: as defined in Rule 4607 (Graphic Arts).
- 3.68 Volatile Organic Compound (VOC): as defined in Rule 1020 (Definitions).
- 3.69 Waste Solvent Material: any solvent which may contain dirt, oil, metal particles, sludge, and/or waste products, or wiping material containing VOCs including, but not limited to, paper, cloth, sponge, rag, or cotton swab used in organic solvent cleaning.
- 3.70 Waterproof Resorcinol Glue: a two-part, resorcinol-resin-based adhesive designed for applications where the bond line must be resistant to conditions of continuous immersion in fresh or salt water.
- 3.71 Wipe Cleaning: a solvent cleaning activity performed by hand rubbing an absorbent material such as a rag, paper, sponge, brush, or cotton swab containing solvent.

### 4.0 Exemptions

- 4.1 The provisions of this rule shall not apply to:
  - 4.1.1 A stationary source that uses 20 gallons or less of adhesives products in a calendar year. Commercial and industrial operations exempted by this section shall maintain monthly records documenting the type and quantity of adhesive products and solvents used and provide the records to the District upon request.
  - 4.1.2 The use of adhesive products containing less than 20 grams VOC per liter.
  - 4.1.3 The testing and evaluation of adhesives in research laboratories, analytical laboratories, or quality assurance laboratories. Laboratory operators shall

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

maintain monthly records documenting the type and quantity of adhesive products used and provide the records to the District upon request.

- 4.1.4 The use of adhesives in tire repair provided the label states “for tire repair use only.”
- 4.1.5 The use of adhesives that are sold or supplied with 8 fluid oz. or less of adhesive in non-reusable containers.
- 4.1.6 The use of aerosol spray adhesive products.
- 4.1.7 Household adhesive products subject to Article 2, Consumer Products, Sections 94507 - 94517, Title 17, California Code of Regulations.
- 4.1.8 Adhesive products which are subject to the VOC limit requirements of Rule 4605 (Aerospace Assembly and Component Coating Operations), Rule 4607 (Graphic Arts), and Rule 4681 (Rubber Tire Manufacturing).
- 4.1.9 Contact adhesives that are subject to the Consumer Product Safety Commission regulations in 16 CFR, Part 1302, that have a flash point greater than 20°F as determined pursuant to those regulations, and that are sold in packages that contain 128 fluid ounces or less.
- 4.1.10 Stripping of cured adhesives, except the stripping of such materials from spray application equipment.
- 4.2 Except for the records required in Section 6.1.3, the prohibition of sale in Section 5.6 shall not apply to the following:
  - 4.2.1 Adhesive products shipped, supplied, or sold exclusively to persons outside the District for use outside the District.
  - 4.2.2 Adhesive products sold to any person who complies with the requirements of Section 5.4.
- 4.3 The VOC content limits of Table 3 shall not apply to the following applications:
  - 4.3.1 Cleaning of solar cells, laser hardware, scientific instruments, or high precision optics.
  - 4.3.2 Cleaning in laboratory tests and analyses, or bench scale or research and development projects.
  - 4.3.3 Cleaning of clutch assemblies where rubber is bonded to metal by means of an adhesive.

# SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

4.3.4 Cleaning of paper-based gaskets.

## 5.0 Requirements

### 5.1 Adhesive VOC Content Limits

5.1.1 The VOC content of adhesive products used for specific applications shall not exceed the following limits, expressed as grams of VOC per liter of adhesive product, excluding water and exempt compounds, or grams of VOC per liter of material for low-solids adhesive products, as applied:

Table 1 - VOC Content Limits for Adhesive Products

Applications	VOC Limits [Grams Per Liter]
Multipurpose Construction	200
Floor Covering Installation	150
Ceramic Tile Installation	130
Perimeter Bonded Sheet Flooring Installation	660
Single-Ply Roof Material Installation	250
Structural Glazing	100
ABS Welding Adhesive	400
CPVC Welding Adhesive	490
PVC Welding Adhesive	510
Other Plastic Cement Welding Adhesive	450
Plastic Cement Welding Adhesive Primer	650
Adhesive Primers	250
Staple and Nail Manufacturing	640
Contact Adhesive	250
Contact Adhesive – Specialty	250
Rubber Vulcanization Adhesive/Primer	850
Waterproof Resorcinol Glue	170

5.1.2 The VOC content of adhesive products, except as provided in Section 5.1.1, shall not exceed the following limits, expressed as grams of VOC per liter of adhesive product, excluding water and exempt compounds, or grams of VOC per liter of material for low-solids adhesive products, as applied:

Table 2 - VOC Content Limits for Adhesive Products

Material Bonded	VOC Limit [Grams Per Liter]
Metal to Metal	30
Porous Materials	120
Plastic Foam	120
Wood	30
Pre-formed Rubber Products	250
All Other Substrates	250

5.1.3 The higher of the two limits from Table 2 applies to the bonding of two dissimilar substrates.

5.1.4 In lieu of complying with the applicable requirements of Sections 5.1.1 through 5.1.3, an operator may control VOC emissions from coating operations with a VOC emission control device that meets the requirements of Section 5.3.

5.2 Adhesive Application Equipment

An operator shall use only the following equipment to apply adhesive:

5.2.1 Electrostatic Application

5.2.2 Flow Coater

5.2.3 Roll Coater

5.2.4 Dip Coater

5.2.5 Hand Application Methods

5.2.6 HVLP Spray

5.2.6.1 HVLP spray equipment shall be operated in accordance with the manufacturer's recommendations.

5.2.6.2 For HVLP spray guns manufactured prior to January 1, 1996, the end user shall demonstrate that the gun meets HVLP spray equipment standards. Satisfactory proof will be either in the form of manufacturer's published technical material or by a demonstration using a certified air pressure tip gauge, measuring the air atomizing pressure dynamically at the center of the air cap and at the air horns.

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

5.2.6.3 A person shall not sell or offer for sale for use within the District any HVLP spray gun without a permanent marking denoting the maximum inlet air pressure in psig at which the gun will operate within the parameters specified in Section 3.0.

5.2.7 Any other application method that demonstrates, to the satisfaction of the APCO and EPA, a coating transfer efficiency of at least 65 percent ( $\geq 65\%$ ) as measured using a test method in Section 6.3.6.

5.2.8 Air-atomized spray may only be used for the application of contact adhesives or specialty contact adhesives.

5.2.9 In lieu of complying with the applicable requirements in Sections 5.2.1 through 5.2.8, an operator may control emissions from coating application equipment with an APCO-approved VOC emission control system that controls the emissions from the source operation and that meets the requirements of Section 5.3.

### 5.3 VOC Emission Control System Requirements

5.3.1 In lieu of the applicable requirements of Section 5.1, 5.2, or 5.4, an operator may install and maintain a VOC emission control system that meets all of the requirements of Sections 5.3.2 through 5.3.5.

5.3.2 The VOC emission control system shall be approved by the APCO.

5.3.3 The VOC emission control system shall comply with the requirements of Section 5.3.4 and 5.3.5 during periods of emission-producing activities.

5.3.4 The VOC emission control system shall be operated with an overall capture and control efficiency of at least 85 percent by weight, as determined in accordance with Section 6.3.

5.3.5 In no case shall compliance through the use of a VOC emission control system result in VOC emissions in excess of the VOC emissions which would result from compliance with the applicable requirements of Sections 5.1, 5.2, or 5.4.

5.3.6 The minimum required overall capture and control efficiency of a VOC emission control system at which an equivalent or greater level of VOC reduction will be achieved shall be calculated by using the following equation:

$$CE = \left[ 1 - \left( \frac{VOC_{LWc}}{VOC_{LWn,Max}} \times \frac{1 - (VOC_{LWn,Max} / D_{n,Max})}{1 - (VOC_{LWc} / D_c)} \right) \right] \times 100$$

SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

Where:

- CE = Minimum Required Overall Capture and Control Efficiency, percent
- VOC<sub>LWc</sub> = VOC Limit, less water and less exempt compounds
- VOC<sub>LWn,Max</sub> = Maximum VOC content of noncompliant adhesive product used in conjunction with a control device, less water and less exempt compounds
- D<sub>n,Max</sub> = Density of solvent, reducer, or thinner contained in the noncompliant adhesive product, containing the maximum VOC content
- D<sub>c</sub> = Density of corresponding solvent, reducer, or thinner used in the compliant adhesive products

5.4 Organic Solvent Cleaning Requirements

5.4.1 An operator shall not use organic solvents for cleaning operations that exceed the VOC content limits specified in Table 3, in accordance with the corresponding effective date.

Table 3 – VOC Limits for Organic Solvents Used in Cleaning Operations

Type of Solvent Cleaning Operation	Effective November 15, 2003 through September 20, 2008	Effective September 21, 2008
	VOC Content Limit Grams of VOC/liter of material (lb/gal)	VOC Content Limit Grams of VOC/liter of material (lb/gal)
A. Product Cleaning During Manufacturing Process or Surface Preparation for Adhesive Application		
1. General	50 (0.42)	25 (0.21)
2. Surface Preparation Prior to Rubber Vulcanization Process	850 (7.1)	850 (7.1)
B. Repair and Maintenance Cleaning	50 (0.42)	25 (0.21)
C. Cleaning of Adhesive Application Equipment	550 (4.6)	25 (0.21)

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 5.4.2 In lieu of complying with the requirements in Table 3, an operator may control VOC emissions from cleaning operations with an APCO-approved VOC emission control system that meets the requirements of Section 5.3.
- 5.4.3 Until September 20, 2008, an operator performing either Table 3 Category A.2 cleaning or Table 3 Category C cleaning using solvent with VOC content greater than 50 g/L and the cleaning is takes place outside the control of an APCO-approved VOC emission control system shall meet the requirements of Sections 5.4.6 through 5.4.8 in addition to the meeting the applicable VOC content limit of Table 3.
- 5.4.4 On and after September 21, 2008, an operator performing Table 3 Category C cleaning outside the control of an APCO-approved VOC emission control system shall only use cleaning material that meets the VOC content limit of Table 3.
- 5.4.5 On and after September 21, 2008, an operator performing Table 3 Category A.2 cleaning using solvent with VOC content greater than 25 g/L and the cleaning is takes place outside the control of an APCO-approved VOC emission control system shall meet the requirements of Sections 5.4.6 through 5.4.8 in addition to the meeting the applicable VOC content limit of Table 3.
- 5.4.6 Cleaning activities that use solvents shall be performed by one or more of the following methods:
  - 5.4.6.1 Wipe cleaning; or
  - 5.4.6.2 Application of solvent from hand-held spray containers from which solvents are dispensed without a propellant-induced force; or
  - 5.4.6.3 Non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or
  - 5.4.6.4 Solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping.

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 5.4.7 Solvent shall not be atomized into the open air unless it is vented to a VOC emission control system that complies with Section 5.3. This provision shall not apply to the cleaning of nozzle tips of automated spray equipment systems, except for robotic systems, and cleaning with spray bottles or containers described in Section 5.4.6.2.
- 5.4.8 An operator shall not use VOC-containing materials to clean spray equipment used for the application of coatings, adhesives, or ink, unless an enclosed system or equipment that is proven to be equally effective at controlling emissions is used for cleaning. If an enclosed system is used, it must totally enclose spray guns, cups, nozzles, bowls, and other parts during washing, rinsing and draining procedures, and it must be used according to the manufacturer's recommendations and must be closed when not in use.
- 5.4.9 In lieu of complying with the applicable requirements of Sections 5.4.6 through 5.4.8, an operator shall install and maintain a VOC emission control system that meets the requirements of Section 5.3 to control emissions from the solvent cleaning operation.

### 5.5 Solvent Storage and Disposal Requirements

An operator shall store or dispose of coatings, adhesives, catalysts, thinners, fresh or spent solvents, and waste solvent materials such as cloth, paper, etc., in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty. The containers used for disposal of adhesive materials, solvents, or any unused VOC containing materials shall be self-closing.

### 5.6 Prohibition of Sale

Except as provided in Section 4.2, no person shall supply, sell, or offer for sale any adhesive product that does not meet the limits as specified in Section 5.1 or 5.3.

## 6.0 Administrative Requirements

### 6.1 Recordkeeping

6.1.1 Coatings Records: An operator subject to Sections 5.1 or 5.3 shall maintain the following records:

6.1.1.1 Daily records of the type and quantity of all adhesives, primers, and solvents used in each operation.

6.1.1.2 Records of the VOC content, in grams VOC per liter, of all adhesive materials used or stored at the stationary source.

# SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

6.1.1.3 Records of the VOC content of all solvents used and stored at the stationary source.

## 6.1.2 VOC Emission Control System Records

An operator using a VOC emission control device as a means of complying with this rule shall maintain daily records of key system operating parameters which will demonstrate continuous operation and compliance of the emission control system during periods of emission-producing activities. Key system operating parameters are those necessary to ensure compliance with VOC limits. The parameters may include, but are not limited to, temperatures, pressures, and flow rates.

## 6.1.3 Prohibition of Sale Exemption Records

A person who claims exemption under Section 4.2 shall maintain records for all adhesive products sold that do not meet the limits as specified in Section 5.1. The records shall include the following information:

6.1.3.1 Type, quantity, and VOC content, in grams per liter, of the adhesive products sold.

6.1.3.2 Name, address, and telephone number of the persons to whom the adhesive products are sold.

## 6.1.4 Solvent Cleaning Records

An operator subject to Section 5.4 shall also comply with the following recordkeeping requirements:

6.1.4.1 Keep a copy of the manufacturer's product data sheet or material safety data sheet of the solvents used for organic solvent cleaning activities.

6.1.4.2 Maintain a current list of solvents that are being used for organic solvent cleaning activities. The list shall include the following information:

6.1.4.2.1 The name of the solvent and its manufacturer's name.

6.1.4.2.2 The VOC content of the solvent expressed in grams/liter or lb/gallon.

6.1.4.2.3 When the solvent is a mixture of different materials that are blended by the operator, the mix ratio of the

batch shall be recorded and the VOC content of the batch shall be calculated and recorded in order to determine compliance with the specified limits of VOC content, as applied.

6.1.4.2.4 The type of cleaning activity for each solvent that is being used in accordance with the applicable cleaning category specified in Table 3 of this rule.

6.1.4.2.5 On and after September 20, 2007, the quantity of solvents used for cleaning operations shall be kept on a daily basis.

6.1.5 Records Retention: The operator shall retain the records specified in Sections 6.1.1 through 6.1.4, as applicable, on site for a period of five years, make the records available on site during normal business hours to the APCO, ARB, or EPA, and submit the records to the APCO, ARB, or EPA upon request.

## 6.2 Labeling Requirements

6.2.1 VOC Content: Each container of adhesive product subject to this rule shall display the maximum VOC content of the adhesive product as applied. VOC content shall be displayed as grams of VOC per liter of adhesive product, excluding water and exempt compounds, or grams of VOC per liter of material for low-solids adhesive products. Each container of solvent subject to this rule shall display the maximum VOC content (in grams of VOC per liter of material) as supplied.

6.2.2 Thinning Recommendations: Each container of adhesive product subject to this rule shall display a statement of the manufacturer's recommendations regarding thinning, reducing, or mixing of the adhesive product with any other VOC containing material. Mixing recommendations shall specify a ratio which results in a compliant, as applied, adhesive product.

6.2.3 Manufacturers of any solvents subject to this rule shall indicate on the solvent container, or on a separate product data sheet or material safety data sheet, the name of the solvent, manufacturer's name, the VOC content, and density of the solvent, as supplied. The VOC content shall be expressed in units of gm/liter or lb/gallon.

## 6.3 Test Methods

The analysis of solvents, adhesive products, and control efficiency shall be determined by the following methods:

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

- 6.3.1 The VOC and solids content of adhesive products and solvents shall be determined using EPA Method 24 or other test method approved by ARB and EPA.
- 6.3.2 The capture efficiency for a VOC emission control system's collection device(s) shall be determined according to EPA's technical document, "Guidelines for Determining Capture Efficiency," January 9, 1995 and 40 CFR 51, Appendix M, Methods 204-204F, as applicable, or any other method approved by EPA, ARB, and the APCO.
- 6.3.3 The control efficiency of a VOC emission control system's control device(s) shall be determined using EPA Methods 2, 2A, or 2D for measuring flow rates and EPA Methods 25, 25A, or 25B for measuring total gaseous organic concentrations at the inlet and outlet of the control device. EPA Test Method 18 or ARB Method 422 shall be used to determine the emissions of exempt compounds.
- 6.3.4 For VOC emission control systems that consist of a single VOC emission collection device connected to a single VOC emission control device, the overall capture and control efficiency shall be calculated by using the following equation:

$$CE_{\text{CAPTURE AND CONTROL}} = [ CE_{\text{CAPTURE}} \times CE_{\text{CONTROL}} ] / 100 \%$$

Where:

$CE_{\text{CAPTURE AND CONTROL}}$  = Overall Capture and Control Efficiency, in percent

$CE_{\text{CAPTURE}}$  = Capture Efficiency of the collection device, in percent, as determined in Section 6.3.2

$CE_{\text{CONTROL}}$  = Control Efficiency of the control device, in percent, as determined in Section 6.3.3

### 6.3.5 Determination of Solvent Losses from Spray Gun Cleaning Systems

The passive and active solvent losses from spray gun cleaning systems shall be determined by using SCAQMD "General Test Method for Determining Solvent Losses from Spray Gun Cleaning Systems" dated October 3, 1989. The test solvent for this determination shall be lacquer thinner with a minimum vapor pressure of 105 mm Hg at 20°C. The minimum temperature shall be 15°C.

### 6.3.6 Transfer Efficiency

Transfer efficiency shall be determined by one of the following:

## SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

6.3.6.1 SCAQMD method “Spray Equipment Transfer Efficiency Test Procedure for Equipment User, May 24, 1989, or

6.3.6.2 Any other test method for transfer efficiency for which written approval of the EPA and the APCO has been obtained.

### 6.4 Multiple Test Methods

When more than one test method or set of test methods is specified for any testing, a violation of any requirement of this rule established by any one of the specified test methods or set of test methods shall constitute a violation of this rule.

### 6.5 Version of Test Methods

All ASTM test methods referenced in Section 6.0 are the most recently EPA-approved version that appears in the CFR as Materials Approved for Incorporation by Reference.

This page intentionally blank.