

ARB Staff Summary:

Advanced BioEnergy, Aberdeen, South Dakota Corn Ethanol Dry Mill LCFS Pathway ETHC065 Carbon Intensity Adjustment

May 17, 2013

Pathway Summary

Advanced BioEnergy, LLC (ABE Aberdeen) operates a corn ethanol plant in Aberdeen, South Dakota. The plant is a dry mill, natural-gas-fired facility producing dry distillers grains with solubles (DDGS) and wet distillers grains with solubles (WDGS). Approximately 84 percent of the DGS produced is DDGS and the remaining 16 percent is WDGS. ABE Aberdeen applied for a Method 2A fuel pathway under the California Low Carbon Fuel Standard (LCFS) in August of 2011. In January of 2012, staff assigned ABE Aberdeen's pathway an LCFS identification code of ETHC065, and recommended it for approval at a carbon intensity (CI) of 90.89 gCO₂e/MJ.¹

In April of 2013, ABE Aberdeen requested that its pathway CI be reduced to 88.59 gCO₂e/MJ, citing an error in the natural gas heating value used to calculate the pathway CI. At the time the original application was submitted, the applicant believed that the energy amounts shown on the invoices from the natural gas supplier were lower heating values (LHV). The applicant has since confirmed that they were actually gross or higher heating values (HHV). Recalculating the pathway CI using the LHV reduced ABE Aberdeen's CI to 88.59 gCO₂e/MJ. This ARB Staff Summary updates the original ABE Aberdeen Staff Summary, but incorporates by reference all sections of that Summary except the pathway carbon intensity value sought by the applicant.

Carbon Intensity of Ethanol Produced

The applicant provided a signed letter from its natural gas supplier stating (a) that the heating values shown on its invoices were "gross" heating values, and (b) that the industry-standard method for converting gross heating values to lower heating values is to divide them by 1.11. The applicant used this method to convert the heating value of the natural gas its plant consumed to a LHV basis. Using the resulting LHV to recalculate its pathway CI produced a value of 88.59 gCO₂e/MJ for pathway ETHC065.

¹ This and all staff-approved LCFS pathways are posted to <http://www.arb.ca.gov/fuels/lcfs/2a2b/2a-2b-apps.htm>

The use of the correct natural gas heating value has the effect of reducing the amount of natural gas used per gallon of ethanol produced by an amount the applicant specifies as confidential. ABE Aberdeen has provided a signed letter confirming that current and anticipated future plant operations are consistent with the operations described in the original application posted on ARB website (please see footnote 1 for the URL). The operating conditions placed on the ABE Aberdeen plant in the original ETHCO65 Staff summary will therefore remain in effect. Those conditions are as follows:²

1. Thermal energy and electricity use shall not exceed the current values that are classified by the applicant as confidential business information.
2. Condition 1, above, effectively limits ABE Aberdeen to the production of no more than 84 percent dry DGS for the ethanol sold into the California market (drying a higher proportion of its DGS co-product will increase energy consumption and carbon intensity beyond the values specified in the company’s Method 2A application).

Table 1: Proposed Lookup Table Entries

Fuel	Pathway Identifier	Pathway Description	Carbon Intensity in gCO ₂ e/MJ (Including Indirect Effects)		
			Direct Emission	Land Use or Other Indirect Effect	Total
Ethanol	ETHC065	2A Application (Specific Conditions Apply): Midwest; Dry Mill; 84% Dry DGS, 16% Wet DGS; NG	58.59	30	88.59

Staff Analysis and Recommendation

Staff has replicated, using the CA-GREET 1.8b spreadsheet, the reduced carbon intensity of 88.59 gCO₂e/MJ requested by ABE Aberdeen for Pathway ETHC065. ABE Aberdeen has confirmed that its plant is capable of continuing to operate at that CI. On the basis of these findings, and subject to the conditions in this summary, staff recommends that ABE Aberdeen’s application for a CI of

² Compliance with the “not-to-exceed” values will be based on monthly, quarterly, or annual average values, as determined by operational conditions. Calculation of the average values can exclude periods of abnormal operations, such as planned maintenance or force majeure events.

88.59 gCO₂e/MJ for pathway ETHC065 be approved. Staff further recommends that this adjusted CI take effect on the date it is posted to the public LCFS Method 2 web site, and apply solely to fuel volumes sold on and after that date.