

The California Low-Emission Vehicle Regulations

(As of December 1, 1999)

The California low-emission vehicle (LEV) regulations are administered by the California Air Resources Board (ARB) and apply to passenger cars, light-duty trucks and medium-duty vehicles. They are contained in various sections of chapter 1 (Motor Vehicle Pollution Control Devices), division 3 (Air Resources Board), title 13, California Code of Regulations (CCR), which commences with section 1900. The LEV exhaust emission standards were originally adopted in a 1990-1991 rulemaking, and generally became applicable in the 1994 model year. The LEV program also includes requirements for the introduction of zero-emission vehicles (ZEVs).

Following a November 5, 1998 hearing, the ARB adopted the California "LEV II" regulations, which generally become applicable with the 2004 model year (although earlier certification to the LEV II standards is permitted). The LEV II rulemaking also included the adoption of Compliance Assurance Program "CAP 2000" amendments which establish new motor vehicle certification and in-use test requirements — developed jointly with the U.S. Environmental Protection Agency — applicable to 2001 and subsequent model motor vehicles. The LEV II regulations were formally adopted August 5, 1999. They were filed with the California Secretary of State October 28, 1999, and became operative November 27, 1999. The original LEV standards are now referred to as the "LEV I" standards.

The LEV I Regulations

The LEV I standards are contained primarily in section 1960.1, which includes all of the California exhaust emission standards for 1981 through 2003 model-year passenger cars, light-duty trucks and medium-duty vehicles. The key portions of section 1960.1 pertaining to the LEV I program are:

- § 1960.1(e)(2) Formaldehyde exhaust emission standards for 1993-2003 model methanol-fueled passenger cars, light-duty trucks and medium-duty vehicles.
- § 1960.1(e)(3) Formaldehyde exhaust emission standards for 1992-2006 model LEV I TLEVs, LEVs, ULEVs and SULEVs in the passenger car, light-duty truck, and medium-duty vehicle classes.
- § 1960.1(f)(2) The non-LEV so-called "Tier 1" standards for 1995 through 2003 model passenger cars and light-duty trucks.
- § 1960.1(g)(1) The "LEV I" TLEV, LEV and ULEV standards for passenger cars and light-duty trucks.
- § 1960.1(g)(2) The fleet average non-methane organic gas (NMOG) requirements for passenger cars and light-duty trucks for the 1994 through 2000 model years (the fleet average NMOG requirements for the 2001-2003 model years are now in section 1961(b)(1)(A)). The fleet average NMOG mechanism requires manufacturers to introduce an incrementally cleaner mix of Tier 1, TLEV, LEV, ULEV and ZEV vehicles each year, with the fleet average NMOG value for passenger cars and lighter light-duty trucks decreasing from 0.25 gram/mile in the 1994 model year to 0.062 gram/mile in the 2003 model year.
- § 1960.1(h)(1) The non-LEV so-called "Tier 1" standards for 1995 through 2003 model medium-duty vehicles.
- § 1960.1(h)(2) The "LEV I" LEV, ULEV and SULEV standards for medium-duty vehicles (the phase-in requirements are in note (10) to the table in section 1960.1(h)(2)).

§ 1960.1(p) The cold temperature carbon monoxide standards for 1996 through 2000 model vehicles.

In addition, section 1960.1(q) and (r) contain the following Supplemental Federal Test Procedure (SFTP) standards which apply to both LEV I and LEV II vehicles:

§1960.1(q) The SFTP standards for 2001 and subsequent model passenger cars and light-duty trucks other than LEVs, ULEVs, and ZEVs (the phase-in requirements are in note (9) to the table in §1960.1(q)).

§1960.1(r) The SFTP exhaust emission standards for 2001 and subsequent model LEVs and ULEVs in the passenger cars and light-duty truck classes, and 2003 and subsequent LEVs, ULEVs, and SULEVs in the medium-duty classes (the phase-in requirements are in note (10) to the table in §1960.1(r)).

Section 1956.8, which establishes exhaust emission standards for heavy-duty vehicles, contains two subsections containing optional standards for engines used in incomplete medium-duty vehicles or diesel engines used in medium-duty vehicles. Engines subject to this option are tested in accordance with the heavy-duty test procedures incorporated by reference in section 1956.8(b) and (d).

§1956.8(g) Tier 1 exhaust emission standards for 1995 and subsequent model engines used in incomplete medium-duty vehicles.

§1956.8(h) LEV, ULEV, SULEV standards for engines used in incomplete medium-duty vehicles, and for diesel engines used in medium-duty LEVs, ULEVs and SULEVs.

The LEV I standards in the subsections of section 1960.1 listed above are also contained in a comprehensive document incorporated by reference in section 1960.1(k) — the “California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles.” This complete 135-page document is available on the ARB’s Internet site. To reduce testing burdens, ARB has to the extent feasible based the California test procedures on the corresponding federal test procedures administered by U.S. EPA. The Standards and Test Procedures document accordingly incorporates the federal test procedures contained in subparts A, B, and C, Part 86, Title 40, Code of Federal Regulations with modifications for the California program.

All 2001 and subsequent model passenger cars, light-duty trucks and medium-duty vehicles certified to the LEV I or LEV II standards will be subject to the CAP 2000 certification procedures — the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles,” incorporated by reference in section 1961(d). This document is also available on the ARB’s Internet site, and incorporates the federal test procedures contained in subparts B, C and S, Part 86, Title 40, Code of Federal Regulations with modifications for the California program.

The ZEV Regulation

The LEV I regulations also included standards for ZEVs, and requirements that specified percentages of 1998 and subsequent model passenger cars and light-duty trucks with a loaded vehicle weight of 0-3750 lbs. be certified as ZEVs. As originally adopted in the 1990-1991 LEV I rulemaking, the percentages were 2% for 1998-2000 model vehicles, 5% for 2001-2002 model vehicles, and 10% for 2003 and subsequent model vehicles. In a 1996 rulemaking, the ARB eliminated the requirements for the 1998-2002 model years, but maintained the 10% requirements for the 2003 and subsequent model years. The ZEV requirements were originally contained in note (9) of the table in section 1960.1(g)(2). In the LEV II rulemaking, the ARB moved all of the ZEV provisions to new section 1962, and added provisions pertaining to partial ZEV credits.

Section 1962(e) incorporates by reference the “California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric Vehicles, in the Passenger Car, Light-Duty Truck, and Medium-Duty Vehicle Classes,” available on the ARB’s Internet site.

The LEV II Regulations

The LEV II exhaust emission standards and requirements are contained in section 1961, and will be phased in over the 2004 through 2007 model years. One of the major changes made by the LEV II standards is that all light-duty trucks will be subject to the same emission standards as passenger cars, and vehicles under 8500 lbs. gross vehicle weight (including sport utility vehicles) that had previously been treated as medium-duty vehicles will start to be treated as light-duty trucks. Section 1961 includes the following subsections:

- § 1961(a) The LEV II exhaust emission standards.
- § 1961(b) The LEV II emissions standards phase-in requirements (including fleet average NMOG requirements for passenger cars and light-duty trucks in section 1961(b)(1), a schedule containing the minimum percentages of 2004-2007 passenger cars and light-duty trucks that must be certified to the LEV II rather than LEV I standards in section 1961(b)(2), and medium-duty vehicle phase-in requirements in section 1961(b)(3)).
- § 1961(c) Calculation of NMOG credits and debits.
- § 1961(d) Test Procedures.
- § 1961(e) Abbreviations.

Another element of the LEV II regulations is the LEV II evaporative emission standards, which are contained in section 1976(b)(1)(F) and are phased in during the 2004 - 2006 model years. The preexisting evaporative emission standards are in section 1976(b)(1)(B) and (C).

Related Requirements

In addition to the LEV exhaust emission standards in sections 1960.1 and 1961, a number of other ARB requirements apply to LEVs. Included in this document are title 13, California Code of Regulations, sections 1965 (Emission Control and Smog Index Labels - 1979 and Subsequent Model-Year Motor Vehicles), 1978 (Standards and Test Procedures for Vehicle Refueling Emissions), 2062 (Assembly-Line Test Procedures - 1998 and Subsequent Model Years), and 2101 (Compliance Testing and Inspection - New Vehicle Selection, Evaluation, and Enforcement). Other requirements not set forth in this document include requirements for on-board diagnostic (OBDII) systems (§1968.1), fill pipes (§2235), emission warranties (§§2037 and 2038), recalls (§§2111 and following) and related provisions.

TABLE OF CONTENTS

<u>Section</u>	<u>Page No.</u>
Section 1900.....	1
Section 1956.8	3
Section 1960.1	7
Section 1961.....	42
Section 1962.....	57
Section 1965.....	66
Section 1976.....	67
Section 1978.....	75
Section 2062.....	77
Section 2101.....	78

Title 13, California Code of Regulations

§ 1900. Definitions.

(a) The definitions in this section supplement and are governed by the definitions set forth in chapter 2 (commencing with section 39010), part 1, division 26 of the Health and Safety Code. The definitions set forth in the applicable model-year new vehicle certification and assembly-line test procedures adopted in this chapter are hereby incorporated by reference.

(b) In addition to the definitions incorporated under subdivision (a), the following definitions shall govern the provisions of this chapter.

[Definitions applicable only to warranty or recall provisions not in this compilation are not set forth]

* * * *

(4) "Gaseous fuels" means any liquefied petroleum gas, liquefied natural gas, or compressed natural gas fuels for use in motor vehicles.

(5) "Heavy-duty engine" means an engine which is used to propel a heavy-duty vehicle.

(6) "Heavy-duty vehicle" means any motor vehicle having a manufacturer's gross vehicle weight rating greater than 6,000 pounds, except passenger cars.

* * * *

(8) "Light-duty truck" means any 2000 and subsequent model motor vehicle certified to the standards in section 1961(a)(1) rated at 8,500 pounds gross vehicle weight or less, and any other motor vehicle rated at 6,000 pounds gross vehicle weight or less, which is designed primarily for purposes of transportation of property or is a derivative of such a vehicle, or is available with special features enabling off-street or off-highway operation and use.

(9) "Medium-duty vehicle" means any pre-1995 model year heavy-duty vehicle having a manufacturer's gross vehicle weight rating of 8,500 pounds or less; any 1992 through 2006 model-year heavy-duty low-emission, ultra-low-emission, super-ultra-low-emission or zero-emission vehicle certified to the standards in section 1960.1(h)(2) having a manufacturer's gross vehicle weight rating of 14,000 pounds or less; any 1995 through 2003 model year heavy-duty vehicle certified to the standards in section 1960.1(h)(1) having a manufacturer's gross vehicle weight rating of 14,000 pounds or less; and any 2000 and subsequent model heavy-duty low-emission, ultra-low-emission, super-ultra-low-emission or zero-emission vehicle certified to the standards in Section 1961(a)(1) or 1962 having a manufacturer's gross vehicle weight rating between 8,501 and 14,000 pounds.

* * * *

(11) "Passenger car" means any motor vehicle designed primarily for transportation of persons and having a design capacity of twelve persons or less.

* * * *

(14) "Subgroup" means a set of vehicles within an engine family distinguishable by characteristics contained in the manufacturer's application for certification.

* * * *

(16) "Reactivity adjustment factor" means a fraction applied to the NMOG emissions from a vehicle powered by a fuel other than conventional gasoline for the purpose of determining a gasoline-equivalent NMOG level. The reactivity adjustment factor is defined as the ozone-forming potential of clean fuel vehicle exhaust divided by the ozone-forming potential of gasoline vehicle exhaust.

(17) "Small volume manufacturer" means, with respect to the 2001 and subsequent model-years, a manufacturer with California sales less than 4,500 new passenger cars, light-duty trucks, medium-duty vehicles, heavy-duty vehicles and heavy-duty engines based on the average number of vehicles sold for the three previous consecutive model years for which a manufacturer seeks certification; however, for manufacturers certifying for the first time in California model-year sales shall be based on projected California sales. A manufacturer's California sales shall consist of all vehicles or engines produced by the manufacturer and delivered for sale in California, except that vehicles or engines produced by the manufacturer and marketed in California by another manufacturer under the other manufacturer's nameplate shall be treated as California sales of the marketing manufacturer. For purposes of compliance with the zero-emission vehicle requirements, heavy-duty vehicles and engines shall not be counted as part of a manufacturer's sales.

(18) "Intermediate volume manufacturer" means any pre-2001 model year manufacturer with California sales between 3,001 and 35,000 new light- and medium-duty vehicles per model year based on the average number of vehicles sold by the manufacturer each model year from 1989 to 1993; any 2001 through 2002 model year manufacturer with California sales between 4,501 and 35,000 new light- and medium-duty vehicles per model year based on the average number of vehicles sold by the manufacturer each model year from 1989 to 1993; and any 2003 and subsequent model year manufacturer with California sales between 4,501 and 35,000 new light- and medium-duty vehicles based on the average number of vehicles sold for the three previous consecutive model years for which a manufacturer seeks certification. For a manufacturer certifying for the first time in California, model year sales shall be based on projected California sales.

(19) "Large volume manufacturer" means any 2000 and subsequent model year manufacturer that is not a small volume manufacturer or an intermediate volume manufacturer.

Note: Authority cited: Sections 39600, 39601, 43013, 43018, 43101, and 43104 Health and Safety Code.
Reference: Sections 39002, 39003, 39010, 39500, 40000, 43000, 43013, 43100, 43101, 43101.5, 43102, 43104, 43106, and 43204, Health and Safety Code.

§ 1956.8. Exhaust Emission Standards and Test Procedures - 1985 and Subsequent Model Heavy-Duty Engines and Vehicles.

(a) *[Exhaust emission standards for heavy-duty diesel engines and heavy-duty natural-gas-fueled, liquefied-petroleum-gas-fueled and methanol-fueled engines derived from diesel-cycle engines; not applicable to passenger cars, light-duty trucks and medium-duty vehicles and accordingly not set forth.]*

(b) The test procedures for determining compliance with standards applicable to 1985 and subsequent heavy-duty diesel engines and vehicles and the requirements for participation in the averaging, banking and trading programs, are set forth in the "California Exhaust Emission Standards and Test Procedures for 1985 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" adopted April 8, 1985, as last amended April 15, 1999, which is incorporated herein by reference.

(c) *[Exhaust emission standards for heavy-duty Otto-cycle engines and heavy-duty natural-gas-fueled, liquefied-petroleum-gas-fueled and methanol-fueled engines derived from Otto-cycle engines; not applicable to passenger cars, light-duty trucks and medium-duty vehicles and accordingly not set forth.]*

(d) The test procedures for determining compliance with standards applicable to 1987 and subsequent model heavy-duty Otto-cycle engines and vehicles are set forth in the "California Exhaust Emission Standards and Test Procedures for 1987 and Subsequent Model Heavy-Duty Otto-Cycle Engines and Vehicles," adopted April 25, 1986, as last amended June 24, 1996, which is incorporated by reference herein.

(e) A manufacturer may elect to certify heavy-duty vehicles of 10,000 pounds or less maximum gross vehicle weight rating as medium-duty vehicles under section 1960.1 of this chapter, in which event the heavy-duty emission standards and test procedures in this section shall not apply.

(f) *[Use of engines certified to meet federal emission standards, or which are demonstrated to meet appropriate federal emission standards, in up to a total of 100 heavy-duty vehicles in a calendar year when the executive officer has determined that no engine certified to meet California emission standards exists which is suitable for use in the vehicles; not applicable to passenger cars, light-duty trucks and medium-duty vehicles and accordingly not set forth.]*

(g) The exhaust emissions from new 1995 and subsequent model-year engines used in incomplete medium-duty vehicles or diesel engines used in medium-duty vehicles shall not exceed:

Exhaust Emission Standards^A
(grams per brake horsepower-hour)

<u>Model Year</u>	<u>Carbon Monoxide</u>	<u>Non-methane Hydrocarbon and Oxides of Nitrogen^B</u>	<u>Particulates^C</u>
1995 ^D and Subsequent	14.4	3.9	0.10

^A This set of standards is optional. Manufacturers of engines used in incomplete medium-duty vehicles or diesel engines used in medium-duty vehicles from 8501-14,000 pounds, gross vehicle weight may choose to comply with these standards as a alternative to the primary emission standards and test procedures specified in section 1960.1, Title 13, California Code of Regulations. Manufacturers that choose to comply with these optional heavy-duty standards and test procedures shall specify, in the application for certification, an in-use compliance test procedure, as provided in section 2139(c), Title 13, California Code of Regulations.

^B This standard is the sum of the individual non-methane hydrocarbon emissions and oxides of nitrogen emissions. For methanol-fueled engines, non-methane hydrocarbons shall mean organic material hydrocarbon equivalent.

^C This standard shall only apply to diesel engines and vehicles.

^D In the 1995 model-year only, manufacturers may certify up to 50 percent of their medium-duty engines or vehicles to the applicable 1994 model-year standards and test procedures. For the 1995 through 1997 models, alternative in-use compliance is available for medium-duty manufacturers. A manufacturer may use alternative in-use compliance for up to 100 percent of its fleet in the 1995 and 1996 model years and up to 50 percent of its fleet in the 1997 model year. The percentages shall be determined from the manufacturers' projected California sales of medium-duty vehicles. For engines certified to the standards and test procedures of this subsection, "alternative in-use compliance" shall consist of an allowance of 25 percent over the HC + NOx standard. In-use compliance testing shall be limited to vehicles or engines with less than 90,000 miles.

(h) The exhaust emissions from new 1992 and subsequent model-year engines used in incomplete medium-duty low-emission vehicles, ultra-low-emission vehicles, and super-ultra-low-emission vehicles, and for diesel engines used in medium-duty low-emission vehicles, ultra-low-emission vehicles and super-ultra-low-emission vehicles shall not exceed:

**Exhaust Emission Standards for Engines Used in Incomplete Medium-Duty
Low-Emission Vehicles, Ultra-Low-Emission Vehicles, and Super
Ultra-Low-Emission Vehicles, and for Diesel Engines Used in Medium-Duty
Low-Emission Vehicles, Ultra-Low-Emission Vehicles, and
Super Ultra-Low-Emission Vehicles^{A,F}
(grams per brake horsepower-hour)**

<i>Model Year</i>	<i>Vehicle Emissions Category^B</i>	<i>Carbon Monoxide</i>	<i>Non-Methane Hydrocarbons and Oxides of Nitrogen^C</i>	<i>Formaldehyde</i>	<i>Particulates^D</i>
1992 ^E - 2001	LEV	14.4	3.5 ^K	0.050	0.10 ^K
2002-2003 ^E	LEV	14.4	3.0 ^K	0.050	0.10 ^K
1992-2003 ^{E,H}	ULEV	14.4	2.5 ^K	0.050	0.10 ^K
2004 and subsequent	ULEV - Opt A.	14.4	2.5 ^{G,I,J,K}	0.050	0.10 ^{JK}
2004 and subsequent	ULEV - Opt. B	14.4	2.4 ^{G,I,J,K}	0.050	0.10 ^{JK}
1992 and subsequent	SULEV	7.2	2.0 ^K	0.025	0.05 ^K

- A This set of standards is optional. Manufacturers of engines used in incomplete medium-duty vehicles or diesel engines used in medium-duty vehicles from 8501-14,000 pounds gross vehicle weight rating may choose to comply with these standards as an alternative to the primary emission standards and test procedures specified in section 1960.1, Title 13, California Code of Regulations. Manufacturers that choose to comply with these optional heavy-duty standards and test procedures shall specify, in the application for certification, an in-use compliance test procedure, as provided in section 2139(c), Title 13, California Code of Regulations.
- B “LEV” means low-emission vehicle.
“ULEV” means ultra-low-emission vehicle.
“SULEV” means super ultra-low-emission vehicle.
- C This standard is the sum of the individual non-methane hydrocarbon emissions and oxides of nitrogen emissions. For methanol-fueled engines, non-methane hydrocarbons shall mean organic material hydrocarbon equivalent (“OMHCE”).
- D This standard shall only apply to diesel engines and vehicles.

- ^E Manufacturers may certify engines used in incomplete medium-duty vehicles or diesel engines used in medium-duty vehicles to these standards to meet the requirements of section 1956.8(g), Title 13, California Code of Regulations.
- ^F In-use compliance testing shall be limited to vehicles or engines with fewer than 90,000 miles.
- ^G [The U.S. EPA is considering the adoption of amendments to the federal emission standards for engines used in incomplete medium-duty vehicles or diesel engines used in medium-duty vehicles as they existed June 24, 1996. If the U.S. EPA promulgates amendments to the emission standards for this category, the ARB will hold a noticed public hearing within one year of such promulgation to consider the adoption of similar or identical standards in California.]
- ^H For engines certified to the 3.5 grams per brake horsepower-hour (g/bhp-hr) LEV standards, the in-use compliance standard shall be 3.7 g/bhp-hr for the first two model years of introduction. For engines certified to the 2002 and 2003 model year LEV standards, the in-use compliance standard shall be 3.2 g/bhp-hr. For engines certified to the 1992 through 2003 model year ULEV standards, the in-use compliance standard shall be 2.7 g/bhp-hr for the first two model years of introduction. For engines certified to the 1992 and subsequent SULEV standards, the in-use compliance standard shall be 2.2 g/bhp-hr for the first two model years of introduction.
- ^I Manufacturers have the option of certifying to either option A or B. Manufacturers electing to certify to Option A must demonstrate that the NMHC emissions do not exceed 0.5 g/bhp-hr.
- ^J Emissions averaging may be used to meet these standards for diesel engines, using the requirements for participation in averaging, banking and trading programs, as set forth in the "California Exhaust Emission Standards and Test Procedures for 1985 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles", adopted April 8, 1985, as last amended April 15, 1999, incorporated by reference in paragraph (b), above.
- ^K Engines of 1998 and subsequent model years may be eligible to generate averaging, banking and trading credits based on these standards according to the requirements of the averaging, banking and trading programs described in "California Exhaust Emission Standards and Test Procedures for 1985 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles", adopted April 8, 1985, as last amended April 15, 1999, incorporated by reference in paragraph (b), above.

NOTE: Authority cited: Sections 39600, 39601, 43013, 43018, 43101, 43103, 43104, and 43806, Health and Safety Code, and Vehicle Code section 28114. Reference: Sections 39002, 39003, 43000, 43013, 43018, 43100, 43101, 43101.5, 43102, 43103, 43104, 43106, 43204, and 43806, Health and Safety Code.

§ 1960.1. Exhaust Emission Standards and Test Procedures - 1981 through 2006 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles.

(a) *[Exhaust emission standards for 1981 model passenger cars, light-duty trucks and medium-duty vehicles; not set forth]*

(b) *[Exhaust emission standards for 1982 model passenger cars, light-duty trucks and medium-duty vehicles; not set forth]*

(c) *[Exhaust emission standards for 1983 model passenger cars, light-duty trucks and medium-duty vehicles; not set forth]*

(d) *[Exhaust emission standards for 1984 through 1990 model passenger cars, light-duty trucks and medium-duty vehicles; not set forth]*

(e)(1) *[Exhaust emission standards for 1989 through 1994 model passenger cars, light-duty trucks and medium-duty vehicles; not set forth]*

(e)(2) The exhaust emissions from new 1993 through 2003 model methanol-fueled vehicles, including fuel-flexible vehicles, shall meet all the applicable requirements in (e)(1), (f)(1) and (f)(2) with the following modifications and additions:

**1993 THROUGH 2003 METHANOL-SPECIFIC
EXHAUST EMISSION STANDARDS**

<i>Vehicle Type¹</i>	<i>Loaded Vehicle Weight (lbs.)³</i>	<i>Durability Vehicle Basis (mi)</i>	<i>Formaldehyde (mg/mi) Certification</i>	<i>In-Use Compliance²</i>
PC	All	50,000	15	23 (1993-1995) 15 (1996- 2003)
LDT,MDV	0-3750	50,000	15	23 (1993-1995) 15 (1996- 2003)
LDT,MDV	3751-5750	50,000	18	27 (1993-1995) 18 (1996- 2003)
MDV	5751-8500	50,000	22	33 (1993-1995) 22 (1996- 2003)
MDV	8501-10,000	50,000	28	36 (1995) 28 (1996- 2003)
MDV	10,001-14,000	50,000	36	45 (1995) 36 (1996- 2003)

- (1) "PC" means passenger cars.
 "LDT" means light-duty trucks.
 "MDV" means medium-duty vehicles.
- (2) If the formaldehyde in-use compliance level is above the respective certification level but does not exceed the in-use compliance level, and based on a review of information derived from a statistically valid and representative sample of vehicles, the Executive Officer determines that a substantial percentage of any class or category of such vehicle exhibits, prior to 50,000 miles or 5 years, whichever occurs first, an identifiable, systematic defect in a component listed in Section 1960.1.5(c)(2), Title 13 California Code of Regulations, which causes a significant increase in emissions above those exhibited by vehicles free of such defects and of the same class or category and having the same period of use and mileage, the Executive Officer may invoke the enforcement authority under subchapter 2.5, Title 13, California Code of Regulations, commencing with Section 2111, to require remedial action by the vehicle manufacturer. Such remedial action shall be limited to owner notification and repair or replacement of the defect component. As used in this section, the term "defect" shall not include failures which are the result of abuse, neglect, or improper maintenance.
- (3) For 1995-2003 model year medium-duty vehicles certifying to the standards and test procedures specified in Section 1960.1(h)(1), Title 13, California Code of Regulations, "Loaded Vehicle

Weight” shall mean “Test Weight”, which is the average of the vehicle’s curb weight and gross vehicle weight.

(e)(3) The exhaust emissions from new 1992 through 2006 model-year “LEV I” transitional low-emission vehicles, low-emission vehicles, ultra-low emission vehicles, and super ultra-low-emission vehicles, including fuel-flexible and dual-fuel vehicles, shall meet all the requirements in (g)(1), and (h)(2) with the following additions:

**FORMALDEHYDE EXHAUST EMISSION STANDARDS
IN THE LIGHT-DUTY AND MEDIUM-DUTY VEHICLE WEIGHT CLASSES^{5,6,7}**
[“milligrams per mile” (or “mg/mi”)]

<i>Vehicle Type¹</i>	<i>Vehicle Weight (lbs.)²</i>	<i>Durability Vehicle Basis Emission (mi)</i>	<i>Vehicle Category³</i>	<i>Formaldehyde (mg/mi)^{4,5}</i>
PC and LDT	All 0-3750	50,000	TLEV	15 (23)
			LEV	15 (15)
			ULEV	8 (12)
		100,000	TLEV	18
			LEV	18
			ULEV	11
LDT	3751-5750	50,000	TLEV	18 (27)
			LEV	18 (18)
			ULEV	9 (14)
		100,000	TLEV	23
			LEV	23
			ULEV	13
MDV	0-3750	50,000	LEV	15 (15)
			ULEV	8 (12)
			LEV	22
MDV	3751-5750	50,000	ULEV	12
			LEV	18 (18)
			ULEV	9 (14)
		120,000	SULEV	4 (7)
			LEV	27
			ULEV	13
MDV	5751-8500	50,000	SULEV	6
			LEV	22 (22)
			ULEV	11 (17)
		120,000	SULEV	6 (8)
			LEV	32
			ULEV	16
MDV	8501-10,000	50,000	SULEV	8
			LEV	28 (28)
			ULEV	14 (21)
		120,000	SULEV	7 (10)
			LEV	40
			ULEV	21
MDV	10,001-14,000	50,000	SULEV	10
			LEV	36 (36)
			ULEV	18 (27)
		120,000	SULEV	9 (14)
			LEV	52
			ULEV	26
			SULEV	13

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
"MDV" means medium-duty vehicles.
 - (2) For light-duty or medium-duty vehicles, Vehicle Weight shall mean "Loaded Vehicle Weight" (or "LVW") or "Test Weight" (or "TW"), respectively.
 - (3) "TLEV" means transitional low-emission vehicle.
"LEV" means low-emission vehicle.
"ULEV" means ultra-low-emission vehicle.
"SULEV" means super ultra-low-emission vehicle.
 - (4) Formaldehyde exhaust emission standards apply to vehicles certified to operate on any available fuel, including fuel-flexible and dual-fuel vehicles.
 - (5) The standards in parentheses are intermediate in-use compliance standards for 50,000 miles.
 - a. For PCs and LDTs from 0-5750 lbs. LVW, including fuel-flexible and dual-fuel vehicles, intermediate in-use compliance standards shall apply to TLEVs through the 1995 model year, and LEVs and ULEVs through the 1998 model year. In-use compliance with standards beyond 50,000 miles shall be waived through the 1995 model year for TLEVs, and through the 1998 model year for LEVs and ULEVs.
 - b. For MDVs from 0-14,000 lbs. TW, including fuel-flexible and dual-fuel vehicles, intermediate in-use compliance standards shall apply to LEVs, ULEVs, and SULEVs through the 1999 model year. In-use compliance with standards beyond 50,000 miles shall be waived through the 1999 model year for LEVs, ULEVs, and SULEVs.
 - (6) Manufacturers shall demonstrate compliance with the above standards for formaldehyde at 50° F, according to the procedure specified in section 11k of the "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k). Hybrid electric, natural gas, and diesel-fueled vehicles shall be exempt from 50°F test requirements.
 - (7) In-use compliance testing shall be limited to PCs and LDTs with fewer than 75,000 miles and MDVs with fewer than 90,000 miles.
-

(f)(1) [Exhaust emission standards for new 1993 and 1994 model passenger cars and light-duty trucks, except those produced by a small volume manufacturer; not set forth]

(f)(2) "Tier 1" Exhaust Emission Standards for PCs and LDTs. The exhaust emissions from new 1995 through 2003 model Tier 1 passenger cars and light-duty trucks shall not exceed:

**1995-2003 MODEL-YEAR TIER 1 PASSENGER CAR AND
LIGHT-DUTY TRUCK EXHAUST EMISSIONS STANDARDS^{5,6,8,10}**
(grams per mile)

<u>Vehicle Type¹</u>	<u>Loaded Vehicle Weight (lbs)</u>	<u>Durability Vehicle Basis (mi)</u>	<u>Non-Methane Hydrocarbons^{2,7}</u>	<u>Carbon Monoxide⁷</u>	<u>Oxides of Nitrogen^{1,3}</u>
PC	All	50,000	0.25	3.4	0.4 ⁴
PC	All	100,000	0.31	4.2	0.6 ⁹
Diesel PC	All	100,000	0.31	4.2	1.0
(Option 2)					
LDT	0-3750	50,000	0.25	3.4	0.4 ⁴
LDT	0-3750	100,000	0.31	4.2	0.6 ⁹
Diesel LDT	0-3750	100,000	0.31	4.2	1.0
(Option 2)					
LDT	3751-5750	50,000	0.32	4.4	0.7
LDT	3751-5750	100,000	0.40	5.5	0.97 ⁹
Diesel LDT	3751-5750	100,000	0.40	5.5	1.5
(Option 1)					

- (1) "PC" means passenger cars.
"LDT" means light-duty trucks.
- (2) For methanol- or ethanol-fueled vehicles certifying to these standards, including fuel-flexible vehicles when certifying on methanol or ethanol, "Non-Methane Hydrocarbons" shall mean "Organic Material Non-Methane Hydrocarbon Equivalent" (or "OMNMHCE").
- (3) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 1.33 times the applicable passenger car standards and 2.00 times the applicable light-duty truck standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.

- (4) Small volume manufacturers may choose to certify to an optional 0.7 g/mi NO_x standard for the 1995 model year only, pursuant to the conditions set forth in sections 1960.1(f)(1) and 1960.1.5.
 - (5) Diesel passenger cars and light-duty trucks certifying to these standards are subject to a particulate exhaust emission standard of 0.08 g/mi, determined on a 50,000 mile durability vehicle basis.
 - (6) For all vehicles, except those certifying to optional diesel standards, in-use compliance with the exhaust emission standards shall be limited to vehicles with less than 75,000 miles.
 - (7) For the 1995 and 1996 model years, all manufacturers, except those certifying to optional diesel standards, are permitted alternative in-use compliance. Alternative in-use compliance is permitted for 60% of a manufacturer's vehicles in the 1995 model year and 20% of a manufacturer's vehicles in the 1996 model year. For the 1995 and 1996 model years, small volume manufacturers only are permitted alternative in-use compliance for 100% of the fleet. The percentages shall be applied to the manufacturer's total projected sales of California-certified passenger cars and light-duty trucks for the model year. "Alternative in-use compliance" shall consist of the following:
 - a. For all passenger cars and those light-duty trucks from 0-3750 lbs., loaded vehicle weight, except those diesel vehicles certifying to optional 100,000 mile standards, in-use compliance standards shall be 0.32 g/mi non-methane hydrocarbon and 5.2 g/mi carbon monoxide for 50,000 miles.
 - b. For light-duty trucks from 3751-5750 lbs., loaded vehicle weight, except those diesel light-duty trucks certifying to optional 100,000 mile standards, in-use compliance standards shall be 0.41 g/mi non-methane hydrocarbon and 6.7 g/mi carbon monoxide for 50,000 miles.
 - c. In-use compliance standards shall be waived beyond 50,000 miles.
 - (8) All passenger cars and light-duty trucks, except those diesel vehicles certifying to optional standards, are subject to non-methane hydrocarbon, carbon monoxide, and oxides of nitrogen standards determined on a 50,000 mile durability basis and non-methane hydrocarbon and carbon monoxide standards determined on a 100,000 mile durability basis.
 - (9) 100,000 mile NO_x standards are applicable for 1996 and subsequent model-year vehicles.
 - (10) Each manufacturer shall also comply with the requirements specified in section 1960.1(g)(2).
-

(g)(1) “LEV I” Exhaust Emission Standards for PCs and LDTs. The exhaust emissions from new 1992 through 2003 model-year “LEV I” transitional low-emission vehicles, and new 1992 through 2006 model-year “LEV I” low-emission vehicles and ultra-low-emission vehicles, in the passenger car and light-duty truck classes shall not exceed:

**LEV I EXHAUST EMISSION STANDARDS
FOR TRANSITIONAL LOW-EMISSION VEHICLES, LOW-EMISSION VEHICLES,
ULTRA-LOW-EMISSION VEHICLES AND ZERO-EMISSION VEHICLES
IN PASSENGER CAR AND LIGHT-DUTY TRUCK VEHICLE CLASSES^{6,7,8,9,10}**
[grams per mile (or “g/mi”)]

<u>Vehicle Type¹</u>	<u>Loaded Vehicle Weight (lbs)</u>	<u>Durability Vehicle Basis(mi)</u>	<u>Vehicle Emission Category²</u>	<u>Non-Methane Organic Gases^{3,4}</u>	<u>Carbon Monoxide</u>	<u>Oxides of Nitrogen⁵</u>
PC and All LDT	50,000	TLEV	0.125	3.4	0.4	
	0-3750	LEV	0.075	3.4	0.2	
			ULEV	0.040	1.7	0.2
		100,000	TLEV	0.156	4.2	0.6
			LEV	0.090	4.2	0.3
			ULEV	0.055	2.1	0.3
LDT	3751-5750	50,000	TLEV	0.160	4.4	0.7
			LEV	0.100	4.4	0.4
			ULEV	0.050	2.2	0.4
		100,000	TLEV	0.200	5.5	0.9
			LEV	0.130	5.5	0.5
			ULEV	0.070	2.8	0.5

- (1) “PC” means passenger cars.
“LDT” means light-duty trucks.
“LVW” means loaded vehicle weight.
“Non-Methane Organic Gases” or “NMOG” means the total mass of oxygenated and non-oxygenated hydrocarbon emissions.
- (2) “TLEV” means transitional low-emission vehicle.
“LEV” means low-emission vehicle.
“ULEV” means ultra-low-emission vehicle.
- (3) *Compliance with NMOG Standard.* To demonstrate compliance with an NMOG standard, NMOG emissions shall be measured in accordance with the “California Non-Methane Organic Gas Test Procedures” as adopted July 12, 1991 and last amended August 5, 1999, which is incorporated herein by reference.
- a. *Reactivity Adjustment.* For TLEVs, LEVs, and ULEVs certified to operate exclusively on any fuel other than conventional gasoline, and for fuel-flexible and dual-fuel TLEVs, LEVs, and ULEVs when certifying on a fuel other than gasoline, manufacturers shall multiply

NMOG exhaust certification levels by the applicable reactivity adjustment factor set forth in section 13 of the “California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1960.1(k), or in section I.E.5. of the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1961(d), or established by the Executive Officer pursuant to Appendix VIII or section II.D. respectively of the foregoing test procedures. In addition, natural gas vehicles certifying to TLEV, LEV or ULEV standards shall calculate a reactivity-adjusted methane exhaust emission value by multiplying the methane exhaust certification level by the applicable methane reactivity adjustment factor set forth in section 13 or in section I.E.5. of the above-referenced test procedures as applicable. The product of the NMOG exhaust certification levels and the reactivity adjustment factor shall be compared to the exhaust NMOG mass emission standards established for the particular vehicle emission category to determine compliance. For natural gas vehicles, the reactivity-adjusted NMOG value shall be added to the reactivity-adjusted methane value and then compared to the exhaust NMOG mass emission standards established for the particular vehicle emission category to determine compliance.

b. *Fleet Average Requirement.* Each manufacturer shall certify PCs or LDTs to meet the exhaust mass emission standards for TLEVs, LEVs, ULEVs, or the exhaust emission standards of sections 1960.1(e)(1), 1960.1(f)(1), or 1960.1(f)(2), Title 13, California Code of Regulations, or as Zero-Emission Vehicles, such that the manufacturer’s fleet average NMOG values for California-certified PCs and LDTs from 0-3750 lbs. LVW, and LDTs from 3751-5750 lbs. LVW produced and delivered for sale in California are less than or equal to the requirement for the corresponding Model Year, Vehicle Type, and LVW Class in section 1960.1(g)(2), Title 13, California Code of Regulations.0

(4) *NMOG Standards for Fuel-Flexible and Dual-Fuel Vehicles.* Fuel-flexible and dual-fuel PCs and LDTs from 0-5750 lbs. LVW shall be certified to exhaust mass emission standards for NMOG established for the operation of the vehicle on any available fuel other than gasoline, and gasoline.

a. *Reactivity Adjustment.* For TLEVs, LEVs, and ULEVs, when certifying for operation on a fuel other than gasoline, manufacturers shall multiply exhaust NMOG certification levels by the applicable reactivity adjustment factor. In addition to multiplying the exhaust NMOG certification levels by the applicable reactivity adjustment factor, exhaust methane certification levels for natural gas vehicles shall be multiplied by the applicable methane reactivity adjustment factor and the resulting value shall be added to the reactivity-adjusted NMOG value. The exhaust NMOG certification levels for fuel-flexible or dual-fuel vehicles when certifying on gasoline shall not be multiplied by a reactivity adjustment factor.

b. *Standards for Fuel-Flexible and Dual-Fuel Vehicles Operating on Gasoline.* For PCs and LDTs from 0- 5750 lbs. LVW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on gasoline shall be:

Vehicle Type	Loaded Vehicle Weight (LVW)	Emission Category	Durability Vehicle Basis (g/mi)	
			50,000 Mile	100,000 Mile

PCs, LDT	All, 0-3750	TLEV	0.25	0.31
		LEV	0.125	0.156
		ULEV	0.075	0.090
LDT	3751-5750	TLEV	0.32	0.40
		LEV	0.160	0.200
		ULEV	0.100	0.130

- (5) *Highway NOx.* The maximum projected emissions of “Oxides of Nitrogen” (or “NOx”) measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR 600 Subpart B) shall be not greater than 1.33 times the applicable light-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (6) *Intermediate In-Use Compliance Standards.* The following standards are intermediate in-use compliance standards for 50,000 and 100,000 miles for PCs and LDTs from 0-5750 lbs. LVW, including fuel-flexible and dual-fuel vehicles when operating on any available fuel other than gasoline. Intermediate in-use compliance standards shall apply to TLEVs through the 1995 model year as follows:

	NMOG (g/mi)
PCs and LDTs 0-3750 lbs. LVW	0.188
LDTs 3751-5750 lbs. LVW	0.238

In-use compliance with standards beyond 50,000 miles shall be waived through the 1995 model year for TLEVs, and through the 1998 model year for LEVs and ULEVs. For LEVs and ULEVs, the following intermediate in-use standards shall apply:

Vehicle Type	Durability Vehicle Basis	LEV (g/mi)			ULEV (g/mi)			
		Model Year	NMOG	NOx	Model Year	NMOG	CO	NOx
PCs, 0-3750 lb. LVW LDTs	50,000	through 1998	0.100	0.3	through 1998	0.058	2.6	0.3
	50,000	1999	0.100	0.3	1999-2002	0.055	2.1	0.3
	100,000	1999	0.125	0.4	1999-2002	0.075	3.4	0.4
3751-5750 lb. LVW LDTs	50,000	through 1998	0.128	0.5	through 1998	0.075	3.3	0.5
	50,000	1999	0.130	0.5	1999-	0.070	2.8	0.5

					2002			
	100,000	1999	0.160	0.7	1999-2002	0.100	4.4	0.7

a. *Reactivity Adjustment.* For TLEVs, LEVs, and ULEVs designed to operate on any fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when operating on any fuel other than gasoline, exhaust NMOG mass emission results shall be multiplied by the applicable reactivity adjustment factor to determine compliance with intermediate in-use compliance standards for NMOG. In addition to multiplying the exhaust NMOG emission results by the applicable reactivity adjustment factor, the exhaust methane emission results for natural gas vehicles shall be multiplied by the applicable methane reactivity adjustment factor and the resulting value shall be added to the reactivity-adjusted NMOG value. Exhaust NMOG mass emissions from fuel-flexible or dual-fuel vehicles when operating on gasoline shall not be multiplied by a reactivity adjustment factor.

b. *Intermediate In-Use Standards for Fuel-Flexible and Dual-Fuel Vehicles Operating on Gasoline.* For fuel-flexible and dual-fuel PCs and LDTs from 0-5750 lbs. LVW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles when the vehicle is operated on gasoline shall be:

<i>Vehicle Type</i>	<i>Loaded Vehicle Weight (LVW)</i>	<i>Emission Category</i>	<i>Durability Vehicle Basis (g/mi) 50,000 mi</i>
PCs, LDT	All, 0-3750	TLEV	0.32
		LEV	0.188
		ULEV	0.100
LDT	3751-5750	TLEV	0.41
		LEV	0.238
		ULEV	0.128

Intermediate in-use compliance standards shall apply to TLEVs through the 1995 model year, and to LEVs and ULEVs through the 1998 model year. In-use compliance with standards beyond 50,000 miles shall be waived through the 1995 model year for TLEVs and through the 1998 model year for LEVs and ULEVs.

- (7) *Diesel Standards.* Manufacturers of diesel vehicles shall also certify to particulate standards at 100,000 miles. For all PCs and LDTs from 0-3750 lbs. LVW, the particulate standard is 0.08 g/mi, 0.08 g/mi, and 0.04 g/mi for TLEVs, LEVs, and ULEVs, respectively. For LDTs from 3751-5750 lbs. LVW, the particulate standard is 0.10 g/mi, 0.10 g/mi, and 0.05 g/mi for TLEVs, LEVs and ULEVs, respectively. For diesel vehicles certifying to the standards set forth in Title 13, section 1960.1(g)(1), "NMOG" shall mean non-methane hydrocarbons.
- (8) *50°F Requirement.* Manufacturers shall demonstrate compliance with the above standards for NMOG, CO, and NOx at 50°F, according to the procedure specified in section 11k of the "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars,

Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1960.1(k), or according to the procedure specified in section II.C. of the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1961(d), as applicable. Hybrid electric, natural gas and diesel-fueled vehicles shall be exempt from 50°F test requirements.

- (9) *Limit on In-Use Testing.* In-use compliance testing shall be limited to vehicles with fewer than 75,000 miles.
- (10) *HEV Requirements.* Deterioration factors for hybrid electric vehicles shall be based on the emissions and mileage accumulation of the auxiliary power unit. For certification purposes only, Type A hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors), and demonstrating compliance with 100,000 mile emission standards shall not be required. For certification purposes only, Type B hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 100,000 mile emission standards (using 75,000 mile deterioration factors). For certification purposes only, Type C hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 100,000 mile emission standards (using 100,000 mile deterioration factors).
- (11) *NMOG Credit for Direct Ozone Reduction Technology.* A manufacturer that certifies vehicles equipped with direct ozone reduction technologies shall be eligible to receive NMOG credits that can be applied to the NMOG exhaust emissions of the vehicle when determining compliance with the standard. In order to receive credit, the manufacturer must submit the following information for each vehicle model, including, but not limited to:
 - (a) a demonstration of the airflow rate through the direct ozone reduction device and the ozone-reducing efficiency of the device over the range of speeds encountered in the SFTP test cycle;
 - (b) an evaluation of the durability of the device for the full useful life of the vehicle; and
 - (c) a description of the on-board diagnostic strategy for monitoring the performance of the device in-use.

Using the above information, the Executive Officer shall determine the value of the NMOG credit based on the calculated change in the one-hour peak ozone level using an approved airshed model.

(g)(2) The fleet average non-methane organic gas exhaust emission values from passenger cars and light-duty trucks produced and delivered for sale in California by a manufacturer each model year from 1994 through 2000 shall not exceed:

**FLEET AVERAGE NON-METHANE ORGANIC GAS EXHAUST MASS EMISSION
REQUIREMENTS FOR LIGHT-DUTY VEHICLE WEIGHT CLASSES^{7,8,9}**

[grams per mile" (or "g/mi")]

<i>Vehicle Type¹</i>	<i>Loaded Vehicle Weight (lbs.)</i>	<i>Durability Vehicle Basis (mi)⁷</i>	<i>Model Year</i>	<i>Fleet Average Non-Methane Organic Gases^{2,3,4,5,6}</i>
PC and LDT	All 0-3750	50,000	1994	0.250
			1995	0.231
			1996	0.225
			1997	0.202
			1998	0.157
			1999	0.113
LDT	3751-5750	50,000	2000	0.073
			1994	0.320
			1995	0.295
			1996	0.287
			1997	0.260
			1998	0.205
			1999	0.150
			2000	0.099

- (1) "PC" means passenger cars.
 "LDT" means light-duty trucks.
 "TLEV" means transitional low-emission vehicle.
 "LEV" means low-emission vehicle.
 "ULEV" means ultra-low-emission vehicle.
 "LVW" means loaded vehicle weight.
- (2) "Non-Methane Organic Gases" (or "NMOG") means the total mass of oxygenated and non-oxygenated hydrocarbon emissions.
- (3) *HEV Categories.* For the purpose of calculating fleet average NMOG values, a manufacturer may adjust the certification levels of hybrid electric vehicles (or "HEVs") based on the range of the HEV without the use of the engine. For the purpose of calculating the adjusted NMOG emissions, the following definitions shall apply:
- "Type A HEV" shall mean an HEV which achieves a minimum range of 60 miles over the All-Electric Range Test as defined in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k), or in "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1961(d), as applicable.
- "Type B HEV" shall mean an HEV which achieves a range of 40 - 59 miles over the All-Electric Range Test as defined in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k), or in "California Exhaust Emission Standards and

Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1961(d), as applicable.

“Type C HEV” shall mean an HEV which achieves a range of 0 - 39 miles over the All-Electric Range Test as defined in “California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1960.1(k), or in “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1961(d), as applicable, and all other HEVs excluding “Type A” and “Type B” HEVs.

a. For the purpose of calculating fleet average NMOG values, vehicles which have no tailpipe emissions but use fuel-fired heaters and which are not certified as ZEVs shall be treated as “Type A HEV ULEVs.”

- (4) *Calculation of Fleet Average NMOG Value (PCs and LDTs 0-3750 lbs. LVW).* Each manufacturer’s fleet average NMOG value for the total number of PCs and LDTs from 0-3750 lbs. LVW produced and delivered for sale in California shall be calculated in units of g/mi NMOG according to the following equation, where the term “Produced” means produced and delivered for sale in California:

$$\begin{aligned} & \{[(\text{No. of Vehicles Certified to the Exhaust Emission Standards in section 1960.1 (e)(1) and Produced}) \times (0.39)] + \\ & [\text{No. of Vehicles Certified to the Phase-In Exhaust Emission Standards in section 1960.1 (f)(1) and Produced} \times (0.25)] + \\ & [\text{No. of Vehicles Certified to the Phase-Out Exhaust Emission Standards in section 1960.1 (f)(1) and Produced} \times (0.39)] + \\ & [(\text{No. of Vehicles Certified to the Exhaust Emission Standards in section 1960.1(f)(2) and Produced}) \times (0.25)] + \\ & [(\text{No. of TLEVs excluding HEVs and Produced}) \times (0.125)] + \\ & [(\text{No. of LEVs excluding HEVs and Produced}) \times (0.075)] + \\ & [(\text{No. of ULEVs excluding HEVs and Produced}) \times (0.040)] + \\ & (\text{HEV contribution factor}) \} \div \end{aligned}$$

(Total No. of Vehicles Produced, Including Zero-Emission Vehicles and HEVs):

a. “HEV contribution factor” shall mean the NMOG emission contribution of HEVs to the fleet average NMOG value. The HEV contribution factor shall be calculated in units of g/mi as follows, where the term “Produced” means produced and delivered for sale in California:

HEV contribution factor =

$$\begin{aligned} & \{[\text{No. of “Type A HEV” TLEVs Produced}] \times (0.100) + \\ & [\text{No. of “Type B HEV” TLEVs Produced}] \times (0.113) + \\ & [\text{No. of “Type C HEV” TLEVs Produced}] \times (0.125)\} + \\ & \{[\text{No. of “Type A HEV” LEVs Produced}] \times (0.057) + \\ & [\text{No. of “Type B HEV” LEVs Produced}] \times (0.066) + \\ & [\text{No. of “Type C HEV” LEVs Produced}] \times (0.075)\} + \\ & \{[\text{No. of “Type A HEV” ULEVs Produced}] \times (0.020) + \\ & [\text{No. of “Type B HEV” ULEVs Produced}] \times (0.030) + \\ & [\text{No. of “Type C HEV” ULEVs Produced}] \times (0.040)\} \end{aligned}$$

b. "Zero-Emission Vehicles" (or "ZEVs") classified as LDTs 3751-5750 lbs. LVW which have been counted toward the ZEV requirements for PCs and LDTs 0-3750 lbs. LVW as specified in note (9) shall be included in the equation of note (4).

c. Beginning with the 1996 model year, manufacturers that produce and deliver for sale in California PCs and LDTs 0-3750 lbs. LVW that are certified to federal Tier I exhaust emission standards in 40 CFR 86.094-8 and 86.094-9 shall add the following term to the numerator of the fleet average NMOG equation in note (4) calculate their fleet average NMOG values accordingly:

[No. of Vehicles Certified to federal Tier I exhaust emission standards and Produced) x (0.25)]

(5) *Calculation of Fleet Average NMOG Value (LDTs 3751-5750 lbs. LVW).* Manufacturers that certify LDTs from 3751-5750 lbs. LVW, shall calculate a fleet average NMOG value in units of g/mi NMOG according to the following equation, where the term "Produced" means produced and delivered for sale in California:

$$\begin{aligned} & \{[(\text{No. of Vehicles Certified to the Exhaust Emission Standards in section 1960.1 (e)(1), and Produced} \times (0.50))] + \\ & \quad [(\text{No. of Vehicles Certified to the Phase-In Exhaust Emission Standards in section 1960.1 (f)(1), and Produced} \times (0.32))] + \\ & \quad [(\text{No. of Vehicles Certified to the Phase-Out Exhaust Emission Standards in section 1960.1 (f)(1), and Produced} \times (0.50))] + \\ & \quad [(\text{No. of Vehicles Certified to the Exhaust Emission Standards in section 1960.1 (f)(2), and Produced} \times (0.32))] + \\ & \quad [(\text{No. of TLEVs Produced excluding HEVs}) \times (0.160)] + [(\text{No. of LEVs Produced excluding HEVs}) \times (0.100)] + \\ & \quad [(\text{No. of ULEVs Produced excluding HEVs}) \times (0.050)] + \\ & \quad (\text{HEV contribution factor}) \} \div \\ & (\text{Total No. of Vehicles Produced, Including ZEVs and HEVs}). \end{aligned}$$

a. "HEV contribution factor" shall mean the NMOG emission contribution of HEVs to the fleet average NMOG. The HEV contribution factor shall be calculated in units of g/mi as follows, where the term "Produced" means produced and delivered for sale in California.
HEV contribution factor =

$$\begin{aligned} & \{[\text{No. of "Type A HEV" TLEVs Produced}] \times (0.130) + \\ & \quad [(\text{No. of "Type B HEV" TLEVs Produced}) \times (0.145) + \\ & \quad [(\text{No. of "Type C HEV" TLEVs Produced}) \times (0.160)]] + \\ & \quad \{[\text{No. of "Type A HEV" LEVs Produced}] \times (0.075) + \\ & \quad [(\text{No. of "Type B HEV" LEVs Produced}) \times (0.087) + \\ & \quad [(\text{No. of "Type C HEV" LEVs Produced}) \times (0.100)]] + \\ & \quad \{[\text{No. of "Type A HEV" ULEVs Produced}] \times (0.025) + \\ & \quad [(\text{No. of "Type B HEV" ULEVs Produced}) \times (0.037) + \\ & \quad [(\text{No. of "Type C HEV" ULEVs Produced}) \times (0.050)]] \} \end{aligned}$$

b. Only ZEVs which have been certified as LDTs 3751-5750 lbs. LVW and which have not been counted toward the ZEV requirements for PCs and LDTs 0-3750 lbs. LVW as specified in note (9) shall be included in the equation of note (5).

c. Beginning with the 1996 model year, manufacturers that produce and deliver for sale in California LDTs 3751-5750 lbs. LVW that are certified to the Tier I exhaust emission standards in 40 CFR 86.094-9 shall add the following term to the numerator of the fleet average NMOG equation in note (5) and calculate their fleet average NMOG values accordingly:

[(No. of Vehicles Certified to federal Tier I exhaust emission standards and Produced and Delivered for Sale in California) x (0.32)]

(6) *Requirements for Small Volume Manufacturers.* As used in this subsection, the term "small volume manufacturer" shall mean any vehicle manufacturer with California sales less than or equal to 3000 new PCs, LDTs and MDVs per model year based on the average number of vehicles sold by the manufacturer each model year from 1989 to 1991, except as noted below. For manufacturers certifying for the first time in California, model-year sales shall be based on projected California sales. In 2000 and subsequent model years, small volume manufacturers shall comply with the fleet average NMOG requirements set forth below.

a. Prior to the model year 2000, compliance with the specified fleet average NMOG requirements shall be waived.

b. In the 2000 model year, small volume manufacturers shall not exceed a fleet average NMOG value of 0.075 g/mi for PCs and LDTs from 0-3750 lbs. LVW calculated in accordance with note (4).

c. In the 2000 model year, small volume manufacturers shall not exceed a fleet average NMOG value of 0.100 g/mi for LDTs from 3751-5750 lbs. LVW calculated in accordance with note (5).

d. If a manufacturer's average California sales exceeds 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall no longer be treated as a small volume manufacturer and shall comply with the fleet average requirements applicable for larger manufacturers as specified in section 1960.1(g)(2) beginning with the fourth model year after the last of the three consecutive model years.

e. If a manufacturer's average California sales falls below 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall be treated as a small volume manufacturer and shall be subject to requirements for small volume manufacturers as specified in section 1960.1(g)(2) beginning with the next model year.

(7) *Calculation of NMOG Credits/Debits and Procedure for Offsetting Debits.*

a. In 1992 through 2000 model years, manufacturers that achieve fleet average NMOG values lower than the fleet average NMOG requirement for the corresponding model year shall receive credits in units of g/mi NMOG determined as:

$$\{[(\text{Fleet Average NMOG Requirement}) - (\text{Manufacturer's Fleet Average NMOG Value})] \times (\text{Total No. of Vehicles Produced and Delivered for Sale in California, Including ZEVs and HEVs})\}.$$

Manufacturers with fleet average NMOG values greater than the fleet average requirement for the corresponding model year shall receive debits in units of g/mi NMOG equal to the amount of negative credits determined by the aforementioned equation. For any given model year, the total g/mi NMOG credits or debits earned for PCs and LDTs 0-3750 lbs. LVW and for LDTs 3751-5750 lbs. LVW shall be summed together. The resulting amount shall constitute the g/mi NMOG credits or debits accrued by the manufacturer for the model year.

b. For the 1994 through 1997 model years, manufacturers shall equalize emission debits within three model years and prior to the end of the 1998 model year by earning g/mi NMOG emission credits in an amount equal to their g/mi NMOG debits, or by submitting a commensurate

amount of g/mi NMOG credits to the Executive Officer that were earned previously or acquired from another manufacturer. For 1998 through 2000 model years, manufacturers shall equalize emission debits by the end of the following model year. If emission debits are not equalized within the specified time period, the manufacturer shall be subject to the Health and Safety Code section 43211 civil penalty applicable to a manufacturer which sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the emission debits are not equalized by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's emission standards shall be determined by dividing the total amount of g/mi NMOG emission debits for the model year by the g/mi NMOG fleet average requirement for PCs and LDTs 0-3750 lbs. LVW applicable for the model year in which the debits were first incurred.

c. The g/mi NMOG emission credits earned in any given model year shall retain full value through the subsequent model year. The g/mi NMOG value of any credits not used to equalize the previous model-year's debit, shall be discounted by 50% at the beginning of the second model year after being earned, discounted to 25% of its original value if not used by the beginning of the third model year after being earned, and will have no value if not used by the beginning of the fourth model year after being earned.

d. In order to verify the status of a manufacturer's compliance with the fleet average requirements for a given model year, and in order to confirm the accrual of NMOG credits or debits, each manufacturer shall submit an annual report to the Executive Officer which sets forth the production data used to establish compliance, by no later than March 1 of the calendar year following the close of the completed model year.

(8) *Credits for Pre-1994 Model-Year Vehicles.* Manufacturers that produce and deliver for sale in California vehicles certified to the phase-in exhaust emission standards in section 1960.1 (f)(1), or vehicles certified to the exhaust emission standards in sections 1960.1(f)(2) or 1960.1(g)(1) and/or ZEVs, in the 1992 and 1993 model years, shall receive emission credits as determined by the equations in footnotes (4), (5), and (7).

a. For PCs and LDTs from 0-3750 lbs. LVW, the fleet average NMOG requirement for calculating a manufacturer's emission credits shall be 0.390 and 0.334 g/mi NMOG for vehicles certified for the 1992 and 1993 model years, respectively.

b. For LDTs from 3751-5750 lbs. LVW, the fleet average NMOG requirement for calculating a manufacturer's emission credits shall be 0.500 and 0.428 g/mi NMOG for vehicles certified for the 1992 and 1993 model years, respectively.

c. Emission credits earned prior to the 1994 model year shall be considered as earned in the 1994 model year and discounted in accordance with the schedule specified in footnote (7).

(h)(1) *"Tier 1" Exhaust Emission Standards for MDVs.* The exhaust emission from new 1995 through 2003 model Tier 1 medium-duty vehicles shall not exceed:

**1995-2003 MODEL-YEAR TIER 1
MEDIUM-DUTY VEHICLE EXHAUST EMISSIONS STANDARDS** ^{1,2,3,7,8}
(grams per mile)

<i>Test Weight(lbs.)</i>	<i>Durability Vehicle Basis(mi)</i>	<i>Non-Methane Hydrocarbons⁴</i>	<i>Carbon Monoxide</i>	<i>Oxides of Nitrogen⁵</i>	<i>Particulates⁶</i>
0-3,750	50,000	0.25	3.4		0.4 n/a
0-3,750	120,000	0.36	5.0	0.55	0.08
3,751-5,750	50,000	0.32	4.4		0.7 n/a
3,751-5,750	120,000	0.46	6.4	0.98	0.10
5,751-8,500	50,000	0.39	5.0		1.1 n/a
5,751-8,500	120,000	0.56	7.3	1.53	0.12
8,501-10,000	50,000	0.46	5.5		1.3 n/a
8,501-10,000	120,000	0.66	8.1	1.81	0.12
10,001-14,000	50,000	0.60	7.0	2.0	n/a
10,001-14,000	120,000	0.86	10.3	2.77	0.12

- (1) "n/a" means not applicable.
"Test Weight" shall mean the average of the vehicle's curb weight and gross vehicle weight.
- (2) Manufacturers have the option of certifying engines used in incomplete and diesel medium-duty vehicles from 8501-14,000 pounds gross vehicle weight to the heavy-duty engine standards and test procedures set forth in Section 1956.8(e), Title 13, California Code of Regulations. Manufacturers certifying incomplete or diesel medium-duty vehicles to the heavy-duty engine standards and test procedures shall specify, in the application for certification, an in-use compliance test procedure, as provided in section 2139(c), Title 13, California Code of Regulations.
- (3) For the 1995 model year only, manufacturers of medium-duty vehicles may certify a maximum of 50 percent of their vehicles to the applicable 1994 model year standards and test procedures. For the 1995 model year only, small volume manufacturers may certify 100 percent of their vehicles to the applicable 1994 model-year standards and test procedures. The percentage shall be based upon each manufacturer's projected sales of California-certified medium-duty vehicles.
- (4) For methanol- and ethanol-fueled vehicles certifying to these standards, including fuel-flexible vehicles when certifying on methanol or ethanol, "Non-Methane

Hydrocarbons” shall mean “Organic Material Non-Methane Hydrocarbon Equivalent” (or “OMNMFHCE”).

- (5) The maximum projected emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall be not greater than 2.00 times the applicable medium-duty vehicle standards shown in the table. Both the projected emissions and the HWFET standards shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
 - (6) Particulate standards are only applicable for diesel vehicles and shall be determined on a 120,000 mile basis.
 - (7) In-use compliance testing shall be limited to vehicles with less than 90,000 miles. For the 1995 through 1997 model years, alternative in-use compliance is available for medium-duty vehicle manufacturers. A manufacturer may use alternative in-use compliance for up to 100 percent of its fleet in the 1995 and 1996 model years and up to 50 percent of its fleet in the 1997 model year. Small volume manufacturers may use alternative in-use compliance for up to 100 percent of their fleets in the 1995 through 1997 model years. The percentages shall be determined from the manufacturer's projected California sales of medium-duty vehicles. For vehicles certified to the standards and test procedures of this subsection, “alternative in-use compliance” shall consist of an in-use allowance of 25 percent over the applicable 1995 model-year non-methane hydrocarbon, carbon monoxide, and oxides of nitrogen 50,000 mile emission standards and a waiver of the emission standards beyond 50,000 miles.
 - (8) All medium-duty vehicles, except diesel-fueled vehicles and those incomplete and diesel vehicles certifying to heavy-duty engine test procedures, are subject to 50,000 mile and 120,000 mile non-methane hydrocarbon, carbon monoxide, and oxides of nitrogen standards. Diesel-fueled vehicles shall be subject to 120,000 mile non-methane hydrocarbon, carbon monoxide, oxides of nitrogen, and particulate standards only.
-

(h)(2) “*LEV I*” *Exhaust Emission Standards for MDVs*. The exhaust emissions from new 1992 through 2006 model-year medium-duty LEV I low-emission vehicles, ultra-low-emission vehicles and super ultra-low-emission vehicles shall not exceed:

**LEV I EXHAUST EMISSION STANDARDS FOR
 LOW-EMISSION VEHICLES, ULTRA-LOW EMISSION VEHICLES AND
 SUPER-ULTRA-LOW-EMISSION VEHICLES
 IN THE MEDIUM-DUTY VEHICLE WEIGHT CLASS^{8,9,10,11,12,13,14,15,16}**
 [grams per mile (or "g/mi")]

<i>Test Weight (lbs)¹</i>	<i>Durability Vehicle Basis (mi)</i>	<i>Vehicle Emission Category²</i>	<i>Non-Methane Organic Gases^{1,3,4}</i>	<i>Carbon Monoxide</i>	<i>Oxides of Nitrogen^{3,5}</i>	<i>Particulates^{6,7}</i>
0-3750	50,000	LEV	0.125	3.4	0.4	n/a
		ULEV	0.075	1.7	0.2	n/a
	120,000	LEV	0.180	5.0	0.6	0.08
		ULEV	0.107	2.5	0.3	0.04
3751-5750	50,000	LEV	0.160	4.4	0.4	n/a
		ULEV	0.100	4.4	0.4	n/a
		SULEV	0.050	2.2	0.2	n/a
	120,000	LEV	0.230	6.4	0.6	0.10
		ULEV	0.143	6.4	0.6	0.05
		SULEV	0.072	3.2	0.3	0.05
5751-8500	50,000	LEV	0.195	5.0	0.6	n/a
		ULEV	0.117	5.0	0.6	n/a
		SULEV	0.059	2.5	0.3	n/a
	120,000	LEV	0.280	7.3	0.9	0.12
		ULEV	0.167	7.3	0.9	0.06
		SULEV	0.084	3.7	0.45	0.06
8501-10,000	50,000	LEV	0.230	5.5	0.7	n/a
		ULEV	0.138	5.5	0.7	n/a
		SULEV	0.069	2.8	0.35	n/a
	120,000	LEV	0.330	8.1	1.0	0.12
		ULEV	0.197	8.1	1.0	0.06
		SULEV	0.100	4.1	0.5	0.06
10,001-14,000	50,000	LEV	0.300	7.0	1.0	n/a
		ULEV	0.180	7.0	1.0	n/a
		SULEV	0.09	3.5	0.5	n/a
	120,000	LEV	0.430	10.3	1.5	0.12
		ULEV	0.257	10.3	1.5	0.06
		SULEV	0.130	5.2	0.7	0.06

- (1) “Test Weight” (or “TW”) shall mean the average of the vehicle’s curb weight and gross vehicle weight.
“Non-Methane Organic Gases” (or “NMOG”) means the total mass of oxygenated and non-oxygenated hydrocarbon emissions.
- (2) “LEV” means low-emission vehicle.
“ULEV” means ultra-low-emission vehicle.
“SULEV” means super-ultra-low-emission vehicle.
- (3) *Compliance with NMOG Standards.* To determine compliance with an NMOG standard, NMOG emissions shall be measured in accordance with “California Non-Methane Organic Gas Test Procedures” adopted July 12, 1991 and last amended August 5, 1999, which is incorporated herein by reference.
 - a. *Reactivity Adjustment.* For LEVs and ULEVs certified to operate on an available fuel other than conventional gasoline, including fuel-flexible or dual-fuel vehicles when certifying on a fuel other than gasoline, manufacturers shall multiply the NMOG exhaust certification levels by the applicable reactivity adjustment factor set forth in Section 13 of the “California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1960.1(k), or in section I.E.5. of the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles” as incorporated by reference in section 1961(d), or established by the Executive Officer pursuant to Appendix VIII or section II.D. respectively of the foregoing test procedures. In addition, natural gas vehicles certifying to LEV or ULEV standards shall calculate a reactivity-adjusted methane exhaust emission value by multiplying the methane exhaust certification level by the applicable methane reactivity adjustment factor set forth in section 13 or in section I.E.5. of the above-referenced test procedures as applicable. The product of the exhaust NMOG certification levels and the reactivity adjustment factor shall be compared to the exhaust NMOG mass emission standard established for the particular vehicle emission category to determine compliance. For natural gas vehicles, the reactivity-adjusted NMOG value shall be added to the reactivity-adjusted methane value and then compared to the exhaust NMOG mass emission standards established for the particular vehicle emission category to determine compliance.
 - b. *Pre-1998 NOx standards.* Prior to the 1998 model year, the 50,000 mile and 120,000 mile LEV exhaust mass emission standards for NOx shall be: 0.7 and 1.0 g/mi for MDVs from 3751-5750 lbs. TW, 1.1 and 1.5 g/mi for MDVs from 5751-8500 lbs. TW, 1.3 and 1.8 g/mi for MDVs from 8501-10,000 lbs. TW, and 2.0 and 2.8 g/mi for MDVs from 10,001-14,000 lbs. TW, respectively.
- (4) *NMOG Standards for Fuel-Flexible and Dual-Fuel Vehicles.* Fuel-flexible and dual-fuel “Medium-Duty Vehicles” (or “MDVs”) from 0-14,000 lbs. TW shall be certified to exhaust mass emission standards for NMOG established for the operation of the vehicle on a fuel other than gasoline, and gasoline.
 - a. *Reactivity Adjustment.* For LEVs and ULEVs when certifying on the fuel other than gasoline, manufacturers shall multiply the exhaust NMOG certification levels by the applicable reactivity adjustment factor. In addition to multiplying the exhaust NMOG certification levels by the applicable reactivity adjustment factor, the exhaust methane certification level for natural gas vehicles shall be multiplied by the applicable methane reactivity adjustment factor and the resulting value shall be added to the reactivity-adjusted NMOG value. When certifying on gasoline, the exhaust NMOG certification levels of fuel-flexible and dual-fuel vehicles shall not be multiplied by a reactivity adjustment factor.

b. *Standards for Fuel-Flexible and Dual-Fuel Vehicles Operating on Gasoline.* For MDVs from 0-14,000 lbs. TW, the applicable exhaust mass emission standard for NMOG when certifying the vehicle for operation on gasoline shall be:

<i>Test Weight (lbs.)</i>	<i>Vehicle Emission Category</i>	<i>50,000 (g/mi)</i>	<i>120,000 (g/mi)</i>
0-3750	LEV	0.25	0.36
	ULEV	0.125	0.180
3751-5750	LEV	0.32	0.46
	ULEV	0.160	0.230
	SULEV	0.100	0.143
5751-8500	LEV	0.39	0.56
	ULEV	0.195	0.280
	SULEV	0.117	0.167
8501-10,000	LEV	0.46	0.66
	ULEV	0.230	0.330
	SULEV	0.138	0.197
10,001-14,000	LEV	0.60	0.86
	ULEV	0.300	0.430
	SULEV	0.180	0.257

- (5) *Highway NOx.* The maximum projected emissions of "Oxides of Nitrogen" (or "NOx") measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR Part 600 Subpart B) shall not be greater than 2.00 times the applicable MDV standards shown in the table. Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi before being compared.
- (6) Particulate standards are only applicable for diesel vehicles and shall be determined on a 120,000 mile basis.
- (7) "n/a" means not applicable.
- (8) *Certification of Incomplete and Diesel Vehicles.* Manufacturers have the option of certifying engines used in incomplete and diesel MDVs to the heavy-duty engine standards and test procedures set forth in Section 1956.8(g) or (h), Title 13, California Code of Regulations. Manufacturers certifying incomplete or diesel MDVs to the heavy-duty engine standards and test procedures shall specify in the application for certification an in-use compliance procedure as provided in Section 2139(c), Title 13, California Code of Regulations. For diesel vehicles certifying to the standards set forth in Title 13, section 1960.1(h)(2), "NMOG" shall mean non-methane hydrocarbons.
- (9) *Intermediate In-Use Compliance Standards.* The following intermediate in-use compliance standards for 50,000 miles and 120,000 miles for MDVs from 3751-14,000 lbs. TW, including

fuel-flexible and dual-fuel vehicles when operating on an available fuel other than gasoline, shall apply for the specified model years only:

<i>Intermediate In-Use Compliance Standards*</i> (in grams per mile)										
<i>Emission Category</i>	<i>Model Year</i>	<i>Durability Vehicle Basis (mi)</i>	<i>3751-5750 lbs.</i>		<i>5751 - 8500 lbs.</i>		<i>8501-10,000 lbs.</i>		<i>10,001-14,000 lbs.</i>	
			<i>NMOG</i>	<i>NOx</i>	<i>NMOG</i>	<i>NOx</i>	<i>NMOG</i>	<i>NOx</i>	<i>NMOG</i>	<i>NOx</i>
LEV	through 1997	50,000	0.238	0.7	0.293	1.1	0.345	1.3	0.450	2.0
	1998-1999	50,000	0.238	0.6	0.293	0.9	0.345	1.0	0.450	1.5
	2000	50,000	--	0.6	--	0.9	--	1.0	--	1.5
	2000	120,000	--	0.8	--	1.2	--	1.3	--	2.0
ULEV	through 1999	50,000	0.128	0.6	0.156	0.9	0.184	1.0	0.240	1.5
	2000	50,000	0.128	0.6	0.156	0.9	0.184	1.0	0.240	1.5
	2000	120,000	0.160	0.8	0.195	1.2	0.230	1.3	0.300	2.0
	2001-2002	50,000	0.128	--	0.156	--	0.184	--	0.240	--
	2001-2002	120,000	0.160	--	0.195	--	0.230	--	0.300	--
SULEV	through 2002	50,000	0.072	0.3	0.084	0.45	0.100	0.5	0.130	0.7
	2002	120,000	0.100	0.4	0.117	0.6	0.138	0.65	0.180	1.0

In-use compliance with standards beyond 50,000 miles shall be waived through the 1999 model year for LEVs and ULEVs and through the 2001 model year for SULEVs.

*Dashes mean that the standard in the section (h)(2) table applies.

a. *Reactivity Adjustment.* For LEVs and ULEVs designed to operate on an available fuel other than conventional gasoline, including fuel-flexible and dual-fuel vehicles when operating on an available fuel other than gasoline, NMOG exhaust mass emission results shall be multiplied by the applicable reactivity adjustment factor to determine compliance with intermediate in-use compliance standards for NMOG. In addition to multiplying the exhaust NMOG mass emission results by the applicable reactivity adjustment factor, natural gas vehicles shall multiply the exhaust methane mass emission results by the applicable methane reactivity adjustment factor and add that value to the reactivity-adjusted NMOG value. For fuel-flexible and dual-fuel vehicles when operating on gasoline, NMOG emission results shall not be multiplied by a reactivity adjustment factor.

b. *Gasoline Standards for Fuel-Flexible and Dual-Fuel Vehicles.* For fuel-flexible and dual-fuel MDVs from 0-14,000 lbs. TW, intermediate in-use compliance standards for NMOG emissions at 50,000 miles, when the vehicle is operated on gasoline, shall be:

<i>Fuel-Flexible and Dual-Fuel MDVs Intermediate In-Use Compliance Standards</i>		
<i>Test Weight (lbs.)</i>	<i>Vehicle Emission Category</i>	<i>50,000 (g/mi)</i>
0-3750	LEV	0.32
	ULEV	0.188
3751-5750	LEV	0.41
	ULEV	0.238
	SULEV	0.128
5751-8500	LEV	0.49
	ULEV	0.293
	SULEV	0.156
8501-10,000	LEV	0.58
	ULEV	0.345
	SULEV	0.184
10,001-14,000	LEV	0.75
	ULEV	0.450
	SULEV	0.240

Intermediate in-use compliance standards shall apply to LEVs and ULEVs through the 1999 model year and to SULEVs through the 2001 model year. Compliance with the standards beyond 50,000 miles shall be waived through the 1999 model year for LEVs and ULEVs and through the 2001 model year for SULEVs.

(10) *Medium-Duty Vehicle Phase-In Requirements.* Each manufacturer's MDV fleet shall be defined as the total number of California certified MDVs from 0-14,000 lbs. TW produced and delivered for sale in California.

a. Manufacturers of MDVs shall certify an equivalent percentage of their MDV fleet according to the following phase-in schedule:

<i>Model Year</i>	<i>Vehicles Certified to Title 13 CCR Section 1960.1(h)(1) or (h)(2)</i>	<i>Vehicles Certified to Title 13 CCR Section 1956.8(g) or (h) (%)</i>

	(<i>%</i>)					
	Tier 1	LEV	ULEV	Tier 1	LEV	ULEV
1998	73	25	2	100	0	0
1999	48	50	2	100	0	0
2000	23	75	2	100	0	0

c. The percentages shall be applied to the manufacturers' total production of California-certified medium-duty vehicles delivered for sale in California.

d. These requirements shall not apply to small volume manufacturers. Small volume manufacturers shall comply with the requirements of note (16) below.

- (11) *Definition of HEV.* For the purpose of calculating "Vehicle Equivalent Credits" (or "VECs"), the contribution of hybrid electric vehicles (or "HEVs") will be calculated based on the range of the HEV without the use of the engine. For purpose of calculating the contribution of HEVs to the VECs, the following definitions shall apply:

"*Type A HEV*" shall mean an HEV which achieves a minimum range of 60 miles over the All-Electric Range Test as defined in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k), or in "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1961(d), as applicable.

"*Type B HEV*" shall mean an HEV which achieves a range of 40 - 59 miles over the All-Electric Range Test as defined in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k), or in "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1961(d), as applicable.

"*Type C HEV*" shall mean an HEV which achieves a range of 0 - 39 miles over the All-Electric Range Test as defined in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k), or in "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1961(d), as applicable, and all other HEVs excluding "Type A" and "Type B" HEVs.

- (12) *Calculation of Vehicle Equivalent Credits.* In 1992 through 2000 model years, manufacturers that produce and deliver for sale in California MDVs in excess of the equivalent requirements for LEVs and/or ULEVs certified to the exhaust emission standards set forth in this section (h)(2) or Title 13, CCR Section 1956.8(h), shall receive VECs calculated in accordance with the following equation, where the term "Produced" means produced and delivered for sale in California:

$$\begin{aligned} & \{[(\text{No. of LEVs Produced excluding HEVs}) + (\text{No. of "Type C HEV" LEVs Produced})] + \\ & [(\text{No. of "Type A HEV" LEVs Produced}) \times (1.2)] + \\ & [(\text{No. of "Type B HEV" LEVs Produced}) \times (1.1)] - \\ & (\text{Equivalent No. of LEVs Required to be Produced})\} + \\ & \{(1.4) \times [(\text{No. of ULEVs Produced excluding HEVs}) + (\text{No. of "Type C HEV" ULEVs Produced})] + \end{aligned}$$

$$\begin{aligned}
& [(1.7) \times (\text{No. of "Type A HEV" ULEVs Produced})] + \\
& [(1.5) \times (\text{No. of "Type B HEV" ULEVs Produced})] - \\
& [(1.4) \times (\text{Equivalent No. of ULEVs Required to be Produced})] + \\
& \{ [(1.7) \times [(\text{No. of SULEVs Produced excluding HEVs}) + (\text{No. of "Type C HEV" SULEVs Produced})] + \\
& [(\text{No. of "Type A HEV" SULEVs Produced}) \times (1.7)] + \\
& [(\text{No. of "Type B HEV" SULEVs}) \times (1.5)] - \\
& [(1.7) \times [(\text{Equivalent No. of SULEVs Required to be Produced})] + \\
& [(2.0) \times (\text{No. of ZEVs Certified and Produced as MDVs})].
\end{aligned}$$

a. Manufacturers that fail to produce and deliver for sale in California the equivalent quantity of MDVs certified to LEV and/or ULEV exhaust emission standards, shall receive "Vehicle-Equivalent Debits" (or "VEDs") equal to the amount of negative VECs determined by the aforementioned equation.

b. Manufacturers shall equalize emission debits within one model year by earning VECs in an amount equal to their previous model-year's total of VEDs, or by submitting a commensurate amount of VECs to the Executive Officer that were earned previously or acquired from another manufacturer. Any manufacturer which fails to equalize emission debits within the specified time period shall be subject to the Health and Safety Code civil penalty applicable to a manufacturer which sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the emission debits are not equalized by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's emission standards shall be equal to the amount of VEDs incurred.

c. The VECs earned in any given model year shall retain full value through the subsequent model year.

d. The value of any VECs not used to equalize the previous model-year's debit, shall be discounted by 50% at the beginning of second model year after being earned, discounted to 25% of its original value if not used by the beginning of the third model year after being earned, and will have no value if not used by the beginning of the fourth model year after being earned.

e. Any VECs earned prior to the 1998 model year shall be treated as earned in the 1998 model year and discounted in accordance with the schedule specified in note (12)(d).

f. Only ZEVs certified as MDVs shall be included in the calculation of VECs.

g. In order to verify the status of a manufacturer's compliance with the phase-in requirements of this section and in order to confirm the accrual of VECs or VEDs, each manufacturer shall submit an annual report to the Executive Officer which sets forth the production data used to establish compliance by no later than March 1 of the calendar year following the close of the model year.

(13) *50°F Requirement.* Manufacturers shall demonstrate compliance with the above standards for NMOG, carbon monoxide, and oxides of nitrogen at 50°F, according to the procedure specified in section 11k of the "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1960.1(k), or according to the procedure specified in section II.C. of the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" as incorporated by reference in section 1961(d), as applicable. Hybrid electric, natural gas and diesel-fueled vehicles shall be exempt from 50°F test requirements.

(14) In-use compliance testing shall be limited to vehicles with fewer than 90,000 miles.

- (15) *HEV Requirements.* Deterioration factors for hybrid electric vehicles shall be based on the emissions and mileage accumulation of the auxiliary power unit. For certification purposes only, Type A hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors), and demonstrating compliance with 120,000 mile emission standards shall not be required. For certification purposes only, Type B hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 120,000 mile emission standards (using 90,000 mile deterioration factors). For certification purposes only, Type C hybrid electric vehicles shall demonstrate compliance with 50,000 mile emission standards (using 50,000 mile deterioration factors) and 120,000 mile emission standards (using 120,000 mile deterioration factors).
- (16) *Requirements for Small Volume Manufacturers.* As used in Section 1960.1(h)(2), the term "small volume manufacturer" shall mean any vehicle manufacturer with California sales less than or equal to 3000 new PCs, LDTs, and MDVs per model year based on the average number of vehicles sold by the manufacturer each model year from 1992 to 1994, except as otherwise noted below. For manufacturers certifying for the first time in California, model-year sales shall be based on projected California sales.
- a. Prior to the model year 2001, small volume manufacturers shall not be required to certify, produce, or deliver LEVs and ULEVs for sale in California.
 - b. If a manufacturer's average California sales exceeds 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall no longer be treated as a small volume manufacturer and shall comply with the LEV and ULEV requirements applicable for larger manufacturers as specified in Section 1960.1(h)(2) beginning with the fourth model year after the last of the three consecutive model years.
 - c. If a manufacturer's average California sales falls below 3000 units of new PCs, LDTs, and MDVs based on the average number of vehicles sold for any three consecutive model years, the manufacturer shall be treated as a small volume manufacturer and shall be subject to requirements for small volume manufacturers as specified in Section 1960.1(h)(2) beginning with the next model year.

(i) *[Not applicable after December 31, 1990]*

(j) For Option 1 in the tables in sections (f)(1) and (f)(2), the hydrocarbon and carbon monoxide compliance shall be determined on a 50,000-mile durability basis. For Option 2 in the table in section (f)(2), the hydrocarbon and carbon monoxide compliance shall be determined on a 100,000-mile durability basis.

(k) The test procedures for determining compliance with these standards are set forth in "California Exhaust Emission Standards and Test Procedures for 1981 through 1987 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles," adopted by the state board on November 23, 1976, as last amended May 20, 1987, and in "California Exhaust Emission Standards and Test Procedures for 1988 through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles," adopted by the state board on May 20, 1987 as last amended August 5, 1999, both which are incorporated herein by reference, and in "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles," as incorporated by reference in section

1961(d). The test procedures for determining the compliance of 2001 through 2006 model-year hybrid electric vehicles with the standards set forth in this section are set forth in "California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric Vehicles, in the Passenger Car, Light-Duty Truck, and Medium-Duty Vehicle Classes, as incorporated by reference in section 1962(e).

(l) With respect to any new vehicle required to comply with the standards set forth in paragraphs (a) through (h), the manufacturer's written maintenance instructions for in-use vehicles shall not require scheduled maintenance more frequently than or beyond the scope of maintenance permitted under the test procedures referenced in paragraph (k) above. Any failure to perform scheduled maintenance shall not excuse an emissions violation unless the failure is related to or causative of the violation.

(m) Any 1982, 1983, and 1984 model year vehicle required to comply with the standards set forth in paragraphs (b), (c), (d), and (f) which is subject to a standard set by federal law or regulation controlling emissions of particulate matter must conform to such standard.

(n) For purposes of section 1960.1(a) through (f), section 1960.1(h)(1), and section 1960.1.5, "small volume manufacturer" for the 2000 and earlier model years is any vehicle manufacturer which was subject to "in lieu" standards pursuant to section 202(b)(1)(B) of the Federal Clean Air Act (42 U.S.C. section 7521(b)(1)(B), as amended November 16, 1977) or a vehicle manufacturer with California sales not exceeding 3,000 new motor vehicles per model year based on previous model-year sales; however, for manufacturers certifying for the first time in California model year sales shall be based on projected California sales.

(o) [Reserved]

(p) The cold temperature exhaust carbon monoxide emission levels from new 1996 through 2000 and subsequent model-year passenger cars, light-duty trucks and medium-duty vehicles shall not exceed:

**1996 AND SUBSEQUENT MODEL-YEAR COLD TEMPERATURE
CARBON MONOXIDE EXHAUST EMISSIONS STANDARDS FOR
PASSENGER
CARS, LIGHT-DUTY TRUCKS, AND MEDIUM-DUTY VEHICLES^{1,2}**
(grams per mile)

<u>Vehicle Type</u>	<u>Loaded Vehicle Weight (lbs.)</u>	<u>Durability Vehicle Basis (mi)</u>	<u>Carbon Monoxide</u>
Passenger Car	All	50,000	10.0
Light-Duty Truck	0-3750	50,000	10.0
Light-Duty Truck	3751-5750	50,000	12.5
Medium-Duty Vehicle	0-3750	50,000	10.0
Medium-Duty Vehicle	3751-8500 ³	50,000	12.5

- (1) These standards are applicable to vehicles tested in accordance with 40 CFR Part 86 Subpart C, at a nominal temperature of 20°F (-7°C).
- (2) Natural gas vehicles, diesel-fueled vehicles, hybrid electric vehicles, and zero-emission vehicles are exempt from these standards.
- (3) Medium-duty vehicles with a gross vehicle weight rating greater than 8,500 lbs. are exempt from this standard.

(q) The Supplemental Federal Test Procedure (SFTP) exhaust emission levels from new 2001 and subsequent model passenger cars and light-duty trucks, other than low-emission vehicles, ultra-low-emission vehicles, and zero-emission vehicles, shall not exceed:

**SFTP EXHAUST EMISSION STANDARDS FOR 2001 AND SUBSEQUENT
MODEL-YEAR PASSENGER CARS AND LIGHT-DUTY TRUCKS
OTHER THAN LOW-EMISSION VEHICLES, ULTRA-LOW-EMISSION
VEHICLES, AND ZERO-EMISSION VEHICLES**
(grams per mile)^{4,5,6,7,8,9,10}

Vehicle Type ¹	Loaded Vehicle Weight (lbs.)	Durability Vehicle Basis (mi)	Fuel Type	NMHC ² + NOx ¹ Composite ³	A/C ¹ Test	CO ¹	
						US06 ¹ Test	Composite Option ³
PC	All	50,000	Gasoline	0.65	3.0	9.0	3.4
			Diesel	1.48	NA	9.0	3.4
		100,000	Gasoline	0.91	3.7	11.1	4.2
			Diesel	2.07	NA	11.1	4.2
LDT	0-3750	50,000	Gasoline	0.65	3.0	9.0	3.4
			Diesel	1.48	NA	9.0	3.4
		100,000	Gasoline	0.91	3.7	11.1	4.2
			Diesel	2.07	NA	11.1	4.2
LDT	3751-5750	50,000	Gasoline	1.02	3.9	11.6	4.4
			Diesel	NA	NA	NA	NA
		100,000	Gasoline	1.37	4.9	14.6	5.5
			Diesel	NA	NA	NA	NA

(1) *Abbreviations.*

“PC” means passenger car.

“LDT” means light-duty truck.

“NMHC+NOx” means non-methane hydrocarbon plus oxides of nitrogen emissions.

“CO” means carbon monoxide emissions.

“A/C” means air-conditioning.

“US06” means the test cycle designed to evaluate emissions during aggressive and microtransient driving.

- (2) *Non-Methane Hydrocarbon Emissions.* For PCs and LDTs certified to the FTP exhaust standards in section 1960.1(f)(2), hydrocarbon emissions shall be measured in accordance with the “California Non-Methane Hydrocarbon Test Procedures” as last amended May 15, 1990, which is incorporated herein by reference. For PCs and LDTs certified as transitional low-emission vehicles, hydrocarbon emissions shall be measured in accordance with Part B (Determination of Non-Methane Hydrocarbon Mass Emissions by Flame Ionization Detection) of the “California Non-Methane Organic Gas Test Procedures” as incorporated by reference in section 1960.1(g)(1), note (3). For alcohol-fueled vehicles certifying to these standards, including flexible-fuel vehicles when certifying on methanol or ethanol, “Non-Methane Hydrocarbons” shall mean “Organic Material Non-Methane Hydrocarbon Equivalent.”

- (3) *Composite Standards.* Compliance with the composite standards shall be demonstrated using the calculations set forth in the section 86.164-00, Title 40, Code of Federal Regulations, as adopted October 22, 1996, which is incorporated herein by reference.
- (4) *SFTP.* SFTP means the additional test procedure designed to measure emissions during aggressive and microtransient driving, as described in section 86.159-00, Title 40, Code of Federal Regulations, as adopted October 22, 1996, over the US06 cycle, and also the test procedure designed to measure urban driving emissions while the vehicle's air conditioning system is operating, as described in section 86.160-00, Title 40, Code of Federal Regulations, as adopted October 22, 1996, over the SC03 cycle. These sections of the Code of Federal Regulations are incorporated herein by reference.
- (5) *Applicability to Alternative Fuel Vehicles.* These SFTP standards do not apply to vehicles certified on fuels other than gasoline and diesel fuel, but the standards do apply to the gasoline and diesel fuel operation of flexible-fuel vehicles and dual-fuel vehicles.
- (6) *Air to Fuel Ratio Requirement.* With the exception of cold-start conditions, warm-up conditions and rapid-throttle motion conditions ("tip-in" or "tip-out" conditions), the air to fuel ratio shall not be richer at any time than, for a given engine operating condition (e.g., engine speed, manifold pressure, coolant temperature, air charge temperature, and any other parameters), the leanest air to fuel mixture required to obtain maximum torque (lean best torque), with a tolerance of six percent of the fuel consumption. The Executive Officer may approve a manufacturer's request for approval to use additional enrichment in subsequent testing if the manufacturer demonstrates that additional enrichment is needed to protect the vehicle, occupants, engine, or emission control hardware.
- (7) *A/C-on Specific Calibrations.* A/C-on specific calibrations (e.g. air to fuel ratio, spark timing, and exhaust gas recirculation), may be used which differ from A/C-off calibrations for given engine operating conditions (e.g., engine speed, manifold pressure, coolant temperature, air charge temperature, and any other parameters). Such calibrations must not unnecessarily reduce the NMHC+NOx emission control effectiveness during A/C-on operation when the vehicle is operated under conditions which may reasonably be expected to be encountered during normal operation and use. If reductions in control system NMHC+NOx effectiveness do occur as a result of such calibrations, the manufacturer shall, in the Application for Certification, specify the circumstances under which such reductions do occur, and the reason for the use of such calibrations resulting in such reductions in control system effectiveness.

A/C-on specific "open-loop" or "commanded enrichment" air-fuel enrichment strategies (as defined below), which differ from A/C-off "open-loop" or "commanded enrichment" air-fuel enrichment strategies, may not be used, with the following exceptions: cold-start and warm-up conditions, or, subject to Executive Officer approval, conditions requiring the protection of the vehicle, occupants, engine, or emission control hardware. Other than these exceptions, such strategies which are invoked based on manifold pressure, engine speed, throttle position, or other engine parameters shall use the same engine parameter criteria for the invoking of this air-fuel enrichment strategy and the same degree of enrichment regardless of whether the A/C is on or off.

"Open-loop" or "commanded" air-fuel enrichment strategy is defined as enrichment of the air to fuel ratio beyond stoichiometry for the purposes of increasing engine power output and the protection of engine or emissions control hardware. However, "closed-loop biasing," defined as small changes in the air-fuel ratio for the purposes of optimizing vehicle emissions or driveability, shall not be

considered an “open-loop” or “commanded” air-fuel enrichment strategy. In addition, “transient” air-fuel enrichment strategy (or “tip-in” and “tip-out” enrichment), defined as the temporary use of an air-fuel ratio rich of stoichiometry at the beginning or duration of rapid throttle motion, shall not be considered an “open-loop” or “commanded” air-fuel enrichment strategy.

(8) *“Lean-On-Cruise” Calibration Strategies.* In the Application for Certification, the manufacturer shall state whether any “lean-on-cruise” strategies are incorporated into the vehicle design. A “lean-on-cruise” air-fuel calibration strategy is defined as the use of an air-fuel ratio significantly greater than stoichiometry, during non-deceleration conditions at speeds above 40 mph. “Lean-on-cruise” air-fuel calibration strategies shall not be employed during vehicle operation in normal driving conditions, including A/C-usage, unless at least one of the following conditions is met:

1. Such strategies are substantially employed during the FTP or SFTP, or
2. Such strategies are demonstrated not to significantly reduce vehicle NMHC+NOx emission control effectiveness over the operating conditions in which they are employed, or
3. Such strategies are demonstrated to be necessary to protect the vehicle, occupants, engine, or emission control hardware.

If the manufacturer proposes to use a “lean-on-cruise” calibration strategy, the manufacturer shall specify the circumstances under which such a calibration would be used, and the reason or reasons for the proposed use of such a calibration.

The above provisions shall not apply to vehicles powered by “lean-burn” engines or Diesel-cycle engines. A “lean-burn” engine is defined as an Otto-cycle engine designed to run at an air-fuel ratio significantly greater than stoichiometry during the large majority of its operation.

(9) *Phase-In Requirements.* For the purposes of this section 1960.1(q) only, each manufacturer’s PC and LDT fleet shall be defined as the total projected number of PCs and LDTs from 0-5750 pounds loaded vehicle weight certified to the FTP exhaust standards of section 1960.1(f)(2) and certified as transitional low-emission vehicles sold in California. As an option, a manufacturer may elect to have its total PC and LDT fleet defined, for the purposes of this section 1960.1(q) only, as the total projected number of the manufacturer’s PCs and LDTs, other than zero-emission vehicles, certified and sold in California.

a. Manufacturers of PCs and of LDTs, except small volume manufacturers, shall certify a minimum percentage of their PC and LDT fleet according to the following phase-in schedule.

<i>Model Year</i>	<i>Percentage of PC and LDT Fleet</i>
2001	25
2002	50
2003	85
2004 and subsequent	100

- b. Small volume manufacturers of PCs and LDTs shall certify 100% of their PC and LDT fleet in the 2004 and subsequent model years.

- (10) *Single-Roll Electric Dynamometer Requirement.* For all vehicles certified to the SFTP standards, a :
 "Duty Vehicles" as incorporated by reference in section 1960.1(k), must be used for all types of emission testing to determine compliance with the associated emission standards.

(r) The Supplemental Federal Test Procedure (SFTP) standards in this section represent the maximum SFTP exhaust emissions at 4,000 miles ± 250 miles or at the mileage determined by the manufacturer for emission-data vehicles in accordance with the "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles," as incorporated by reference in section 1960.1(k), and with the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles," as incorporated by reference in section 1961(d). The SFTP exhaust emission levels from new 2001 and subsequent model low-emission vehicles, ultra-low-emission vehicles and super ultra-low-emission vehicles in the passenger car and light-duty truck class, and new 2003 and subsequent low-emission vehicles, ultra-low-emission vehicles, and super-ultra-low-emission vehicles in the medium-duty class, shall not exceed:

**SFTP EXHAUST EMISSION STANDARDS
 FOR LOW-EMISSION VEHICLES, ULTRA-LOW-EMISSION VEHICLES, AND
 SUPER-ULTRA-LOW-EMISSION VEHICLES IN THE PASSENGER CAR, LIGHT-
 DUTY TRUCK, AND MEDIUM-DUTY VEHICLE CLASSES**
 (grams per mile)^{6,7,8,9,10,11}

Vehicle Type ¹	Loaded Vehicle Weight (lbs.) ²	US06 Test ¹		A/C Test ^{1,5}	
		NMHC ⁴ + NOx ¹	CO ¹	NMHC ⁴ + NOx ¹	CO ¹
PC	All	0.14	8.0	0.20	2.7
LDT	0-3750	0.14	8.0	0.20	2.7
LDT	3751-5750	0.25	10.5	0.27	3.5
MDV	3751-5750	0.40	10.5	0.31	3.5
MDV	5751-8500 ³	0.60	11.8	0.44	4.0

- (1) *Abbreviations and Definitions.* For the purposes of this SFTP standards table only, the following abbreviations and definitions apply:
 "PC" means passenger car.

“LDT” means light-duty truck, defined as any motor vehicle rated at 6,000 pounds gross vehicle weight or less, which is designed primarily for purposes of transportation of property or is a derivative of such a vehicle, or is available with special features enabling off-street or off-highway operation and use.

“MDV” means medium-duty truck, defined as any motor vehicle having a manufacturer’s gross vehicle weight rating of greater than 6,000 pounds and less than 14,001 pounds, except passenger cars.

“NMHC+NO_x” means non-methane hydrocarbon plus oxides of nitrogen emissions.

“CO” means carbon monoxide emissions.

“US06” means the test cycle designed to evaluate emissions during aggressive and microtransient driving.

“A/C” means air-conditioning.

- (2) For MDVs, “Loaded Vehicle Weight” shall mean “Test Weight,” which is the average of the vehicle’s curb weight and gross vehicle weight.
- (3) Vehicles with a gross vehicle weight rating over 8,500 pounds are exempted from the requirements of this subsection.
- (4) *Non-Methane Hydrocarbon Emissions.* Hydrocarbon emissions shall be measured in accordance with Part B (Determination of Non-Methane Hydrocarbon Mass Emissions by Flame Ionization Detection) of the “California Non-Methane Organic Gas Test Procedures” as incorporated by reference in section 1960.1(g)(1), note (3). For alcohol-fueled vehicles certifying to these standards, including flexible-fuel vehicles when certifying on methanol or ethanol, “Non-Methane Hydrocarbons” shall mean “Organic Material Non-Methane Hydrocarbon Equivalent.”
- (5) *A/C-on Specific Calibrations.* A/C-on specific calibrations (e.g. air to fuel ratio, spark timing, and exhaust gas recirculation), may be used which differ from A/C-off calibrations for given engine operating conditions (e.g., engine speed, manifold pressure, coolant temperature, air charge temperature, and any other parameters). Such calibrations must not unnecessarily reduce the NMHC+NO_x emission control effectiveness during A/C-on operation when the vehicle is operated under conditions which may reasonably be expected to be encountered during normal operation and use. If reductions in control system NMHC+NO_x effectiveness do occur as a result of such calibrations, the manufacturer shall, in the Application for Certification, specify the circumstances under which such reductions do occur, and the reason for the use of such calibrations resulting in such reductions in control system effectiveness.

A/C-on specific “open-loop” or “commanded enrichment” air-fuel enrichment strategies (as defined below), which differ from A/C-off “open-loop” or “commanded enrichment” air-fuel enrichment strategies, may not be used, with the following exceptions: cold-start and warm-up conditions, or, subject to Executive Officer approval, conditions requiring the protection of the vehicle, occupants, engine, or emission control hardware. Other than these exceptions, such strategies which are invoked based on manifold pressure, engine speed, throttle position, or other engine parameters shall use the same engine parameter criteria for the invoking of this air-fuel enrichment strategy and the same degree of enrichment regardless of whether the A/C is on or off.

“Open-loop” or “commanded” air-fuel enrichment strategy is defined as enrichment of the air to fuel ratio beyond stoichiometry for the purposes of increasing engine power output and the protection of

engine or emissions control hardware. However, "closed-loop biasing," defined as small changes in the air-fuel ratio for the purposes of optimizing vehicle emissions or driveability, shall not be considered an "open-loop" or "commanded" air-fuel enrichment strategy. In addition, "transient" air-fuel enrichment strategy (or "tip-in" and "tip-out" enrichment), defined as the temporary use of an air-fuel ratio rich of stoichiometry at the beginning or duration of rapid throttle motion, shall not be considered an "open-loop" or "commanded" air-fuel enrichment strategy.

- (6) *SFTP*. SFTP means the additional test procedure designed to measure emissions during aggressive and microtransient driving, as described in section 86.159-00, Title 40, Code of Federal Regulations, as adopted October 22, 1996, over the US06 cycle, and also the test procedure designed to measure urban driving emissions while the vehicle's air conditioning system is operating, as described in section 86.160-00, Title 40, Code of Federal Regulations, as adopted October 22, 1996, over the SC03 cycle. These sections of the Code of Federal Regulations are incorporated herein by reference.
- (7) *Applicability to Alternative Fuel Vehicles*. These SFTP standards do not apply to vehicles certified on fuels other than gasoline and diesel fuel, but the standards do apply to the gasoline and diesel fuel operation of flexible-fuel vehicles and dual-fuel vehicles.
- (8) *Air to Fuel Ratio Requirement*. With the exception of cold-start conditions, warm-up conditions and rapid-throttle motion conditions ("tip-in" or "tip-out" conditions), the air to fuel ratio shall not be richer at any time than, for a given engine operating condition (e.g., engine speed, manifold pressure, coolant temperature, air charge temperature, and any other parameters), the leanest air to fuel mixture required to obtain maximum torque (lean best torque), with a tolerance of six percent of the fuel consumption. The Executive Officer may approve a manufacturer's request for approval to use additional enrichment in subsequent testing if the manufacturer demonstrates that additional enrichment is needed to protect the vehicle, occupants, engine, or emission control hardware.
- (9) *"Lean-On-Cruise" Calibration Strategies*. In the Application for Certification, the manufacturer shall state whether any "lean-on-cruise" strategies are incorporated into the vehicle design. A "lean-on-cruise" air-fuel calibration strategy is defined as the use of an air-fuel ratio significantly greater than stoichiometry, during non-deceleration conditions at speeds above 40 mph. "Lean-on-cruise" air-fuel calibration strategies shall not be employed during vehicle operation in normal driving conditions, including A/C-usage, unless at least one of the following conditions is met:
 1. Such strategies are substantially employed during the FTP or SFTP, or
 2. Such strategies are demonstrated not to significantly reduce vehicle NMHC+NOx emission control effectiveness over the operating conditions in which they are employed, or
 3. Such strategies are demonstrated to be necessary to protect the vehicle, occupants, engine, or emission control hardware.

If the manufacturer proposes to use a "lean-on-cruise" calibration strategy, the manufacturer shall specify the circumstances under which such a calibration would be used, and the reason or reasons for the proposed use of such a calibration.

The above provisions shall not apply to vehicles powered by “lean-burn” engines or Diesel-cycle engines. A “lean-burn” engine is defined as an Otto-cycle engine designed to run at an air-fuel ratio significantly greater than stoichiometry during the large majority of its operation.

(10) *Phase-In Requirements.* For the purposes of this 1960.1(r) section only, each manufacturer’s PC and LDT fleet shall be defined as the total projected number of low-emission and ultra-low-emission PCs and LDTs from 0-5750 pounds loaded vehicle weight sold in California. Each manufacturer’s MDV fleet shall be defined as the total projected number of low-emission, ultra-low-emission, and super-ultra-low-emission MDVs less than 8501 pounds gross vehicle weight rating sold in California.

a. Manufacturers of PCs, LDTs, and MDVs, except small volume manufacturers, shall certify a minimum percentage of their PC and LDT fleet, and a minimum percentage of their MDV fleet, according to the following phase-in schedule.

	<i>Percentage</i>	
<i>Model Year</i>	<i>PC, LDT</i>	<i>MDV</i>
2001	25	NA
2002	50	NA
2003	85	25
2004	100	50
2005 and subsequent	100	100

b. Manufacturers may use an “Alternative or Equivalent Phase-in Schedule” to comply with the phase-in requirements. An “Alternative Phase-in” is one that achieves at least equivalent emission reductions by the end of the last model year of the scheduled phase-in. Model-year emission reductions shall be calculated by multiplying the percent of vehicles (based on the manufacturer’s projected California sales volume of the applicable vehicle fleet) meeting the new requirements per model year by the number of model years implemented prior to and including the last model year of the scheduled phase-in. The “cumulative total” is the summation of the model-year emission reductions (e.g., a four model-year 25/50/85/100 percent phase-in schedule would be calculated as: (25%*4 years) + (50%*3 years) + (85%*2 years) + (100%*1 year) = 520). Any alternative phase-in that results in an equal or larger cumulative total than the required cumulative total by the end of the last model year of the scheduled phase-in shall be considered acceptable by the Executive Officer under the following conditions: 1) all vehicles subject to the phase-in shall comply with the respective requirements in the last model year of the required phase-in schedule and 2) if a manufacturer uses the optional phase-in percentage determination in section 1960.1(q) note (9), the cumulative total of model-year emission reductions as determined only for PCs and LDTs certified to this section 1960.1(r) must also be equal to or larger than the required cumulative total by end of the 2004 model year. Manufacturers shall be allowed to include vehicles introduced before the first model year of the scheduled phase-in (e.g., in the previous example, 10 percent introduced one year before the scheduled phase-in begins would be calculated as: (10%*5 years) and added to the cumulative total).

- c. Small volume manufacturers of PCs, LDTs, and MDVs shall certify 100% of their PC a
- (11) *Single-Roll Electric Dynamometer Requirement.* For all vehicles certified to the SFTP standards, a :
Duty Vehicles” as incorporated by reference in section 1960.1(k), must be used for all types of
emission testing to determine compliance with the associated emission standards.

NOTE: Authority cited: Sections 39600, 39601, 43013, 43018, 43101, 43104, and 43105, Health and Safety Code. Reference: Sections 39002, 39003, 39667, 43000, 43009.5, 43013, 43018, 43100, 43101, 43101.5, 43102, 43103, 43104, 43105, 43106, 43107, and 43204 - 43205.5, Health and Safety Code.

§ 1961. Exhaust Emission Standards and Test Procedures - 2004 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles.

Introduction. This section 1961 contains the California “LEV II” exhaust emission standards for 2004 and subsequent model passenger cars, light-duty trucks and medium-duty vehicles. A manufacturer must demonstrate compliance with the exhaust standards in section 1961(a) applicable to specific test groups, and with the composite phase-in requirements in section 1961(b) applicable to the manufacturer’s entire fleet. Section 1961(b) also includes the manufacturer’s fleet-wide composite phase-in requirements for the 2001 - 2003 model years.

Prior to the 2004 model year, a manufacturer that produces vehicles that meet the standards in section 1961(a) has the option of certifying the vehicles to those standards, in which case the vehicles will be treated as LEV II vehicles for purposes of the fleet-wide phase-in requirements. Similarly, 2004 - 2006 model-year vehicles may be certified to the “LEV I” exhaust emission standards in section 1960.1(g)(1) and (h)(2), in which case the vehicles will be treated as LEV I vehicles for purposes of the fleet-wide phase-in requirements.

A manufacturer has the option of certifying engines used in incomplete and diesel medium-duty vehicles with a gross vehicle weight rating of greater than 8,500 lbs. to the heavy-duty engine standards and test procedures set forth in title 13, CCR, sections 1956.8(g) and (h).

(a) *Exhaust Emission Standards.*

(1) *“LEV II” Exhaust Standards.* The following standards represent the maximum exhaust emissions for the intermediate and full useful life from new 2004 and subsequent model-year “LEV II” LEVs, ULEVs, and SULEVs, including fuel-flexible, bi-fuel and dual fuel vehicles when operating on the gaseous or alcohol fuel they are designed to use:

**LEV II Exhaust Mass Emission Standards for New 2004 and Subsequent Model
LEVs, ULEVs, and SULEVs
in the Passenger Car, Light-Duty Truck and Medium-Duty Vehicle Classes**

Vehicle Type	Durability Vehicle Basis (mi)	Vehicle Emission Category	NMOG (g/mi)	Carbon Monoxide (g/mi)	Oxides of Nitrogen (g/mi)	Formaldehyde (mg/mi)	Particulate from diesel vehicles (g/mi)
All PCs; LDTs 8500 lbs. GVW or less Vehicles in this category are tested at their loaded vehicle weight	50,000	LEV	0.075	3.4	0.05	15	n/a
		LEV, Option 1	0.075	3.4	0.07	15	n/a
		ULEV	0.040	1.7	0.05	8	n/a
	120,000	LEV	0.090	4.2	0.07	18	0.01
		LEV, Option 1	0.090	4.2	0.10	18	0.01
		ULEV	0.055	2.1	0.07	11	0.01
		SULEV	0.010	1.0	0.02	4	0.01
	150,000 (Optional)	LEV	0.090	4.2	0.07	18	0.01
		LEV, Option 1	0.090	4.2	0.10	18	0.01
		ULEV	0.055	2.1	0.07	11	0.01
		SULEV	0.010	1.0	0.02	4	0.01
	MDVs 8501 - 10,000 lbs. GVW Vehicles in this category are tested at their adjusted loaded vehicle weight	120,000	LEV	0.195	6.4	0.2	32
ULEV			0.143	6.4	0.2	16	0.06
SULEV			0.100	3.2	0.1	8	0.06
150,000 (Optional)		LEV	0.195	6.4	0.2	32	0.12
		ULEV	0.143	6.4	0.2	16	0.06
		SULEV	0.100	3.2	0.1	8	0.06
MDVs 10,001-14,000 lbs. GVW Vehicles in this category are tested at their adjusted loaded vehicle weight	120,000	LEV	0.230	7.3	0.4	40	0.12
		ULEV	0.167	7.3	0.4	21	0.06
		SULEV	0.117	3.7	0.2	10	0.06
	150,000 (Optional)	LEV	0.230	7.3	0.4	40	0.12
		ULEV	0.167	7.3	0.4	21	0.06
		SULEV	0.117	3.7	0.2	10	0.06

(2) *Reactivity Adjustment in Determining Compliance with the NMOG Standard*

(A) The NMOG emission results from all TLEVs, LEVs, ULEVs and SULEVs certifying on a fuel other than conventional gasoline shall be numerically adjusted to establish an NMOG exhaust mass emission value equivalent. The manufacturer shall multiply measured NMOG exhaust emission results by the appropriate reactivity adjustment factor set forth in section 1961(a)(2)(B) or established in accordance with the test procedures incorporated by reference in section 1961(d). The reactivity adjustment factor represents the ratio of the NMOG specific reactivity of a low-emission vehicle designed to operate on a fuel other than conventional gasoline compared to the NMOG baseline specific reactivity of vehicles in the same vehicle emission category operated on conventional gasoline.

(B) The following reactivity adjustment factors apply through the 2003 model year:

	Light-Duty Vehicles 0-6000 lbs. GVW			Medium-Duty Vehicles 6001 lbs. - 14,000 lbs. GVW	
	TLEV	LEV	ULEV	LEV	ULEV
Fuel	Baseline Specific Reactivity (grams ozone / gram NMOG)				
Conventional Gasoline	3.42	3.13	3.13	3.13	3.13
	Reactivity Adjustment Factors				
Phase 2 RFG	0.98	0.94	0.94	0.94	0.94
M85	0.41	0.41	0.41	0.41	0.41
Natural Gas	1.0	0.43	0.43	0.43	0.43
LPG	1.0	0.50	0.50	0.50	0.50
	Methane Reactivity Adjustment Factors				
Natural Gas	0.0043	0.0047	0.0047	0.0047	0.0047

(3) *NMOG Standards for Bi-Fuel, Fuel-Flexible and Dual-Fuel Vehicles Operating on Gasoline.* For fuel-flexible, bi-fuel, and dual-fuel PCs, LDTs and MDVs, compliance with the NMOG exhaust mass emission standards shall be based on exhaust emission tests both when the vehicle is operated on the gaseous or alcohol fuel it is designed to use, and when the vehicle is operated on gasoline. A manufacturer must demonstrate compliance with the applicable exhaust mass emission standards for NMOG, CO, NO_x and formaldehyde set forth in the table in section 1961(a)(1) when certifying the vehicle for operation on the gaseous or alcohol fuel.

The following standards represent the maximum NMOG emissions when the vehicle is operating on gasoline. A manufacturer shall not apply a reactivity adjustment factor to the exhaust NMOG mass emission result when operating on gasoline. Testing at 50°F is not required

for fuel-flexible, bi-fuel and dual-fuel vehicles when operating on gasoline. The applicable CO, NOx and formaldehyde standards are set forth in section 1961(a)(1).

LEV II NMOG Standards for Bi-Fuel, Fuel-Flexible and Dual-Fuel Vehicles Operating on Gasoline (g/mi)			
Vehicle Type	Vehicle Emission Category	Durability Vehicle Basis	
		50,000 mi	120,000 mi
All PCs; LDTs, 0-8500 lbs. GVW	LEV	0.125	0.156
	ULEV	0.075	0.090
	SULEV	0.010	0.040
MDVs, 8501-10,000 lbs. GVW	LEV	n/a	0.230
	ULEV	n/a	0.167
	SULEV	n/a	0.117
MDVs, 10,001-14,000 lbs. GVW	LEV	n/a	0.280
	ULEV	n/a	0.195
	SULEV	n/a	0.143

(4) *50°F Exhaust Emission Standards.* All light- and medium-duty LEVs, ULEVs and SULEVs must demonstrate compliance with the following exhaust emission standards for NMOG and formaldehyde (HCHO) measured on the FTP (40 CFR, Part 86, Subpart B) conducted at a nominal test temperature of 50°F, as modified by Part II, Section C of the “California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles” incorporated by reference in section 1961(d). The NMOG mass emission result shall be multiplied by the applicable reactivity adjustment factor, if any, prior to comparing to the applicable adjusted 50,000 mile certification standards set forth below. Emissions of CO and NOx measured at 50°F shall not exceed the standards set forth in §1961(a)(1) applicable to vehicles of the same emission category and vehicle type subject to a cold soak and emission test at 68° to 86°F. Natural gas and diesel-fueled vehicles are exempt from the 50° F test requirements.

Vehicle Weight Class	Vehicle Emission Category (g/mi)					
	LEV		ULEV		SULEV	
	NMOG	HCHO	NMOG	HCHO	NMOG	HCHO
PCs; LDTs 0-8500 lbs. GVW	0.150	0.030	0.080	0.016	0.02	0.008

MDVs 8501-10,000 lbs. GVW	0.390	0.064	0.286	0.032	0.200	0.016
MDVs 10,001-14,000 lbs. GVW	0.460	0.080	0.334	0.042	0.234	0.020

(5) *Cold CO Standard.* The following standards represent the 50,000 mile cold temperature exhaust carbon monoxide emission levels from new 2001 and subsequent model-year passenger cars, light-duty trucks, and medium-duty vehicles:

**2001 AND SUBSEQUENT MODEL-YEAR COLD TEMPERATURE
CARBON MONOXIDE EXHAUST EMISSIONS STANDARDS FOR PASSENGER
CARS, LIGHT-DUTY TRUCKS, AND MEDIUM-DUTY VEHICLES**
(grams per mile)

Vehicle Type	Carbon Monoxide
All PCs, LDTs 0-3750 lbs. LVW;	10.0
LDTs, 3751 lbs. LVW - 8500 lbs. GVW; LEV I and Tier 1 MDVs 8500 lbs. GVW and less	12.5

These standards are applicable to vehicles tested at a nominal temperature of 20°F (-7°C) in accordance with 40 CFR Part 86 Subpart C, as amended by the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles" incorporated by reference in section 1961(d). Natural gas, diesel-fueled and zero-emission vehicles are exempt from these standards.

(6) *Highway NOx Standard.* The maximum emissions of oxides of nitrogen measured on the federal Highway Fuel Economy Test (HWFET; 40 CFR 600 Subpart B, which is incorporated herein by reference) shall not be greater than 1.33 times the applicable PC and LDT standards or 2.0 times the applicable MDV standards set forth in section 1961(a)(1). Both the projected emissions and the HWFET standard shall be rounded in accordance with ASTM E29-67 to the nearest 0.1 g/mi (or 0.01 g/mi for vehicles certified to the 0.05 or 0.02 g/mi NOx standards) before being compared.

(7) *Supplemental Federal Test Procedure (SFTP) Off-Cycle Emission Standards.* The SFTP exhaust emission levels from new 2004 and subsequent model LEVs, ULEVs, and SULEVs shall not exceed the standards set forth in section 1960.1(r).

(8) *Requirements for Vehicles Certified to the Optional 150,000 Mile Standards.*

(A) *Requirement to Generate Additional Fleet Average NMOG Credit.* A vehicle that is certified to the 150,000 mile standards in section 1961(a) shall generate additional NMOG fleet average credit as set forth in 1961(b)(1) or additional vehicle equivalent credits as set forth in

1961(b)(2) provided that the manufacturer extends the warranty on high cost parts to 8 years or 100,000 miles, whichever occurs first, and agrees to extend the limit on high mileage in-use testing to 105,000 miles.

(B) *Requirement to Generate a Partial ZEV Allowance.* A vehicle that is certified to the 150,000 mile SULEV standards shall also generate a partial ZEV allocation according to the criteria set forth in section C.3 of the "California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric Vehicles, in the Passenger Car, Light-Duty Truck and Medium-Duty Vehicle Classes," incorporated by reference in section 1962(e)."

(9) *Optional LEV II NOx Standard.* A manufacturer may certify up to 4% of its light-duty truck fleet from 3751 lbs. LVW - 8500 lbs. GVW with a maximum base payload of 2500 lbs. or more to the LEV, option 1, standard set forth in 1961(a)(1) based on projected sales of trucks in the LDT2 category. Passenger cars and light-duty trucks 0-3750 lbs. LVW are not eligible for this option.

(10) *Intermediate In-Use Compliance Standards.* For test groups certified prior to the 2007 model year, the following intermediate in-use compliance standards shall apply for the first two model years the test group is certified to the new standard. For SULEVs certified prior to the 2004 model year, the following intermediate in-use compliance SULEV standards shall apply through the 2006 model year.

Emission Category	Durability Vehicle Basis	LEV II PCs and LDTs		LEV II MDVs 8500 - 10,000 lbs. GVW
		NMOG	NOx	NOx
LEV/ULEV	50,000	n/a	0.07	n/a
	120,000	n/a	0.10	0.3
SULEV	120,000	0.02	0.03	0.15

(11) *NMOG Credit for Vehicles with Zero-Evaporative Emissions.* In determining compliance of a vehicle with the applicable exhaust NMOG standard, a gram per mile NMOG factor, to be determined by the Executive Officer based on available data, shall be subtracted from the reactivity-adjusted NMOG exhaust emission results for any vehicle that has been certified to the "zero" evaporative emission standard set forth in title 13, CCR, section 1976(b)(1)(E). This credit shall not apply to a SULEV that generates a partial ZEV allowance.

(12) *NMOG Credit for Direct Ozone Reduction Technology.* A manufacturer that certifies vehicles equipped with direct ozone reduction technologies shall be eligible to receive NMOG credits that can be applied to the NMOG exhaust emissions of the vehicle when

determining compliance with the standard. In order to receive credit, the manufacturer must submit the following information for each vehicle model, including, but not limited to:

- (a) a demonstration of the airflow rate through the direct ozone reduction device and the ozone-reducing efficiency of the device over the range of speeds encountered in the SFTP test cycle;
- (b) an evaluation of the durability of the device for the full useful life of the vehicle; and
- (c) a description of the on-board diagnostic strategy for monitoring the performance of the device in-use.

Using the above information, the Executive Officer shall determine the value of the NMOG credit based on the calculated change in the one-hour peak ozone level using an approved airshed model.

(13) *NOx Credits for Pre-2004 MDVs Certified to the LEV I LEV or ULEV Standards.*

Prior to the 2004 model year, a manufacturer may earn a 0.02 g/mi per vehicle NOx credit for MDVs between 6,000-8500 lbs. GVW certified to the LEV I LEV or ULEV standards for PCs and LDTs set forth in section 1960.1(g)(1). The manufacturer may apply the credit on a per vehicle basis to the NOx emissions of LDTs between 6,000-8500 lbs. GVW certified to the PC/LDT LEV or ULEV standards in section 1961(a)(1) for the 2004 through 2008 model years.

(b) *Emission Standards Phase-In Requirements for Manufacturers.*

(1) *Fleet Average NMOG Requirements for Passenger Cars and Light-Duty Trucks.*

(A) The fleet average non-methane organic gas exhaust mass emission values from the passenger cars and light-duty trucks certified to the Tier 1, LEV I and LEV II standards that are produced and delivered for sale in California each model year by a manufacturer other than a small volume manufacturer shall not exceed:

FLEET AVERAGE NON-METHANE ORGANIC GAS EXHAUST MASS EMISSION REQUIREMENTS FOR LIGHT-DUTY VEHICLE WEIGHT CLASSES (50,000 mile Durability Vehicle Basis)		
Model Year	Fleet Average NMOG (grams per mile)	
	All PCs; LDTs 0-3750 lbs. LVW	LDTs 3751 lbs. LVW - 8500 lbs. GVW
2001	0.070	0.098
2002	0.068	0.095
2003	0.062	0.093

2004	0.053	0.085
2005	0.049	0.076
2006	0.046	0.062
2007	0.043	0.055
2008	0.040	0.050
2009	0.038	0.047
2010+	0.035	0.043

(B) *Calculation of Fleet Average NMOG Value.*

1. Each manufacturer's fleet average NMOG value for the total number of PCs and LDTs produced and delivered for sale in California shall be calculated as follows:

$$\frac{\sum [\text{Number of vehicles in a test group} \times \text{applicable emission standard}] + \sum [\text{Number of hybrid electric vehicles in a test group} \times \text{HEV NMOG factor}]}{\text{Total Number of Vehicles Produced, Including ZEVs and HEVs}}$$

Total Number of Vehicles Produced, Including ZEVs and HEVs

The applicable emission standards to be used in the above equation are as follows:

Model Year	Emission Category	Emission Standard Value	
		All PCs; LDTs 0-3750 lbs. LVW	LDTs 3751-5750 lbs. LVW
2001 and subsequent (§1960.5 "AB 965" vehicles only)	Tier 1	0.25	0.32
2001 - 2003 (§1960.1(f)(2))	Tier 1	0.25	0.32
2001 - 2006 model year vehicles certified to the "LEV I" standards in §1960.1(g)(1) (For TLEVs, 2001 - 2003 model years only)	TLEVs	0.125	0.160
	LEVs	0.075	0.100
	ULEVs	0.040	0.050
Model Year	Emission Category	All PCs; LDTs 0-3750 lbs. LVW	LDTs 3751 lbs. LVW - 8500 lbs. GVW
2004 and subsequent model year vehicles certified to the "LEV II" standards in §1961(a)(1)	LEVs	0.075	0.075

	ULEVs	0.040	0.040
	SULEVs	0.01	0.01
2004 and subsequent model year vehicles certified to the optional 150,000 mile "LEV II" standards for PCs and LDTs in 1961(a)(1)	LEVs	0.06	0.06
	ULEVs	0.03	0.03
	SULEVs	0.0085	0.0085

2. *HEV NMOG Factor.* The HEV NMOG factor for light-duty vehicles is calculated as follows:

$$\text{LEV HEV Contribution Factor} = 0.075 - [(\text{Zero-emission VMT Factor}) \times 0.035]$$

$$\text{ULEV HEV Contribution Factor} = 0.040 - [(\text{Zero-emission VMT Factor}) \times 0.030]$$

where Zero-emission VMT Factor for HEVs is determined in accordance with section 1962.

(C) *Requirements for Small Volume Manufacturers.*

1. In 2001 through 2003 model years, a small volume manufacturer shall not exceed a fleet average NMOG value of 0.075 g/mi for PCs and LDTs from 0-3750 lbs. LVW or 0.100 g/mi for LDTs from 3751-5750 lbs. LVW calculated in accordance with section 1961(b)(1)(B). In 2004 and subsequent model years, a small volume manufacturer shall not exceed a fleet average NMOG value of 0.075 for PCs and LDTs from 0-3750 lbs. LVW or 0.075 for LDTs from 3751 lbs. LVW - 8500 lbs. GVW calculated in accordance with section 1961(b)(1)(B).

2. If a manufacturer's average California sales exceed 4500 units of new PCs, LDTs, MDVs and heavy duty engines based on the average number of vehicles sold for the three previous consecutive model years, the manufacturer shall no longer be treated as a small volume manufacturer and shall comply with the fleet average requirements applicable to larger manufacturers as specified in section 1961(b)(1) beginning with the fourth model year after the last of the three consecutive model years.

3. If a manufacturer's average California sales fall below 4500 units of new PCs, LDTs, MDVs and heavy duty engines based on the average number of vehicles sold for the three previous consecutive model years, the manufacturer shall be treated as a small volume manufacturer and shall be subject to the requirements for small volume manufacturers beginning with the next model year.

(D) ZEVs classified as LDTs (>3750 lbs. LVW) that have been counted toward the ZEV requirement for PCs and LDTs (0-3750 lbs. LVW) as specified in section 1962 shall be included as LDTs in the calculation of a fleet average NMOG value.

(2) *LEV II Phase-In Requirement for PCs and LDTs.* Beginning in the 2004 model year, a manufacturer, except a small volume manufacturer, shall certify a percentage of its PC and LDT fleet to the LEV II standards in section 1961(a) according to the following phase in schedule:

Model Year	PC/LDT1 (%)	LDT2 (%)
2004	25	25
2005	50	50
2006	75	75
2007	100	100

In determining compliance with the phase-in schedule, the fleet shall consist of LEV I and LEV II PCs and LDT1s for the PC/LDT1 calculation, and LEV I and LEV II LDT2s for the LDT2 calculation. LEV I MDVs are not counted in the calculation until they are certified as LEV II LDT2s.

A manufacturer may use an alternative phase-in schedule to comply with these phase-in requirements as long as equivalent NOx emission reductions are achieved by the 2007 model year from each of the two categories -- PC/LDT1 and LDT2. Model year emission reductions shall be calculated by multiplying the percent of either PC/LDT1 or LDT2 vehicles meeting the LEV II standards in a given model year (based on a manufacturer's projected sales volume of vehicles in each category) by 4 for the 2004 model year, 3 for the 2005 model year, 2 for the 2006 model year and 1 for the 2007 model year. The yearly results for PCs/LDT1s shall be summed together to determine a separate cumulative total for PCs/LDT1s and the yearly results for LDT2s shall be summed together to determine a cumulative total for LDT2s. The cumulative total for each category must be equal to or exceed 500 to be considered equivalent. A manufacturer may add vehicles introduced before the 2004 model year (e.g., the percent of vehicles introduced in 2003 would be multiplied by 5) to the cumulative total.

(3) *Medium-Duty Vehicle Phase-In Requirements.*

(A) A manufacturer of MDVs shall certify an equivalent percentage of its MDV fleet according to the following phase-in schedule:

Model Year	Vehicles Certified to §1960.1(h)(1), (h)(2), and §1961(a)(1) (%)		Vehicles Certified to §1956.8(g) or (h) (%)		
	LEV	ULEV	Tier 1	LEV	ULEV
2001	80	20	100	0	0
2002	70	30	0	100	0

2003	60	40	0	100	0
2004 +	40	60	0	0	100

(B) Beginning with the 2004 model year, a manufacturer shall phase-in at least one test group per model year to the MDV LEV II standards.

(C) For the 2001 and subsequent model years, each manufacturer's MDV fleet shall be defined as the total number of California-certified MDVs produced and delivered for sale in California. The percentages shall be applied to the manufacturers' total production of California-certified medium-duty vehicles delivered for sale in California.

(D) *Requirements for Small Volume Manufacturers.* In 2001 and subsequent model years, a small volume manufacturer shall certify, produce, and deliver for sale in California LEVs in a quantity equivalent to 100% of its MDV fleet.

(c) *Calculation of NMOG Credits/Debits*

(1) *Calculation of NMOG Credits for Passenger Cars and Light-Duty Trucks.* In 2001 and subsequent model years, a manufacturer that achieves fleet average NMOG values lower than the fleet average NMOG requirement for the corresponding model year shall receive credits in units of g/mi NMOG determined as:

$$\frac{[(\text{Fleet Average NMOG Requirement}) - (\text{Manufacturer's Fleet Average NMOG Value})]}{(\text{Total No. of Vehicles Produced and Delivered for Sale in California, Including ZEVs and HEVs})}$$

A manufacturer with 2001 and subsequent model year fleet average NMOG values greater than the fleet average requirement for the corresponding model year shall receive debits in units of g/mi NMOG equal to the amount of negative credits determined by the aforementioned equation. For the 2001 and subsequent model years, the total g/mi NMOG credits or debits earned for PCs and LDTs 0-3750 lbs. LVW, for LDTs 3751-5750 lbs. LVW and for LDTs 3751 lbs. LVW - 8500 lbs. GVW shall be summed together. The resulting amount shall constitute the g/mi NMOG credits or debits accrued by the manufacturer for the model year.

(2) *Calculation of Vehicle Equivalent NMOG Credits for Medium-Duty Vehicles.*

(A) In 2001 and subsequent model years, a manufacturer that produces and delivers for sale in California MDVs in excess of the equivalent requirements for LEVs, ULEVs and/or SULEVs certified to the exhaust emission standards set forth in section 1961(a)(1) or to the exhaust emission standards set forth in Title 13, CCR, Section 1956.8(h) shall receive "Vehicle-Equivalent Credits" (or "VECs") calculated in accordance with the following equation, where the term "produced" means produced and delivered for sale in California:

$$\{[(\text{No. of LEVs Produced excluding HEVs}) + (\text{No. of LEV HEVs} \times \text{HEV VEC factor for LEVs})] +$$

$(1.20 \times \text{No. of LEVs certified to the 150,000 mile standards}) -$
 $(\text{Equivalent No. of LEVs Required to be Produced}) +$

$\{[(1.4) \times (\text{No. of ULEVs Produced excluding HEVs}) +$
 $(\text{No. of ULEV HEVs} \times \text{HEV VEC factor for ULEVs})] +$
 $(1.50 \times \text{No. of ULEVs certified to the 150,000 mile standards}) -$
 $[(1.4) \times (\text{Equivalent No. of ULEVs Required to be Produced})]\} +$

$\{[(1.7) \times (\text{No. of SULEVs Produced excluding HEVs}) +$
 $(\text{No. of SULEV HEVs} \times \text{HEV VEC factor for SULEVs})] +$
 $(1.75 \times \text{No. of SULEVs certified to the 150,000 mile standards}) -$
 $[(1.7) \times [(\text{Equivalent No. of SULEVs Required to be Produced})]] +$

$[(2.0) \times (\text{No. of ZEVs Certified and Produced as MDVs})].$

MDVs certified prior to the 2004 model year to the LEV I LEV or ULEV standards for PCs and LDTs 0-3750 lbs. LVW set forth in section E.1 of these test procedures shall receive VECs calculated in accordance with the following equation, where the term “produced” means produced and delivered for sale in California:

$[(1.6) \times (\text{No. of MDVs meeting the LEV I LEV standards for PCs and LDTs 0-3750 lbs. LVW excluding HEVs}) +$
 $(\text{No. of HEVs meeting the LEV I LEV standards for PCs and LDTs 0-3750 lbs. LVW} \times \text{HEV VEC factor for MDVs}$
 $\text{meeting the LEV I LEV standards for PCs and LDTs 0-3750 lbs. LVW}) +$
 $[(1.65 \times \text{No. of MDVs certified to the 150,000 mile LEV I LEV standards for PCs and LDTs 0-3750 lbs.})] +$

$[(1.8) \times (\text{No. of MDVs meeting the LEV I ULEV standards for PCs and LDTs 0-3750 lbs. LVW excluding HEVs}) +$
 $(\text{No. of HEVs meeting the LEV I ULEV standards for PCs and LDTs 0-3750 lbs. LVW} \times \text{HEV VEC factor for MDVs}$
 $\text{meeting the LEV I ULEV standards for PCs and LDTs 0-3750 lbs. LVW}) +$
 $[(1.85 \times \text{No. of MDVs certified to the 150,000 mile LEV I ULEV standards for PCs and LDTs 0-3750 lbs.})].$

(B) *MDV HEV VEC factor.* The MDV HEV VEC factor is calculated as follows:

$1 + [(\text{LEV standard} - \text{ULEV standard}) \times (\text{Zero-emission VMT Factor}) \div \text{LEV standard}]$ for LEVs;
 $1 + [(\text{ULEV standard} - \text{SULEV standard}) \times (\text{Zero-emission VMT Factor}) \div \text{ULEV standard}]$ for ULEVs;
 $1 + [(\text{SULEV standard} - \text{ZEV standard}) \times (\text{Zero-emission VMT Factor}) \div \text{SULEV standard}]$ for SULEVs;
 where “Zero-emission VMT Factor” for an HEV is determined in accordance with section 1962.

The HEV VEC factor for MDVs prior to model year 2004 meeting the LEV I LEV and ULEV standards for PCs and LDTs 0-3750 lbs. LVW is calculated as follows:

$1 + [(\text{MDV SULEV standard} - \text{PC LEV I LEV standard}) \times (\text{Zero-emission VMT Factor}) \div \text{PC LEV I}$
 $\text{LEV standard}]$ for MDVs meeting the LEV I LEV standards for PCs and LDTs 0-3750 lbs. LVW;
 $1 + [(\text{MDV SULEV standard} - \text{PC ULEV standard}) \times (\text{Zero-emission VMT Factor}) \div \text{PC LEV I ULEV}$
 $\text{standard}]$ for MDVs meeting the ULEV I LEV standards for PCs and LDTs 0-3750 lbs. LVW.

(C) A manufacturer that fails to produce and deliver for sale in California the equivalent quantity of MDVs certified to LEV, ULEV and/or SULEV exhaust emission standards, shall receive "Vehicle-Equivalent Debits" (or "VEDs") equal to the amount of negative VECs determined by the equation in section 1961(c)(2)(A).

(D) Only ZEVs certified as MDVs and not used to meet the ZEV requirement shall be included in the calculation of VECs.

(3) *Procedure for Offsetting Debits.*

(A) A manufacturer shall equalize emission debits by earning g/mi NMOG emission credits or VECs in an amount equal to the g/mi NMOG debits or VEDs, or by submitting a commensurate amount of g/mi NMOG credits or VECs to the Executive Officer that were earned previously or acquired from another manufacturer. For 2001 through 2003 and for 2007 and subsequent model years, manufacturers shall equalize emission debits by the end of the following model year. For 2004 through 2006 model years, a manufacturer shall equalize NMOG debits for PCs and LDTs and LEV II MDVs within three model years and prior to the end of the 2007 model year. If emission debits are not equalized within the specified time period, the manufacturer shall be subject to the Health and Safety Code section 43211 civil penalty applicable to a manufacturer which sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the emission debits are not equalized by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of passenger cars and light-duty trucks not meeting the state board's emission standards shall be determined by dividing the total amount of g/mi NMOG emission debits for the model year by the g/mi NMOG fleet average requirement for PCs and LDTs 0-3750 lbs. LVW applicable for the model year in which the debits were first incurred and the number of medium-duty vehicles not meeting the state board's emission standards shall be equal to the amount of VEDs incurred.

(B) The emission credits earned in any given model year shall retain full value through the subsequent model year. The value of any credits not used to equalize the previous model-year's debit shall be discounted by 50% at the beginning of second model year after being earned, shall be discounted to 25% of its original value if not used by the beginning of the third model year after being earned, and will have no value if not used by the beginning of the fourth model year after being earned.

(d) *Test Procedures.* The certification requirements and test procedures for determining compliance with the emission standards in this section are set forth in the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles," adopted on August 5, 1999, which is incorporated herein by reference. In the case of hybrid electric vehicles, the certification requirements and test procedures for determining compliance with the emission standards in this section are set forth in the "California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric

Vehicles, in the Passenger Car, Light-Duty Truck and Medium-Duty Vehicle Classes," incorporated by reference in section 1962(e).

(e) *Abbreviations.* The following abbreviations are used in this section 1961:

"ALVW" means adjusted loaded vehicle weight.

"ASTM" means American Society of Testing and Materials.

"CO" means carbon monoxide.

"FTP" means Federal Test Procedure.

"g/mi" means grams per mile.

"GVW" means gross vehicle weight.

"GVWR" means gross vehicle weight rating.

"HEV" means hybrid-electric vehicle.

"LDT" means light-duty truck.

"LDT1" means a light-duty truck with a loaded vehicle weight of 0-3750 pounds.

"LDT2" means a "LEV II" light-duty truck with a loaded vehicle weight of 3751 pounds to a gross vehicle weight of 8500 pounds or a "LEV I" light-duty truck with a loaded vehicle weight of 3751-5750 pounds.

"LEV" means low-emission vehicle.

"LPG" means liquefied petroleum gas.

"LVW" means loaded vehicle weight.

"MDV" means medium-duty vehicle.

"mg/mi" means milligrams per mile.

"Non-Methane Organic Gases" or "NMOG" means the total mass of oxygenated and non-oxygenated hydrocarbon emissions.

"NOx" means oxides of nitrogen.

"PC" means passenger car.

"SULEV" means super ultra-low-emission vehicle.

"TLEV" means transitional low-emission vehicle.

"ULEV" means ultra-low-emission vehicle.

"VEC" means vehicle-equivalent credits.

"VED" means vehicle-equivalent debits.

"VMT" means vehicle miles traveled.

Note: Authority cited: Sections 39600, 39601, 43013, 43018, 43101, 43104 and 43105, Health and Safety Code. Reference: Sections 39002, 39003, 39667, 43000, 43009.5, 43013, 43018, 43100, 43101, 43101.5, 43102, 43104, 43105, 43106, 43107, 43204, and 43205.5, Health and Safety Code.

§ 1962. Zero-Emission Vehicle Standards for 2003 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles.

(a) *ZEV Emission Standard.* The Executive Officer shall certify new 2003 and subsequent model passenger cars, light-duty trucks and medium-duty vehicles as ZEVs if the vehicles produce zero exhaust emissions of any criteria pollutant (or precursor pollutant) under any and all possible operational modes and conditions. Incorporation of a fuel-fired heater shall not preclude a vehicle from being certified as a ZEV provided: (1) the fuel-fired heater cannot be operated at ambient temperatures above 40°F, (2) the heater is demonstrated to have zero fuel evaporative emissions under any and all possible operational modes and conditions, and (3) the emissions of any pollutant from the fuel-fired heater when operated at an ambient temperature between 68°F and 86°F do not exceed the emission standard for that pollutant for a ULEV under section 1961(a)(1).

A vehicle that would meet the emissions standards for a ZEV except that it uses a fuel-fired heater that can be operated at ambient temperatures above 40°F, that cannot be demonstrated to have zero fuel evaporative emissions under any and all possible operation modes and conditions, or that has emissions of any pollutant exceeding the emission standard for that pollutant for a ULEV under section 1961(a)(1), shall be certified based on the emission level of the fuel-fired heater.

(b) *Percentage ZEV Requirements.* The ZEV requirement for each manufacturer in 2003 and subsequent model years is that at least 10% of the PCs and LDT1s produced by the manufacturer and delivered for sale in California must be ZEVs, subject to the conditions in this section 1962(b). In applying the ZEV requirement, a PC or LDT1 that is produced by a small volume manufacturer, but is marketed in California by another manufacturer under the other manufacturer's nameplate, shall be treated as having been produced by the marketing manufacturer.

(1) *Basic Requirements for Large, Intermediate, and Small Volume Manufacturers.*

(A) *Large Volume Manufacturers.* In 2003 and subsequent model years, a large-volume manufacturer must meet at least 40% of its ZEV requirement with ZEVs, full ZEV allowance vehicles, or ZEV credits generated by such vehicles. The remainder of the large-volume manufacturer's ZEV requirement may be met using partial ZEV allowance vehicles or credits generated by such vehicles.

(B) *Intermediate Volume Manufacturers.* In 2003 and subsequent model years, an intermediate volume manufacturer may meet its ZEV requirement with up to 100 percent partial ZEV allowance vehicles or credits generated by such vehicles.

(C) *Small Volume Manufacturers.* A small volume manufacturer is not required to meet the percentage ZEV requirements. However, a small volume manufacturer may earn and

market credits for the ZEVs or ZEV allowance vehicles it produces and delivers for sale in California.

(2) *Counting ZEVs and ZEV Allowance Vehicles in Fleet Average NMOG Calculations.* Vehicles certified as ZEVs and as full ZEV allowance vehicles shall be counted as ZEVs for the purpose of calculating a manufacturer's fleet average NMOG value and NMOG credits under sections 1960.1(g)(2) and 1961(b) and (c). Partial ZEV allowance vehicles shall be counted as SULEVs certified to the 150,000 mile standards for the purpose of calculating a manufacturer's fleet average NMOG value and NMOG credits under sections 1960.1(g)(2) and 1961(b) and (c).

(3) *Implementation Prior to 2003 Model Year.* Prior to the 2003 model year, a manufacturer that voluntarily produces vehicles meeting the ZEV emission standards applicable to 2003 and subsequent model year vehicles may certify the vehicles to those standards and requirements for purposes of calculating fleet average NMOG exhaust emission values and NMOG credits under sections 1960.1(g)(2) and 1961(b) and (c), and for calculating ZEV credits as set forth in section 1962(d).

(4) *Changes in Small and Intermediate Volume Manufacturer Status.* In 2003 and subsequent model years, if a small volume manufacturer's average California production volume exceeds 4,500 units of new PCs, LDTs, and MDVs based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, or if an intermediate volume manufacturer's average California production volume exceeds 35,000 units of new PCs, LDTs, and MDVs based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, the manufacturer shall no longer be treated as a small volume or intermediate manufacturer, as applicable, and shall comply with the ZEV requirements for intermediate or large volume manufacturers, as applicable, beginning with the fourth model year after the last of the three consecutive model years. If a manufacturer's average California production volume falls below 4,500 or 35,000 units of new PCs, LDTs, and MDVs, as applicable, based on the average number of vehicles produced and delivered for sale for the three previous consecutive model years, the manufacturer shall be treated as a small or intermediate volume manufacturer, as applicable, and shall be subject to the requirements for a small or intermediate volume manufacturer beginning with the next model year. In determining small volume manufacturer status, vehicles produced by one manufacturer and marketed in California by another manufacturer under the other manufacturer's nameplate shall be treated as part of the California production volume of the sales of the marketing manufacturer.

(c) *Partial and Full ZEV Allowance Vehicles.*

(1) This section 1962(c) sets forth the criteria for identifying vehicles delivered for sale in California as partial or full ZEV allowance vehicles. A partial ZEV allowance vehicle is a vehicle that is delivered for sale in California and that qualifies for a partial ZEV allowance of at least 0.2 but less than 1.0. A full ZEV allowance vehicle is a vehicle that is delivered for sale in California and that qualifies for a ZEV allowance of 1.0.

(2) *Baseline Partial ZEV Allowance.* In order for a vehicle to be eligible to receive a partial or full ZEV allowance, the manufacturer must demonstrate compliance with all of the following requirements. A qualifying vehicle will receive a baseline partial ZEV allowance of 0.2.

(A) Certify the vehicle to the 150,00-mile SULEV exhaust emission standards for PCs and LDTs in section 1961(a)(1);

(B) Certify the vehicle to the evaporative emission standards in section 1976(b)(1)(E) (“zero” evaporative emissions standards);

(C) Certify that the vehicle will meet the applicable on-board diagnostic requirements in section 1968.1 for 150,000 miles;

(D) Extend the performance and defects warranty period set forth in sections 2037(b)(2) and 2038(b)(2) to 15 years or 150,000 miles, whichever occurs first.

(3) *Zero-Emission VMT Partial ZEV Allowance.*

(A) A vehicle that meets the requirements of section 1962(c)(2) and has zero-emission vehicle miles traveled (“VMT”) capability will generate an additional ZEV allowance, not to exceed 0.6, according to the following equation:

$$\text{Zero-Emission VMT Partial ZEV Allowance} = 0.6 \times \text{Zero-Emission VMT Factor}$$

where zero-emission VMT factor is the ratio of the zero-emission miles the vehicle travels to the total miles traveled per trip.

(B) The zero-emission VMT factor in the above equation is to be calculated as follows, with the urban all-electric range (AER) determined in accordance with section E.3.(2)(a) of the “California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric Vehicles, in the Passenger Car, Light-Duty Truck and Medium-Duty Vehicle Classes,” incorporated by reference in section 1962(e):

Urban All-Electric Range	Zero-emission VMT Factors:
< 20 miles	0.0
≤ 20 miles to < 100 miles	(30 + [0.5 x Urban AER])/80
≥ 100 miles	1.0

(C) As an alternative to determining the zero-emission VMT factor in accordance with the preceding section 1962(c)(3)(B), a manufacturer may submit for Executive Officer approval

an alternative procedure for determining the zero-emission VMT potential of the vehicle as a percent of total VMT, along with an engineering evaluation that adequately substantiates the zero-emission VMT determination. For example, an alternative procedure may provide that a vehicle with zero-emissions of one regulated pollutant (e.g. NOx) and not another (e.g. NMOG) will qualify for a zero-emission VMT factor of 0.5. Upon approval of the alternative procedure, the Executive Officer shall assign a zero-emission VMT factor not to exceed 1.0.

(D) The Executive Officer shall approve an additional 0.1 zero-emission VMT ZEV allowance for an HEV with an all-electric range greater than 20 miles if the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer that the HEV is equipped with software and/or other strategies that would promote maximum use of off-vehicle charging, and that the strategies employed are reasonably reliable and tamper-proof. In no event, however, may the total zero-emission VMT ZEV allowance for an HEV under section 1962(c)(3) exceed 0.6.

(4) *Partial ZEV Allowance for Advanced ZEV Componentry.* A vehicle that does not qualify for any zero-emission VMT partial ZEV allowance under section 1962(c)(3) shall qualify for an advanced componentry partial ZEV allowance of 0.1, if the manufacturer demonstrates to the reasonable satisfaction of the Executive Officer that the vehicle is equipped with advanced ZEV componentry such as an advanced battery integral to the operation of the vehicle power-train or an electric power-train.

(5) *Partial ZEV Allowance for Fuel-Cycle Emissions.* A vehicle that uses fuel(s) with very low fuel-cycle emissions shall receive a partial ZEV allowance not to exceed 0.2. In order to receive the fuel-cycle partial ZEV allowance, a manufacturer must demonstrate to the Executive Officer, using peer-reviewed studies or other relevant information, that NMOG emissions associated with the fuel(s) used by the vehicle (on a grams/mile basis) are lower than or equal to 0.01 grams/mile. Fuel-cycle emissions must be calculated based on near-term production methods and infrastructure assumptions, and the uncertainty in the results must be quantified. The fuel-cycle partial ZEV allowance is calculated according to the following formula:

$$\text{Partial ZEV Fuel Cycle Allowance} = 0.2 \times [(\text{percent of VMT using fuel(s) meeting the requirements of the preceding paragraph}) / 100]$$

A manufacturer's demonstration to the Executive Officer that a vehicle qualifies for a fuel-cycle partial ZEV allowance shall include test results and/or empirical data supporting the estimate of the relative proportion of VMT while operating on fuel(s) with very low fuel-cycle emissions.

(6) *Calculation of Combined ZEV Allowance for a Vehicle.* The combined ZEV allowance for a qualifying vehicle is the sum of:

(A) The baseline ZEV allowance of 0.2 for vehicles meeting the criteria in section 1962(c)(2);

(B) The zero-emission VMT ZEV allowance, if any, determined in accordance with section 1962(c)(3), not to exceed 0.6;

(C) The advanced ZEV componentry ZEV allowance, if any, determined in accordance with section 1962(c)(4), not to exceed 0.1; and

(D) The fuel-cycle emissions ZEV allowance, if any, determined in accordance with section 1962(c)(5), not to exceed 0.2.

(d) *Generation and Use of ZEV Credits; Calculation of Penalties.* A manufacturer that produces and delivers for sale in California ZEVs, full ZEV allowance vehicles, or partial ZEV allowance vehicles in a given model year exceeding the manufacturer's ZEV requirement set forth in section 1962(b) shall earn ZEV credits in accordance with this section 1962(d).

(1) *Qualification for ZEV Multipliers.*

(A) *1996-1998 Model-Year ZEV Multipliers.*

1. *1996-1998 Model-Year ZEV Multiplier Based on Vehicle Range.*

1996-1998 model-year ZEVs shall qualify for a ZEV multiplier based on vehicle range as follows:

ZEV Multiplier	Vehicle Range (miles)	
	Model Years 1996 and 1997	Model Year 1998
2	any	≥ 100
3	≥ 70	≥ 130

Range shall be determined in accordance with section 9.f.(2)(a) of the "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles," incorporated by reference in section 1960.1(k).

2. *1996-1998 Model-Year ZEV Multiplier Based on Specific Energy of Battery.*

1996-1998 model-year ZEVs shall qualify for a ZEV multiplier based on specific energy of the battery as follows:

ZEV Multiplier	Specific Energy of Battery (w-hr/kg)
2	any

3	≥40
---	-----

3. A 1996-1998 model-year ZEV may qualify for a ZEV multiplier according to section 1962(d)(1)(A)1. or section 1962(d)(1)(A)2., but not both. For purposes of calculating a manufacturer's fleet average NMOG value under section 1960.1(g)(2), each ZEV that qualifies for a ZEV multiplier shall be counted as one vehicle.

(B) *1999-2007 Model-Year ZEV Multiplier Calculation for Extended Electric Range Vehicles.*

1. Each ZEV and full ZEV allowance vehicle that is produced and delivered for sale in California in the 1999 to 2007 model years and that has an extended electric range shall qualify for a ZEV multiplier as follows:

All-electric range	MY 1999-2000	MY 2001 -2002	MY 2003-2005	MY 2006-2007
100-175	6-10	4-6	2-4	1-2

ZEV multipliers under the above schedule will be determined by linear interpolation between the values shown in the above schedule. Range shall be determined in accordance with Section E.3.(2)(a) of the "California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric Vehicles, in the Passenger Car, Light-Duty Truck and Medium-Duty Vehicle Classes," incorporated by reference in section 1962(e). ZEVs that have a refueling time of less than 10 minutes and a range of 100 miles or more shall be counted as having unlimited all-electric range, and shall consequently earn the maximum allowable ZEV multiplier for a specific model year. ZEVs that have a range of 80 to 99 miles shall qualify for ZEV multipliers in 1999-2002 model years in accordance with the following equation:

$$\text{ZEV multiplier} = (\text{minimum allowable ZEV multiplier per above table for a model year}) \times (\text{AER equivalent to a 10 minute recharge}/100) \times 0.5.$$

2. For purposes of calculating a manufacturer's fleet average NMOG value under sections 1960.1(g)(2) and 1961(b) and (c), each extended electric range ZEV shall be counted as one vehicle.

(2) *Effect of ZEV Multipliers.* In calculating the number of ZEVs and full ZEV allowance vehicles produced and delivered for sale in California by a manufacturer in a model year and the ZEV credits from such vehicles, the number of ZEVs and full ZEV allowance vehicles qualifying for a particular ZEV multiplier shall be multiplied by the ZEV multiplier.

(3) *ZEV Credit Calculations.*

(A) *Credits from ZEVs and Full ZEV Allowance Vehicles.* A full ZEV allowance vehicle shall be treated as a ZEV in calculating and applying ZEV credits. The amount of ZEV credits earned by a manufacturer in a given model year from ZEVs shall be expressed in units of g/mi NMOG, and shall be equal to the number of ZEVs produced and delivered for sale in California that the manufacturer applies towards meeting the ZEV requirements for the model year (at least 40% of the ZEV requirement for a large volume manufacturers) subtracted from the number of ZEVs produced and delivered for sale in California by the manufacturer in the model year and then multiplied by the NMOG fleet average requirement for PCs and LDT1s for that model year.

(B) *Credits from Partial ZEV Allowance Vehicles.* The amount of ZEV credits from partial ZEV allowance vehicles earned by a manufacturer in a given model year shall be expressed in units of g/mi NMOG, and shall be equal to the total number of ZEV allowances from partial ZEV allowance vehicles produced and delivered for sale in California that the manufacturer applies towards meeting its ZEV requirement for the model year (a number not to exceed 60% of the ZEV requirement for large volume manufacturers) subtracted from the total number of ZEV allowances from partial ZEV allowance vehicles produced and delivered for sale in California by the manufacturer in the model year and then multiplied by the NMOG fleet average requirement for PCs and LDT1s for that model year.

(C) The number of credits from a manufacturer's ZEVs and full ZEV allowance vehicles shall be maintained separately from the number of credits from the manufacturer's partial ZEV allowance vehicles.

(4) *ZEV Credits for MDVs and LDTs other than LDT1s.* ZEVs classified as MDVs or as LDTs other than LDT1s may be counted toward the ZEV requirement for PCs and LDT1s, and included in the calculation of ZEV credits as specified in this section 1962(d) if the manufacturer so designates.

(5) *Submittal of ZEV Credits.* A manufacturer may meet the ZEV requirements in any given model year by submitting to the Executive Officer a commensurate amount of ZEV credits, consistent with section 1962(b). These credits may be earned previously by the manufacturer or acquired from another manufacturer. The amount of ZEV credits required to be submitted shall be calculated according to the criteria set forth in this section 1962(d).

(6) *Requirement to Make Up a ZEV Deficit.* A manufacturer that produces and delivers for sale in California fewer ZEVs than required in a given model year shall make up the deficit by the end of the next model year by submitting to the Executive Officer a commensurate amount of ZEV credits. The amount of ZEV credits required to be submitted shall be calculated by (A) adding the number of ZEVs produced and delivered for sale in California by the manufacturer for the model year to the number of ZEV allowances from partial ZEV allowance vehicles produced and delivered for sale in California by the manufacturer for the model year (not to exceed 60% of a large volume manufacturer's ZEV requirement), (B) subtracting that total from the number of ZEVs required to be produced and delivered for sale in California by the

manufacturer for the model year, and (C) multiplying the resulting value by the fleet average requirements for PCs and LDT1s for the model year in which the deficit is incurred.

(7) *Penalty for Failure to Meet ZEV Requirements.* Any manufacturer that fails to produce and deliver for sale in California the required number of ZEVs or submit an appropriate amount of ZEV credits and does not make up ZEV deficits within the specified time period shall be subject to the Health and Safety Code section 43211 civil penalty applicable to a manufacturer that sells a new motor vehicle that does not meet the applicable emission standards adopted by the state board. The cause of action shall be deemed to accrue when the ZEV deficits are not balanced by the end of the specified time period. For the purposes of Health and Safety Code section 43211, the number of vehicles not meeting the state board's standards shall be calculated according to the following equation, provided that no more than 60% of a large volume manufacturer's ZEV requirement for a given model year may be satisfied with partial ZEV allowance vehicles or ZEV credits from such vehicles:

$$\frac{(\text{No. of ZEVs required to be produced and delivered for sale in California for the model year}) - (\text{No. of ZEVs produced and delivered for sale in California for the model year}) - (\text{No. of ZEV allowances from partial ZEV allowance vehicles produced and delivered for sale in California for the model year}) - [(\text{Amount of ZEV credits submitted for the model year}) / (\text{the fleet average requirement for PCs and LDT1s for the model-year})]}{1}$$

(e) *Test Procedures.* The certification requirements and test procedures for determining compliance with this section 1962 are set forth in "California Exhaust Emission Standards and Test Procedures for 2003 and Subsequent Model Zero-Emission Vehicles, and 2001 and Subsequent Model Hybrid Electric Vehicles, in the Passenger Car, Light-Duty Truck and Medium-Duty Vehicle Classes," adopted by the state board on August 5, 1999, which is incorporated herein by reference.

(f) *Abbreviations.* The following abbreviations are used in this section 1962:

"AER" means all-electric range.

"HEV" means hybrid-electric vehicle.

"LDT" means light-duty truck.

"LDT1" means a light-truck with a loaded vehicle weight of 0-3750 pounds.

"MDV" means medium-duty vehicle.

"Non-Methane Organic Gases" or "NMOG" means the total mass of oxygenated and non-oxygenated hydrocarbon emissions.

"NOx" means oxides of nitrogen.

"PC" means passenger car.

"SULEV" means super ultra-low-emission-vehicle.

"ULEV" means ultra-low emission vehicle.

"VMT" means vehicle miles traveled.

Note: Authority cited: Sections 39600, 39601, 43013, 43018, 43101, 43104 and 43105, Health and Safety Code. Reference: Sections 39002, 39003, 39667, 43000, 43009.5, 43013, 43018, 43100, 43101, 43101.5, 43102, 43104, 43105, 43106, 43107, 43204, and 43205.5, Health and Safety Code.

* * * *

§ 1965. Emission Control and Smog Index Labels - 1979 and Subsequent Model-Year Motor Vehicles.

In addition to all other requirements, emission control labels required by California certification procedures and smog index labels shall conform to the "California Motor Vehicle Emission Control and Smog Index Label Specifications," adopted March 1, 1978, as last amended August 5, 1999, which is incorporated herein by reference.

Note: Authority cited: Sections 39600, 39601, and 43200, Health and Safety Code. Reference: Sections 39002, 39003, 43000, 43013, 43100, 43101, 43102, 43103, 43104, 43107, and 43200, Health and Safety Code.

* * * *

§ 1976. Standards and Test Procedures for Motor Vehicle Fuel Evaporative Emissions.

(a) *[Fuel evaporative emissions standards for 1970 through 1977 model passenger cars and light-duty trucks; not set forth]*

(b)(1) Evaporative emissions for 1978 and subsequent model gasoline-fueled, 1983 and subsequent model liquefied petroleum gas-fueled, and 1993 and subsequent model alcohol-fueled motor vehicles and hybrid electric vehicles subject to exhaust emission standards under this article, except petroleum-fueled diesel vehicles, compressed natural gas-fueled vehicles, hybrid electric vehicles that have sealed fuel systems which can be demonstrated to have no evaporative emissions, and motorcycles, shall not exceed the following standards:

(A) For vehicles identified below, tested in accordance with the test procedure based on the Sealed Housing for Evaporative Determination as set forth in Title 40, Code of Federal Regulations, sections 86.130-78 through 86.143-90 as they existed July 1, 1989, the evaporative emission standards are:

<i>Vehicle Type</i>	<i>Model Year</i>	<i>Hydrocarbons⁽¹⁾ Diurnal + Hot Soak (grams/test) 50K miles</i>
Passenger cars	1978 and 1979	6.0
Light-duty trucks		6.0
Medium-duty vehicles		6.0
Heavy-duty vehicles		6.0
Passenger cars	1980-1994 ⁽²⁾	2.0
Light-duty trucks		2.0
Medium-duty vehicles		2.0
Heavy-duty vehicles		2.0

(1) Organic Material Hydrocarbon Equivalent, for alcohol-fueled vehicles.

(2) Other than hybrid electric vehicles.

- (B) For the vehicles identified below, tested in accordance with the test procedure which includes the running loss test, the hot soak test, and the 72 hour diurnal test, the evaporative emission standards are:

<i>Vehicle Type</i>	<i>Model Year</i>	<i>Hydrocarbons⁽¹⁾</i>	
		<i>Three-Day Diurnal +Hot Soak (grams/test) Useful Life⁽²⁾</i>	<i>Running Loss (grams/mile) Useful Life⁽²⁾</i>
Passenger cars	1995 through 2005 ⁽³⁾	2.0	0.05
Light-duty trucks		2.0	0.05
Medium-duty vehicles (6,001-8,500 lbs. GVWR) with fuel tanks < 30 gallons		2.0	0.05
with fuel tanks ≥ 30 gallons (8,501-14,000 lbs. GVWR) ⁽⁴⁾		2.5	0.05
Heavy-duty vehicles (over 14,000 lbs. GVWR)		3.0	0.05
Hybrid electric passenger cars	1993 through 2005 ⁽⁵⁾	2.0	0.05
Hybrid electric light-duty trucks		2.0	0.05
Hybrid electric medium-duty vehicles		2.0	0.05

- (1) Organic Material Hydrocarbon Equivalent for alcohol-fueled vehicles.
- (2) For purposes of this paragraph, “useful life” shall have the same meaning as provided in section 2112, title 13, California Code of Regulations. Approval of vehicles which are not exhaust emission tested using a chassis dynamometer pursuant to section 1960.1 or 1961, title 13, California Code of Regulations shall be based on an engineering evaluation of the system and data submitted by the applicant.
- (3) The running loss and useful life three-day diurnal plus hot soak evaporative emission standards (hereinafter “running loss and useful life standards”) shall be phased-in beginning with the 1995 model year. Each manufacturer, except ultra-small volume and small volume manufacturers, shall

certify the specified percent (a) of passenger cars and (b) of light-duty trucks, medium-duty vehicles and heavy-duty vehicles to the running loss and useful life standards according to the following schedule:

<u>Model Year</u>	<u>Minimum Percentage of Vehicles Certified to Running Loss and Useful Life Standards*</u>
1995	10 percent
1996	30 percent
1997	50 percent

* The minimum percentage of motor vehicles of each vehicle type required to be certified to the running loss and useful life standards shall be based on the manufacturer's projected California model-year sales (a) of passenger cars and (b) of light-duty trucks, medium-duty vehicles and heavy-duty vehicles. Optionally, the percentage of motor vehicles can also be based on the manufacturer's projected California model-year sales (a) of passenger cars and light-duty trucks and (b) of medium-duty vehicles and heavy-duty vehicles.

Beginning with the 1998 model year, all motor vehicles subject to the running loss and useful life standards, except those produced by ultra-small volume manufacturers, shall be certified to the specified standards. In the 1999 through the 2005 model years, all motor vehicles subject to the running loss and useful life standards, including those produced by ultra-small volume manufacturers, shall be certified to the specified standards.

All 1995 through 1998 model-year motor vehicles which are not subject to running loss and useful life standards pursuant to the phase-in schedule shall comply with the 50,000-mile standards in effect for 1980 through 1994 model-year vehicles.

- (4) For the 1995 model year only, the evaporative emission standards for complete vehicles in this weight range shall be 2.0 grams/test and compliance with the evaporative emission standards shall be based on the SHED conducted in accordance with the procedures set forth in title 40, Code of Federal Regulations, sections 86.130-78 through 86.143-90 as they existed July 1, 1989. For the 1995 through 2005 model years, the evaporative emission standards for incomplete vehicles in this weight range shall be 2.0 grams/test and compliance with the evaporative emission standards shall be based on the test procedures specified in paragraph 4.g. of the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."
- (5) The running loss and useful life standards for all hybrid electric vehicles shall be effective beginning in the 1993 model year.

(C) For vehicles identified below, tested in accordance with the test procedure which includes the hot soak test and the 48 hour diurnal test, the evaporative emission standards are:

		<i>Hydrocarbons⁽¹⁾</i>
--	--	-----------------------------------

<i>Vehicle Type</i>	<i>Model Year</i>	<i>Two-Day Diurnal + Hot Soak (grams/test) Useful Life⁽²⁾</i>
Passenger cars	1996 through 2005 ⁽³⁾	2.5
Light-duty trucks		2.5
Medium-duty vehicles (6,001-8,500 lbs. GVWR) with fuel tanks < 30 gallons		2.5
		with fuel tanks ≥ 30 gallons
Medium-duty vehicles (8,501-14,000 lbs. GVWR)		3.5
Heavy-duty vehicles (over 14,000 lbs. GVWR)	4.5	
Hybrid electric passenger cars	1996 through 2005 ⁽³⁾	2.5
Hybrid electric light-duty trucks		2.5
Hybrid electric medium-duty vehicles		2.5

- (1) Organic Material Hydrocarbon Equivalent for alcohol-fueled vehicles.
- (2) For purposes of this paragraph, “useful life” shall have the same meaning as provided in section 2112, title 13, California Code of Regulations. Approval of vehicles which are not exhaust emission tested using a chassis dynamometer pursuant to section 1960.1 or 1961, title 13, California Code of Regulations shall be based on an engineering evaluation of the system and data submitted by the applicant.
- (3) The two-day diurnal plus hot soak evaporative emission standards (hereinafter “supplemental standards”) shall be phased-in beginning with the 1996 model year. Those vehicles certified under the running loss and useful life standards for the 1996 through 2005 model years must also be certified under the supplemental standards.
-
- (D) Zero-emission vehicles shall produce zero fuel evaporative emissions under any and all possible operational modes and conditions.
- (E) The optional zero-fuel evaporative emission standards for the three-day and two-day diurnal-plus-hot-soak tests are 0.35 grams per test for passenger cars, 0.50 grams per test for light-duty trucks 6,000 lbs. GVWR and under, and 0.75 grams per test for light-duty trucks from 6,001 to 8,500 lbs. GVWR, to account for vehicle non-fuel evaporative emissions (resulting from paints, upholstery, tires, and other vehicle sources). Vehicles demonstrating compliance with these evaporative emission standards shall also have zero (0.0) grams of fuel evaporative

emissions per test for the three-day and two-day diurnal-plus-hot-soak tests. The “useful life” shall be 15 years or 150,000 miles, whichever occurs first. In lieu of demonstrating compliance with the zero (0.0) grams of fuel evaporative emissions per test over the three-day and two-day diurnal-plus-hot-soak tests, the manufacturer may submit for advance Executive Officer approval a test plan to demonstrate that the vehicle has zero (0.0) grams of fuel evaporative emissions throughout its useful life.

Additionally, in the case of a SULEV vehicle for which a manufacturer is seeking a partial ZEV credit, the manufacturer may prior to certification elect to have measured fuel evaporative emissions reduced by a specified value in all certification and in-use testing of the vehicle as long as measured mass exhaust emissions of NMOG for the vehicle are increased in all certification and in-use testing. The measured fuel evaporative emissions shall be reduced in increments of 0.1 gram per test, and the measured mass exhaust emissions of NMOG from the vehicle shall be increased by a gram per mile factor, to be determined by the Executive Officer, for every 0.1 gram per test by which the measured fuel evaporative emissions are reduced. For the purpose of this calculation, the evaporative emissions shall be measured, in grams per test, to a minimum of three significant figures.

- (F) For the 2004 and subsequent model motor vehicles identified below, tested in accordance with the test procedures described in Title 40, Code of Federal Regulations, sections 86.130-78 through 86.143-90 as they existed July 1, 1989 and as modified by the “California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles” incorporated by reference in section 1976(c), the evaporative emission standards are:

<i>Vehicle Type</i>	<i>Hydrocarbon⁽¹⁾ Standards⁽²⁾⁽³⁾⁽⁴⁾</i>		
	<i>Running Loss (grams per mile)</i>	<i>Three Day Diurnal + Hot Soak (grams per test)</i>	<i>Two-Day Diurnal + Hot Soak (grams per test)</i>
Passenger cars	0.05	0.50	0.65
Light-duty trucks (under 8,501 lbs. GVWR)			
6,000 lbs. GVWR and under	0.05	0.65	0.85
6,001 - 8,500 lbs. GVWR	0.05	0.90	1.15
Medium-duty vehicles (8,501 - 14,000 lbs.)	0.05	1.00	1.25

GVWR)			
Heavy-duty vehicles (over 14,000 lbs. GVWR)	0.05	1.00	1.25

- (1) Organic Material Hydrocarbon Equivalent for alcohol-fueled vehicles.
- (2) For all vehicles certified to these standards, the “useful life” shall be 15 years or 150,000 miles, whichever first occurs. Approval of vehicles which are not exhaust emission tested using a chassis dynamometer pursuant to section 1960.1 or 1961, title 13, California Code of Regulations shall be based on an engineering evaluation of the system and data submitted by the applicant.
- (3) (a) These evaporative emission standards shall be phased-in beginning with the 2004 model year. Each manufacturer, except small volume manufacturers, shall certify at a minimum the specified percentage of its vehicle fleet to the evaporative emission standards in this table or the optional zero-evaporative emission standards in section 1976(b)(1)(E) according to the schedule set forth below. For purposes of this paragraph (a), each manufacturer’s vehicle fleet consists of the total projected California sales of the manufacturer’s gasoline-fueled, liquefied petroleum-fueled and alcohol-fueled passenger cars, light-duty trucks, medium-duty vehicles, and heavy-duty vehicles.

<i>Model Year</i>	<i>Minimum Percentage of Vehicles Certified to the Standards in §§1976(b)(1)(F) and (b)(1)(E)</i>
2004	40
2005	80
2006 and subsequent	100

A small volume manufacturer shall certify 100 percent of its 2006 and subsequent model vehicle fleet to the evaporative emission standards in the table or the optional zero-evaporative emission standards in section 1976(b)(1)(E).

All 2004 through 2005 model-year motor vehicles which are not subject to these standards or the standards in section 1976(b)(1)(E) pursuant to the phase-in schedule shall comply with the requirements of sections 1976(b)(1)(B) and (C).

(b) A manufacturer may use an “Alternative or Equivalent Phase-in Schedule” to comply with the phase-in requirements. An “Alternative Phase-in” is one that achieves at least equivalent emission reductions by the end of the last model year of the scheduled phase-in. Model-year emission reductions shall be calculated by multiplying the percent of vehicles (based on the manufacturer’s projected California sales volume of the applicable vehicle fleet) meeting the new requirements per model year by the number of model years implemented prior to and including the last model year of the scheduled phase-in. The “cumulative total” is the summation of the model-year emission reductions (e.g., the three model-year 40/80/100 percent phase-in schedule would be calculated as:

(40%*3 years) + (80%*2 years) + (100%*1 year) =380). The required cumulative total for the phase-in of these standards is 380 emission reductions. Any alternative phase-in that results in an equal or larger cumulative total than the required cumulative total by the end of the last model year of the scheduled phase-in shall be considered acceptable by the Executive Officer only if all vehicles subject to the phase-in comply with the respective requirements in the last model year of the required phase-in schedule. A manufacturer shall be allowed to include vehicles introduced before the first model year of the scheduled phase-in (e.g., in the previous example, 10 percent introduced one year before the scheduled phase-in begins would be calculated as: (10%*4 years)=40) and added to the cumulative total.

(c) These evaporative emission standards do not apply to zero-emission vehicles.

- (4) In-use compliance whole vehicle testing shall not begin until the motor vehicle is at least one year from the production date and has accumulated a minimum of 10,000 miles. For vehicles introduced prior to the 2007 model year, in-use compliance standards of 1.75 times the "Three-Day Diurnal + Hot-Soak" and "Two-Day Diurnal + Hot-Soak" gram per test standards shall apply for only the first three model years of an evaporative family certified to a new standard.

(b)(2) *[Evaporative emissions standards for gasoline-fueled motorcycles; not set forth]*

(c) The test procedures for determining compliance with the standards in subsection (b) above applicable to 1978 through 2000 model year vehicles are set forth in "California Evaporative Emission Standards and Test Procedures for 1978-2000 Model Motor Vehicles," adopted by the state board on April 16, 1975, as last amended August 5, 1999, which is incorporated herein by reference. The test procedures for determining compliance with standards applicable to 2001 and subsequent model year vehicles are set forth in the "California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles," adopted by the state board on August 5, 1999, which is incorporated herein by reference.

(d) *[Applies to motorcycles only; not set forth]*

(e) *[Applies to motorcycles only; not set forth]*

(f)(2) For the purposes of this section, "ultra-small volume manufacturer" means any vehicle manufacturer with California sales less than or equal to 300 new vehicles per model year based on the average number of vehicles sold by the manufacturer in the previous three consecutive model years, and "small volume manufacturer" means, for 1978 through 2000 model years, any vehicle manufacturer with California sales less than or equal to 3000 new vehicles per model year based on the average number of vehicles sold by the manufacturer in the previous three consecutive model years. For 2001 and subsequent model motor vehicles, "small volume manufacturer" has the meaning set forth in section 1900(a).

Note: Authority cited: Sections 39600, 39601, 39667, 43013, 43018, 43101, 43104 and 43107, Health and Safety Code. Reference: Sections 39003, 39500, 39667, 43000, 43013, 43018, 43100, 43101, 43102, 43104 and 43107, Health and Safety Code.

§ 1978. Standards and Test Procedures for Vehicle Refueling Emissions.

(a)(1) Vehicle refueling emissions for 1998 and subsequent model gasoline-fueled, alcohol-fueled, diesel-fueled, fuel-flexible, and hybrid electric passenger cars, light-duty trucks, and medium-duty vehicles with a gross vehicle weight rating less than 8501 pounds, shall not exceed the following standards. Gaseous fueled vehicles are exempt from meeting these refueling standards. The standards apply equally to certification and in- use vehicles.

Hydrocarbons (for gasoline-fueled, diesel-fueled, and hybrid electric vehicles): 0.20 grams per gallon of fuel dispensed.

Organic Material Hydrocarbon Equivalent (for alcohol-fueled, fuel-flexible, and hybrid electric vehicles): 0.20 grams per gallon of fuel dispensed.

(2) Vehicles powered by diesel fuel are not required to conduct testing to demonstrate compliance with the refueling emission standards set forth above, provided that all of the following provisions are met:

(A) The manufacturer can attest to the following evaluation: "Due to the low vapor pressure of diesel fuel and the vehicle tank temperatures, hydrocarbon vapor concentrations are low and the vehicle meets the 0.20 grams/gallon refueling emission standard without a control system."

(B) The certification requirement described in paragraph (A) is provided in writing and applies for the full useful life of the vehicle, as defined in section 2112.

In addition to the above provisions, the ARB reserves the authority to require testing to enforce compliance and to prevent noncompliance with the refueling emission standard.

Vehicles certified to the refueling emission standard under this provision shall not be counted in the phase-in sales percentage compliance determinations.

(3) The manufacturer shall adhere to the following phase-in schedule, as determined by projected vehicle sales throughout the United States, with the exception of small volume manufacturers.

ORVR Model Year Phase-In Schedule			
Class of Vehicle	40% Fleet	80% Fleet	100% Fleet
Passenger Cars	1998	1999	2000
Light-Duty Trucks 0-6,000 lbs. GVWR	2001	2002	2003

Light-Duty Trucks / Medium-Duty Vehicles 6,001-8,500 lbs. GVWR	2004	2005	2006
--	------	------	------

(A) Prior to the 2001 model year, small volume manufacturers are defined for purposes of this section as any vehicle manufacturer with California actual sales less than or equal to 3000 new vehicles per model year based on the average number of vehicles sold by the manufacturer in the previous three consecutive years.

(B) Small volume manufacturers of passenger cars, as defined in subsection (a)(3)(A), are exempt from the implementation schedule in subsection (a)(3) for model years 1998 and 1999. For small volume manufacturers of passenger cars, the standards of subsection (a)(1), and the associated test procedures, shall not apply until model year 2000, when 100 percent compliance with the standards of this section is required. Small volume manufacturers of light-duty trucks and medium-duty vehicles are not exempt from the implementation schedule in subsection (a)(3).

(b) The test procedures for determining compliance with standards applicable to 1998 through 2000 gasoline, alcohol, diesel, and hybrid electric passenger cars, light-duty trucks, and medium-duty vehicles are set forth in the "California Refueling Emission Standards and Test Procedures for 1998-2000 Model Motor Vehicles," as amended August 5, 1999, which is incorporated herein by reference. The test procedures for determining compliance with standards applicable to 2001 and subsequent gasoline, alcohol, diesel, and hybrid electric passenger cars, light-duty trucks, and medium-duty vehicles are set forth in the "California Refueling Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles," adopted August 5, 1999, which is incorporated herein by reference.

Note: Authority cited: Sections 39600, 39667, 43013, 43018, 43101, and 43104, Health and Safety Code.
Reference: Sections 39003, 39500, 39667, 43000, 43013, 43018, 43101, 43102, and 43104, Health and Safety Code.

* * * *

§ 2062. Assembly-Line Test Procedures - 1998 and Subsequent Model Years.

New 1998 through 2000 model-year passenger cars, light-duty trucks, and medium-duty vehicles, subject to certification and manufactured for sale in California, except for zero-emission vehicles and medium-duty vehicles certified according to the optional standards and test procedures of Section 1956.8, Title 13, California Code of Regulations, shall be tested in accordance with the "California Assembly-Line Test Procedures for 1998 Through 2000 Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles." adopted June 24, 1996, and last amended August 5, 1999, which is incorporated herein by reference. New 2001 and subsequent model-year passenger cars, light-duty trucks, and medium-duty vehicles, subject to certification and manufactured for sale in California, except for zero-emission vehicles and medium-duty vehicles certified according to the optional standards and test procedures of Section 1956.8, Title 13, California Code of Regulations, shall be tested in accordance with the "California Assembly-Line Test Procedures for 2001 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles." adopted August 5, 1999, which is incorporated herein by reference. These test procedures shall also apply to federally certified light-duty motor vehicles, except as provided in "Guidelines for Certification of 1983 and Subsequent Model-Year Federally Certified Light-Duty Motor Vehicles for Sale in California," adopted July 20, 1982, as last amended July 12, 1991, which is incorporated herein by reference.

NOTE: Authority cited: Sections 39515, 39600, 39601, 43013, 43018, 43101, 43104 and 43210, Health and Safety Code. Reference: Sections 39002, 39003, 39500, 43000, 43013, 43018, 43100, 43101, 43101.5, 43102, 43104, 43105, 43106, 43204, 43210, 43211, and 43212, Health and Safety Code.

* * * *

§2101. Compliance Testing and Inspection - New Vehicle Selection Evaluation, and Enforcement Action.

(a) The Executive Officer may, with respect to any new vehicle engine family, test group or subgroup being sold, offered for sale, or manufactured for sale in California, order a vehicle manufacturer to make available for compliance testing and/or inspection a reasonable number of vehicles, and may direct that the vehicles be delivered to the state board at the Haagen-Smit Laboratory, 9528 Telstar Avenue, El Monte, California. Vehicles shall be selected at random from sources specified by the Executive Officer according to a method approved by him/her, which insofar as practical shall exclude (1) vehicles manufactured pursuant to the specific order of an ultimate purchaser or (2) vehicles the selection of which, if not excluded, would result in an unreasonable disruption of the manufacturer's distribution system.

A subgroup may be selected for compliance testing only if the Executive Officer has reason to believe that the emissions characteristics of that subgroup are substantially in excess of the emissions of the engine family or test group as a whole.

(b) If the vehicles are selected for compliance testing, the selection and testing of vehicles and the evaluation of data shall be made in accordance with the "California New Vehicle Compliance Test Procedures," adopted by the state board on June 13, 1976, and last amended August 5, 1999. Motorcycles scheduled for compliance testing shall be selected, tested, and evaluated in accordance with the "California New Motorcycle Compliance Test Procedures," adopted by the state board on June 30, 1977, and amended November 24, 1981.

(c) If the Executive Officer determines, in accordance with the "California New Vehicle Compliance Test Procedures," or the "California New Motorcycle Compliance Test Procedures" that an engine family, test group, or any subgroup within an engine family or test group, exceeds the emission standards for one or more pollutants, the Executive Officer shall notify the manufacturer and may invoke Section 2109. Prior to invoking Section 2109, the Executive Officer shall consider quality audit test results, if any, and any additional test data or other information provided by the manufacturer.

(d) Vehicles selected for inspection shall be checked to verify the presence of those emissions-related components specified in the manufacturer's application for certification, and for the accuracy of any adjustments, part numbers and labels specified in that application. If any vehicle selected for inspection fails to conform to any applicable law in Part 5 (commencing with Section 43000) of Division 26 of the Health and Safety Code, or any regulation adopted by the state board pursuant thereto, other than an emissions standard applied to new vehicles to determine "certification" as specified in Subchapter 1, Article 2 of this Chapter and an assembly-line test procedure specified in Subchapter 2, Article 1 of this Chapter, the executive officer shall notify the manufacturer and may invoke Section 2109. Prior to invoking Section 2109, the executive officer shall consider any information provided by the manufacturer.

NOTE: Authority cited: Sections 39600, 39601 and 43104, Health and Safety Code. Reference: Sections 39002, 39003, 39500, 43000, 43106, 43210, 43211, and 43212, Health and Safety Code.