

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-1-57

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines  
CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and,

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Caterpillar, Inc. 1998 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Agriculture Tractor

Fuel Type: Diesel

<u>Engine Family</u>	<u>Liters (Cubic Inches)</u>	<u>Exhaust Emission Control Systems and Special Features</u>
WCPXL07.OMRB	7.0 (425)	Turbocharger Charge Air Cooler Smoke Puff Limiter

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hp)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Engine Family</u>	<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
	<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
WCPXL07.OMRB	0.2	1.7	6.0	0.2	14	5	22

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 9<sup>th</sup> day of December 1997.



R. B. Summerfield, Chief  
Mobile Source Operations Division

# LARGE ENGINE MODEL SUMMARY

EO: 4-R-1-57

Manufacturer: CATERPILLAR INC. Process Code: New Submission

EPA Engine Family: WCPXL07.0MRB Manufacturer Family Name: N/A

1. Engine Code    2. Engine Model    3. BHP @ RPM (SAE Gross)    4. Fuel Rate: mm/stroke @ peak HP (for diesel only)    5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)    6. Torque @ RPM (SEA Gross)    7. Fuel Rate: mm/stroke @ peak torque    8. Fuel Rate: (lbs/hr) @ peak torque    9. Emission Control Device Per SAE J1930

Note: Peak Hp and Peak torque	fuel rates are	nominal values.	Due to product-	ion engine avgs.	these fuel rates	may change.		
1 - Cert Engine	3304	205 @ 1800	179	72.2	688 @ 1200	222	59.7	EM, DI, TC, SPL,
2	3304	179 @ 2200	143	70.6	590 @ 1400	181	56.9	EM, <del>DCAC</del> , SPL,
3	3304	166 @ 2200	129	51.9	557 @ 1400	165	51.9	EM, <del>DCAC</del> , SPL,
4	3304	155 @ 2000	125	56.0	495 @ 1400	147	46.0	EM, <del>DCAC</del> , SPL,
5	3304	165 @ 2200	128	63.0	525 @ 1400	156	49.0	EM, <del>DCAC</del> , SPL,
6	3304	185 @ 2200	144	71.0	593 @ 1400	175	55.0	EM, <del>DCAC</del> , SPL,
7	3304	200 @ 2200	156	77.0	639 @ 1400	191	60.0	EM, <del>DCAC</del> , SPL,
8	3304	174 @ 1800	151	61.0	658 @ 1200	182	49.0	EM, <del>DCAC</del> , SPL,

CAC