

File



CATERPILLAR, INC.

EXECUTIVE ORDER U-R-001-0172
New Off-Road
Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2002	2CPXL10.3ESX	10.3	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Engine Control Module			Tractor, Dozer; Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
130 ≤ KW < 225	Tier 1	STD	1.3	9.2	N/A	11.4	0.54	20	15	50
75 ≤ KW < 130	Tier 1	STD	N/A	9.2	N/A	N/A	N/A	20	15	50
		FEL	N/A	6.0	N/A	N/A	N/A	N/A	N/A	N/A
		CERT	0.4	5.5	N/A	1.7	0.16	5	1	10

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 4th day of October 2001.

R. B. Summerfield
R. B. Summerfield, Chief
Mobile Source Operations Division

ATTACHMENT

Engine Model Summary Form

C

u-R-001-0172

Manufacturer: **CATERPILLAR INC.**
 Engine category: **Nonroad Over 50 Hp**
 EPA Engine Family: **2CPXL10.3ESX**
 Mfr Family Name: **N/A**
 Process Code: **New Submission**

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
Note: Peak HP and Peak torque fuel rates are nominal values. Due to production engine avgs. these fuel rates may change.								
1. Cert Engine	3176/C-10	439 @ 2100	213	150.1	1365 @ 1500	272	137.4	EM, DI, TC, ECM,
2	3176/C-10	260 @ 2000	140	94.1	845 @ 1400	166	78.2	EM, DI, TC, ECM,
3	3176/C-10	240 @ 2100	132	93.1	932 @ 1500	188	94.7	EM, DI, TC, ECM,
4	3176/C-10	240 @ 2100	132	93.1	932 @ 1500	188	94.7	EM, DI, TC, ECM,
5	3176/C-10	283 @ 2100	142	100.5	972 @ 1400	185	87.2	EM, DI, TC, ECM,
6	3176/C-10	266 @ 2100	133	93.7	916 @ 1400	175	82.4	EM, DI, TC, ECM,
7	3176/C-10	240 @ 2100	127	89.7	779 @ 1400	150	70.8	EM, DI, TC, ECM,
8	3176/C-10	280 @ 2200	138	102.3	993 @ 1400	184	86.9	EM, DI, TC, ECM,
9	3176/C-10	205 @ 2000	122	82.4	834 @ 1000	164	55.3	EM, DI, TC, ECM,
10	3176/C-10	185 @ 2000	113	76.2	755 @ 1000	148	49.9	EM, DI, TC, ECM,
11	3176/C-10	165 @ 2000	102	68.9	676 @ 1000	132	44.4	EM, DI, TC, ECM,
12	3176/C-10	225 @ 2000	133	89.2	939 @ 1000	187	62.8	EM, DI, TC, ECM,
13	3176/C-10	285 @ 2000	122	82.4	834 @ 1000	164	55.3	EM, DI, TC, ECM,
14	3176/C-10	185 @ 2000	113	76.2	755 @ 1000	148	49.8	EM, DI, TC, ECM,
15	3176/C-10	220 @ 2000	130	87.6	892 @ 1000	177	59.6	EM, DI, TC, ECM,
16	3176/C-10	200 @ 2000	120	80.4	814 @ 1000	160	53.7	EM, DI, TC, ECM,
17	3176/C-10	180 @ 2000	111	74.4	735 @ 1000	144	48.6	EM, DI, TC, ECM,
18	3176/C-10	240 @ 2000	140	94.2	971 @ 1000	195	65.7	EM, DI, TC, ECM,
19	3176/C-10	220 @ 2000	130	87.6	892 @ 1000	177	59.6	EM, DI, TC, ECM,
20	3176/C-10	200 @ 2000	120	80.4	814 @ 1000	150	53.7	EM, DI, TC, ECM,
21	3176/C-10	240 @ 2000	140	94.2	971 @ 1000	195	65.7	EM, DI, TC, ECM,
22	3176/C-10	220 @ 2000	130	87.6	892 @ 1000	177	59.6	EM, DI, TC, ECM,
23	3176/C-10	165 @ 2000	102	69.0	676 @ 1000	132	44.4	EM, DI, TC, ECM,
24	3176/C-10	180 @ 2000	111	74.4	735 @ 1000	144	48.6	EM, DI, TC, ECM,

* This model is used for certification engine only, not offer for sale in California
 Power rating