



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2002	2NVXL0530ANF	8.7	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler and Engine Control Module			Generator	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
225≤KW<450	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	N/A	N/A	N/A
		CERT	--	--	5.3	1.7	0.14	--	--	--

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 12<sup>th</sup> day of December 2001.

R. B. Summerfield, Chief  
Mobile Source Operations Division

Manufacturer: International E. O. # U-R-12-57  
 Engine category: Nonroad CI  
 EPA Engine Family: 2NVXL0530ANF  
 Mfr Family Name: DTA 530E  
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)		5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		6. Torque @ RPM (SEA Gross)		7. Fuel Rate: mm/stroke @ peak torque		8. Fuel Rate: (lbs/hr) @ peak torque		9. Emission Control Device Per SAE J1930
			Advertised	Average	Average	Average	Advertised	Average	Average	Average	Average		
GCB330	GCB330	330 @ 1500	249.2	125.2	NA	NA	NA	NA	ECM, TC, CAC,				
GCA350	GCA350	350 @ 1800	204.1	123.0	NA	NA	NA	NA	ECM, TC, CAC,				
GCA325	GCA325	325 @ 1800	221.1	133.3	NA	NA	NA	NA	ECM, TC, CAC,				
GCB310	GCB310	310 @ 1500	242.0	121.6	NA	NA	NA	NA	ECM, TC, CAC,				
GCA305	GCA305	305 @ 1800	205.8	124.1	NA	NA	NA	NA	ECM, TC, CAC,				
GCB300	GCB300	300 @ 1500	235.2	118.2	NA	NA	NA	NA	ECM, TC, CAC,				
GCB275	GCB275	275 @ 1500	229.1	115.1	NA	NA	NA	NA	ECM, TC, CAC,				

Dual ratings  
 GCD325  
 GCD305  
 can be either  
 GCA325 or  
 GCB300  
 GCA305 or  
 GCB275

For GCB 275, International would like to be certified as Tier 2 standard which is the stringent standard <sup>than</sup> required.