

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2004	4JDXL06:8054	6.8	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Smoke Puff Limiter			Compressor, Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
130 ≤ kW < 225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20	15	50
		FEL	-	-	9.0	-	0.33	-	-	-
		CERT	-	-	7.7	0.9	0.28	10	6	25

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 23RD day of December 2003.



Alleg Lyons, Chief
 Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: **Deere Power Systems Group of Deere and**
 Engine category: **Nonroad CI**
 EPA Engine Family: **4JDXL06.8054**
 Mfr Family Name: **350TF**
 Process Code: **New Submission**

Attachment 1082
U-R-004-0182

1.Engine Code	2.Engine Model	3.BHP @ RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@ peak torque	9.Emission Control Device Per SAE J1930
6068TTJ50	6068T	160.93 @ 2200	80.00 @ 2200	57.32 @ 2200	499.27 @ 1400	101.0 @ 1400	46.30 @ 1400	EM SPL
6068TPRNT1	6068T	194.45 @ 2400	90.00 @ 2400	70.55 @ 2400	506.64 @ 1400	104 @ 1400	48.06 @ 1400	EM SPL

TC

Engine Model Summary Form

Manufacturer: **Deere Power Systems Group of Deere and**
 Engine category: **Nonroad CI**
 EPA Engine Family: **4JDXL06.8054**
 Mfr Family Name: **350TF**
 Class Code: **Running Change**

Attachment 2 of 2

U-R-004-0182

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm ³ /stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm ³ /stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
✓6068TT058	6068T	160.93@2200	80.00@2200	57.32@2200	499.27@1400	101.0@1400	46.30@1400	EM SPL <i>DP7,TC</i>
✓6068TTJ51	6068T	170.31@2200	84.60@2200	62.75@2200	518.44@1400	104@1400	49.17@1400	EM SPL <i>↓</i>