California Environmental Protection Agency AIR RESOURCES BOARD	MOTORENFABRIK HATZ GMBH & CO. KG	EXECUTIVE ORDER U-R-034-0052 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2004	4HZXL.3.43V41	1.72, 2.57	Diesel	5000

SPECIAL FEATURES & EMISSION CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION
Direct Diesel Injection	Compressor, Pump, Other Industrial Equipment

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	--	--	6.5	2.7	0.23	1	2	3

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 6TH day of May 2004.

Allen Lyons, Chief
Mobile Source Operations Division

Model Year: 2004
Manufacturer: Motorenfabrik Hatz GmbH & Co. KG
Engine Family: 4HZXL3.43V41

Issued:
Revised: 3/17/2004
E.O. Number: U-R-034-0052

Small Off-Road Engine Model Summary Form

Units for Table: hp

Worst Case?	47. Model Designation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emiss Control Sys
	For model	information,	1716	look	in the	enclosed	4HZXL343	V41.xls	excel file.	EM DDI
	The worst	case engine	1716	marked in	red bold	capital	letters!!!			

2 of 20
U-R-034-0052

2M41
VARIABLE SPEED
4HZXL3.43V41

	RATED POWER		TORQUE	RATED SPEED	FUEL RATE			TORQUE		TORQUE SPEED	FUEL RATE AT MAX. TORQUE		
ENGINE MODE	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41	28,8	38,6	92	3000	49,0	8,2	3,7	105	77	1800	48,5	4,9	2,2
2M41	28,6	38,3	93	2950	49,0	8,1	3,7	105	77	1800	48,5	4,9	2,2
2M41	28,4	38,1	94	2900	49,0	7,9	3,6	105	77	1800	48,5	4,9	2,2
2M41	28,2	37,8	94	2850	49,0	7,8	3,5	105	77	1800	48,5	4,9	2,2
2M41	28,0	37,5	95	2800	49,0	7,6	3,5	105	77	1800	48,5	4,9	2,2
2M41	27,8	37,3	97	2750	49,5	7,6	3,4	105	77	1800	48,5	4,9	2,2
2M41	27,5	36,9	97	2700	49,5	7,5	3,4	105	77	1800	48,5	4,9	2,2
2M41	27,2	36,4	98	2650	49,5	7,3	3,3	105	77	1800	48,5	4,9	2,2
2M41	27,0	36,2	99	2600	49,5	7,2	3,3	105	77	1800	48,5	4,9	2,2
2M41	26,7	35,8	100	2550	49,5	7,0	3,2	106	78	1800	49,0	4,9	2,2
2M41	26,4	35,4	101	2500	50,5	7,0	3,2	105	77	1500	49,5	4,1	1,9
2M41	26,2	35,1	102	2450	50,5	6,9	3,1	105	77	1500	49,5	4,1	1,9
2M41	25,9	34,7	103	2400	50,5	6,8	3,1	104	77	1500	49,0	4,1	1,9
2M41	25,5	34,2	104	2350	50,5	6,6	3,0	104	77	1500	49,0	4,1	1,9

F

3 of 20
U-R-034-0052

2M41
VARIABLE SPEED
4HZXL3.43V41

	RATED POWER		TORQUE	ENGINE SPEED	FUEL RATE			TORQUE		TORQUE SPE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41	27,7	37,1	88	3000	46,5	7,8	3,5	102	75	1800	46,5	4,7	2,1
2M41	27,5	36,9	89	2950	46,5	7,6	3,5	102	75	1800	46,5	4,7	2,1
2M41	27,4	36,7	90	2900	46,5	7,5	3,4	102	75	1800	46,5	4,7	2,1
2M41	27,2	36,4	91	2850	46,5	7,4	3,4	102	75	1800	46,5	4,7	2,1
2M41	27,1	36,3	92	2800	46,5	7,3	3,3	102	75	1800	46,5	4,7	2,1
2M41	26,9	36,0	93	2750	47,0	7,2	3,3	101	74	1800	46,0	4,6	2,1
2M41	26,7	35,8	94	2700	47,0	7,1	3,2	101	74	1800	46,0	4,6	2,1
2M41	26,6	35,6	96	2650	47,0	6,9	3,2	101	74	1800	46,0	4,6	2,1
2M41	26,4	35,4	97	2600	47,5	6,9	3,1	102	75	1800	46,5	4,7	2,1
2M41	26,0	34,8	97	2550	47,5	6,8	3,1	102	75	1800	46,5	4,7	2,1
2M41	25,6	34,3	98	2500	47,5	6,6	3,0	102	75	1800	46,5	4,7	2,1
2M41	25,2	33,8	98	2450	47,5	6,5	2,9	102	75	1800	46,5	4,7	2,1
2M41	24,9	33,4	99	2400	47,5	6,4	2,9	100	74	1500	46,5	3,9	1,8
2M41	24,3	32,6	99	2350	47,5	6,2	2,8	100	74	1500	46,5	3,9	1,8

IFNsi

4 of 20
4-R-034-0852

2M41
VARIABLE SPEED
4HZXL3.43V41

IFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41	26,3	35,2	84	3000	44,0	7,4	3,3	90	66	1800	42,0	4,2	1,9
2M41	26,1	35,0	84	2950	44,0	7,2	3,3	90	66	1800	42,0	4,2	1,9
2M41	26,0	34,8	86	2900	44,0	7,1	3,2	93	69	1800	43,0	4,3	2,0
2M41	25,8	34,6	86	2850	44,0	7,0	3,2	93	69	1800	43,0	4,3	2,0
2M41	25,7	34,4	88	2800	44,0	6,9	3,1	98	72	1800	44,5	4,5	2,0
2M41	25,5	34,2	89	2750	44,5	6,8	3,1	96	71	1800	44,0	4,4	2,0
2M41	25,3	33,9	89	2700	44,5	6,7	3,0	91	67	1800	42,5	4,3	1,9
2M41	25,2	33,8	91	2650	44,5	6,6	3,0	91	67	1800	42,5	4,3	1,9
2M41	25,0	33,5	92	2600	45,0	6,5	3,0	95	70	1500	43,5	3,6	1,7
2M41	24,7	33,1	92	2550	45,0	6,4	2,9	95	70	1500	43,5	3,6	1,7
2M41	24,3	32,6	93	2500	46,0	6,4	2,9	97	72	1500	44,5	3,7	1,7
2M41	23,9	32,0	93	2450	46,0	6,3	2,9	97	72	1500	44,5	3,7	1,7
2M41	23,6	31,6	94	2400	46,0	6,2	2,8	96	71	1500	44,0	3,7	1,7
2M41	23,0	30,8	93	2350	46,0	6,0	2,7	96	71	1500	44,0	3,7	1,7
2M41	25,4	34,0	105	2300	51,0	6,5	3,0	105	77	2300	51,0	6,5	3,0
2M41	24,9	33,4	106	2250	51,0	6,4	2,9	106	78	2250	51,0	6,4	2,9
2M41	24,4	32,7	106	2200	51,0	6,3	2,8	106	78	2200	51,0	6,3	2,8
2M41	23,9	32,0	106	2150	51,0	6,1	2,8	106	78	2150	51,0	6,1	2,8
2M41	23,4	31,4	106	2100	51,0	6,0	2,7	106	78	2100	51,0	6,0	2,7
2M41	22,9	30,7	107	2050	51,0	5,8	2,6	107	79	2050	51,0	5,8	2,6
2M41	22,4	30,0	107	2000	51,0	5,7	2,6	107	79	2000	51,0	5,7	2,6
2M41	21,9	29,3	107	1950	49,5	5,4	2,4	107	79	1950	49,5	5,4	2,4
2M41	21,3	28,5	107	1900	49,5	5,2	2,4	107	79	1900	49,5	5,2	2,4
2M41	20,8	27,9	107	1850	49,5	5,1	2,3	107	79	1850	49,5	5,1	2,3
2M41	20,2	27,1	107	1800	49,5	5,0	2,3	107	79	1800	49,5	5,0	2,3

5 of 20
U-K-034-0052

2M41
VARIABLE SPEED
4HZXL3.43V41

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SPE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41	23,7	31,8	75	3000	40,0	6,7	3,0	89	66	1500	40,5	3,4	1,5
2M41	23,5	31,5	76	2950	40,0	6,6	3,0	89	66	1500	40,5	3,4	1,5
2M41	23,4	31,4	77	2900	40,0	6,5	2,9	88	65	1500	40,0	3,3	1,5
2M41	23,2	31,1	78	2850	40,0	6,4	2,9	88	65	1500	40,0	3,3	1,5
2M41	23,1	31,0	79	2800	40,0	6,2	2,8	96	71	1800	44,0	4,4	2,0
2M41	23,0	30,8	80	2750	40,5	6,2	2,8	88	65	1500	40,0	3,3	1,5
2M41	22,8	30,6	81	2700	40,5	6,1	2,8	88	65	1500	40,0	3,3	1,5
2M41	22,7	30,4	82	2650	40,5	6,0	2,7	88	65	1500	40,0	3,3	1,5
2M41	22,5	30,2	83	2600	40,5	5,9	2,7	88	65	1500	40,0	3,3	1,5
2M41	22,2	29,7	83	2550	40,5	5,8	2,6	88	65	1500	40,0	3,3	1,5
2M41	21,9	29,3	84	2500	41,0	5,7	2,6	88	65	1500	40,0	3,3	1,5
2M41	21,5	28,8	84	2450	41,0	5,6	2,5	88	65	1500	40,0	3,3	1,5
2M41	21,2	28,4	84	2400	41,0	5,5	2,5	88	65	1500	40,0	3,3	1,5
2M41	20,7	27,7	84	2350	41,0	5,4	2,4	93	69	1500	42,5	3,6	1,6
2M41	22,9	30,7	95	2300	47,0	6,0	2,7	100	74	1500	46,5	3,9	1,8

ICFN

6 of 20
U-K-034-0052

2M41Z (Z = Turbocharger with wastegate)
VARIABLE SPEED
4HZXL3.43V41

	RATED POWER		TORQUE	RATED SPEE	FUEL RATE			TORQUE		TORQUE SPEE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41Z	28,1	37,7	89	3000	49,0	8,2	3,7	103	76	1800	48,5	4,9	2,2
2M41Z	27,9	37,4	90	2950	49,0	8,1	3,7	103	76	1800	48,5	4,9	2,2
2M41Z	27,7	37,1	91	2900	49,0	7,9	3,6	103	76	1800	48,5	4,9	2,2
2M41Z	27,5	36,9	92	2850	49,0	7,8	3,5	103	76	1800	48,5	4,9	2,2
2M41Z	27,3	36,6	93	2800	49,0	7,6	3,5	103	76	1800	48,5	4,9	2,2
2M41Z	27,1	36,3	94	2750	49,5	7,6	3,4	103	76	1800	48,5	4,9	2,2
2M41Z	26,8	35,9	95	2700	49,5	7,5	3,4	103	76	1800	48,5	4,9	2,2
2M41Z	26,5	35,5	95	2650	49,5	7,3	3,3	103	76	1800	48,5	4,9	2,2
2M41Z	26,3	35,2	97	2600	49,5	7,2	3,3	103	76	1800	48,5	4,9	2,2
2M41Z	26,0	34,8	97	2550	49,5	7,0	3,2	104	77	1800	49,0	4,9	2,2
2M41Z	25,8	34,6	99	2500	50,5	7,0	3,2	103	76	1500	49,5	4,1	1,9
2M41Z	25,6	34,3	100	2450	50,5	6,9	3,1	103	76	1500	49,5	4,1	1,9
2M41Z	25,3	33,9	101	2400	50,5	6,8	3,1	102	75	1500	49,0	4,1	1,9
2M41Z	24,9	33,4	101	2350	50,5	6,6	3,0	102	75	1500	49,0	4,1	1,9

F

7 of 20
U-R-034-0052

2M41Z [illegible]
VARIABLE SPEED

4HZXL3.43V41

IFNsi

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOI	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lb/ft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41Z	27,0	36,2	86	3000	46,5	7,8	3,5	100	74	1800	46,5	4,7	2,1
2M41Z	26,8	35,9	87	2950	46,5	7,6	3,5	100	74	1800	46,5	4,7	2,1
2M41Z	26,7	35,8	88	2900	46,5	7,5	3,4	100	74	1800	46,5	4,7	2,1
2M41Z	26,5	35,5	89	2850	46,5	7,4	3,4	100	74	1800	46,5	4,7	2,1
2M41Z	26,4	35,4	90	2800	46,5	7,3	3,3	100	74	1800	46,5	4,7	2,1
2M41Z	26,2	35,1	91	2750	47,0	7,2	3,3	99	73	1800	46,0	4,6	2,1
2M41Z	26,0	34,8	92	2700	47,0	7,1	3,2	99	73	1800	46,0	4,6	2,1
2M41Z	25,9	34,7	93	2650	47,0	6,9	3,2	99	73	1800	46,0	4,6	2,1
2M41Z	25,7	34,4	94	2600	47,5	6,9	3,1	100	74	1800	46,5	4,7	2,1
2M41Z	25,3	33,9	95	2550	47,5	6,8	3,1	100	74	1800	46,5	4,7	2,1
2M41Z	25,0	33,5	95	2500	47,5	6,6	3,0	100	74	1800	46,5	4,7	2,1
2M41Z	24,6	33,0	96	2450	47,5	6,5	2,9	100	74	1800	46,5	4,7	2,1
2M41Z	24,3	32,6	97	2400	47,5	6,4	2,9	98	72	1500	46,5	3,9	1,8
2M41Z	23,7	31,8	96	2350	47,5	6,2	2,8	98	72	1500	46,5	3,9	1,8

U-K-024-0052 8 of 20

2M41Z [illegible]

VARIABLE SPEED

4HZXL3.43V41

IFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41Z	25,6	34,3	81	3000	44,0	7,4	3,3	88	65	1800	42,0	4,2	1,9
2M41Z	25,4	34,0	82	2950	44,0	7,2	3,3	88	65	1800	42,0	4,2	1,9
2M41Z	25,3	33,9	83	2900	44,0	7,1	3,2	91	67	1800	43,0	4,3	2,0
2M41Z	25,1	33,6	84	2850	44,0	7,0	3,2	91	67	1800	43,0	4,3	2,0
2M41Z	25,0	33,5	85	2800	44,0	6,9	3,1	94	69	1800	44,0	4,4	2,0
2M41Z	24,8	33,2	86	2750	44,5	6,8	3,1	94	69	1800	44,0	4,4	2,0
2M41Z	24,6	33,0	87	2700	44,5	6,7	3,0	89	66	1800	42,5	4,3	1,9
2M41Z	24,5	32,8	88	2650	44,5	6,6	3,0	89	66	1800	42,5	4,3	1,9
2M41Z	24,3	32,6	89	2600	45,0	6,5	3,0	93	69	1500	43,5	3,6	1,7
2M41Z	24,0	32,2	90	2550	45,0	6,4	2,9	93	69	1500	43,5	3,6	1,7
2M41Z	23,7	31,8	91	2500	46,0	6,4	2,9	95	70	1500	44,5	3,7	1,7
2M41Z	23,3	31,2	91	2450	46,0	6,3	2,9	95	70	1500	44,5	3,7	1,7
2M41Z	23,0	30,8	92	2400	46,0	6,2	2,8	94	69	1500	44,0	3,7	1,7
2M41Z	22,4	30,0	91	2350	46,0	6,0	2,7	94	69	1500	44,0	3,7	1,7
2M41Z	**24,8**	**33,2**	**103**	**2300**	**51,0**	**6,5**	**3,0**	**103**	**76**	**2300**	**51,0**	**6,5**	**3,0**
2M41Z	24,3	32,6	103	2250	51,0	6,4	2,9	103	76	2250	51,0	6,4	2,9
2M41Z	23,8	31,9	103	2200	51,0	6,3	2,8	103	76	2200	51,0	6,3	2,8
2M41Z	23,3	31,2	103	2150	51,0	6,1	2,8	103	76	2150	51,0	6,1	2,8
2M41Z	22,8	30,6	104	2100	51,0	6,0	2,7	104	77	2100	51,0	6,0	2,7
2M41Z	22,3	29,9	104	2050	51,0	5,8	2,6	104	77	2050	51,0	5,8	2,6
2M41Z	21,8	29,2	104	2000	51,0	5,7	2,6	104	77	2000	51,0	5,7	2,6
2M41Z	21,3	28,5	104	1950	49,5	5,4	2,4	104	77	1950	49,5	5,4	2,4
2M41Z	20,8	27,9	105	1900	49,5	5,2	2,4	105	77	1900	49,5	5,2	2,4
2M41Z	20,2	27,1	104	1850	49,5	5,1	2,3	104	77	1850	49,5	5,1	2,3
2M41Z	19,6	26,3	104	1800	49,5	5,0	2,3	104	77	1800	49,5	5,0	2,3

worst case engine:

The 2M41Z engine has more frictional power losses caused by the balancer shafts with the same fuel quantity than the 2M41 at the same rated speed (this engine is without balancer shafts).
This is the worst case engine we tested for the EPA engine family because emissions are divided by less power (g/kWh) at the same fuel quantity specifications.

9 of 20
U-R-034-0052

2M41Z (Vertical Water Cooled Engine with Injection Pump)
VARIABLE SPEED
4HZXL3.43V41

ICFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2M41Z	23,0	30,8	73	3000	40,0	6,7	3,0	87	64	1500	40,5	3,4	1,5
2M41Z	22,8	30,6	74	2950	40,0	6,6	3,0	87	64	1500	40,5	3,4	1,5
2M41Z	22,7	30,4	75	2900	40,0	6,5	2,9	86	63	1500	40,0	3,3	1,5
2M41Z	22,5	30,2	75	2850	40,0	6,4	2,9	86	63	1500	40,0	3,3	1,5
2M41Z	22,4	30,0	76	2800	40,0	6,2	2,8	86	63	1500	40,0	3,3	1,5
2M41Z	22,3	29,9	77	2750	40,5	6,2	2,8	86	63	1500	40,0	3,3	1,5
2M41Z	22,1	29,6	78	2700	40,5	6,1	2,8	86	63	1500	40,0	3,3	1,5
2M41Z	22,0	29,5	79	2650	40,5	6,0	2,7	86	63	1500	40,0	3,3	1,5
2M41Z	21,8	29,2	80	2600	40,5	5,9	2,7	86	63	1500	40,0	3,3	1,5
2M41Z	21,5	28,8	81	2550	40,5	5,8	2,6	86	63	1500	40,0	3,3	1,5
2M41Z	21,3	28,5	81	2500	41,0	5,7	2,6	86	63	1500	40,0	3,3	1,5
2M41Z	20,9	28,0	81	2450	41,0	5,6	2,5	86	63	1500	40,0	3,3	1,5
2M41Z	20,6	27,6	82	2400	41,0	5,5	2,5	86	63	1500	40,0	3,3	1,5
2M41Z	20,1	26,9	82	2350	41,0	5,4	2,4	91	67	1500	42,5	3,6	1,6
2M41Z	22,3	29,9	93	2300	47,0	6,0	2,7	98	72	1500	46,5	3,9	1,8

10 of 20
U-R-034-0052

2L41C (Vertical Water Cooled Engine with Injection Pump)
VARIABLE SPEED
4HZXL3.43V41

F

	RATED POWER		TORQUE	RATED SPEE	FUEL RATE			TORQUE		TORQUE SPEE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2L41C	27,7	37,1	88	3000	47,0	7,9	3,6	98	72	1800	47,5	4,8	2,2
2L41C	27,5	36,9	89	2950	47,0	7,7	3,7	98	72	1800	47,5	4,8	2,2
2L41C	27,3	36,6	90	2900	47,0	7,6	3,6	98	72	1800	47,5	4,8	2,2
2L41C	27,1	36,3	91	2850	47,0	7,5	3,5	96	71	1800	47,0	4,7	2,1
2L41C	26,9	36,0	92	2800	47,0	7,3	3,5	95	70	1800	46,5	4,7	2,1
2L41C	26,7	35,8	93	2750	47,5	7,3	3,4	96	71	1800	47,0	4,7	2,1
2L41C	26,5	35,5	94	2700	47,5	7,1	3,4	96	71	1800	47,0	4,7	2,1
2L41C	26,2	35,1	94	2650	47,5	7,0	3,3	96	71	1800	47,0	4,7	2,1
2L41C	25,9	34,7	95	2600	47,5	6,9	3,3	95	70	1800	46,5	4,7	2,1
2L41C	25,7	34,4	96	2550	47,5	6,8	3,2	96	71	1800	47,0	4,7	2,1
2L41C	25,4	34,0	97	2500	48,0	6,7	3,2	97	72	1500	47,5	4,0	1,8
2L41C	24,9	33,4	97	2450	48,0	6,6	3,1	97	72	1500	47,5	4,0	1,8
2L41C	25,0	33,5	99	2400	49,0	6,6	3,0	99	73	2400	49,0	6,6	3,0
2L41C	23,7	31,8	98	2350	48,0	6,3	3,0	96	71	2350	48,0	6,3	2,9

11 of 20
4-R 03 4-00

2L41C (Cattle for engine [illegible])
VARIABLE SPEED
4HZXL3.43V41

IFNsi

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SPI	FUEL RATE AT MAX. TORQUE		
ENGINE MOI	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2L41C	25,7	34,4	82	3000	45,0	7,5	3,4	93	69	1800	45,5	4,6	2,1
2L41C	25,6	34,3	83	2950	45,0	7,4	3,7	93	69	1800	45,5	4,6	2,1
2L41C	25,4	34,0	84	2900	45,0	7,3	3,6	93	69	1800	45,5	4,6	2,1
2L41C	25,3	33,9	85	2850	45,0	7,1	3,5	92	68	1800	45,0	4,5	2,0
2L41C	25,1	33,6	86	2800	45,0	7,0	3,5	92	68	1800	45,0	4,5	2,0
2L41C	25,0	33,5	87	2750	45,5	7,0	3,4	92	68	1800	45,0	4,5	2,0
2L41C	24,8	33,2	88	2700	45,5	6,8	3,4	92	68	1800	45,0	4,5	2,0
2L41C	24,7	33,1	89	2650	45,5	6,7	3,3	92	68	1800	45,0	4,5	2,0
2L41C	24,5	32,8	90	2600	46,0	6,7	3,3	92	68	1800	45,0	4,5	2,0
2L41C	24,2	32,4	91	2550	46,0	6,5	3,2	93	69	1800	45,5	4,6	2,1
2L41C	23,8	31,9	91	2500	46,5	6,5	3,2	96	71	1500	47,0	3,9	1,8
2L41C	23,4	31,4	91	2450	46,5	6,4	3,1	94	69	1500	46,0	3,8	1,7
2L41C	23,1	31,0	92	2400	46,5	6,2	3,0	94	69	1500	46,0	3,8	1,7
2L41C	22,5	30,2	91	2350	46,5	6,1	3,0	94	69	1500	46,0	3,8	1,7

12 of 20
U-R-034-0052

2L41C (Cylinder horsepower is only holds capacitated)
VARIABLE SPEED
4HZXL3.43V41

IFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SPI	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2L41C	24,4	32,7	74	3150	42,5	7,5	3,4	88	65	1800	43,0	4,3	2,0
2L41C	24,4	32,7	78	3000	42,5	7,1	3,2	88	65	1800	43,0	4,3	2,0
2L41C	24,3	32,6	79	2950	42,5	7,0	3,2	88	65	1800	43,0	4,3	2,0
2L41C	24,1	32,3	79	2900	42,5	6,9	3,1	88	65	1800	43,0	4,3	2,0
2L41C	24,0	32,2	80	2850	42,5	6,8	3,1	86	63	1800	42,0	4,2	1,9
2L41C	23,8	31,9	81	2800	42,5	6,6	3,0	86	63	1800	42,0	4,2	1,9
2L41C	23,7	31,8	82	2750	43,0	6,6	3,0	87	64	1500	43,0	3,6	1,6
2L41C	23,5	31,5	83	2700	43,0	6,5	2,9	88	65	1800	43,0	4,3	2,0
2L41C	23,4	31,4	84	2650	43,0	6,4	2,9	88	65	1800	43,0	4,3	2,0
2L41C	23,2	31,1	85	2600	43,5	6,3	2,9	88	65	1800	43,0	4,3	2,0
2L41C	22,9	30,7	86	2550	43,5	6,2	2,8	88	65	1500	43,0	3,6	1,6
2L41C	22,5	30,2	86	2500	43,5	6,1	2,8	87	64	1500	43,0	3,6	1,6
2L41C	22,2	29,7	87	2450	43,5	5,9	2,7	88	65	1500	43,5	3,6	1,7
2L41C	21,8	29,2	87	2400	43,5	5,8	2,6	87	64	1500	43,0	3,6	1,6
2L41C	21,3	28,5	87	2350	43,5	5,7	2,6	89	66	1500	44,0	3,7	1,7
2L41C	23,5	31,5	98	2300	49,0	6,3	2,9	98	72	2300	49,0	6,3	2,9
2L41C	23,1	31,0	98	2250	49,0	6,1	2,8	98	72	2250	49,0	6,1	2,8
2L41C	22,6	30,3	98	2200	49,0	6,0	2,7	98	72	2200	49,0	6,0	2,7
2L41C	22,2	29,7	99	2150	49,0	5,9	2,7	99	73	2150	49,0	5,9	2,7
2L41C	21,8	29,2	99	2100	49,0	5,7	2,6	99	73	2100	49,0	5,7	2,6
2L41C	21,3	28,5	99	2050	49,0	5,6	2,5	99	73	2050	49,0	5,6	2,5
2L41C	20,9	28,0	100	2000	49,0	5,5	2,5	100	74	2000	49,0	5,5	2,5
2L41C	20,4	27,3	100	1950	48,0	5,2	2,4	100	74	1950	48,0	5,2	2,4
2L41C	19,8	26,5	100	1900	48,0	5,1	2,3	100	74	1900	48,0	5,1	2,3
2L41C	19,3	25,9	100	1850	48,0	5,0	2,2	100	74	1850	48,0	5,0	2,2
2L41C	18,7	25,1	99	1800	48,0	4,8	2,2	99	73	1800	48,0	4,8	2,2

13 of 20
4-R-034-0052

2L41C [illegible]
VARIABLE SPEED
4HZXL3.43V41

ICFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
2L41C	22,0	29,5	70	3000	38,5	6,4	2,9	85	63	1800	41,0	4,1	1,9
2L41C	21,8	29,2	71	2950	38,5	6,3	2,9	85	63	1800	41,0	4,1	1,9
2L41C	21,7	29,1	71	2900	38,5	6,2	2,8	85	63	1800	41,0	4,1	1,9
2L41C	21,6	28,9	72	2850	38,5	6,1	2,8	80	59	1800	38,0	3,8	1,7
2L41C	21,5	28,8	73	2800	38,5	6,0	2,7	80	59	1800	38,0	3,8	1,7
2L41C	21,3	28,5	74	2750	38,5	5,9	2,7	82	60	1800	39,0	3,9	1,8
2L41C	21,2	28,4	75	2700	38,5	5,8	2,6	82	60	1800	39,0	3,9	1,8
2L41C	21,0	28,1	76	2650	38,5	5,7	2,6	82	60	1800	39,0	3,9	1,8
2L41C	20,9	28,0	77	2600	39,0	5,7	2,6	83	61	1800	40,0	4,0	1,8
2L41C	20,6	27,6	77	2550	39,0	5,5	2,5	81	60	1500	40,0	3,3	1,5
2L41C	20,3	27,2	78	2500	39,0	5,4	2,5	81	60	1500	40,0	3,3	1,5
2L41C	19,9	26,7	78	2450	39,0	5,3	2,4	81	60	1500	40,0	3,3	1,5
2L41C	19,6	26,3	78	2400	39,0	5,2	2,4	81	60	1500	40,0	3,3	1,5
2L41C	19,2	25,7	78	2350	39,0	5,1	2,3	81	60	1500	40,0	3,3	1,5
2L41C	21,2	28,4	88	2300	44,0	5,6	2,6	88	65	1500	43,5	3,6	1,7

14 of 20
4-R-034-0052

3M41
VARIABLE SPEED
4HZXL3.43V41

IFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3M41	36,9	49,4	141	2500	46,0	6,4	2,9	148	109	1500	44,5	3,7	1,7
3M41	36,4	48,8	142	2450	46,0	6,3	2,9	148	109	1500	44,5	3,7	1,7
3M41	36,0	48,2	143	2400	46,0	6,2	2,8	147	108	1500	44,0	3,7	1,7
3M41	35,2	47,2	143	2350	46,0	6,0	2,7	147	108	1500	44,0	3,7	1,7
3M41	36,7	49,2	163	2150	51,0	6,1	2,8	163	120	2150	51,0	6,1	2,8
3M41	36,0	48,2	164	2100	51,0	6,0	2,7	164	121	2100	51,0	6,0	2,7
3M41	35,2	47,2	164	2050	51,0	5,8	2,6	164	121	2050	51,0	5,8	2,6
3M41	34,5	46,2	165	2000	51,0	5,7	2,6	165	122	2000	51,0	5,7	2,6
3M41	33,7	45,2	165	1950	49,0	5,3	2,4	165	122	1950	49,0	5,3	2,4
3M41	32,8	44,0	165	1900	49,0	5,2	2,4	165	122	1900	49,0	5,2	2,4
3M41	32,0	42,9	165	1850	49,0	5,1	2,3	165	122	1850	49,0	5,1	2,3
3M41	31,1	41,7	165	1800	49,0	4,9	2,2	165	122	1800	49,0	4,9	2,2

15 8 20
U-K-024-0052

3M41
VARIABLE SPEED

4HZXL3.43V41

ICFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3M41	35,8	48,0	114	3000	40,0	6,7	3,0	133	98	1500	40,5	3,4	1,5
3M41	35,6	47,7	115	2950	40,0	6,6	3,0	133	98	1500	40,5	3,4	1,5
3M41	35,4	47,4	117	2900	40,0	6,5	2,9	132	97	1500	40,0	3,3	1,5
3M41	35,2	47,2	118	2850	40,0	6,4	2,9	132	97	1500	40,0	3,3	1,5
3M41	35,0	46,9	119	2800	40,0	6,2	2,8	132	97	1500	40,0	3,3	1,5
3M41	34,7	46,5	120	2750	40,5	6,2	2,8	132	97	1500	40,0	3,3	1,5
3M41	34,5	46,2	122	2700	40,5	6,1	2,8	132	97	1500	40,0	3,3	1,5
3M41	34,3	46,0	124	2650	40,5	6,0	2,7	132	97	1500	40,0	3,3	1,5
3M41	34,0	45,6	125	2600	40,5	5,9	2,7	132	97	1500	40,0	3,3	1,5
3M41	33,6	45,0	126	2550	40,5	5,8	2,6	132	97	1500	40,0	3,3	1,5
3M41	33,2	44,5	127	2500	41,0	5,7	2,6	132	97	1500	40,0	3,3	1,5
3M41	32,8	44,0	128	2450	41,0	5,6	2,5	132	97	1500	40,0	3,3	1,5
3M41	32,4	43,4	129	2400	41,0	5,5	2,5	132	97	1500	40,0	3,3	1,5
3M41	31,7	42,5	129	2350	41,0	5,4	2,4	139	103	1500	42,5	3,6	1,6
3M41	35,0	46,9	145	2300	47,0	6,0	2,7	153	113	1500	46,5	3,9	1,8

16 of 20
4-R-034-0052

3M41Z (Z stands for engine with balancer shaft)
VARIABLE SPEED
4HZXL3.43V41

IFNsi

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3M41Z	36,5	48,9	148	2350	48,0	6,3	2,9	155	114	1800	47,5	4,8	2,2

3M41Z (Z stands for engine with balancer shaft)
VARIABLE SPEED
4HZXL3.43V41

IFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3M41Z	36,4	48,8	136	2550	45,0	6,4	2,9	142	105	1500	43,5	3,6	1,7
3M41Z	36,2	48,5	138	2500	46,0	6,4	2,9	146	108	1500	44,5	3,7	1,7
3M41Z	35,7	47,8	139	2450	46,0	6,3	2,9	146	108	1500	44,5	3,7	1,7
3M41Z	35,3	47,3	140	2400	46,0	6,2	2,8	145	107	1500	44,0	3,7	1,7
3M41Z	34,5	46,2	140	2350	46,0	6,0	2,7	145	107	1500	44,0	3,7	1,7
3M41Z	36,7	49,2	159	2200	51,0	6,3	2,8	159	117	2200	51,0	6,3	2,8
3M41Z	36,0	48,2	160	2150	51,0	6,1	2,8	160	118	2150	51,0	6,1	2,8
3M41Z	35,3	47,3	161	2100	51,0	6,0	2,7	161	119	2100	51,0	6,0	2,7
3M41Z	34,5	46,2	161	2050	51,0	5,8	2,6	161	119	2050	51,0	5,8	2,6
3M41Z	33,8	45,3	161	2000	51,0	5,7	2,6	161	119	2000	51,0	5,7	2,6
3M41Z	33,0	44,2	162	1950	49,0	5,3	2,4	162	119	1950	49,0	5,3	2,4
3M41Z	32,1	43,0	161	1900	49,0	5,2	2,4	161	119	1900	49,0	5,2	2,4
3M41Z	31,7	42,5	164	1850	49,0	5,1	2,3	164	121	1850	49,0	5,1	2,3
3M41Z	30,7	41,1	163	1800	49,0	4,9	2,2	163	120	1800	49,0	4,9	2,2

17 8 20
4-R-034-005

3M41Z (2 cylinder engine with injection pump)
VARIABLE SPEED

4HZXL3.43V41

ICFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SPE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3M41Z	35,0	46,9	111	3000	40,0	6,7	3,0	131	97	1500	40,5	3,4	1,5
3M41Z	34,8	46,6	113	2950	40,0	6,6	3,0	131	97	1500	40,5	3,4	1,5
3M41Z	34,6	46,4	114	2900	40,0	6,5	2,9	130	96	1500	40,0	3,3	1,5
3M41Z	34,4	46,1	115	2850	40,0	6,4	2,9	130	96	1500	40,0	3,3	1,5
3M41Z	34,2	45,8	117	2800	40,0	6,2	2,8	130	96	1500	40,0	3,3	1,5
3M41Z	33,9	45,4	118	2750	40,5	6,2	2,8	130	96	1500	40,0	3,3	1,5
3M41Z	33,7	45,2	119	2700	40,5	6,1	2,8	130	96	1500	40,0	3,3	1,5
3M41Z	33,5	44,9	121	2650	40,5	6,0	2,7	130	96	1500	40,0	3,3	1,5
3M41Z	33,2	44,5	122	2600	40,5	5,9	2,7	130	96	1500	40,0	3,3	1,5
3M41Z	32,8	44,0	123	2550	40,5	5,8	2,6	130	96	1500	40,0	3,3	1,5
3M41Z	32,5	43,6	124	2500	41,0	5,7	2,6	130	96	1500	40,0	3,3	1,5
3M41Z	32,1	43,0	125	2450	41,0	5,6	2,5	130	96	1500	40,0	3,3	1,5
3M41Z	31,7	42,5	126	2400	41,0	5,5	2,5	130	96	1500	40,0	3,3	1,5
3M41Z	31,0	41,5	126	2350	41,0	5,4	2,4	137	101	1500	42,5	3,6	1,6
3M41Z	34,3	46,0	142	2300	47,0	6,0	2,7	151	111	1500	46,5	3,9	1,8

3L41C (3 cylinder engine with injection pump)
VARIABLE SPEED

4HZXL3.43V41

F

	RATED POWER		TORQUE	RATED SPEE	FUEL RATE			TORQUE		TORQUE SPEE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3L41C	36,2	48,5	147	2350	48,0	6,3	2,9	158	117	1800	48,5	4,9	2,2

18 8 20
4-R-034-005

3L41C (3 cylinder engine with injection pump)
VARIABLE SPEED

4HZXL3.43V41

IFNsi

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SPE	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3L41C	36,6	49,0	137	2550	46,0	6,5	3,0	140	103	1800	45,5	4,6	2,1
3L41C	36,1	48,4	138	2500	46,5	6,5	2,9	147	108	1500	47,0	3,9	1,8
3L41C	35,6	47,7	139	2450	46,5	6,4	2,9	143	105	1500	46,0	3,8	1,7
3L41C	35,1	47,0	140	2400	46,5	6,2	2,8	143	105	1500	46,0	3,8	1,7
3L41C	34,4	46,1	140	2350	46,5	6,1	2,8	146	108	1800	47,0	4,7	2,1

19 20 U-Z-024-005

3L41C (CHINA 1st GROUP (2011/191) & 1st PHASE)
VARIABLE SPEED

4HZXL3.43V41

IFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3L41C	36,7	49,2	111	3150	42,5	7,5	3,4	132	97	1800	43,0	4,3	2,0
3L41C	36,7	49,2	117	3000	42,5	7,1	3,2	132	97	1800	43,0	4,3	2,0
3L41C	36,5	48,9	118	2950	42,5	7,0	3,2	132	97	1800	43,0	4,3	2,0
3L41C	36,3	48,6	120	2900	42,5	6,9	3,1	132	97	1800	43,0	4,3	2,0
3L41C	36,2	48,5	121	2850	42,5	6,8	3,1	129	95	1800	42,0	4,2	1,9
3L41C	36,0	48,2	123	2800	42,5	6,6	3,0	129	95	1800	42,0	4,2	1,9
3L41C	35,8	48,0	124	2750	43,0	6,6	3,0	133	98	1500	43,0	3,6	1,6
3L41C	35,6	47,7	126	2700	43,0	6,5	2,9	132	97	1800	43,0	4,3	2,0
3L41C	35,4	47,4	128	2650	43,0	6,4	2,9	132	97	1800	43,0	4,3	2,0
3L41C	35,2	47,2	129	2600	43,5	6,3	2,9	132	97	1800	43,0	4,3	2,0
3L41C	34,7	46,5	130	2550	43,5	6,2	2,8	133	98	1500	43,0	3,6	1,6
3L41C	34,2	45,8	131	2500	43,5	6,1	2,8	133	98	1500	43,0	3,6	1,6
3L41C	33,7	45,2	131	2450	43,5	5,9	2,7	133	98	1500	43,0	3,6	1,6
3L41C	33,3	44,6	132	2400	43,5	5,8	2,6	135	100	1500	43,5	3,6	1,7
3L41C	32,5	43,6	132	2350	43,5	5,7	2,6	150	111	1500	47,0	3,9	1,8
3L41C	35,9	48,1	149	2300	49,0	6,3	2,9	149	110	2300	49,0	6,3	2,9
3L41C	35,1	47,0	149	2250	49,0	6,1	2,8	149	110	2250	49,0	6,1	2,8
3L41C	34,3	46,0	149	2200	49,0	6,0	2,7	149	110	2200	49,0	6,0	2,7
3L41C	33,6	45,0	149	2150	49,0	5,9	2,7	149	110	2150	49,0	5,9	2,7
3L41C	32,8	44,0	149	2100	49,0	5,7	2,6	149	110	2100	49,0	5,7	2,6
3L41C	32,0	42,9	149	2050	49,0	5,6	2,5	149	110	2050	49,0	5,6	2,5
3L41C	31,2	41,8	149	2000	49,0	5,5	2,5	149	110	2000	49,0	5,5	2,5
3L41C	30,4	40,7	149	1950	48,0	5,2	2,4	149	110	1950	48,0	5,2	2,4
3L41C	29,6	39,7	149	1900	48,0	5,1	2,3	149	110	1900	48,0	5,1	2,3
3L41C	28,8	38,6	149	1850	48,0	5,0	2,2	149	110	1850	48,0	5,0	2,2
3L41C	28,0	37,5	149	1800	48,0	4,8	2,2	149	110	1800	48,0	4,8	2,2

20 of 20
4-K-034-0052

3L41C (Contents for engine usually noise capsulated)
VARIABLE SPEED
4HZXL3.43V41

ICFN

	RATED POWER		TORQUE	NGINE SPEE	FUEL RATE			TORQUE		TORQUE SP	FUEL RATE AT MAX. TORQUE		
ENGINE MOD	[kW]	[hp]	[Nm]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]	[Nm]	[lbft]	[rpm]	[mm**3/H]	[lbs/hr]	[KG/h]
3L41C	33,0	44,2	105	3000	38,5	6,4	2,9	127	94	1800	41,0	4,1	1,9
3L41C	32,9	44,1	106	2950	38,5	6,3	2,9	127	94	1800	41,0	4,1	1,9
3L41C	32,7	43,8	108	2900	38,5	6,2	2,8	127	94	1800	41,0	4,1	1,9
3L41C	32,5	43,6	109	2850	38,5	6,1	2,8	119	88	1800	38,0	3,8	1,7
3L41C	32,4	43,4	110	2800	38,5	6,0	2,7	119	88	1800	38,0	3,8	1,7
3L41C	32,2	43,1	112	2750	38,5	5,9	2,7	122	90	1800	39,0	3,9	1,8
3L41C	32,0	42,9	113	2700	38,5	5,8	2,6	122	90	1800	39,0	3,9	1,8
3L41C	31,9	42,7	115	2650	38,5	5,7	2,6	122	90	1800	39,0	3,9	1,8
3L41C	31,7	42,5	116	2600	39,0	5,7	2,6	124	91	1800	40,0	4,0	1,8
3L41C	31,2	41,8	117	2550	39,0	5,5	2,5	124	91	1500	40,0	3,3	1,5
3L41C	30,8	41,3	118	2500	39,0	5,4	2,5	124	91	1500	40,0	3,3	1,5
3L41C	30,4	40,7	118	2450	39,0	5,3	2,4	124	91	1500	40,0	3,3	1,5
3L41C	29,9	40,1	119	2400	39,0	5,2	2,4	124	91	1500	40,0	3,3	1,5
3L41C	29,3	39,3	119	2350	39,0	5,1	2,3	120	88	1500	37,5	3,1	1,4
3L41C	32,3	43,3	134	2300	44,0	5,6	2,6	134	99	2300	44,0	5,6	2,6