

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2006	6JDXL06.8055	4.5, 6.8	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Smoke Puff Limiter			Tractor, Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
130 ≤ kW < 225	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		FEL	-	-	9.3	-	0.33	-	-	-
		CERT	-	-	7.7	0.9	0.28	10	6	25

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 2<sup>nd</sup> day of December 2005.

*Raphael S. Lyons*  
 for Allen Lyons, Chief  
 Mobile Source Operations Division

# Engine Model Summary Form

**Manufacturer:** John Deere Power Systems of Deere and  
**Engine category:** Nonroad CI  
**EPA Engine Family:** 6JDXL06.8055  
**Mfr Family Name:** 350TG  
**Ass Code:** New Submission

*Attachment*  
 U-R-004-0258

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@ peak torque	8.Fuel Rate: (lbs/hr)@ peak torque	9.Emission Control Device Per SAE J1930
6068TP054	6068T	109.30@2100	55.60@2100	37.48@2100	345.88@1400	66.4@1400	31.53@1400	EM SPL TC DFI
6068TP055	6068T	116.67@2300	58.00@2300	44.10@2300	365.05@1300	73.0@1300	31.09@1300	EM SPL TC DFI
6068TP056	6068T	129.41@2300	61.00@2300	47.07@2300	393.07@1400	78.3@1400	36.80@1400	EM SPL TC DFI
6068TP058	6068T	154.89@2100	77.30@2100	54.57@2100	503.69@1500	98.8@1500	49.72@1500	EM SPL TC DFI
4045TN050	4045T	105.95@2200	78.00@2200	37.48@2200	291.30@1400	88.0@1400	26.90@1400	EM SPL TC DFI
6068TP062	6068T	109.30@2100	55.60@2100	37.48@2100	345.88@1400	66.4@1400	31.53@1400	EM SPL TC DFI
6068TPRNT2	6068T	194.45@2400	90.00@2400	70.55@2400	506.64@1400	104@1400	48.06@1400	EM SPL TC DFI
6068TN054	6068T	173.00@2200	84.10@2200	62.46@2200	483.04@1400	61.35@1400	45.53@1400	EM SPL TC DFI
4045TE051	4045T	115.33@2500	77.00@2500	41.89@2500	291.30@1400	91.0@1400	28.00@1400	EM SPL TC DFI