

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2006	6NHXL06.7DTA	3.9, 4.5, 6.7	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler and Smoke Puff Limiter			Loader, Tractor, Dozer, Excavator, Harvester, Crawler and Grader	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
75 ≤ kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
		CERT	--	--	6.2	0.7	0.28	15	7	42

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 6<sup>TH</sup> day of October 2005.

  
 Allen Lyons, Chief  
 Mobile Source Operations Division

# Engine Model Summary Form

ATTACHMENT Pg 1 of 1

U-R-008-0055

Manufacturer: **CNH UK LTD**  
 Engine category: **Nonroad CI**  
 EPA Engine Family: **6NHXL06.7DTA**  
 Mfr Family Name: **F4BE0484**  
 Process Code: **New Submission**

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
N/A	F4BE0484H*D	121 @ 2000	100	N/A	369 @ 1400	111	N/A	EM. SPL. TAA. <b>DDZ</b>
N/A	F4GE0684C*D	173 @ 2300	83	N/A	516 @ 1400	102	N/A	EM. SPL. TAA.
N/A	F4GE0684F*D	148 @ 2000	80	N/A	498 @ 1400	98	N/A	EM. SPL. TAA.
N/A	F4GE0684E*D	161 @ 2300	78	N/A	465 @ 1400	92	N/A	EM. SPL. TAA.
N/A	F4GE0684G*D	143 @ 2300	69	N/A	450 @ 1400	88	N/A	EM. SPL. TAA.
N/A	F4CE0684C*D	114 @ 2200	59	N/A	384 @ 1400	78	N/A	EM. SPL. TAA.
N/A	F4BE0484E*D	117 @ 2000	95	N/A	332 @ 1400	101	N/A	EM. SPL. TAA.
N/A	F4GE0484C*D	126 @ 2300	92	N/A	369 @ 1400	110	N/A	EM. SPL. TAA.
N/A	F4BE0484F*D	118 @ 2200	89	N/A	332 @ 1400	108	N/A	EM. SPL. TAA.
N/A	F4GE0484G*D	110 @ 2200	83	N/A	354 @ 1400	107	N/A	EM. SPL. TAA.
N/A	F4CE0484B*D	99 @ 2200	76	N/A	322 @ 1400	97	N/A	EM. SPL. TAA.
N/A	F4GE0484E*D	119 @ 2000	97	N/A	355 @ 1400	108	N/A	EM. SPL. TAA.
N/A	F4GE0684H*D	168 @ 2200	84	N/A	531 @ 1400	105	N/A	EM. SPL. TAA.
N/A	F4GE0684P*D	141 @ 2200	70	N/A	450 @ 1400	88	N/A	EM. SPL. TAA.
N/A	F4GE0684R*D	114 @ 2200	59	N/A	384 @ 1400	78	N/A	EM. SPL. TAA.
N/A	F4GE0684S*D	129 @ 2200	64	N/A	395 @ 1400	76	N/A	EM. SPL. TAA.
N/A	F4GE0684Q*D	150 @ 2200	74	N/A	429 @ 1400	82	N/A	EM. SPL. TAA.
N/A	F4CE0684B*D	129 @ 2200	64	N/A	395 @ 1400	76	N/A	EM. SPL. TAA.
N/A	F4CE0684D*D	150 @ 2200	74	N/A	429 @ 1400	82	N/A	EM. SPL. TAA.
N/A	F4BE0484D*D	127 @ 2200	94	N/A	354 @ 1400	109	N/A	EM. SPL. TAA.
N/A	F4CE0484A*D	110 @ 2200	87.9	N/A	354 @ 1400	107.3	N/A	EM. SPL. TAA.
N/A	F4CE0684F*D	129 @ 2200	69.5	N/A	424 @ 1400	84	N/A	EM. SPL. TAA.