

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2006	6KBXL02.2FCD	1.647, 2.197	Diesel	5000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Indirect Diesel Injection, Electronic Control Module			Loader, Compressor, Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	--	--	5.5	1.3	0.30	4	5	8

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 29th day of December 2005.


 for Allen Lyons, Chief
 Mobile Source Operations Division

Engine Model S

Attachment
UR-025-0240

Manufacturer: **KUBOTA Corporation**
 Engine category: **Nonroad CI**
 EPA Engine Family: **6KBXL02.2FCDD**
 Mfr Family Name: **N/A**
 Process Code: **New Submission**

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
D1703-ES01	D1703-ES	36.5@2800	33.3	15.6	81.8@1700	38.0	10.8	N/A
D1703-ES02	D1703-ES	34.5@2700	31.9	14.4	81.8@1500	37.9	9.5	N/A
D1703-ES03	D1703-ES	31.9@2400	32.2	13.0	78.2@1550	35.6	9.3	N/A
D1703-ES04	D1703-ES	29.4@2200	32.0	11.8	79.1@1600	36.0	9.7	N/A
D1703-M-ES01	D1703-M-ES	36.5@2800	33.3	15.6	82.9@1600	38.5	10.3	N/A
D1703-M-ES02	D1703-M-ES	36.7@2800	33.0	15.5	82.4@1700	37.9	10.8	N/A
D1703-M-ES03	D1703-M-ES	34.7@2700	32.3	14.6	81.9@1500	37.7	9.5	N/A
D1703-M-ES04	D1703-M-ES	29.4@2200	33.0	12.2	79.1@1600	36.3	9.7	N/A
D1703-M-ES05	D1703-M-ES	32.9@2600	32.2	14.0	77.4@1700	36.1	10.3	N/A
V2203-ES01	V2203-ES	48.4@2800	32.3	20.2	108.1@1700	37.0	14.1	N/A
V2203-ES02	V2203-ES	43.9@2600	30.7	17.8	108.1@1500	37.1	12.4	N/A
V2203-ES03	V2203-ES	42.5@2400	31.9	17.1	105.0@1500	35.6	11.9	N/A
V2203-ES04	V2203-ES	42.5@2400	31.9	17.1	101.9@1700	33.9	12.9	N/A
V2203-ES05	V2203-ES	42.5@2400	31.9	17.1	101.0@1700	33.4	12.7	N/A
V2203-ES06	V2203-ES	41.7@2300	32.6	16.8	105.9@1600	36.1	12.9	N/A
V2203-ES07	V2203-ES	38.9@2200	31.3	15.4	97.9@1600	31.9	11.4	N/A
V2203-ES08	V2203-ES	38.9@2200	31.3	15.4	102.3@1600	34.3	12.3	N/A
V2203-ES09	V2203-ES	37.3@2100	31.4	14.7	101.0@1500	33.4	11.2	N/A
V2203-ES10	V2203-ES	48.4@2800	32.3	20.2	106.4@1600	38.0	12.9	N/A
V2203-ES11	V2203-ES	45.6@2700	31.2	18.8	107.7@1500	37.0	12.4	N/A
V2203-ES12	V2203-ES	43.9@2600	30.7	17.8	103.6@1700	35.0	13.3	N/A
V2203-ES13	V2203-ES	46.9@2650	32.5	19.3	106.4@1700	36.0	13.7	N/A
V2203-ES14	V2203-ES	34.9@2000	30.4	13.6	96.9@1600	32.1	11.5	N/A
V2203-ES15	V2203-ES	44.0@2450	32.3	17.7	104.1@1600	35.2	12.6	N/A
V2203-ES16	V2203-ES	36.9@2200	29.6	14.7	105.5@1500	35.8	12.0	N/A
V2203-ES17	V2203-ES	36.2@1950	33.7	14.7	93.4@1300	32.2	9.4	N/A

ECM