

	YANMAR CO., LTD.	EXECUTIVE ORDER U-R-028-0352 New Off-Road Compression-Ignition Engines
---	-------------------------	---

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2007	7YDXL3.32K4T	3.319	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger			Crane, Loader, Tractor, Dozer, Pump, Compressor, Excavator	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		CERT	-	-	4.4	1.4	0.23	6	2	18

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 22nd day of December 2006.


 for Annette Hebert, Chief
 Mobile Source Operations Division

Engine Model Summary Form

ATTACHMENT
U-R-028-0352

Manufacturer: Yanmar Co., Ltd.
 Engine category: Nonroad CI
 EPA Engine Family: 7YDXL3.32K4T
 Mfr Family Name: N/A
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
N/A	4TNV98T-VM1	88.5/2600	64.5	37.0	230.8/1400	73.6	22.7	EM DP1TC
N/A	4TNV98T-M	88.0/2600	62.3	35.7	229.3/1800	68.9	27.3	EM
N/A	4TNV98T-N	85.7/2500	62.0	34.2	226.4/1800	68.2	27.1	EM
N/A	4TNV98T-P	82.6/2400	62.3	32.9	223.4/1800	67.2	26.7	EM
N/A	4TNV98T-Q	79.1/2300	59.6	30.2	226.4/1500	67.6	22.3	EM
N/A	4TNV98T-S	75.8/2200	59.5	28.8	226.5/1500	67.6	22.3	EM
N/A	4TNV98T-V	72.4/2100	57.7	26.7	218.8/1300	65.5	18.8	EM
N/A	4TNV98T-W	69.1/2000	57.9	25.5	218.0/1300	64.8	18.6	EM
N/A	S4D98E-2N	85.7/2500	62.0	34.2	226.4/1800	68.2	27.1	EM
N/A	S4D98E-2P	82.6/2400	62.3	32.9	223.4/1800	67.2	26.7	EM
N/A	S4D98E-2Q	79.1/2300	59.6	30.2	226.4/1500	67.6	22.3	EM
N/A	4IR18T	85.7/2500	62.0	34.2	226.4/1800	68.2	27.1	EM
N/A	4CG1T-N	85.7/2500	62.0	34.2	226.4/1800	68.2	27.1	EM
N/A	4CG1T-P	82.6/2400	62.3	32.9	223.4/1800	67.2	26.7	EM
N/A	4CG1T-Q	79.1/2300	59.6	30.2	226.4/1500	67.6	22.3	EM
N/A	4CG1T-S	75.8/2200	59.5	28.8	226.5/1500	67.6	22.3	EM
N/A	4CG1T-V	72.4/2100	57.7	26.7	218.8/1300	65.5	18.8	EM
N/A	4CG1T-W	69.1/2000	57.9	25.5	218.0/1300	64.8	18.6	EM
N/A	D3.4ACAE2SW	82.6/2400	62.3	32.9	223.4/1800	67.2	26.7	EM
N/A	D3.4ACAE2SW	82.6/2400	62.3	32.9	223.4/1800	67.2	26.7	EM
N/A	4CG1T-XZT01	75.8/2200	59.5	28.8	210.1/1500	64.4	21.3	EM