California Environmental Protection Agency AIR RESOURCES BOARD	FUJI HEAVY INDUSTRIES, LTD.	EXECUTIVE ORDER U-U-012-0194 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (cc)	ENGINE CLASS	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
2007	7FJXS.4042GA	404	4-stroke, > 225 cc	Gasoline

DURABILITY HOURS	SPECIAL FEATURES & EMISSION CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION
500	EM	Pump, Pressure Washer, Stump Beater, Generator, Compressor, Leaf Blower, Commercial Turf and Industrial Equipment
ENGINE CODES/MODELS (rated power in kilowatt, kW)	EH360Y [2,3,4] (7.6 kW), EH360Y [2, 3, 4, 5, 6] (8.2 kW)	

ABBREVIATIONS: EM=engine modification TWC/OC=three-way/oxidizing catalyst WUTWC/WUOC=warm-up TWC/OC O2S=oxygen sensor HO2S=heated O2S EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multi port fuel injection SFI=sequential MFI TBI=throttle body fuel injection DFI=direct fuel injection TC/SC=turbo/super charger CAC=charge air cooler 2(prefix)=parallel (2)(suffix)=in series ECM=engine control module

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 90.109 of the "California Exhaust Emission Standards and Test Procedures for 1995 and Later Small Off-Road Engines," adopted September 25, 2003.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	12.1	549	*
FAMILY EMISSION LEVEL	*	*	*
CERTIFICATION LEVEL	7.8	426	*

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 30th day of May 2006.

J. Lourenco

for Allen Lyons, Chief
Mobile Source Operations Division

ATTACHMENT 1 OF 1

Model Year: 2007 | Issued: March 22, 2006 | Page: 9

Manufacturer : Fuji Heavy Industries Ltd. | Revised:

Engine Family: 7FJXS.4042GA | E.O. Number : U-U-012-0194

CARB

Small Off-Road Engine Model Summary Form

Units for Table: kW

Worst Case?	47. Model Desig-nation	48. Sales Code	49. Displ (cc)	50. Bore/ Stroke	51. Ignition Timing	52. Max Power	53. Rated Speed (RPM)	54. Rated Torque	55. Torque Speed (RPM)	56. Emission Control Sys.
	EH360Y2	50-State	404	89/65	24 deg.	7.6	3600	27.5	2500	EM
	EH360Y3	50-State	404	89/65	24 deg.	7.6	3600	27.5	2500	EM
	EH360Y4	50-State	404	89/65	24 deg.	7.6	3600	27.5	2500	EM
	EH410Y2	50-State	404	89/65	24 deg.	8.2	3600	28.4	2500	EM
	EH410Y3	50-State	404	89/65	24 deg.	8.2	3600	28.4	2500	EM
x	EH410Y4	50-State	404	89/65	24 deg.	8.2	3600	28.4	2500	EM
	EH410Y5	50-State	404	89/65	24 deg.	8.2	3600	28.4	2500	EM
	EH410Y6	50-State	404	89/65	24 deg.	8.2	3600	28.4	2500	EM
				(mm)	(BTDC)	(kW)		(N-m)		