

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION					
MANUFACTURER	MODEL YEAR	EXECUTIVE ORDER	ENGINE FAMILY	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
FUJI HEAVY INDUSTRIES, LTD.	2007	U-U-012-0210	7FJXS.1691SA	169	Gasoline
EQUIPMENT DESCRIPTION					
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION		
2007	CM	3.6, 12.0, 13.0, 14.0, 15.0, 16.0	Compressor, Pump, Pressure Washer, Stump Beater, Generator, Non-Backpack Blower, Leaf Blower and Go-Kart		
EMISSION CONTROL SYSTEMS		EQUIPMENT MODEL			
Carbon Canister, Metal Tank		EX17- [01, 02, 03, 04, 05, 06, 07]			

C=canister S=sealed tank M=metal P=treated HDPE or PE C=coextruded L=selar N=nylon A=acetal O=other

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*not applicable		PERFORMANCE BASED (g/day)			
STANDARD		EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL		CERTIFICATION LEVEL	
*		*		*	
DESIGN BASED					
FUEL HOSE PERMEATION (g/m ² /day)		FUEL TANK PERMEATION (g/m ² /day)		CARBON CANISTER BUTANE WORKING CAPACITY (g/l)	
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER
15	G-05-018, C-U-05-003	*	*	≥ 1.0	1.7


BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission limit declared by the manufacturer for use in the averaging and banking program and in lieu of an emission standard for certification. It serves as the applicable evaporative emission standard for determining compliance of any equipment within this evaporative family under 13 CCR Sections 2754.2(e)(1) and 2765(a).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 19 day of September 2006.



Annette Hebert, Chief
 Mobile Source Operations Division



ATTACHMENT 1 OF 1

**Small Off-Road Evaporative Certification Database Form
(Supplementary Information)**

MODEL SUMMARY

S1. Worst Case (Check One)	S2. Engine or Equipment Model	S3. Sales Codes (Check all appropriate)		S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	S6. Fuel Tank Vol. (Liters)	S7. Fuel Tank Internal Surface Area (m ²)	S8. Fuel Line Type	S9. Nominal Fuel Line Length (mm) ⁽¹⁾	S10. Fuel Line Inside Diameter (mm)	S11. Exhaust Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister or Other Venting Control Executive Order
		CA Only	50-State											
x	EX17-01	X		I	CARB	3.6	0.140	Multi-layer	110	6.35	7FJXS.1691SA	-	G-05-018	-
	EX17-02	X		I	CARB	14.0	0.509	Multi-layer	260 & 110	6.0	7FJXS.1691SA	-	C-U-05-003	-
	EX17-03	X		I	CARB	14.0	0.509	Multi-layer	185 & 110	6.0	7FJXS.1691SA	-	C-U-05-003	-
	EX17-04	X		I	CARB	13.0	0.4776	Multi-layer	185 & 110	6.0	7FJXS.1691SA	-	C-U-05-003	-
	EX17-05	X		I	CARB	12.0	0.4229	Multi-layer	110	6.0	7FJXS.1691SA	-	C-U-05-003	-
	EX17-06	X		I	CARB	16.0	0.4385	Multi-layer	110	6.0	7FJXS.1691SA	-	C-U-05-003	-
	EX17-07	X		I	CARB	15.0	0.4676	Multi-layer	110	6.0	7FJXS.1691SA	-	C-U-05-003	-

(1) The nominal fuel line length can be grouped into increment of ±3 inches (76 mm).