



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2008	8H3XM1.50D40	1.131 & 1.508	Diesel	5000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Indirect Diesel Injection			Marine Engine	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19≤KW<37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	N/A	N/A	N/A
		CERT	--	--	3.7	1.1	0.23	--	--	--

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 8 day of January 2008.

Annette Hebert, Chief
Mobile Source Operations Division

ATTACHMENT 1 OF 1

Engine Model Summary Template

U-R-026-0216

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
3H3XM1.50D40	D1-30D	HH28/3200M	28.0@3200	24.3+/-1.7	12.8+/-0.9	53.1@2200	26.1+/-1.7	9.5+/-0.6	IFI
SH3XM1.50D40	D1-30E	GJ28/3200M	28.0@3200	24.1+/-1.7	12.7+/-0.9	51.6@2400	24.5+/-1.4	9.7+/-0.6	IFI
8H3XM1.50D40	D2-40D	HN39/3200M	39.0@3200	24.9+/-2.2	17.5+/-1.5	73.8@1800	26.1+/-2.4	10.3+/-0.9	IFI
SH3XM1.50D40	D2-40E	GM39/3200M	39.0@3200	24.1+/-1.4	16.9+/-1.0	72.2@1800	24.5+/-1.4	9.7+/-0.6	IFI

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
8H3XM1.50D40	D1-30D	HH28/3200M	28.0@3200	24.3+/-1.7	12.8+/-0.9	53.1@2200	26.1+/-1.7	9.5+/-0.6	IFI
8H3XM1.50D40	D2-40D	HN39/3200M	39.0@3200	24.9+/-2.2	17.5+/-1.5	73.8@1800	26.1+/-2.4	10.3+/-0.9	IFI
8H3XM1.50D40	D1-30F	GJ28/3200M	28.0@3200	24.1+/-1.7	12.7+/-0.9	51.6@2400	24.5+/-1.4	9.7+/-0.6	IFI
8H3XM1.50D40	D2-40F	GM39/3200M	39.0@3200	24.1+/-1.4	16.9+/-1.0	72.2@1800	24.5+/-1.4	9.7+/-0.6	IFI