

California Environmental Protection Agency Air Resources Board	WINCO, INC.	EXECUTIVE ORDER U-U-106-0006 New Off-Road Small Spark-Ignition Equipment
--	--------------------	--

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION			
MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
BRIGGS & STRATTON CORPORATION	EBSXS.4792HH (U-U-002-0833)	479	Gasoline
	EBSXS.6272HN (U-U-002-0838)	627	
	EBSXS.8962HP (U-U-002-0836)	896	
HONDA MOTOR CO., LTD.	EHNXS.2702AB (U-U-001-0654-1)	270	Gasoline
	EHNXS.3892AC (U-U-001-0658-1)	389	
	EHNXS.3892AB (U-U-001-0657-1)	389	
	EHNXS.6882AA (U-U-001-0662)	688	

S.A. = See Attachment
TBC = To Be Certified

EQUIPMENT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION
2014	CM	26.5, 56.7	Generator Set

EMISSION CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL
Canister/Metal	See Attachment

A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code:- Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.


FUEL HOSE PERMEATION (grams ROG/m ² /day)		FUEL TANK PERMEATION (grams ROG/m ² /day)		CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)	
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER
15	C-U-06-010	*	*	1.4	Q-09-023, Q-07-013A

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 21st day of January 2014.


 Erik White, Chief
 Mobile Source Operations Division

**Small Off-Road Evaporative Certification Database Form
(Supplementary Information)**

MODEL SUMMARY

S1. Worst Case (Check One)	S2. Engine or Equipment Model	S3. Sales Codes (check all appropriate)			S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	S6. Fuel Tank Vol. (Liters)	S7. Fuel Tank Internal Surface Area (m ²)	S8. Fuel Line Type	S9. Nominal Fuel Line Length ⁽¹⁾ (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Exhaust Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister or Other Venting Control Executive Order
		CA Only	49-State	50-State											
X	DL5000H			X	II	CARB	26.5	0.62	Multi-Layer	786.384	6.35	EHNXS.2702AB	Steel 2766	C-U-06-010	Q-09-023
	WC5000H			X	II	CARB	26.5	0.62	Multi-Layer	786.384	6.35	EHNXS.2702AB	Steel 2766	C-U-06-010	Q-09-023
	DL6000H/HE			X	II	CARB	26.5	0.62	Multi-Layer	737.616	6.35	EHNXS.3892AC	Steel 2766	C-U-06-010	Q-09-023
	WC6000H/HE			X	II	CARB	26.5	0.62	Multi-Layer	737.616	6.35	EHNXS.3892AC	Steel 2766	C-U-06-010	Q-09-023
	DL7000H/HE			X	II	CARB	26.5	0.62	Multi-Layer	737.616	6.35	EHNXS.3892AB	Steel 2766	C-U-06-010	Q-09-023
	WC7000H/HE			X	II	CARB	26.5	0.62	Multi-Layer	737.616	6.35	EHNXS.3892AB	Steel 2766	C-U-06-010	Q-09-023
	HT6000HE			X	II	CARB	26.5	0.62	Multi-Layer	737.616	6.35	EHNXS.3892AC	Steel 2766	C-U-06-010	Q-09-023
	HT7000HE			X	II	CARB	26.5	0.62	Multi-Layer	737.616	6.35	EHNXS.3892AB	Steel 2766	C-U-06-010	Q-09-023
	W9000VE			X	II	CARB	26.5	0.62	Multi-Layer	533.4	6.35	EBSXS.4792HH	Steel 2766	C-U-06-010	Q-09-023
	WC10000VE			X	II	CARB	26.5	0.62	Multi-Layer	533.4	6.35	EBSXS.6272HN	Steel 2766	C-U-06-010	Q-09-023
	WL12000HE			X	II	CARB	56.7	0.94	Multi-Layer	330.09	6.35	EHNXS.6882AA	Steel 2766	C-U-06-010	Q-07-013A
	HT12000HE			X	II	CARB	56.7	0.94	Multi-Layer	330.09	6.35	EHNXS.6882AA	Steel 2766	C-U-06-010	Q-07-013A