Jrli

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER M-1-282
Relating to Certification of New Motorcycles

KAWASAKI HEAVY INDUSTRIES, LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and,

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Kawasaki Heavy Industries, Ltd. exhaust emission control systems are certified as described below for four-stroke gasoline-powered motorcycles:

Engine Family	Displacement Cubic Centimeters	Class	Exhaust Emission Control Systems & Special Features
YKAXC.676AAA	676	III	Pulsed Secondary Air Injection

Vehicle models and transmissions are listed on the attachment. Production motorcycles shall be in all material respects the same as those for which certification is granted.

The following are the exhaust emission standards and exhaust emission certification values for this engine family. The designated hydrocarbons standard shall be listed on the permanent tune-up label:

Hydrocarbon Standards (Corporate Average) Grams per Kilometer	Hydrocarbon Standards (Designated) Grams per Kilometer	Hydrocarbons (Certification) Grams per Kilometer	Carbon Monoxide (Standard) Grams per Kilometer	Carbon Monoxide (Certification) Grams per Kilometer
1.0	1.3	0.8	12	10

BE IT FURTHER RESOLVED: That the above-described certification is subject to the following terms, limitations and conditions:

The above designated hydrocarbons standard shall be the exhaust limit for this engine family during the model year and therefore cannot be redesignated by the manufacturer. It represents the hydrocarbons exhaust emission standard applicable to this engine family that shall be applied when determining compliance of any motorcycle within this engine family pursuant to Section 2101 of Title 13, California Code of Regulations. It will also be used to determine compliance with the above corporate average hydrocarbons standard as required per Section 1958(b), Title 13 of the California Code of Regulations.

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That these motorcycles are found exempt from compliance with the Air Resources Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" pursuant to Executive Order G-70-16-E.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 4th day of November 1999.

R. B. Summerfield, Chief
Mobile Source Operations Division

Issued: SEP 0 9 1999
Revised:

E.O.#: M-1-282

Engine Family: YKAXC.676AAA

Motorcycle Model Summary Form

65. Model Designation	66. Worst Case	67. Disp. (cc)	68. Bore / Stroke (mm)	69. Basic Ignition Timing (degrees)	70 Power (kW)	71 Rated Speed (rpm)	72 Rated Torque (Nm)	73. Rated Speed (rpm)
EJ650-A2	Yes	676	72.0 X 83.0	10°/900 rpm	37	7000	56	5500

65. Model Designation	74. EIM (kg)	75. Loaded Vehicle Weight Range (kg)	76 Road Load (nt)	77 Total Vehicle Mass (kg)	78 Full Weight with All Factory Options (kg)	79. Trans. Type	80 N/V
EJ650-A2	340	336 ~ 345	143.6	212	265	M-5	37.99

Issued: SEP 0 9 1999
Revised:

E.O.#: M-1-282

Motorcycle Engine Family Information Form

0.1

1. Manufacturer: KAWASAKI HEAVY INDUSTRIES, LTD.

2. Certification Contact Person, address, phone, and fax:

Jeffrey D. Shetler / David Corey
Kawasaki Motors Corp., USA.
9950 Jeronimo Road, Irvine. CA 92618-2084
Tel : 949-770-0400 Fax : 949-460-5602

3. Model Year: 2000

4. Process Code: New
(new, correction, revision, r/c, f/f. etc.)

5. Engine Family: YKAXC.676AAA
50s Engine Code: —
49s Engine Code: —
Calif. Engine Code: EJ650A-AC1

6. Emission Control System: EM+~~AIR~~ PAIR

7. Calif. Designated Standard: 1.3 gm/km

8. Projected Annual Sales: __

CONFIDENTIAL

9. New Technology _ Yes X No
If yes, cite the correspondence or reference the submittal document:

10. Displacement: 676cm³

11. Number of Cylinders: 2

12. Cylinder Arrangement: Inline-2

13. Cylinder Head Configuration: SOHC

14. Type of Cooling: Air

15. Combustion Cycle: 4

16. Method of Aspiration: Natural

17. Fuel System: Carburetor

18. Number of Catalytic Converters: NA

19. Adjustable Parameters:

Parameter(s)	Adjustable Range (or NA)	Tamper Resistance Method (or NA)	Method Approved
Air adjuster on carburetor (Air/Fuel Ratio)	NA	an aluminum cap is placed over the adjusting screw.	Carry over

20. AECDs in the Emission Control Systems:

Exhaust System	Evaporative System
AECDs In System: EM and ~~AIR~~ PAIR	AECDs In System: Sealed loop with Canister

Application Processed by: Joseph Jegede Date: 11/3/99
Reviewed by: [signature] Date: 11/3/99

E.O. #: M-1-282

Engine Family: YKAXC.676AAA

Motorcycle Test Information Form

27. Are you carrying over test results from a previously certified family? _ Yes X No
    a) If yes, indicate family name:
    b) Is the family being certified identical to the family from which the data is being carried over?

28. Model Designation of Test Vehicle: EJ650A

29. Test Information Number: 00-1

30. Vehicle ID: JKAEJEA13XA000015

31. Service Accumulation Duration: 15000 (km)

32. Maximum Rated Power: 37 kW @ 7000 RPM

33. Displacement: 676 cc

34. Certification Fuel: Indolene: 91-95 RON

35. Test Data Set: Test 1

36. Road Load: 143.6 nt at 65 kph

37. Inertia Mass: 340 kg

38. N/V: 37.99

39. EVAP. Bench Test Method Approved:
    Date: 2/23/1983

    Reference: 84ARB-03

40. Unscheduled Maintenance: _ Yes X No

41. If yes, Vehicle Log provided: NA

42. Exhaust Emission Deterioration Factors:

		Emission Values	
Test Number	System Kilometers	HC	CO
1	3513	0.85	10.3
2	6012	0.66	10.2
3	6042	0.49	7.8
4	12013	0.77	7.7
5	12043	0.66	7.3
6	15012	0.76	10.2
7			
Interpolated Values at 15000 km:		**HC = 0.7196**	**CO = 8.3981**
Extrapolated Values at 30000 km:		**HC = 0.7737**	**CO = 7.0784**

Check one:	
Regular DF	X
Modified DF	
If different vehicle specify vehicle ID	

43. Emission Test Results:

Official Test Results		Test 1	Test 2	Test 3	Test 4		Deterioration Factors
g/km	CO	10.2				(X)	1.000
g/km	CO^2	80.6					----------
g/km	HC	0.76				(X)	1.075
g/test	Evap.	0.557				(+)	0.036

44. Certification Levels:

g/km	CO	10			
g/km	HC	0.8			
g/test	Evap.	0.557			

Issued: SEP 09 1999
Revised:

E.O.#: M-1-282

Engine Family: YKAXC.676AAA

Evaporative Emission Information

45. Evaporative Family: YKAXC17.0A07
46. Number of Evap. Canisters: 1
47. Design Working Capacity: 17.0 g
48. Configuration: Sealed loop
49. Number of Storage Areas: 1
50. Fuel Reservoir Volume: 2.2 liters
51. Vent System Configuration: Sealed loop
52. Nominal Tank Capacity: 18 liters
53. Engine Displacement Class: III
54. Storage Medium Composition: Activated carbon
55. Evap. Canister Medium Volume: 400cm³
56. Evap. Family Sales: 600
57. Engine Code: EX305B-AC1••••Bench test
    EX500A-AC1••••Durability test
58. Evap. Emission Family Code: YKAXC17.0A07
59. Evap. Emission Family Group: CV32-001
60. **Overall Evap D.F.** = 0.036
    •Evap certification level = 0.557 g/test

Bench DF

61. Test Vehicle ID: JKAEXLB14DA002384
62. Test Results:

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3500	1.219
2	15000	1.240
3		
4		
5		
6		
7		
Interpolated Values at 15000 km: = 1.240		
Extrapolated Values at 30000 km: = 1.2674		
Bench Test D.F. = 0.027		

Check One:	
Regular DF:	X
Modified DF:	
If different vehicle specify the vehicle ID	

Vehicle DF

63. Test Vehicle ID: JKAEXVA10HA000005
64. Test Results.

Test Number	System Kilometers	Evap. Emission Values (g/test)
1	3547	0.515
2	5127	0.592
3	5157	0.505
4	9836	0.469
5	9866	0.801
6	15013	0.521
7		
Interpolated Values at 15000 km: = 0.5874		
Extrapolated Values at 30000 km: = 0.6314		
Vehicle Test D.F. = 0.044		