

E.O. Book

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-42-5  
Relating to Approval of New Motor Vehicles

WHITE MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 39150 and 39151 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Section 39023 of the Health and Safety Code and Executive Order G-45-1;

IT IS ORDERED AND RESOLVED: That White Motor Corporation 1975 model year diesel-powered engines in heavy-duty motor vehicles are approved for the engine family described below:

<u>Engine Family</u>	<u>Engine Size CID</u>	<u>Engine Model</u>	<u>Type</u>
D-4800-T	478	D-4800-T	Turbocharged

Section 39152, Part I, Division 26 of the California Health and Safety Code requires that the manufacturer affix a decal to the side window to the rear of the driver or, if there is no such window on the driver's side, to the windshield of the motor vehicle.


The following are the recommended values to be listed on the decal:

<u>Engine Family</u>	<u>Hydrocarbon plus Nitrogen Dioxide grams/brake horsepower-hour</u>	<u>Carbon Monoxide grams/brake horsepower-hour</u>
D-4800-T	7	5

Vehicles approved under this Executive Order must conform to all applicable California emission regulations.

The Department of Motor Vehicles, the California Highway Patrol, and the Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California, this 3 day of September, 1974.



G. C. Hass, Chief  
Division of Vehicle  
Emissions Control

AIR RESOURCES BOARD  
 SUPPLEMENTAL INFORMATION  
 1975 MODEL YEAR  
 HEAVY-DUTY DIESEL ENGINES

EXECUTIVE ORDER NO. A-42-5

Engine Family	Engine Models	Engine CID	Method of Aspiration *	Fuel Pump Mfr. Part No.	Injectors Mfr. Part No.	Performance Specifications		Remarks (Emission System)
						H.P. and RPM	Initial Injection Timing	
D-4800-T	D-4800-T	478	TC	American Bosch 40-3850216-D	American Bosch 380331	180 HP @ 2400 RPM	20 BTDC	Aneroid Control for turbocharger (Puff limiter). Idle speed 800 RPM

Abbreviations:

- \* N.A. - Natural Aspiration.
- T.C. - Turbocharged.
- T.C.A. - Turbocharged and Aftercooled.