State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-13-87

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

CATERPILLAR, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following 1995 model-year Caterpillar, Inc. diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family	Engine Displacement Liters	(Cubic Inches)	Exhaust Emission Control Systems and Special Features
SCP629EZDARM	10.3	(629)	Turbocharger Charge Air Cooler Engine Control Module

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Particulates
1.3	15.5	5.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Engine Family	Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Particulates
SCP629EZDARM	0.1	1.5	4.6	0.07

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 14th day of February, 1995.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

E.O. # A-13-87

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
HEAVY-DUTY DIESEL-STANDARD ENGINES

Manufacturer: Caterpillar Inc. Engine Family: SCP629EZDARM

Displacement: 10.3 / Liters 629 / Cubic Inches

Maximum Rated Power: 365 HP @ 1800 RPM Engine Configuration: I6

Ignition: Compression X Compression with Glow Plug ____ Spark ____

Fuel Type (s): Dedicated ____ Flex-Fuel ____ Dual-Fuel ____ Diesel X M100 ____ M85 ____

CNG ____ LNG ____ LPG ____ Other (specify) ____

Diesel Cert Fuel: 13CCR 2282 ____ 40 CFR 86.1313-90 ____ 40 CFR 86.1313-94 X

Primary Intended Service Class: LHD ____ MHD ____ HHD X Urban Bus ____

Exhaust ECS (incl. MFI, TC, CAC) CAC, ECM, TC

Use abbreviations per SAE J1930 SEP91)

Engine Model (Eng. Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm^3/stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX / Catalytic Converter Part No.
3176(A1)	365 @ 1800	196 (118.7)	1165414	1236032	---	---
3176(A2)	350 @ 1800	186 (112.8)	1165414	1220785		
3176(A3)	335 @ 1800	178 (107.7)	1165414	1236035		

ISSUE DATE	15 DEC 94							
REVISION NUMBER								
REVISION DATE								

h:\amipro\95epa\arb\arbsds39