State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-21-117

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-3;

IT IS ORDERED AND RESOLVED: That the following Cummins Engine Company, Inc. 1995 model diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family	Liters	(Cubic Inches)	Exhaust Emission Control Systems and Special Features
SCE505D6DAAW (413F)	8.3	(505)	Turbocharger Charge Air Cooler Oxidation Catalytic Converter

Engine models and codes are listed on attachments.

The exhaust certification emission standards for this engine family in grams per brake horsepower-hour are as follows:

Total Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Particulates
1.3	15.5	5.0	0.10

The exhaust certification emission values for this engine family in grams per brake horsepower-hour are as follows:

Engine Family	Total Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Particulates
SCE505D6DAAW (413F)	0.2	0.9	4.5	0.06

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 5th day of December, 1994.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

E.O.# A-21-117

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
HEAVY-DUTY DIESEL-STANDARD ENGINES

Manufacturer Cummins Engine Company, Inc. Engine Family (413F) SCE505D6DAAW

Displacement: / 8.3 Liters / 505 Cubic Inches

Maximum Rated Power: 264 HP @ 2100 RPM Engine Configuration: 1-6

Ignition: Compression X Compression with Glow Plug_ Spark_

Fuel Type(s): Dedicated_ Flex-Fuel_ Dual-Fuel_ Diesel X M100_ M85_

CNG_ LNG_ LPG_ Other (specify)_

Diesel Cert Fuel: 13 CCR 2282_ 40 CFR 86.1313-90_ 40 CFR 86.1313-94 X

Primary Intended Service Class: LHD_ MHD X HHD_ Urban Bus_

Exhaust ECS (include.MFI, TC, CAC): OC (TC, CAC)

(use abbreviations per SAE J1930 SEP91)

Engine Model (Eng Code)	Rated HP @ RPM	Fuel Rate @ Rated HP mm3 / stroke (lbs/hr)	Fuel Pump & Injector Part No.	ECM/PCM Part No.	EGR Valve Part No.	PTOX / Catalytic Converter Part No.
C8.3-275 (1566)	264 @ 2100	136 (96.0)	FP:3922446 FP:3927923 IN:3922913 IN:3926117	N/A	N/A	3926265
C8.3-275 (1566)	260 @ 2200	132 (98.3)	FP:3922427 FP:3927924 IN:3922913 IN:3926117	N/A	N/A	3926265
C8.3-250 (1566)	240 @ 2200	120 (89.3)	FP:3922449 IN:3922913 IN:3926117	N/A	N/A	3926265

Date Issued:

Revisions: