

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-21-282-1
Relating to Certification of New Heavy-Duty Engines and Vehicles

CUMMINS ENGINE COMPANY, INC.

Pursuant to the authority vested in the Air Resources Board at Sections 43100, 43101, and 43102 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned at Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9; and

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Cummins Engine Company, Inc. and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following 2000 model-year Cummins Engine Company, Inc. diesel engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

<u>Engine Family</u>	<u>Displacement</u>		<u>Exhaust Emission Control Systems and Special Features</u>
	<u>Liters</u>	<u>Cubic Inches</u>	
YCEXH0359BAI (403O)	5.9	359	Turbocharger Charge Air Cooler Powertrain Control Module Oxidation Catalytic Converter Direct Diesel Injection

Engine models and codes are listed on attachments.

BE IT ORDERED AND RESOLVED: That the following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour under the Federal Test Procedure ("FTP") for Heavy-Duty Diesel Engines (Title 13, California Code of Regulations, Section 1956.8):

	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulate Matter</u>
"FTP"	1.3	15.5	4.0	0.10

BE IT FURTHER RESOLVED: That pursuant to the Settlement Agreement and any modifications thereof, the aforementioned engine family is also subject to the following emission standards, in grams per brake horsepower-hour, under the EURO III tests in the Settlement Agreement, and a "Not-to-Exceed" nitrogen oxides emission standard of 5.0 grams per brake horsepower-hour:

	<u>Total Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulate Matter</u>
"EURO III"	1.3	15.5	4.0	0.10

BE IT FURTHER RESOLVED: That the following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

	Total <u>Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Particulate Matter</u>
"FTP"	0.1	0.6	3.4	0.07
"EURO III"	0.0	0.1	3.7	0.08

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2035 *et seq.*).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

1. The Settlement Agreement is in effect.
2. The manufacturer is in compliance with all applicable certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

Executive Order A-21-282 issued on December 30, 1999, is hereby superseded by Executive Order A-21-282-1.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 21st day of April 2000.



R. B. Summerfield, Chief
Mobile Source Operations Division

Engine Model Summary Form

A-21-282-1

ATTACHMENT

Manufacturer: Cummins Engine Company, Inc.
 Engine category: On-highway HDDE
 EPA Engine Family: YCEXH0359BAI
 Mfr Family Name: 4030
 Process Code: New Submission

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
2595;FR90550	ISB 225	215@2500	94	79.4	520@1600	102	55.2	PCM, TC, CAC, ▲
2595;FR90551	ISB 210	210@2500	90	76.0	520@1400	102	48.3	PCM, PC , CAC,
2596;FR90552	ISB 190	193@2500	84	71.2	520@1400	102	48.2	PCM, PC , CAC,
2597;FR90553	ISB 185	175@2500	78	65.8	420@1600	83	44.8	PCM, PC , CAC, OC

Part Number Supplementary Form

Manufacturer: Cummins Engine Company, Inc.
 Engine category: On-highway HDDE
 EPA Engine Family: YCEXH0359BAI
 Mfr Family Name: 4030
 Process Code: New Submission

ATTACHMENT

Engine Code	Engine Model	Injection Pump	Injector	Turbo Charge	Electronic Control Module	After Treatment Device (Specify)	Smoke Puff Limiter	Description	Sensor Assemblies Part Number
CPL2595	ISB 225	3944983	3944197	3538865	3942860	3926233		Engine Position	3943409
CPL2595	ISB 210			3538868	3944124			Engine Position	4002066
CPL2595				3538881				Boost Pressure	3329617
CPL2595								Boost Pressure	3348747
CPL2595								Coolant Temp	3865346
CPL2595								Int Mnfld Temp	3865345
CPL2595								Int Mnfld Temp	3408345
CPL2596	ISB 190	3944983	3944200	3538865	3942860	3926233		Engine Position	3943409
CPL2596				3538868	3944124			Engine Position	4002066
CPL2596				3538881				Boost Pressure	3329617
CPL2596								Boost Pressure	3348747
CPL2596								Coolant Temp	3865346
CPL2596								Int Mnfld Temp	3865345
CPL2597	ISB 185	3944983	3944205	3538865	3942860	3926233		Int Mnfld Temp	3408345
CPL2597				3538868	3944124			Engine Position	3943409
CPL2597				3538881				Engine Position	4002066
CPL2597								Boost Pressure	3329617
CPL2597								Boost Pressure	3348747
CPL2597								Coolant Temp	3865346
CPL2597								Int Mnfld Temp	3865345
CPL2597								Int Mnfld Temp	3408345