California Environmental Protection Agency AIR RESOURCES BOARD	INTERNATIONAL TRUCK AND ENGINE CORPORATION	EXECUTIVE ORDER A-004-0281 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board (ARB) by Health and Safety Code (HSC) Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-02-003; and

Pursuant to the December 15, 1998 Settlement Agreement (SA) between ARB and the manufacturer, and any modifications thereof to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZE (liter)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas)	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS (L/M/H HDD=light/medium/heavy heavy-duty [HD] diesel; UB=urban bus; HDO=HD Otto)
2003	3NVXH0530ATA	8.7	Diesel	Diesel	MHDD

SPECIAL FEATURES & EMISSION CONTROL SYSTEMS	ENGINE MODELS / CODES (rated power in horsepower, hp)
DDI, CTOX, TC, CAC, ECM	CG275 / CG275 (275 hp)

GVWR=gross vehicle weight rating TWC/OC=three-way/oxidizing catalyst WU (prefix) =warm-up cat. O2S=oxygen sensor HO2S=heated O2S TBI=throttle body fuel injection MFI=multi port fuel injection SFI=sequentialMFI DDI/IDI=direct /indirect diesel injection TC/SC=turbo/super charger CAC=charge air cooler EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR SPL=smoke puff limiter ECM/PCM=engine /powertrain control module EM=engine modification 2 (prefix)=parallel (2) (suffix)=in series HC=hydrocarbon NMHC=non-methane HC NOx=oxides of nitrogen CO=carbon monoxide PM=particulate matter HCHO=formaldehyde g/bhp-hr=grams per brake horsepower-hour CTOX=Continuous Trap oxidizer

The following are the exhaust emission standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT), in g/bhp-hr, for this engine family under the "Federal Test Procedure" (FTP) (Title 13, California Code of Regulations, (13 CCR) Section 1956.1 (urban bus) or 1956.8 (other than urban bus)), and under the "Euro III Test Procedure" (EURO) in the Settlement Agreement, including EURO's "Not-to-Exceed" standard(s). "Diesel" CO certification compliance may have been demonstrated pursuant to Code of Federal Regulations, Title 40, Part 86, Subpart A, Section 86.091-23(c)(2)(i) in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [ ] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR Section 1956.1 or 1956.8 are in parentheses.)

			EURO'S NOT-TO-EXCEED STD				NMHC: *		NOx: *		NMHC+NOx: *		PM: *	
* = not applicable	HC		NMHC		NOx		NMHC+NOx		CO		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
(DIRECT) STD	1.3	*	*	*	*	*	*	*	15.5	*	*	*	*	*
AVERAGE STD	*	*	*	*	4.0	*	*	*	*	*	0.10	*	*	*
FEL	*	*	*	*	3.0	*	*	*	*	*	0.01	*	*	*
CERT	0.1	*	*	*	3.0	*	*	*	6.4	*	0.01	*	*	*

BE IT FURTHER RESOLVED: That certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs. The FEL(s) shall not be used to generate any ABT emission credits.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR Sections 1965 (emission control labels), and 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: That the above-described certification is also subject to the following terms, limitations, and conditions. The manufacturer must take appropriate measures to ensure that all vehicles equipped with engines covered by this Executive Order bear appropriate labels in the vehicle fuel tank filler area and the driver's dashboard-area disclosing the low sulfur (15 ppm maximum) fuel requirement. The manufacturer must take appropriate measures to ensure that all vehicles equipped with engines covered by this Executive Order are sold only to fleets with central fueling capability for low sulfur fuel. The manufacturer must require these fleet owners to sign agreements which require the fleet owner to use appropriate low sulfur diesel fuel and stipulate that the fleet owner is at risk of voiding the warranty for use of improper diesel fuel.

BE IT FURTHER RESOLVED: That the listed engine models are conditionally certified subject to the following conditions: (1) The Settlement Agreement is in effect; and, (2) The manufacturer is in compliance with all applicable certification requirements of the Settlement Agreement and any modifications thereof.

Engines certified under this Executive Order shall conform to all applicable California emission regulations and all requirements under the Settlement Agreement and any modifications thereof.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 24th day of December 2002.

Raphael Susnowitz

for Allen Lyons, Chief
Mobile Source Operations Division