BI-PHASE TECHNOLOGIES LLC

EXECUTIVE ORDER A-360-0018 New On-Road Heavy-Duty Engines Page 1 of 1 Pages

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2, and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL | ENGINE FAN | ENGINE FAMILY | | FUEL TYPE 1 | STANDARDS & TEST | INTENDED SERVICE | ECS & SPECIAL FEATURES 3 | DIAGNOSTIC 6 | | | |
|---|--|--|--|--|---|---|---|--|--|--|--|
| YEAR ENGINE PANIL | | | SIZES (L) | | PROCEDURE | CLASS 2 | TWC, HO2S(2), SFI | N/A | | | |
| 2012 | CBPTE06.0 | PTE06.0G12 6.0 LPG Otto HDO | | 1440, 11020(2), 011 | 14// | | | | | | |
| | PENGINE'S IDLE | | | ADDI | IONAL IDLE EMISSIONS CONTROL 5 | | | | | | |
| | N/A | | | | N | /A | | | | | |
| ENGINE (L) ENGINE MODELS / CODES (rated power, in hp) | | | | | | | | | | | |
| 6.0 | | GM 6.0 / 1 (300) | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| • most cool | inable: C\AMB=ases | a vehicle : | voight ratios: 12 CC | P www-Title 12 California Code o | f Posidations Sact | ion w/7: 40 CE | R 86.abc=Title 40, Code of Federal Regulation | s Section 86 and | | | |
| | icable; GvvvR=gros ≔horsepower; kw=k | | | R xyz= fille 13, California Code o | Regulations, Sect | 1011 XYZ, 40 CF | K 66.abc - Title 40, Code of Federal Regulation | s, 3ection 66.a5c, | | | |
| | | | | ied petroleum gas; E85=85% eth | anoi fuel; MF=mult | i fuel a.k.a. BF | =bi fuel; DF=dual fuel; FF=flexible fuel; | | | | |
| | | | | irban bus; HDO=heavy duty Otto; | | | | | | | |
| up catalyst NOS=nitro injection; T ECM/PCM | ; DPF=diesel particu gen oxide sensor; TE rC/SC=turbo/ super i =engine/powertrain d | ilate filter; BI=throttle charger; (control mo | PTOX=periodic trap body fuel injection; CAC=charge air cool- dule; EM=engine mo | o oxidizer, HO2S/O2S=heated/ox SFI/MFI=sequential/multi port fuel er; EGR / EGR-C=exhaust gas re odification; 2 (prefix)=parallel; (2 | ygen sensor; HAF: l injection; DGI=din ecirculation / cooled t) (suffix)=in series | S/AFS=heated/: ect gasoline inje EGR; PAIR/Ai | ctive catalytic reduction – urea / – ammonia; V air-fuel-ratio sensor (a.k.a., universal or linear o ection; GCARB=gaseous carburetor; IDI/DDI= IR=pulsed/secondary air injection; SPL=smoki | oxygen sensor); :indirect/direct diese e puff limiter; | | | |
| ESS=er | ngine shutdown syst :R 1956.8(a)(6)(D); I | em (per 1: E xempt =6 | 3 CCR 1956.8(a)(6)(exempted per 13 CCF | A)(1); 30g =30 g/hr NOx (per 13 C R 1956.8(a)(6)(B) or for CNG/LNG | CCR 1956.8(a)(6)(C fuel systems; N/A |); APS =interna =not applicable | al combustion auxiliary power system; ALT=al e(e.g., Otto engines and vehicles); | ternative method | | | |
| | | | | 971); OBD=on-board diagnostic s | | | , | | | | |

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

| in | NMHC | | NOx | | NMHC+NOx | | со | | PM | | нсно | |
|----------|------|------|------|------|----------|------|------|------|-------|------|--------|------|
| g/bhp-hr | FTP | EURO | FTP | EURO | FTP | EURO | FTP | EURO | FTP | EURO | FTP | EURO |
| STD | 0.14 | ٠ | 0.20 | • | • | * | 15.5 | • | 0.01 | • | 0.050 | * |
| FEL | * | • | * | ٠ | • | • | * | * | * | • | • | • |
| CERT | 0.08 | * | 0.14 | • | • | * | 6.6 | • | 0.006 | • | 0.0006 | • |
| NTE | • | | | | • | | • | | • | | • | |

4. g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter, HCHO=formaldehyde; (Rev.: 2007-02-26)

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of October 2011.

Annette Hebert, Chief

Mobile Source Operations Division

Engine Model Summary Template

| Engine Family | 1.Engine Code | 2.Engine M odel | 3.BHP@RPM (SAE Gross) | 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 6.Torque @ RPM (SEA Gross) | | | 9.Emission Control ueDevice Per SAE J1930 |
|---------------|---------------|------------------------|--|--|--|-------------------------------|--|--|--|
| CBPTE06.0LPG | 1 | 6m 6.0 | 300@4400 | | | 360@4000 | | | |
| | | -Isuzu NPR-HD | | | ria sid filada supus para saara a phantana dalah sisus di Tabbah dalah pununsaka dar | | | | TUC, HU25(2), SEI |
| | | GMC NPR+HD | ng punggan at a la manggan ang mara ang manggan ang manggan ang manggan ang manggan ang manggan ang manggan an | | | | | | |
| | | Chevy NPR-HD | | | | | No. dans 1. of 15 million and 16 mil | | mad Mada de Salada de la 1979 de deservación en como en en esta de la Salada de la como en en entre en entre e |
| | | | | | | | and a little of the latter of | | en i metanomialel e este elektroni entre entre este est e este esta esta esta esta esta esta est |
| | | <u>GMC G4500-</u> | | | | | oleanist alphanistic property for a select than at the first terminal case as well | | |
| | | Chevy G4500 | | | | | entens - nema@@lechdo.com/proposal portroller town can (1) - h. c. com/proposal | and the second section of the s | |
| | | | | | | | | - April Mary a decrease Arthress helders helders a secretary and the later for the North | |
| | | | | | | | | | |