STANDARDS INTENDED

ECS & SPECIAL FEATURES

⊘ Air Resources Board

ENGINE SIZES (L)

MODEL YEAR

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE '	& TEST	SERVICE	ECS & SPECIAL FEATURES	DIAGNOSTIC 5				
			Flexible Fuel:	PROCEDURE	CLASS 2						
2013	DFMXE05.4BWC	5.4	Ethanol (E85) / Gasoline (Tier 2 Unleaded)	Otto	HDO	TWC, HO2S, SFI, 2AFS	OBD (F)				
	PENGINE'S IDLE		ADDI	TIONAL IDLE EM	ISSIONS CO	NTROL 4					
	N/A		N/A								
ENGINE (L)	ENGINE MODELS / CODES (rated power, in hp)									
5.4	1	E450 Incomplete / DE414Y05, DE414W05 (255 for all codes)									
*				*	***************************************						
L=liter; hp: CNG/LN 2 L/M/H h	=horsepower; kw=kilowatt; NG=compressed/liquefied n HDD=light/medium/heavy he mission control system; TW	hr=hour; atural gas; LPG= eavy-duty diesel; IC/OC=three-way	liquefied petroleum gas; E85=85% eth UB=urban bus; HDO=heavy duty Otto; /oxidizing catalyst; NAC=NOx adsorption	anol fuel; MF=mult	i fuel a.k.a. BF	R 86.abc=Title 40, Code of Federal Regulatio =bi fuel; DF=dual fuel; FF=flexible fuel; stive catalytic reduction – urea / – ammonia;	WU (prefix) =warm-				

EUS=emission control system; TWC/UC=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U/ SCR-N=selective catalytic reduction – urea / – emmonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFVMFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/ super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=persallel; (2) (auffix)=in series;

ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); APS =internal combustion auxiliary power system; ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);

EMD=engine manufacturer diagnostic system; OBD(F) / (P) / (\$)=full / partial / partial with fine / on-board diagnostic;

FUEL TYPE

DIAGNOSTIC 5

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavyduty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		co		PM		нсно		
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	
STD	0.14 [0.14]	*	0.20 [0.20]	*	*	*	14.4 [14.4]	*	0.01 [0.01]	*	0.01 [0.01]	*	
FEL	*	•	*	*	*	•	•	•		*	•	*	
CERT	0.07 [0.08]	*	0.07 [0.14]	*	*	•	2.7 [4.4]	•	*	*	0.003 [0.001]	*	
NTE	•		•		*			*		*		*	

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions sting; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitroge (Rev.: 2007-02-26) CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1971.1 (on-board diagnostic, full or partial compliance), and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

day of August 2012. Executed at El Monte, California on this

> Annette Hebert, Chief Mobile Source Operations Division