

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-76
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1985 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

<u>Engine Family</u>	<u>Displacement Cubic Inches (Liters)</u>	<u>Exhaust Emission Control Systems (Special Features)</u>
FTY2.4T2FCC7	144.4 (2.4)	Air Injection - Valve Exhaust Gas Recirculation Three-Way Catalyst with Closed Loop

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the certification emission standards for this engine family to be listed on the window decal required by "California Assembly-Line Test Procedures for 1983 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles":

<u>Equivalent Inertia Weight</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0-3999	0.39	9.0	1.0

The following are the certification emission values for the above engine family:

<u>Equivalent Inertia Weight</u>	<u>Hydrocarbons Grams per Mile</u>	<u>Carbon Monoxide Grams per Mile</u>	<u>Nitrogen Oxides Grams per Mile</u>
0-3999	0.20	5.9	0.5

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.15 of Title 13, California Administrative Code which includes repair or replacement of emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1981 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the Executive Officer has been provided all material required to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2036).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30th day of July, 1984.


K. D. Drachand, Chief
Mobile Source Division

1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Manufacturer Toyota Motor Corporation
Engine Family FTY2.4T2FCC7

Executive Order No. A-14-76
Evaporative Family EV-R
Engine CID (Liters) 144.4 (2.4)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
EEC-Electronic Engine Control
EI-Electronic Ignition
ESAC-Electronic Spark Advance Control
VA-Vacuum Advance
VR-Vacuum Retard

Exhaust Emissions Control System

AIP-Air Injection-Pump
AIV-Air Injection-Valve
CL-Closed Loop
EGR-Exhaust Gas Recirculation
EM-Engine Modification
OC-Oxidation Catalyst System
TOC-Trap Oxidizer Continual
TOP-Trap Oxidizer Periodical
TR-Thermal Reactor
TWC-Three Way Catalyst System

Special Features

CCV-Combustion Chamber Valve
CFI-Central Fuel Injection
DID-Diesel Injection-Direct
DIP-Diesel Injection-Prechamber
EFI-Electronic Fuel Injection
IC-Intercooler
MFI-Mechanical Fuel Injection
TC-Turbocharged

Fuel System

CFI, CL, DID, DIP, EFI, MFI
nV-nVenturi Carburetor
W-Variable Venturi

VEHICLE MODELS :

RN50L-KRA } -MRA } -PRA }	} Short P.V. Truck	RN55L-MRA } -MDA } -MDCA }	} Long P.V. Truck	RN55L-PRA } -PDA } -PDCA }	} Long 4WD P.V.	RN60L-MRA } RN65L-MDA } -MDCA }
---------------------------------	--------------------	----------------------------------	-------------------	----------------------------------	-----------------------	---------------------------------------

DRIVE SYSTEM : RN50L, RN55L series; Front Engine/Rear - Wheel Drive
RN60L, RN65L series; Front Engine/ 4 - Wheel Drive

1985 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars Light-Duty Trucks Medium-Duty Vehicles Gas Diesel
 Manufacturer Toyota Motor Corporation Page 2
 Engine Family FTY2 4T2FCC7 Engine Code 1 thru 4
 ECS (Special Features) AIV + CL + EGR + TWC CID (Liter) - 144.4(2.4)
 Type 4 cyl. in-line

Engine code	Vehicle Models (If Coded see attachment) Refer to 08.13.03.00	Trans.	Equiv. Test Weight	Ign. System CA, EI, VA Part No. [Distributor]	Fuel System CL, 2V Part No. [Carburetor]	EGR Valve Part No.	Label Ident. Part No.
1, 2	RN50L-KRA	M4	2,750 2,875	19100-35150	21100-35310	25620-35120	11298-35620
	RN50L-MRA RN55L-MRA -MDA -MDCA	M5	2,875 3,000				
	RN60L-MRA RN65L-MDA -MDCA	M5	3,250 3,375 3,500				
3, 4	RN50L-PRA RN55L-PRA -PDA -PDCA	A4	2,875 3,000				

Comments : See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

*Add 10% to dyno test HP for air conditioning usage.