State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-145-B
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1989 model-year Toyota Motor Company exhaust emission control systems are certified as described below for gasoline-powered light-duty trucks:

Engine Family	Displacement Liters (Cubic Inches)	Exhaust Emission Control Systems (Special Features)
KTY2.4T5FCD5	2.4 (144.4)	Air Injection - Valve Exhaust Gas Recirculation Three-Way Catalyst Heated Oxygen Sensors (2) (Electronic Port Fuel Injection) (On-Board Diagnostics)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

Loaded Vehicle Weight(lbs.)	Hydrocarbons (Grams per Mile)	Carbon Monoxide (Grams per Mile)	Nitrogen Oxides (Grams per Mile)
3751-5750	0.50	9.0	1.0

The following are the certification emission values for this engine family:

Loaded Vehicle Weight(lbs.)	Hydrocarbons (Grams per Mile)	Carbon Monoxide (Grams per Mile)	Nitrogen Oxides (Grams per Mile)
3751-5750	0.21	1.7	0.1

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 8th day of September, 1988.

K. D. Drachand, Chief
Mobile Source Division

A-14-145-B

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET E.O. # _____

Page 1

Manufacturer Toyota Motor Corporation Engine Family KTY2.4T5FCD5

Evaporative Family EV-E Engine Type 4 cyl. in-line

Liters (CID) 2.4 (144.4)

ABBREVIATIONS

Ignition System

CA-Centrifugal Advance
ECU-Electronic Control Unit
EI-Electronic Ignition
ESAC-Electronic Spark Advance Control
VA-Vacuum Advance
VR-Vacuum Retard

Fuel System

'I, EPFI, MPFI, SFI,
DID, DIP, HOS, OS
nV-nVenturi Carburetor
VV-Variable Venturi Carburetor

Exhaust Emissions Control System

AIP-Air Injection - Pump
AIV-Air Injection - Valve
EGR-Exhaust Gas Recirculation
EIC-Electronic Injection Control (Diesel Only)
EM-Engine Modification
SPL-Smoke Puff Limiter or Throttle Delay
TOC-Trap Oxidizer, Continual
TOP-Trap Oxidizer, Periodical
DBC-Dual Bed Catalyst
OC-Oxidation Catalyst
TWC-Three-Way Catalyst
WUOC-Warm-up Oxidation Catalyst
WUTWC-Warm-up Three-Way Catalyst
OS-Oxygen Sensor
HOS-Heated Oxygen Sensor

Special Features

CFI-Central Fuel Injection or Throttle Body Injection
EPFI-Electronic Port Fuel Injection
MPFI-Mechanical Port Fuel injection
SFI-Sequential Fuel Injection
DID-Diesel Injection-Direct
DIP-Diesel Injection-Prechamber
TC-Turbocharger
SC-Supercharger
IC-Intercooler or Aftercooler
CCV-Combustion Chamber Valve
OBD-On-Board Diagnostics

VEHICLE MODELS :

Truck 4WD
RN110L-CRLSEA
-CRMDEA (With air conditioner)
-CRMSEA
-CRPDEA
-CRPSEA

Engine: Front X Mid. _____ Rear _____

Drive: FWD _____ RWD _____ 4WD Full time _____ 4WD Part time X

Note : To identify applicable emission standard, it is shown on the tune-up label.

E.O. # A-14-145-B

1989 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

Passenger Cars ___ Light-Duty Trucks x Medium-Duty Vehicles ___ Gas x Diesel ___

Manufacturer Toyota Motor Corporation Engine family KTY2.4T5FCD5

Liter (CID) 2.4 (144.4) Eng. Type 4 cyl. in-line

Emission Control Sys. (Special Features) AIV + EGR + TWC + HOS + HOS (EPFI +OBD)

Engine code	Vehicle Models (If Coded see attachment) (Dyno Hp: Refer to 08.13.03.00)	Trans. Type	Equiv. Test Weight	Ign. System ECU,EI,ESAC Part No. [Computer] [Knock sensor]*1	Fuel System CL, EPFI Part No. [Computer] [Air flow meter] [Injector]	EGR Valve Part No.	Catalyst Part No.
2 & 4	RN110L-CRLSEA -CRMSEA	M5	3,750 3,875	89661-35160 89615-35030 89615-35040	89661-35160 22250-35050 23250-35040	25620-35100	18450-65020 (H01)*2
4	RN110L-CRMDEA						
5 thru 8	RN110L-CRPDEA -CRPSEA	A4	3,875	89661-35180 89615-35030 89615-35040	89661-35180 22250-35050 23250-35040	25620-35130	

Comments : See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment.

Note *1 Maker : 89615-35030 : MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.
89615-35040 : NIPPONDENSO CO., LTD.

Note *2 : Parenthetical information represents identifying marks found on production parts.