

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-497
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1992 model Ford Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: NFM5.0V5FXC8 Displacement: 5.0 Liters (302 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Exhaust Gas Recirculation
- Dual Heated Oxygen Sensors
- Secondary Air Injection
- Dual Warm-Up Three-Way Catalysts
- Three-Way Catalyst
- Sequential Multipoint Electronic Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The emission standards for this engine family in grams per mile are as follows:

<u>Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>
0.39	7.0	0.4

The certification emission values for this engine family in grams per mile are as follows:

<u>Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>
0.07	1.4	0.2

BE IT FURTHER RESOLVED: That the vehicle models listed also comply with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s]..." for the aforementioned model year (Title 13, California Code of Regulations, Section 1968).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2290).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 15th day of July, 1991.


R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1992 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEETManufacturer FORD MOTOR COMPANY Eng. Family NFM5.OV5FXC8Pass Cars XX Lt-Duty Trucks Med-Duty Vehicles Fuel Type GASOLINEEng. Type V-8 Liter (CID) 5.0 (302) Evap. Family HMEmission Control System & Special Features EGR/2HO2S/AIR/2WUTWC/TWC/SMPI
(Use abbreviations per SAE J1930 June88)Engine: Front XX Mid. Rear Drive: FWD RWD XX 4WD-FT 4WD-PT

Eng. Code/ (Cert Std.)	Veh. Models (If Coded see Attachmt.)	Trans. Type: A-Auto M-Man.	ETW	RLHP (DPA)	Ign. Sys. (PCME/PROM) Part No. -12A650-	EGR Syst. Part No -9F483-	Catalyst Part No. -F5250-
122TRO0A/N	T-BIRD 2DR (with sport facia)	A-4	4000	9.2 a/ (A/C) 8.4 a/ (NAC) 9.5 b/ (A/C) 8.6 b/ (NAC) 9.5 c/ (A/C) 8.6 c/ (NAC)	F1MF-GA	F1SE-AC	F2SC-AB
Certification Standards							
	NMHC: 0.39			a/	P205/70R15 TIRES		
	CO: 7.0			b/	P215/70R15 TIRES		
	NOx: 0.4			c/	P215/65R15 TIRES		
	EVAP: 2.0						

1992 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEETManufacturer FORD MOTOR COMPANY Eng. Family NFM5.OV5FXC8Pass Cars X Lt-Duty Trucks Med-Duty Vehicles Fuel Type GASOLINEEng. Type V-8 Liter (CID) 5.0 (302) Evap. Family HMEmission Control System & Special Features EGR/2HO2S/AIR/2WUTWC/TWC/SMPI
(Use abbreviations per SAE J1930 June88)Engine: Front X Mid. Rear Drive: FWD RWD X 4WD-FT 4WD-PT

Eng. Code/ (Cert Std.)	Veh. Models (If Coded see Attachmt.)	Trans. Type: A-Auto M-Man.	Equiv. Test Weight	RLHP (DPA)	Ign. Sys. (PCME/PROM) Part No.	EGR Syst. Part No	Catalyst Part No.
122TROOA/N	T-BIRD 2DR (w/o sport facia)	A-4	4000	8.9 ¹ / _(A/C) 8.1 ¹ / _(NAC) 9.1 ² / _(A/C) 8.3 ² / _(NAC)	F1MF-GA	F1SE-AC	F2SC-AB
	COUGAR 2DR			9.2 ¹ / _(A/C) 8.4 ¹ / _(NAC) 9.9 ² / _(A/C) 9.0 ² / _(NAC) 9.6 ³ / _(A/C) 8.8 ³ / _(NAC)			
	Certification Standards						
	NMHC: 0.39						
	CO: 7.0						
	NOx: 0.4						
	EVAP: 2.0						
				1/ P205/70R15 TIRES			
				2/ P215/70R15 TIRES			
				3/ COUGAR XR7 P225/60ZR16 TIRES			