file

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-195
Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: STK1.5VJG2EK Displacement: 1.5 Liters (91 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Warm-Up Three Way Catalytic Converter
Three Way Catalytic Converter
Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection
On-Board Diagnostic II

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon Monoxide	Nitrogen Oxides	Formaldehyde
50,000	0.125	3.4	0.4	0.015
100,000	0.156	4.2	0.6	0.018

Reactivity Adjustment Factor for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1995 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon Monoxide	Nitrogen Oxides	Formaldehyde
50,000	0.086	0.8	0.0 (0.03)	0.001
100,000	0.091	0.9	0.0 (0.03)	0.001

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with these standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 6th day of June, 1994.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET E.O.# A-16-195 page __ of __

Manufacturer Mazda Motor Corporation Engine Family STK1.5VJG2EK

Passenger Car X (PC) Light-Duty Truck ___ (T1/T2) Medium-Duty Vehicle ___ (M1/M2/M3/M4/M5)

Stds Type: TLEV (Tier 0/1, AB965, TLEV, LEV, ULEV) Vehicle Type (FFV, HEV(Type A/B/C)): N/A

Fuel Type PHASE 2 Evaporative Family STK1178BYM11

Engine Config. I-4 Liter(CID) 1.5 (91.0)

Engine: Front X Mid. ___ Rear___ Drive: FWD X RWD ___ 4WD-FT ___ 4WD-PT ___

Exhaust ECS & Special Features (incl. CARB, MFI, etc.) TWC, WU-TWC, HO2S, EGR, SFI, OBD2

(use abbreviations per SAE 1930 MAY91)

Evap Std: 100 K Single Cert Std for Multi-Class Eng Fam: N/A

Exh Cert Fuel(s): Phase II Fuel Type(s): Gasoline Hybrid: N/A

APU Cycle: ~~Otto~~ N/A

Engine Code (Cert. Std.)	Vehicle Models (if coded see attachment)	Trans. Type A-automatic M-manual	ETW	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Part. No.
2Z5D2AAN	Mazda Protege	M5	2750	6.3	Distributor:	EGR	Pre:
2Z5D2AAA				6.9	B6BF	Control	Z502
2Z5DTAAN		A4	2875	6.3	ECU:	Valve:	Main:
2Z5DTAAA				6.9	Z503 18 881A	B6BF	Z502
					Z504 18 881A		

N = no A/C
A = A/C

Certification Standard:

	NMHC	CO	NOx	HCHO	EVAP.
50,000 miles	0.125 g/mile	3.4 g/mile	0.4 g/mile	15 mg/mile	2.0 g/test
100,000 miles	0.156 g/mile	4.2 g/mile	0.6 g/mile	18 mg/mile	---

	at 2500 rpm N/L	at idle
Idle HC	220 ppm	100 ppm
Idle CO	1.2 %	1.0 %

Revisions:
1290