State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-266
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1995 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: STY3.41JG1GK Displacement: 3.4 Liters (206.1 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection
Exhaust Gas Recirculation
Heated Oxygen Sensors (two)
Three Way Catalytic Converter
On-Board Diagnostic II

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

| Loaded Vehicle Weight (lbs.) | Miles | Non-Methane Hydrocarbons | Carbon Monoxide | Nitrogen Oxides |
|---|---|---|---|---|
| 0-3750 | 50,000 | 0.25 | 3.4 | 0.4 |
| | 100,000 | 0.31 | 4.2 | n/a |

The certification exhaust emission values for this engine family in grams per mile are:

| Loaded Vehicle Weight (lbs.) | Miles | Non-Methane Hydrocarbons | Carbon Monoxide | Nitrogen Oxides |
|---|---|---|---|---|
| 0-3750 | 50,000 | 0.11 | 1.3 | 0.2 |
| | 100,000 | 0.12 | 1.5 | n/a |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements-1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, Medium-Duty Vehicles and Engines" (Title 13, California Code Of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 4th day of August, 1994.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

# 1995 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
## PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA
Engine Family: STY3.41JG1GK
Evaporative Family: STY1095DYM00
Evap Std: 50K x Useful Life with R/L___
Exh Std: Tier-0___ Tier-1 x TLEV___ LEV___ ULEV___ ZEV___; EPA Tier-0___ EPA Tier-1___
Veh Class(es): PC___ LDT1 x LDT2___ MDV1___ MDV2___ MDV3___ MDV4___ MDV5___
Single Cert Std for Multi-Class Eng Fam:___ (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo x Ph2___ Diesel: 13 CCR 2282___ or 40 CFR 86.113-90___ or -94___
M85___ CNG___ LPG___ Other (specify)___
Fuel Type(s): Dedicated x Flex-Fuel___ Dual-Fuel___ Gasoline x Diesel___ M85___
CNG___ LNG___ LPG___ Other (specify)___
Hybrid: Type A___ B___ C___, APU Cycle (e.g., Otto, Diesel, Turbine)___
Engine Configuration: V-6 Displacement: 3.4 / ___ Liters 206.1 / ___ Cubic Inches
Engine: Front x Mid ___ Rear ___ Drive: FWD ___ RWD x 4WD-FT ___ 4WD-PT ___
Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI, EGR, HO2S(2), TWC, OBD2
(use abbreviations per SAE J1930 SEP91)

| Engine code (also list CA/49/50ST | Vehicle Models (if coded see attachmt.) | Trans. Type: A/L-auto M-manual | ETW or Test Wt | DPA or RLHP | Ignition (ECM/PCM) Part No. | EGR System Part No. | Catalytic Converter Part No. |
|---|---|---|---|---|---|---|---|
| 1 | VCK11L-TRMDKA<br>-TRMRKA<br>-TRMSKA | M5 | 3750 | 12.8, 13.6<br>12.3, 13.6<br>13.6 | 89661-34120 | 25620-62050 | S97 |
| 2 | VCK11L-TRMDKA<br>-TRMRKA<br>-TRMSKA | | 3750 | 13.6, 15.0<br>13.6, 15.0<br>15.0 | | | |
| 3 | VCK11L-TRSDKA<br>-TRSSKA | L4 | 3750 | 12.3, 13.6<br>13.6 | 89661-34130 | 25620-62060 | |
| 4 | VCK11L-TRSDKA<br>-TRSSKA | | 3750<br>3875 | 13.6, 15.0<br>15.0 | | | |

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

VEHICLE MODELS :

TOYOTA T100 2WD

VCK11L-TRMDKA VCK11L-TRSDKA
-TRMSKA -TRSSKA
-TRMRKA