File

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-283-A
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Toyota Motor Corporation, exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TTY3.0VJG1GK Displacement: 3.0 Liters (182.7 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection
Exhaust Gas Recirculation
Dual Heated Oxygen Sensors
Three Way Catalytic Converter
Heated Oxygen Sensor

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.15	1.3	0.2	4.7
100,000	0.17	1.5	0.2	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 19th day of July 1995.

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

17.11.00

E.O.# A-14-283-A
Page 1

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: TTY3.0VJG1GK Evap Fam: TTY1073DYMA0
All Eng Codes in Eng Fam: CA x 49S ___ 50S ___ AB965 ___
Exh Std: CA Tier-1 x TLEV ___ LEV ___ ULEV ___ ZEV ___; US EPA Tier-1 ___
Evap std: 50K x Useful Life with R/L ___ In-Use Exh Std: Full In Use x Alt In Use ___
Veh Class(es): PC x LDT1 ___ LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated x Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline x Diesel ___
CNG ___ LNG ___ LPG ___ M85 ___ Other(specify) ___
Emiss Test Fuel(s): Indo x Ph2 ___ CNG ___ LPG ___ M85 ___ Other(specify) ___
Diesel: 13CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
Service Accum: Std AMA X Mod AMA ___ Mfr ADP ___ Other(specify) ___
NMOG Test Procedure: N/A x Std ___ Equiv ___ R/L Test Proc: SHED ___ Pt Source ___
Hybrid: Type A ___ B ___ C ___, APU Cycle(e.g., Otto, Diesel, Turbine): ___
Engine Configuration: V-6 Displacement: 3.0 / ___ Liters 182.7 / ___ Cubic Inches
Valves per Cylinder: 4 Rated HP: 188 @ 5,200 RPM
Engine: Front x Mid ___ Rear ___ Drive: FWD x RWD ___ 4WD-FT ___ 4WD-PT ___
Exhaust ECS(e.g., MFI, EGR, TC, CAC): SFI, EGR,2HO2S, TWC,HO2S
(use abbreviations per SAE J1930 SEP91)

Engine Code/ (also list CA/ 49S/ 50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4 stc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic converter part No.
1	MCV10L-AEPGKA MCV10L-AEPNKA MCV10L-CEPNKA MCV10L-CCPNKA MCV10L-CEPGKA	L4	3,625 3,750	5.6 5.0 5.6	89661-06230 89661-33690	25620-20010	P04
	MCV10L-AEPSKA MCV10L-CEPSKA MCV10L-CCPSKA		3,625	7.5 7.2	89661-06240 89661-33700		
	MCV10L-CWPNKA		3,875	6.8	89661-06230 89661-33690		

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

VEHICLE MODELS:

Camry	Camry Wagon
MCV10L-AEPGKA	MCV10L-CWPNKA
MCV10L-AEPNKA	
MCV10L-AEPSKA	
MCV10L-CCPNKA	
MCV10L-CCPSKA	
MCV10L-CEPGKA	
MCV10L-CEPNKA	
MCV10L-CEPSKA	

E.O.# A-14-283-A
Page 1 of 2

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

7.1

Manufacturer: TOYOTA Exh Eng Fam: TTY3.0VJG1GK Evap Fam: TTY1073DYMA0
All Eng Codes in Eng Fam: CA x 49S ___ 50S ___ AB965 ___
Exh Std: CA Tier-1 x TLEV ___ LEV ___ ULEV ___ ZEV ___; US EPA Tier-1 ___
Evap std: 50K x Useful Life with R/L ___ In-Use Exh Std: Full In Use x Alt In Use ___
Veh Class(es): PC x LDT1 ___ LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated x Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline x Diesel ___
CNG ___ LNG ___ LPG ___ M85 ___ Other(specify) ___
Emiss Test Fuel(s): Indo x Ph2 ___ CNG ___ LPG ___ M85 ___ Other(specify) ___
Diesel: 13CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
Service Accum: Std AMA X Mod AMA ___ Mfr ADP ___ Other(specify) ___
NMOG Test Procedure: N/A x Std ___ Equiv ___ R/L Test Proc: SHED ___ Pt Source ___
Hybrid: Type A ___ B ___ C ___, APU Cycle(e.g., Otto, Diesel, Turbine): ___
Engine Configuration: V-6 Displacement: 3.0 / Liters 182.7 / Cubic Inches
Valves per Cylinder: 4 Rated HP: 188 @ 5,200 RPM
Engine: Front x Mid ___ Rear ___ Drive: FWD x RWD ___ 4WD-FT ___ 4WD-PT ___
Exhaust ECS(e.g., MFI, EGR, TC, CAC): SFI, EGR,2HO2S,TWC,HO2S
(use abbreviations per SAE J1930 SEP91)

		Sect/Page#
1	Authorized Representative	01.02.00
2	Fuel Specifications	03.00.00
3	Test Equipment	04.00.00
4	Test Procedure	05.00.00
5	Mileage Accumulation Route	02.04.00
6	Emission Warranty Statement	17.10.00
7	Maint: Cert/Req'd/Recm'd	06.00.00
8	Emiss Label/Vac Hose Diag	07.00.00
9	Evap Control System	19.00.00
10	Engine Parameters	20.01.00
11	Fuel System	08.01.00.00
12	Iginition System	08.01.00.00
13	Exhaust Control System	20.02.00
14	Proj Sales(LDT/MDV Split)	17.13.00
15	Vehicle Description	20.02.08
16	Evap Bench Test Procedure	13.02.02
17	R/L Temp & Press Profiles	N/A
18	EDV Selection	02.03.02
19	Prod Veh same as Test Veh	17.01.01

		Sect/Page#
21	Gen Std, increase in Emiss, Safety, Meets all Reqmts	20.03.05
22	Emission Label Durability	07.00.00
23	Driveability Statement	17.01.02
24	Adjustable Parameters	08.16.01.00
25	Tamper Resistance Method(s)	08.16.02.00
26	Fill Pipe Specifications	17.04.00
27	High Altitude Compliance	17.02.00
28	OBD Sys incl Marked Revisions	02.06.00
29	I&M Test Procedure & Data	17.11.00
30	50 Degree F Compliance	N/A
31	Manufacturer's RAF	N/A
32	Phase-In Plans: Exh Cert Stds	N/A
	Exh In-Use Stds	17.18.00
	Evap Cert Stds	17.19.00
33	NMOG Fleet Average Calculation	17.15.00
34	AB965 Credits/Withdrawals	N/A
35	EPA Certificate	after EO
36	Equiv NMOG Proc--ARB Approval	N/A

20 Test Vehicle Information	Durability Data Vehicle	Emission Data Vehicle	Emission Data Vehicle	Emission Data Vehicle
C/O or C/A MY & ID	C/O 94-D3	___ 95-MZ1	___ 95-MZ4	___ ___
Vehicle Log Page(s)	20.03.04	20.03.04	20.03.04	
Zero Mile Book Page(s)	17.12.01(94MY)	20.03.06	20.03.06	
Maint Logs & Engr Eval	17.12.02(94MY)	N/A	N/A	

Continued on next page