 Mel

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-75
Relating to Certification of New Motor Vehicles

SAAB AUTOMOBILE AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Saab Automobile AB exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VSA2.0VJGKEK Displacement: 2.0 Liters (121 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection
Heated Oxygen Sensors (Two)
Three Way Catalytic Converter
Turbocharger
Charge Air Cooler

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.10	1.4	0.2	7.5
100,000	0.11	1.7	0.2	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," pursuant to provisions in said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 12th day of September 1996.

John Kowalski for

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

E.O.# A-22-75

199 7 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page___

Manufacturer: SAAB Exh Eng Fam: VSA2.0VJGKEK Evap Fam: VSA1080BYPEA
All Eng Codes in Eng Fam: CA___ 49S___ 50S X AB965___
Exh Std: CA Tier-1 X TLEV___ LEV___ ULEV___ ZEV___; US EPA Tier-1_
Evap Std: 50K X Useful Life with R/L___ In-Use Exh Std: Full In Use X Alt In Use X
Veh Class(es): PC X LDT1___ LDT2___ MDV1___ MDV2___ MDV3___ MDV4___ MDV5___
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated___ Flex-Fuel___ Dual-Fuel___ Bi-Fuel___ Gasoline X Diesel___
CNG___ LNG___ LPG___ M85___ Other (specify)___
Emiss Test Fuel(s): Indo X Ph2___ CNG___ LPG___ M85___ Other (specify)___
Diesel: 13 CCR 2282___ 40 CFR 86.113-90___ 40 CFR 86.113-94___
Service Accum: Std AMA X Mod AMA___ Mfr ADP___ Other (specify)___
NMOG Test Procedure: N/A X Std___ Equiv___ R/L Test Proc: SHED___ Pt Source N/A
Hybrid: Type A___ B___ C___, APU Cycle (e.g., Otto, Diesel, Turbine):___
Engine Configuration: I4 Displacement: 2.0 / ___ Liters 121 / ___ Cubic Inches
Valves per Cylinder: 4 Rated HP: 185 @ 5500 RPM
Engine: Front X Mid___ Rear___ Drive: FWD X RWD___ 4WD-FT___ 4WD-PT___
Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI, HO2S(2), TWC, TC, CAC
(use abbreviations per SAE J1930 SEP91)

Engine Code (also list CA/49ST/50ST	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
B204L3 (50ST)	9000SE Coupe	L4	3500	7.2	47 80 284	N/A	46 23 104
	9000SE Hatchback						
	9000SE Convertible	M5			47 80 276		

Date Issued:

Revisions: