Tili

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-775
Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Ford Motor Company exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: WFMXT04.2AAA Displacement: 4.2 Liters (255 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters (two)
Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
3751-5750	50,000	0.32	4.4	0.7	12.5
	100,000	0.40	5.5	0.97	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
3751-5750	50,000	0.09	1.4	0.1	2.0
	100,000	0.12	1.9	0.18	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16th day of July 1997.

R. B. Summerfield, Chief
Mobile Source Operations Division

E.O.# A-10-775

1998 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
EXHAUST/EVAPORATIVE SYSTEM & CALIFORNIA REQUIREMENTS
PASSENGER CARS, LIGHT-DUTY AND MEDIUM-DUTY TRUCKS

Mfgr. **FORD MOTOR COMPANY** Exhaust Engine Family: **WFMXT04.2AAA(WT4.2AAA)**

Engine Code Types: **CA X** 49S___ 50S___ Evap Emissions Family: **WFMXE0160BOE**

Exh Std: Tier-0___ **Tier-1 X** TLEV___LEV___ ULEV___ ZEV___ EPA TIER-0___ TIER-1__

Evap Std: 50K___ **Useful Life with R/L X** R/L Test Proc. Point Source ORVR NO

Veh Class(es): PC___ LDT1___ **LDT2 X** MDV1___ MDV2___ MDV3___ MDV4___ MDV5__

Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1,MDV1,MDV2,MDV3,MDV4)

Service Accum: Mod. AMA

Exh Cert Fuel(s): Indo___ **Ph2 X** Diesel: 13 CCR 2282___ or 40CFR 86.113-90___ or -94__
M85___ CNG___ LPG___ Other (specify)

Fuel Type(s): Dedicated___ Flex Fuel___ Dual-Fuel___
Gasoline X Diesel___ M85___ CNG___ LPG___ Other (specify)_____

Hybrid: Type A___ B___ C___, APU Cycle (eg.., Otto, Diesel, Turbine)_____

Engine Config **V-Block 6** **Displacement:** **4.2L (255)** Liters (Cubic Inches)

Valves/Cyl: **2** **Rated HP:** **205 @ 4400 RPM**

Engine: Front X Mid___ Rear___ **Drive:** FWD___ **RWD X** 4WD-FT___ **4WD-PT X**

Exhaust Control System and Special Features **2TWC(2)HO2S(2)EGR, SFI,**
(Use abbreviations per SAE J1930 SEP91)

Engine Code (also list CA/49ST/50ST	Vehicle Models (if coded see attachment)	Trans. Type A-Automatic M-Manual	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
844RR05N	F150 RKL 2WD	A(DU)	4250	*	F8UF-LB	F65E-AA	F65A-BH,AE
844RR05N	F150 RKL 2WD	A(DU)	4500				
844SR05N	F150 RKS 2WD	A(DU)	4250		F8UF-MB		
844SR05N	F150 RKL 2WD	A(DU)	4500				
844RR05A	F150 RKS 2WD	A(DU)	4250		F8UF-LB		
844SR05A	F150 RKS 2WD	A(DU)	4250		F8UF-MB		
844SR05A	F150 RKL 2WD	A(DU)	4500				
844RR05N	F150 RKL 2WD	A(DU)	4500		F8UF-LB		
844RR05A	F150 SKS 2WD	A(DU)	4500				
844RR05A	F150 SKL 2WD	A(DU)	4750				
844SR05A	F150 SKS 2WD	A(DU)	4500		F8UF-MB		
844SR05A	F150 SKL 2WD	A(DU)	4750				
844RR05A	F150 SKS 2WD	A(DU)	4500				
844RR05A	F150 SKL 2WD	A(DU)	4750				
844SR05A	F150 SKS 2WD	A(DU)	4500		F8UF-LB		
844SR05N	F150 SKL 2WD	A(DU)	4750				
844SR05N	F150 RKS 4WD	A(DU)	4750		F8UF-LB		F65A-DH/CG
844SR05N	F150 RKL 4WD	A(DU)	4750				
844SR05A	F150 RKS 4WD	A(DU)	4750				
844SR05A	F150 RKL 4WD	A(DU)	4750				
843RR00N	F150 RKS 2WD	M(RE)	4250		F85F-ALA		F65A-BH,AE
843RR00N	F150 RKL 2WD	M(RE)	4500				
843SR00N	F150 RKS 2WD	M(RE)	4250		F85F-AMA		
843SR00N	F150 RKL 2WD	M(RE)	4500				

* *See page 20.09.17.02-3 for DPA values.*

Engine Family: **WT4.2AAA**

Issue Date: JUN 14 1997
Revised:

1998 SUPPLEMENTAL DATA SHEET

EO# A-10-775

Engine Code (also list CA/49ST/50ST	Vehicle Models (if coded see attachment)	Trans. Type A-Automatic M-Manual	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
843RR00A	F150 RKS 2WD	M(RE)	4250	*	F85F-ALA	F65E-AA	F65A-DH,CG
843SR00A	F150 RKS 2WD	M(RE)	4250		F85F-AMA		
843SR00A	F150 RKL 2WD	M(RE)	4500				
843RR00A	F150 RKL 2WD	M(RE)	4500		F85F-ALA		
843RR00N	F150 SKS 2WD	M(RE)	4500				
843RR00N	F150 SKL 2WD	M(RE)	4750				
843SR00N	F150 SKS 2WD	M(RE)	4500		F85F-AMA		
843SR00N	F150 SKL 2WD	M(RE)	4750				
843RR00A	F150 SKS 2WD	M(RE)	4500		F85F-ALA		
843RR00A	F150 SKL 2WD	M(RE)	4750				
843SR00A	F150 SKS 2WD	M(RE)	4500		F85F-AMA		
843SR00A	F150 SKL 2WD	M(RE)	4750				
843RR00N	F150 RKS 4WD	M(RE)	4750		F85F-ALA		F65A-BH,AE
843RR00N	F150 RKL 4WD	M(RE)	4750				
843SR00N	F150 RKS 4WD	M(RE)	4750		F85F-AMA		
843SR00N	F150 RKL 4WD	M(RE)	4750				
843RR00N	F150 RKS 4WD	M(RE)	4750		F85F-ALA		
843RR00N	F150 RKL 4WD	M(RE)	4750				
843SR00N	F150 RKS 4WD	M(RE)	4750		F85F-AMA		
843SR00N	F150 RKL 4WD	M(RE)	4750				

* *See page 20.09.17.02-3 for DPA values.*

Engine Family: WT4.2AAA

Issue Date: JUN 14 1997
Revised:

Engine Family: WT4.2AAA
Issue Date: JUN 14 1997
Revised:

20.09.17.02 - 3

1998 SUPPLEMENTAL DATA SHEET

EO # A-10-775

1998 TRUCK DPA CHART

		< - - -	NON -	AC	- - - >	< - - -	A	C	- - - >	Ambient Dyno Coefficients			Track Force Coefficients	
VEHICLE LINE	ETW	CDT	CODE	DPA	TRLHP (HP)	CDT	CODE	DPA	TRLHP (HP)	A	B	C	F0	F2
		% = LVW/ALVW (BOTH)			$ = ALVW					(LBS)	(LBS/MPH)	(LBS/(MPH)^2)	(LBS)	(LBS/(MPH)^2)
F-150 4x2 (LD)	4250	14.26	(R)	13.2	18.37	13.40	(R)	14.5	19.55	23.87	-0.3134	0.04093	38.10	0.03975
(PN96)	4500	14.96	(R)	13.2	18.54	14.03	(R)	14.5	19.77	23.87	-0.3134	0.04093	38.10	0.03975
MANUAL TRANS	4750	15.60	(R)	13.2	18.77	14.67	(R)	14.5	19.96	22.38	-0.2266	0.03926	38.80	0.03931
$	5000	16.27	(R)	13.2	18.94	15.30	(R)	14.5	20.14	27.38	-0.2437	0.04021	41.10	0.04009
$	5250	16.95	(R)	13.2	19.09	15.94	(R)	14.5	20.30	27.37	-0.2009	0.03961	43.20	0.03986
F-150 4x2 (LD)	4250	13.95	(A)	13.3	18.78	13.24	(A)	14.6	19.79				41.10	0.04158
(PN96)	4500	14.57	(A)	13.3	19.04	13.76	(A)	14.6	20.16				43.40	0.04049
AUTO TRANS (4R70W-DUC)	4750	15.20	(A)	13.3	19.26	14.29	(A)	14.6	20.49				43.50	0.04212
P235/70R16 TIRE $	5000	15.83	(A)	13.3	19.47	14.81	(A)	14.6	20.81				47.50	0.04112
$	5250	16.45	(A)	13.3	19.67	15.33	(A)	14.6	21.11				49.80	0.03856
$	5500	17.06	(A)	13.3	19.85	15.85	(A)	14.6	21.39				51.80	0.03903
F-150 4x2 (LD)	4500	14.27	(R)	13.3	19.44	13.41	(R)	14.6	20.69					
(PN96)	4750	15.02	(R)	13.3	19.49	14.11	(R)	14.6	20.75					
AUTO TRANS (4R70W-DUC)	5000	15.80	(R)	13.3	19.51	14.75	(R)	14.6	20.88					
P255/70R16 TIRE $	5500	17.29	(R)	13.3	19.61	16.04	(R)	14.6	21.14					
F-150 4x2 (LD)	4250	13.95	(R)	12.9	18.78	13.24	(R)	14.2	19.79				41.10	0.04158
(PN96)	4500	14.57	(R)	12.9	19.04	13.76	(R)	14.2	20.16				43.40	0.04049
AUTO TRANS (4R70W-DUA)	4750	15.20	(R)	12.9	19.26	14.29	(R)	14.2	20.49				43.50	0.04212
P235/70R16 TIRE $	5000	15.83	(R)	12.9	19.47	14.81	(R)	14.2	20.81				47.50	0.04112
$	5250	16.45	(R)	12.9	19.67	15.33	(R)	14.2	21.11				49.80	0.03856
$	5500	17.06	(R)	12.9	19.85	15.85	(R)	14.2	21.39				51.80	0.03903
F-150 4x2 (LD)	4250	13.77	(R)	13.4	19.03	13.00	(R)	14.7	20.15	33.49	-0.6831	0.04511	42.02	0.04065
(PN96)	4500	14.54	(R)	13.4	19.08	13.69	(R)	14.7	20.26	33.49	-0.6831	0.04511	42.02	0.04065
AUTO TRANS (4R70W-DUA)	4750	15.30	(R)	13.4	19.14	14.39	(R)	14.7	20.35	36.81	-0.7551	0.04613	43.23	0.04084
P255/70R16 A/S TIRE $	5000	16.07	(R)	13.4	19.18	15.08	(R)	14.7	20.44	38.41	-0.7428	0.04224	48.28	0.03754
$	5250	16.83	(R)	13.4	19.23	15.78	(R)	14.7	20.51	38.41	-0.7428	0.04224	48.28	0.03754
$	5500	17.60	(R)	13.4	19.26	16.47	(R)	14.7	20.58	43.41	-0.9323	0.04616	49.45	0.03895

(C) Certification point, (R) Regressed point,
(A) Adjusted, (CB) Cookbook, (P) Projection
97DPATRK.xls

A. C. D'Ambrosi
Certification Engineering - VEE
12/18/96

Engine Family: WT4.2AAA

Issue Date: JUN 14 1997

Revised:

20.09.17.02 - 4

1998 SUPPLEMENTAL DATA SHEET

EO # A-10-775

1998 TRUCK DPA CHART

VEHICLE LINE		ETW	< - - - CDT	NON - CODE	AC DPA	- - - > TRLHP (HP)	< - - - CDT	A CODE	C DPA	- - - > TRLHP (HP)	Ambient Dyno Coefficients A	B	C	Track Force Coefficients F0	F2
% = LVW/ALVW (BOTH) ♦ = ALVW											(LBS)	(LBS/MPH)	(LBS/(MPH)^2)	(LBS)	(LBS/(MPH)^2)
F-150 4x2 (LD)		4250	13.92	(R)	13.3	18.62	13.44	(R)	14.6	19.49	29.76	-0.6688	0.04555	41.23	0.04090
(PN96)		4500	14.57	(R)	13.3	19.04	13.92	(R)	14.6	19.93	29.76	-0.6688	0.04555	41.23	0.04090
AUTO TRANS (4R70W-DUA)		4750	15.21	(R)	13.3	19.25	14.40	(R)	14.6	20.33	35.86	-0.8637	0.04767	43.44	0.04085
P255/70R16 A/T TIRE	♦	5000	15.86	(R)	13.3	19.43	14.88	(R)	14.6	20.71	43.32	-1.0092	0.04730	47.51	0.03954
	♦	5250	16.51	(R)	13.3	19.60	15.36	(R)	14.6	21.07	43.32	-1.0092	0.04730	47.51	0.03954
	♦	5500	17.15	(R)	13.3	19.77	15.84	(R)	14.6	21.40	42.05	-0.7866	0.04499	50.76	0.03960
F-150 4x2 (LD)		4500	14.20	(R)	14.2	19.53	13.17	(R)	15.6	21.06	34.03	-0.7428	0.04679	46.16	0.04070
(PN96)		4750	14.91	(R)	14.2	19.64	13.89	(R)	15.6	21.08	33.23	-0.7725	0.0469	45.71	0.04036
AUTO TRANS (E4OD)	%	5000	15.62	(R)	14.2	19.73	14.60	(R)	15.6	21.11	37.88	-0.7424	0.04614	50.90	0.03975
P235/70R16 TIRE	♦	5250	16.33	(R)	14.2	19.82	15.31	(R)	15.6	21.14	37.88	-0.7424	0.04614	50.90	0.03975
	♦	5500	17.04	(R)	14.2	19.90	16.02	(R)	15.6	21.16	39.05	-0.6925	0.04398	52.99	0.03855
F-150 4x2 (LD)		4500	13.94	(R)	14.8	19.90	13.13	(R)	16.2	21.13	33.67	-0.7408	0.04764	47.11	0.04156
(PN96)		4750	14.63	(R)	14.8	20.01	13.74	(R)	16.2	21.31	34.83	-0.6974	0.04548	49.26	0.03995
AUTO TRANS (E4OD)		5000	15.33	(R)	14.8	20.11	14.34	(R)	16.2	21.49	38.27	-0.6751	0.04506	53.11	0.03983
P255/70R16 TIRE	♦	5250	16.02	(R)	14.8	20.20	14.94	(R)	16.2	21.66	38.27	-0.6751	0.04506	53.11	0.03983
	♦	5500	16.71	(R)	14.8	20.29	15.54	(R)	16.2	21.82	39.82	-0.7001	0.04439	55.41	0.03896
F-150 4x2 (LD)		4250	12.56	(R)	14.9	20.86	11.86	(R)	16.3	22.09					
(PN96) - CANADA ONLY		4500	13.12	(R)	14.9	21.14	12.37	(R)	16.3	22.42					
AUTO TRANS (E4OD)		4750	13.67	(R)	14.9	21.42	12.87	(R)	16.3	22.75					
LT245/75R16 A/S & A/T TIRE	%	5000	14.23	(R)	14.9	21.66	13.38	(R)	16.3	23.04					
	♦	5250	14.78	(R)	14.9	21.90	13.87	(R)	16.3	23.33					
	♦	5500	15.34	(R)	14.9	22.10	14.37	(R)	16.3	23.59					
F-150 4x4 (LD)		4750	13.13	(R)	16.0	22.30	12.44	(R)	17.4	23.54				49.72	0.04705
(PN96)		5000	13.76	(R)	16.0	22.40	12.99	(R)	17.4	23.73				50.93	0.04744
MANUAL TRANS	%	5250	14.40	(R)	16.0	22.47	13.54	(R)	17.4	23.90				52.04	0.04709
	♦	5500	15.04	(R)	16.0	22.54	14.09	(R)	17.4	24.06				54.97	0.04569
F-150 4x4 (LD)		4750	13.21	(R)	16.0	22.16	12.48	(R)	17.4	23.46	43.24	-0.8864	0.05197	53.53	0.04598
(PN96)		5000	13.79	(R)	16.0	22.35	13.05	(R)	17.4	23.62	43.24	-0.8864	0.05197	53.53	0.04598
AUTO TRANS (4R70W)	%	5250	14.37	(R)	16.0	22.52	13.62	(R)	17.4	23.76	42.09	-0.9640	0.05310	54.55	0.04589
P235/70R16 TIRE	♦	5500	14.95	(R)	16.0	22.68	14.19	(R)	17.4	23.89	42.81	-0.7890	0.05086	57.71	0.04529
F-150 4x4 (LD)		4750	13.88	(A)	15.6	21.10	13.14	(A)	17.0	22.28	41.20	-0.8064	0.04864	53.31	0.04381
(PN96)		5000	14.19	(A)	15.6	21.72	13.41	(A)	17.0	22.98	41.20	-0.8064	0.04864	53.31	0.04381
AUTO TRANS (4R70W)	%	5250	14.49	(A)	15.6	22.33	13.67	(A)	17.0	23.67	43.81	-0.9616	0.05245	54.05	0.04633
P255/70R16 TIRE A/S	♦	5500	14.80	(A)	15.6	22.91	13.94	(A)	17.0	24.32	43.95	-0.8231	0.05099	56.28	0.04620

(C) Certification point, (R) Regressed point,
(A) Adjusted, (CB) Cookbook, (P) Projection
97DPATRK.xls

A. C. D'Ambrosi
Certification Engineering - VEE
12/18/96

Engine Family: WT4.2AAA

Issue Date: JUN 14 1997

Revised:

20.09.17.02 - 5

1998 SUPPLEMENTAL DATA SHEET

EO #A-10-725

1998 TRUCK DPA CHART

VEHICLE LINE	ETW	< - - - CDT	NON - CODE	AC DPA	- - - > TRLHP (HP)	< - - - CDT	A CODE	C DPA	- - - > TRLHP (HP)	Ambient Dyno Coefficients A (LBS)	B (LBS/MPH)	C (LBS/(MPH)^2)	Track Force Coefficients F0 (LBS)	F2 (LBS/(MPH)^2)
		% = LVW/ALVW (BOTH)			$ = ALVW									
F-150 4x4 (LD)	4750	13.11	(A)	16.1	22.33	12.38	(A)	17.5	23.65	43.55	-0.8045	0.05101	55.91	0.04648
(PN96)	5000	13.50	(A)	16.1	22.83	12.74	(A)	17.5	24.19	43.55	-0.8045	0.05101	55.91	0.04648
AUTO TRANS (4R70W)	5250	13.89	(A)	16.1	23.30	13.10	(A)	17.5	24.70	42.69	-0.8783	0.05029	57.61	0.04712
P255/70R16 TIRE A/T $	5500	14.27	(A)	16.1	23.76	13.46	(A)	17.5	25.19	47.20	-0.7962	0.05151	61.27	0.04704
P265/70R17 TIRE A/T														
F-150 4x4 (LD)	5000	13.63	(R)	16.0	22.61	12.84	(R)	17.4	24.00	40.43	-1.0491	0.05003	61.99	0.04315
(PN96)	5250	14.04	(R)	16.0	23.05	13.26	(R)	17.4	24.41	47.56	-1.0689	0.05449	65.24	0.04362
AUTO TRANS (E4OD) $	5500	14.44	(R)	16.0	23.48	13.68	(R)	17.4	24.78	49.06	-0.9602	0.05295	68.62	0.04311
P235/70R16 TIRE														
- - - - - - - - - - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - - - -	- - - - - -	- - - - - - - -	- - - - - - - - - -	- - - - - - - - - -	- - - - - - - - - -
F-150 4x4 (LD)	5000	13.10	(R)	15.5	23.53	12.48	(R)	16.9	24.70	44.97	-1.0579	0.05535	65.09	0.04439
(PN96)	5250	13.76	(R)	15.5	23.52	12.98	(R)	16.9	24.93	43.97	-0.9633	0.05471	66.34	0.04517
AUTO TRANS (E4OD) $	5500	14.42	(R)	15.5	23.51	13.48	(R)	16.9	25.15	39.91	-0.6802	0.04956	69.30	0.04269
P255/70R16 TIRE A/S														
- - - - - - - - - - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - - - -	- - - - - -	- - - - - - - -	- - - - - - - - - -	- - - - - - - - - -	- - - - - - - - - -
F-150 4x4 (LD)	5000	13.06	(R)	16.2	23.62	12.31	(R)	17.6	25.04	47.86	-1.1564	0.05716	64.74	0.04552
(PN96)	5250	13.59	(R)	16.2	23.81	12.84	(R)	17.6	25.20	50.72	-1.1228	0.05519	68.79	0.04367
AUTO TRANS (E4OD) $	5500	14.12	(R)	16.2	24.01	13.36	(R)	17.6	25.38	52.88	-1.0673	0.05462	70.67	0.04427
P255/70R16 TIRE A/T														
- - - - - - - - - - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - - - -	- - - - - -	- - - - - - - -	- - - - - - - - - -	- - - - - - - - - -	- - - - - - - - - -
F-150 4x4 (LD)	5000	13.02	(R)	15.2	23.67	12.08	(R)	16.6	25.51	34.79	-0.7736	0.05436	61.79	0.04642
(PN96)	5250	13.55	(R)	15.2	23.88	12.60	(R)	16.6	25.28	40.39	-0.9199	0.05379	65.51	0.04609
AUTO TRANS (E4OD) $	5500	14.08	(R)	15.2	24.08	13.52	(R)	16.6	25.08	43.00	-0.8488	0.05320	68.95	0.04479
P265/70R17 TIRE A/T														
- - - - - - - - - - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - -	- - - - - - - -	- - - - - -	- - - - - - - -	- - - - - - - - - -	- - - - - - - - - -	- - - - - - - - - -
F-150 4x4 (LD)	4750	12.62	(R)	16.6	23.20	11.94	(R)	18.0	24.52					
(PN96) - CANADA ONLY	5000	13.05	(R)	16.6	23.62	12.40	(R)	18.0	24.86					
AUTO TRANS (E4OD) %	5250	13.53	(R)	16.6	23.92	12.86	(R)	18.0	25.16					
LT245/75R16 A/S & A/T TIRE $	5500	13.98	(R)	16.6	24.25	13.32	(R)	18.0	25.45					

(C) Certification point, (R) Regressed point,
(A) Adjusted, (CB) Cookbook, (P) Projection
97DPATRK.xls

A. C. D'Ambrosi
Certification Engineering - VEE
12/18/96