File

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-20-159
Relating to Certification of New Motor Vehicles

ISUZU MOTORS LIMITED

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Isuzu Motors Limited exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: WSZXT03.52GK Displacement: 3.2 Liters (193 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters
Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
3751-5750	50,000	0.160	4.4	0.7	0.018	12.5
	100,000	0.200	5.5	0.9	0.023	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for NMOG reflect application of a 0.98 RAF for 1998 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
3751-5750	50,000	0.081	1.9	0.4	0.0002	9.7
	100,000	0.085	2.1	0.4	0.0002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 19th day of June 1997.

John Kowalski for

R. B. Summerfield, Chief
Mobile Source Operations Division

17.07.00-1

E.O. # A-20-159

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer : ISUZU MOTORS LIMITED Exh Eng Fam : WSZXT03.52GK Evap. Fam : WSZXT0095MEO
All Engine Codes in Engine Family : CA ___ 49S ___ 50S x AB965 ___ , ORVR : YES ___ NO x
Exh Std : CA Tier-1 ___ TLEV x LEV ___ ULEV ___ SULEV ___ ; US EPA Tier-1 x
Veh Class(es) : PC ___ LDT 1 ___ LDT2 x MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
Single Cert Std for Multi-Class Eng Fam : N/A (specify : N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s) : Dedicated X Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline x Diesel ___
CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) ___
Exh Emiss Test Fuel(s) : Indo ___ CBG x CNG ___ LPG ___ M85 ___ Other (specify) ___
Diesel : 13 CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
Evaporative Emission Test Procedure : California ___ Federal x
Service Accum : Std AMA X Mod AMA ___ Mfr ADP ___ Other (specify) ___
NMOG Test Procedure : N/A ___ Std x Equiv ___ R/L Test Proc : SHED ___ Pt Source x
Engine Configuration : V6 Displacement : 3.2 / ___ Liters 193 / ___ Cubic Inches
Valves per Cylinder : 4 Rated HP : 205 @ 5400 RPM
Engine : Front x Mid ___ Rear ___ Drive : FWD ___ RWD x 4WD-FT ___ 4WD-PT x
Exhaust ECS (e.g., MFI, EGR, TC, CAC) : SFI, EGR, 2TWC, 2HO2S (2)
(use abbreviations per SAE J1930 JUN 93)

Engine code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment	Trans. (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
352G-2	XM-R1A YM-R1A XM-R1B YM-R1B	M6	3875	15.5	PCM 8162429090	8170961782	TWC 8251670620
	XM-S1B YM-S1B XM-S1C YM-S1C		4250				
352G-3	XM-R1A YM-R1A XM-R1B YM-R1B	A4	4000	15.4	PCM 8162429291		
	XM-R1C YM-R1C XM-S1B YM-S1B XM-S1C YM-S1C		4250				

XM-R1A : RODEO 2WD, Long Wheelbase, P215 tire
XM-R1B : RODEO 2WD, Long Wheelbase, P235 tire
XM-R1C : RODEO 2WD, Long Wheelbase, P245 tire
XM-S1B : RODEO 4WD, Long Wheelbase, P235 tire
XM-S1C : RODEO 4WD, Long Wheelbase, P245 tire
YM-R1A : HONDA PASSPORT 2WD, Long Wheelbase, P215 tire
YM-R1B : HONDA PASSPORT 2WD, Long Wheelbase, P235 tire
YM-R1C : HONDA PASSPORT 2WD, Long Wheelbase, P245 tire
YM-S1B : HONDA PASSPORT 4WD, Long Wheelbase, P235 tire
YM-S1C : HONDA PASSPORT 4WD, Long Wheelbase, P245 tire

Date Issueed : 4-10-97 (98B-03) Revisions : 6-10-97 (98B-04)

E.O. # A-20-159

1998 MODEL - YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT - DUTY TRUCKS AND MEDIUM - DUTY VEHICLES

Manufacturer : ISUZU MOTORS LIMITED Exh Eng Fam : WSZXT03.52GK Evap. Fam : WSZXT0095PE0
All Engine Codes in Engine Family : CA ___ 49S ___ 50S x AB965 ___ , ORVR : YES ___ NO x
Exh Std : CA Tier-1 ___ TLEV x LEV ___ ULEV ___ SULEV ___ ; US EPA Tier-1 x
Veh Class(es) : PC ___ LDT 1 ___ LDT2 x MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
Single Cert Std for Multi-Class Eng Fam : N/A (specify : N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s) : Dedicated ___ Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline x Diesel ___
CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) ___
Exh Emiss Test Fuel(s) : Indo ___ CBG x CNG ___ LPG ___ M85 ___ Other (specify) ___
Diesel : 13 CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
Evaporative Emission Test Procedure : California ___ Federal x
Service Accum : Std AMA x Mod AMA ___ Mfr ADP ___ Other (specify) ___
NMOG Test Procedure : N/A ___ Std x Equiv ___ R/L Test Proc : SHED ___ Pt Source x
Engine Configuration : V6 Displacement : 3.2 / ___ Liters 193 / ___ Cubic Inches
Valves per Cylinder : 4 Rated HP : 205 @ 5400 RPM
Engine : Front x Mid ___ Rear ___ Drive : FWD ___ RWD x 4WD-FT ___ 4WD-PT x
Exhaust ECS (e.g., MFI, EGR, TC, CAC) : SFI, EGR, 2TWC, 2HO2S (2)
(use abbreviations per SAE J1930 JUN 93)

Engine code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment	Trans. (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
352G-2	WM-S3B WM-S3C	M5	4000	15.5	PCM 8162429090	8170961782	TWC 8261676620

WM-S3B : AMIGO 4WD, Short Wheelbase, P235 tire
WM-S3C : AMIGO 4WD, Short Wheelbase, P245 tire

This SDS sheet was effected on our running change No. RC98T05 which introduce new vehicle model AMIGO.

Date Issueed : 9-8-97(98B-08) Revised : 11-19-97(98B-09)