State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-169-A
Relating to Certification of New Motor Vehicles

MERCEDES-BENZ AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Mercedes-Benz AG exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: WMBXV06.0GNU Displacement: 6.0 Liters (365 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection
Secondary Air Injection
Dual Heated Oxygen Sensors (two)
Dual Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.12	1.0	0.1	3.4
100,000	0.12	1.0	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

SUPERSEDED

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and are conditionally certified to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles." The conditional certification of the listed vehicle models is at the request of the manufacturer using projection of 80,000-mile bench test data to demonstrate durability and determine deterioration factors. The final 100,000-mile data will be obtained and submitted by the manufacturer at a later date to validate the subject conditional certification. If, for any reason, the 100,000-mile data result in non-compliance of the listed vehicle models with the aforementioned evaporative and refueling standards, the certification condition shall not have been met and the listed vehicle models shall not be covered by this Executive Order. In such event, the manufacturer shall assume full liabilities including recall and possible penalties under the California Health and Safety Code for vehicles sold in connection with this Executive Order. Additionally, in such event all affected vehicles shall be withheld from further sales until full compliance with the applicable evaporative and refueling emission standards is demonstrated to the satisfaction of the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

SUPERSEDED

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3 day of October 1997.

R. B. Summerfield, Chief
Mobile Source Operations Division

SUPERSEDED

E. O. # A-3-169-A

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Mercedes-Benz Exh. Eng Family: WMBXV06.0GNU Evap. Family: WMBXR0155MYY
All Eng Codes in Eng Fam: CA ___ 49S ___ 50S X AB965 ___ ORVR Yes X No ___
Exh Std: CA Tier-1 X TLEV ___ LEV ___ ULEV ___ SULEV ___ US EPA Tier-1 X
Veh Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: ___ (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated ___ Flex-Fuel ___ Dual-Fuel ___ Bi-Fuel ___ Gasoline X Diesel ___
CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) ___
Exh. Emiss Test Fuel(s): Indo X CBG ___ CNG ___ LPG ___ M85 ___ Other (specify) ___
Diesel: 13 CCR 2282 ___ 40 CFR 86.113-90 ___ 40 CFR 86.113-94 ___
Evaporative Emission Test Procedure: California ___ Federal X
Service Accum: Std AMA ___ Mod AMA X Mfr ADP ___ Other (specify) ___
NMOG Test Procedure: N/A X Std ___ Equiv ___ R/L Test Proc. SHED X Pt Source ___

Engine Configuration: V-12 Displacement: 6.0 Liters 365 Cubic Inches
Valves per Cylinder: 4 Rated HP: 389 / 5200 RPM
Engine: Front X Mid ___ Rear ___ Drive: FWD ___ RWD X 4WD-FT ___ 4WD-PT ___
Exhaust ECS (eg., MFI, EGR, TC, CAC): SFI / AIR / 2 HO2S(2) / 2 TWC
(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type (A 4, M 5 etc)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
M 120-5	SL 600	L 5	4 750	6.6	A 021 545 25 32	---	A 129 490 47 14 or A 129 490 20 14 (left)
							A 129 490 48 14 or A 129 490 21 14 (right)

SUPERSEDED

Revisions: