File

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-332
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: WTYXT03.4BBH Displacement: 3.4 Liters (206.1 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection
Exhaust Gas Recirculation
Heated Oxygen Sensors (two)
Three Way Catalytic Converter

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight(lbs.)	Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
0-3750	50,000	0.25	3.4	0.4	10.0
	100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight(lbs.)	Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
0-3750	50,000	0.11	1.6	0.2	4.3
	100,000	0.11	1.9	0.2	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 10th day of June 1997.

R. B. Summerfield, Chief
Mobile Source Operations Division

E.O.# A-14-332

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXT03.4BBH Evap Fam: WTYXE0095AE0
All Eng Codes in Eng Fam: CA __ 49S __ 50S x AB965 __ , ORVR: YES __ NO x
Exh Std: CA Tier-1 x TLEV __ LEV __ ULEV __ SULEV __ , US EPA Tier-1 x
Veh Class(es): PC __ LDT1 x LDT2 __ MDV1 __ MDV2 __ MDV3 __ MDV4 __ MDV5 __
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated x Flex-Fuel __ Dual-Fuel __ Bi-Fuel __ Gasoline x Diesel __
CNG __ LNG __ LPG __ M85 __ Other (specify) __
Exh Emiss Test Fuel(s): Indo x CBG __ CNG __ LPG __ M85 __ Other (specify) __
Diesel: 13 CCR 2282 __ 40 CFR 86.113-90 __ 40 CFR 86.113-94 __
Evaporative Emission Test Procedure: California __ Federal x
Service Accum: Std AMA x Mod AMA __ Mfr ADP __ Other (specify) __
NMOG Test Procedure: N/A x Std __ Equiv __ R/L Test Proc: SHED x Pt Source __
Engine Configuration: V-6 Displacement: 3.4 Liters 206.1 Cubic Inches
Valves per Cylinder: 4 Rated HP1: 190@4800 RPM
Engine: Front x Mid __ Rear __ Drive: FWD __ RWD x 4WD-FT __ 4WD-PT __
Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,EGR,HO2S(2),TWC
(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49S/ 50ST	Vehicle Models (if coded see attachment)	Trans. (M5, A4, etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR system Part No.	Catalytic Converter Part No.
1	VZN150L-CRMDKAB	M5	3375	11.4	Before R/C 98-TR-2: 89661-04390	25620-62050	S98
2	VZN150L-CRMDKAB		3375	12.5	After R/C 98-TR-2: 89661-04391		
3	VZN150L-CRSDKAB	L4	3375	11.4	Before R/C 98-TR-2: 89661-04400	25620-62060	
4	VZN150L-CRSDKAB		3375	12.5	After R/C 98-TR-2: 89661-04401		

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

VEHICLE MODELS:

TOYOTA TACOMA 2WD

VZN150L-CRMDKAB
VZN150L-CRSDKAB

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXT03.4BBH Evap Fam: WTYXE0115AE0
All Eng Codes in Eng Fam: CA __ 49S __ 50S x AB965 __ , ORVR: YES __ NO x
Exh Std: CA Tier-1 x TLEV __ LEV __ ULEV __ SULEV __ , US EPA Tier-1 x
Veh Class(es): PC __ LDT1 x LDT2 __ MDV1 __ MDV2 __ MDV3 __ MDV4 __ MDV5 __
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated x Flex-Fuel __ Dual-Fuel __ Bi-Fuel __ Gasoline x Diesel __
CNG __ LNG __ LPG __ M85 __ Other (specify) _____
Exh Emiss Test Fuel(s): Indo x CBG __ CNG __ LPG __ M85 __ Other (specify) _____
Diesel: 13 CCR 2282 __ 40 CFR 86.113-90 __ 40 CFR 86.113-94 __
Evaporative Emission Test Procedure: California __ Federal x
Service Accum: Std AMA x Mod AMA __ Mfr ADP __ Other (specify) _____
NMOG Test Procedure: N/A x Std __ Equiv __ R/L Test Proc: SHED x Pt Source __
Engine Configuration: V-6 Displacement: 3.4 Liters 206.1 Cubic Inches
Valves per Cylinder: 4 Rated HP1: 190@4800 RPM
Engine: Front x Mid __ Rear __ Drive: FWD __ RWD x 4WD-FT __ 4WD-PT __
Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,EGR,HO2S(2),TWC
(use abbreviations per SAE J1930 JUN93)

(also list CA/49S/ 50ST	Vehicle Models (if coded see attachment)	(M5, A4, etc.)	or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR system Part No.	Catalytic Converter Part No.
1	VCK11L-TRMDKA	M5	3750	12.3/13.6	Before R/C 98-TR-2: 89661-34330	25620-62050	S97
2	VCK11L-TRMDKA		3750	13.6/15.0	After R/C 98-TR-2: 89661-34331		
3	VCK11L-TRSDKA	L4	3750	12.3/13.6	Before R/C 98-TR-2: 89661-0W050	25620-62060	
4	VCK11L-TRSDKA		3750	13.6/15.0	After R/C 98-TR-2: 89661-0W051		

Comments : Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment.

VEHICLE MODELS:

TOYOTA T100 2WD

VCK11L-TRMDKA
VCK11L-TRSDKA