State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-319
Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: WTYXV02.2GXB Displacement: 2.2 Liters (132 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection
Exhaust Gas Recirculation
Air Fuel Ratio Sensor
Warm Up Three Way Catalytic Converter
Three Way Catalytic Converter
Heated Oxygen Sensor

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon Monoxide	Nitrogen Oxides	Formaldehyde	Carbon Monoxide (20°F)
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 1998 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon Monoxide	Nitrogen Oxides	Formaldehyde	Carbon Monoxide (20°F)
50,000	0.046	0.6	0.1	0.001	3.3
100,000	0.048	0.6	0.2	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 23rd day of July 1997.

R. B. Summerfield, Chief
Mobile Source Operations Division

E.O.# A-14-319

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXV02.2GXB Evap Fam: WTYXR0135AK1
All Eng Codes in Eng Fam: CA x 49S __ 50S __ AB965 __ , ORVR: YES x NO __
Exh Std: CA Tier-1 __ TLEV __ LEV x ULEV __ SULEV __ , US EPA Tier-1 __
Veh Class(es): PC x LDT1 __ LDT2 __ MDV1 __ MDV2 __ MDV3 __ MDV4 __ MDV5 __
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated x Flex-Fuel __ Dual-Fuel __ Bi-Fuel __ Gasoline x Diesel __
CNG __ LNG __ LPG __ M85 __ Other (specify) _____
Exh Emiss Test Fuel(s): Indo __ CBG x CNG __ LPG __ M85 __ Other (specify) _____
Diesel: 13 CCR 2282 __ 40 CFR 86.113-90 __ 40 CFR 86.113-94 __
Evaporative Emission Test Procedure: California Federal
Service Accum: Std AMA __ Mod AMA __ Mfr ADP x Other (specify) _____
NMOG Test Procedure: N/A __ Std x Equiv __ R/L Test Proc: SHED x Pt Source __
Engine Configuration: I-4 Displacement: 2.2 Liters 132.0 Cubic Inches
Valves per Cylinder: 4 Rated HP1: 130@5200 RPM
Engine: Front x Mid __ Rear __ Drive: FWD x RWD __ 4WD-FT __ 4WD-PT __
Exhaust ECS (e.g., MFI, EGR, TC, CAC): SFI,EGR,A/F S(*1),WU-TWC,TWC,HO2S
(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49S/ 50ST	Vehicle Models (if coded see attachment)	Trans. (M5, A4, etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR system Part No.	Catalytic Converter Part No.
1	SXV20L-CEMDKA	M5	3375	6.7	89661-06500	25620-74320	U03*2 U97*3
2	SXV20L-CEMDKA		3375	7.4	89661-06550		
3	SXV20L-CEPDKA	L4	3375	6.7	89661-3T270	25620-74330	
4	SXV20L-AEPGKA		3500	7.4	89661-3T290		
	SXV20L-AEPNKA				89661-06510		
	SXV20L-CEPDKA		3375		89661-06560		
	SXV20L-CEPGKA		3500				
	SXV20L-CEPNKA						

Comment : Please refer to manufacturer's HP list for correct dyno HP setting based on model and equipment.

Note*1 : A/F S means Air-Fuel ratio sensor.
*2 : Maker ; TOYOTA MOTOR CORPORATION
*3 : Maker ; TABC, Inc.

E.O.# A-14-319

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: TOYOTA Exh Eng Fam: WTYXV02.2GXB Evap. Fam: WTYXR0135AK1

VEHICLE MODELS:

CAMRY
SXV20L-AEPGKA
SXV20L-AEPNKA
SXV20L-CEMDKA
SXV20L-CEPDKA
SXV20L-CEPGKA
SXV20L-CEPNKA