Dale'

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-410
Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Chrysler Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: XCRXV02.0VB2 Displacement: 2.0 Liters (122 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter
Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection
Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Hydrocarbons	Carbon Monoxide	Nitrogen Oxides	Carbon Monoxide (20°F)
50,000	0.14	2.1	0.2	3.0
100,000	0.16	2.6	0.3	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2nd day of June 1998.

R. B. Summerfield, Chief
Mobile Source Operations Division

1999 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

E.O. # A-9-410
Page 1 of 1

Manufacturer: Chrysler Corporation Exh Eng Fam: XCRXV02.0VB2 Evap Fam: XCRXE010IG1A
All Eng Codes in Eng Fam: CA X 49S X 50S ____ AB965 ____ ORVR: YES ____ NO X
Exh Std: CA Tier-1 X TLEV ____ LEV ____ ULEV ____ SULEV ____; US EPA Tier-1 ____
Veh Class(es): PC X LDT1 ____ LDT2 ____ MDV1 ____ MDV2 ____ MDV3 ____ MDV4 ____ MDV5 ____
Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel ____ Dual-Fuel ____ Bi-Level ____ Gasoline X Diesel ____
CNG ____ LNG ____ LPG ____ M85 ____ Other (specify) ____
Emis Test Fuel(s): Indo ____ CBG X CNG ____ LPG ____ M85 ____ Other(specify) ____
Diesel: 13 CCR 2282 ____ or 40 CFR 86.113-90 ____ or 40 CFR 86.113-94 ____
Evaporative Emission Test Procedure: California ____ Federal X
Service Accum: Std AMA ____ Mod AMA X Mfr ADP ____ Other (Specify) ____
NMOG Test Procedure: N/A X Std ____ Equiv ____ R/L Test Proce: SHED ____ Pt Source X
Engine Configuration: I-4 Displacement: / 2.0 Liters / 122 Cubic Inches
Valves per Cylinder: 4 Rated HP: 150 @ 6500 RPM
Engine: Front X Mid ____ Rear ____ Drive: FWD X RWD ____ 4WD-FT ____ 4WD-PT ____
Exhaust ECS (eg., EGR, MFI, TC, CAC): EGR, HO2S(2), SFI, TWC, OBDII
(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
CA-100 (CA)	PLDH22 PLDH42 PLPH22 PLPH42	A3	2875	SEE ATTACHMENT	05269826AD	04287602	05278476
CM-100	PLDH22 PLDH42 PLPH22 PLPH42	M5	2875		05269823AE		
	PLDL22 PLPL22		2750				
CM-200	PLDH22 PLDH42 PLPH22 PLPH42		2875		05269825AD		
	PLDL22 PLPL22		2750				

Date Issued: 03/17/98

Revisions: ____

VL01-SDS/99

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER

Engine Family: XCRXV02.0VB2
Evaporative Fam: XCRXE0101G1A

Certificate #:

Model ID	Car Line	California Sales
PLDH22	Neon	YES
PLDH42	Neon	YES
PLDL22	Neon	YES
PLPH22	Neon	YES
PLPH42	Neon	YES
PLPL22	Neon	YES

```
Model Codes
JA C H  41
|  | |  |
|  | |  --- Body Style
|  | |       22=2 door coupe
|  | |       27=2 door convertible
|  | |       41=4 door sedan
|  | |       42=4 door subcompact sedan
|  | |
|  | ------ Trim Level
|  |         H=High Line     S=Sport
|  |         P=Premium       L=Low Line
|  |
|  -------- Division
|            L,C=Chrysler    D=Dodge
|            X=Eagle         P=Plymouth
|
---------- Car Line
            JA=Cirrus, Stratus, Breeze    PL=Neon
            JX=Sebring Convertible
            LH=Concorde, New Yorker, LHS, Vision, Intrepid
            SR=Viper    , PR=Prowler
```

1999
XCRXV02.0VB2

Chrysler Corporation
Family Tire Usage

ATTACHMENT TO SDS PAGE 1
OF EXECUTIVE ORDER A-9-410

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW ETW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	LOADED VEHICLE WEIGHT COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	COLD CO ELECTRIC DYNO COEFFICIENTS TARGET A (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 DEG WHEN NEEDED)	B	C	SET A	B	C	ADJUSTED LOADED VEHICLE WGT ALVW ETW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
PLDH22	ECC	DD4	FA Y	0	C	2875	STD	99	TJJ	TZA		14.92	6.0	32	32	42.70		0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH22	ECC	DD4	FA Y	0	F	2875	STD	99	TJJ	TZA		14.92	6.0	32	32	42.70		0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH22	ECC	DD4	FW Y	0	C	2875	STD	99	TJY	TZA		15.78	6.1	32	32	39.66		0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH22	ECC	DD4	FW Y	0	F	2875	STD	99	TJY	TZA		15.78	6.1	32	32	39.66		0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH22	ECC	DGC	FW Y	0	C	2875	STD	99	TJY	TZA		14.65	6.1	32	32	41.42		0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93		0.02160								
PLDH22	ECC	DGC	FW Y	0	F	2875	STD	99	TJY	TZA		14.65	6.1	32	32	41.42		0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93		0.02160								
PLDH42	ECC	DD4	FA Y	0	C	2875	STD	99	TJJ	TZA		14.92	6.0	32	32	42.70		0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH42	ECC	DD4	FA Y	0	F	2875	STD	99	TJJ	TZA		14.92	6.0	32	32	42.70		0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH42	ECC	DD4	FW Y	0	C	2875	STD	99	TJY	TZA		15.78	6.1	32	32	39.66		0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH42	ECC	DD4	FW Y	0	F	2875	STD	99	TJY	TZA		15.78	6.1	32	32	39.66		0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLDH42	ECC	DGC	FW Y	0	C	2875	STD	99	TJY	TZA		14.65	6.1	32	32	41.42		0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93		0.02160								
PLDH42	ECC	DGC	FW Y	0	F	2875	STD	99	TJY	TZA		14.65	6.1	32	32	41.42		0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93		0.02160								
PLDL22	ECC	DD4	FA Y	0	C	2750	STD	99	TJJ	TZA		14.41	6.0	32	32	41.77		0.02125								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69		0.01889								
PLDL22	ECC	DD4	FA Y	0	F	2750	STD	99	TJJ	TZA		14.41	6.0	32	32	41.77		0.02125								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69		0.01889								
PLDL22	ECC	DD4	FW Y	0	C	2750	STD	99	TEX	TZA		16.98	6.1	32	32	32.61		0.01865								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69		0.01889								
PLDL22	ECC	DD4	FW Y	0	F	2750	STD	99	TEX	TZA		16.98	6.1	32	32	32.61		0.01865								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69		0.01889								
PLPH22	ECC	DD4	FA Y	0	C	2875	STD	99	TJJ	TZA		14.92	6.0	32	32	42.70		0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLPH22	ECC	DD4	FA Y	0	F	2875	STD	99	TJJ	TZA		14.92	6.0	32	32	42.70		0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLPH22	ECC	DD4	FW Y	0	C	2875	STD	99	TJY	TZA		15.78	6.1	32	32	39.66		0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLPH22	ECC	DD4	FW Y	0	F	2875	STD	99	TJY	TZA		15.78	6.1	32	32	39.66		0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60		0.01889								
PLPH22	ECC	DGC	FW Y	0	C	2875	STD	99	TJY	TZA		14.65	6.1	32	32	41.42		0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93		0.02160								
PLPH22	ECC	DGC	FW Y	0	F	2875	STD	99	TJY	TZA		14.65	6.1	32	32	41.42		0.02224								

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - VL01 - 400 /

Report Date: 03/18/98
Time: 09:29:34

1999
XCRXV02.0VB2

Chrysler Corporation
Family Tire Usage

ATTACHMENT TO SDS PAGE 1
OF EXECUTIVE ORDER A-9-410

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW ETW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	LOADED VEHICLE WEIGHT: TARGET (LINE 1 IS 20 DEG)	COLD CO ELECTRIC DYNO COEFFICIENTS: A	B	C	SET A (LINE 2 IS 50 DEG WHEN NEEDED)	B	C	ADJUSTED LOADED VEHICLE WGT: ALVW ETW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93			0.02160								
PLPH42	ECC	DD4	FA	Y	0	C	2875	STD	99	TJJ	TZA	14.92	6.0	32	32	42.70			0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60			0.01889								
PLPH42	ECC	DD4	FA	Y	0	F	2875	STD	99	TJJ	TZA	14.92	6.0	32	32	42.70			0.02125								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60			0.01889								
PLPH42	ECC	DD4	FW	Y	0	C	2875	STD	99	TJY	TZA	15.78	6.1	32	32	39.66			0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60			0.01889								
PLPH42	ECC	DD4	FW	Y	0	F	2875	STD	99	TJY	TZA	15.78	6.1	32	32	39.66			0.02020								
							OPT	99	TEW	TZA		16.04	6.1	32	32	41.60			0.01889								
PLPH42	ECC	DGC	FW	Y	0	C	2875	STD	99	TJY	TZA	14.65	6.1	32	32	41.42			0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93			0.02160								
PLPH42	ECC	DGC	FW	Y	0	F	2875	STD	99	TJY	TZA	14.65	6.1	32	32	41.42			0.02224								
							OPT	99	TEW	TZA		14.64	6.0	32	32	42.93			0.02160								
PLPL22	ECC	DD4	FA	Y	0	C	2750	STD	99	TJJ	TZA	14.41	6.0	32	32	41.77			0.02125								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69			0.01889								
PLPL22	ECC	DD4	FA	Y	0	F	2750	STD	99	TJJ	TZA	14.41	6.0	32	32	41.77			0.02125								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69			0.01889								
PLPL22	ECC	DD4	FW	Y	0	C	2750	STD	99	TEX	TZA	16.98	6.1	32	32	32.61			0.01865								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69			0.01889								
PLPL22	ECC	DD4	FW	Y	0	F	2750	STD	99	TEX	TZA	16.98	6.1	32	32	32.61			0.01865								
							OPT	99	TEW	TZA		15.50	6.1	32	32	40.69			0.01889								

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

Report Date: 03/18/98