

File

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-236
Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: XTKXV02.5VB2 Displacement: 2.5 Liters (152 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

- Three Way Catalytic Converter
- Dual Heated Oxygen Sensors
- Heated Oxygen Sensors (two)
- Exhaust Gas Recirculation
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Oxides of Nitrogen</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Oxides of Nitrogen</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.17	1.4	0.1	7.2
100,000	0.19	1.6	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).


BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 20th day of July 1998.

A handwritten signature in cursive script, appearing to read "John Kouslelis for".

R. B. Summerfield, Chief
Mobile Source Operations Division

1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

A-16-236
E.O.# _____ Page _____

Manufacturer Mazda Motor Corporation Exh Eng Fam: XTKV02.5VB2 Evap Fam: XTKXR0125BFA
 All Engine Codes in Engine Family: CA _____ 49S _____ 50S X AB965 _____, ORVR: YES X NO _____
 Exh Std: CA Tier-1 X TLEV _____ LEV _____ ULEV _____ SULEV _____, US EPA Tier-1 _____
 Veh Class (es): PC X LDT1 _____ LDT2 _____ MDV1 _____ MDV2 _____ MDV3 _____ MDV4 _____ MDV5 _____
 Single Cert Std for Multi-Class Eng Fam: N/A (specify : N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type (s): Dedicated X Flex-Fuel _____ Dual-Fuel _____ Bi-Fuel _____ Gasoline X Diesel _____
 CNG _____ LNG _____ LPG _____ M85 _____ Other (specify) _____
 Exh Emiss Test Fuel (s): Indo X CBG _____ CNG _____ LPG _____ M85 _____ Other (specify) _____
 Diesel: 13 CCR 2282 _____ 40CFR 86.113-90 _____ 40 CFR 86.113-94 _____
 Evaporative Emission Test Procedure: California _____ Federal X
 Service Accum: Std. AMA X Mod AMA _____ Mfr ADP _____ Other (specify) _____
 NMOG Test Procedure: N/A X Std _____ Equip _____ R/L Test Proc: SHED _____ PT Source X
 Engine Configuration: V-6 Displacement: 2.5 / _____ Liters 152.4 / _____ Cubic Inches
 Valves per Cylinder: 4 Rated HP: _____ 170 @ _____ 6000 RPM
 Engine: Front X Mid. _____ Rear _____ Drive: FWD X RWD _____ 4WD-FT _____ 4WD-PT _____
 Exhaust ECS (e.g., MFI, EGR, TC, CAC): HO2S(2) / ZHO2S/TWC/EGR/SFI

(Use abbreviations per SAE J1930 MAY91)

Engine Code (also list CA/ 49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Part No.
BKLD2AA8	626	M5	3250	##	Distributor: N.A. ECU: KLM8, KLG6	EGR Control Valve: KLG4	KLG4
BKLD2AAW				##			
BKLDTAA8		A4	3375	##	Distributor: N.A. ECU: KLM9, KLG7		
BKLDTAAW				##			
HC (g/mi)		0.41 / ... / ...					
NMOG (g/mi)		... / ... / ...					
Non-methane HC (g/mi)		0.25 / 0.31 / ...					
CO (g/mi)		3.4 / 4.2 / ...					
NOx (g/mi)		0.4 / 0.6 / ...					
HWFET NOx (g/mi)		0.5 / 0.8 / ...					
Evap. (EPA : g/test)		... / 2.0 / ...					
Evap. (ARB : g/test)		... / 2.0 / ...					
Evap. (Abbrev : g/test)		... / 2.5 / ...					
Running Loss (g/test)		... / 0.05 / ...					
Spit Back (g/test)		... / ... / ...					
ORVR (g/gallon)		... / 0.2 / ...					
Cold CO (g/mi)		10.0 / ... / ...					
Idle CO for LDT (%)		... / ... / ...					
HCHO (mg/mi)		... / ... / ...					
CST -HC		at idle: 100. at 2500rpm: 100					
CST -CO		at idle: 0.5. at 2500rpm: 0.5					
NMOG (g/mi) for 50°F		... / ... / ...					
HCHO (mg/mi) for 50°F		... / ... / ...					

Revisions:

Issue Date	May 15, 1998			
Rev. No.				
Date				