State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-464
Relating to Certification of New Motor Vehicles

DAIMLERCHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year DaimlerChrysler Corporation exhaust emission control systems are certified as described below for medium-duty vehicles:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YGRXA0360H31 Displacement: 5.2 Liters (318 Cubic Inches)
5.9 Liters (360 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter
Dual Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection
Dual Warm Up Oxidation Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
3751-5750	50,000	0.160	4.4	0.4	0.018	12.5
	120,000	0.230	6.4	0.6	0.027	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for NMOG reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
3751-5750	50,000	0.070	1.4	0.2	0.002	6.4
	120,000	0.073	1.9	0.2	0.003	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the medium-duty vehicle phase-in requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" (Title 13, California Code of Regulations, Section 1960.1(h)(2)).

BE IT FURTHER RESOLVED: That under the submitted medium-duty vehicle phase-in compliance plan, if the manufacturer incurs "Vehicle Equivalent Debits" for the aforementioned model year due to the manufacturer's failure to produce and deliver for sale in California the equivalent quantity of medium-duty vehicles certified to low-emission vehicle and/or ultra-low-emission vehicle exhaust emission standards required by the above-referenced standards and test procedures, all "Vehicle Equivalent Debits" incurred by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 1st day of July 1999.

R. B. Summerfield, Chief
Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: DaimlerChrysler Corp. Exh Eng Fam: YCRXA0360H31 Evap. Fam: YCRXE0174G3H & YCRXE0174G4H
All Eng Codes in Eng Fam: CA X 49S ___ 50S ___ AB965 ___ ORVR: YES ___ NO X
Exh Std: CA Tier-1 __TLEV __ LEV X ULEV __ SULEV __ US: EPA Tier-1 __ NLEV __
Veh Class(es): PC __ LDT1 __ LDT2 __ MDV1 __ MDV2 X MDV3 __ MDV4 __ MDV5 __
Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel __ Dual-Fuel __ Bi-Level __ Gasoline X Diesel __
CNG __ LNG __ LPG __ M85 __ E85 __ Other(specify) ___
Emis Test Fuel(s): Indo __ CBG X CNG __ LPG __ M85 __ E85 __ Other(specify) ___
Diesel: 13 CCR 2282 __ 40 CFR 86.113-90 __ 40 CFR 86.113-94 __
Evaporative Emission Test Procedure: California ___ Federal X
Service Accum: Std AMA ___ Mod AMA ___ Mfr ADP X Other(specify) ___
NMOG Test Procedure: N/A ___ Std __ Equiv X R/L Test Proc: SHED __ Pt Source __
Engine Configuration: V-8 Displacement 5.2/5.9L Liters 318 / 360 Cubic Inches
Valves per Cylinder: 2 Rated Horsepower: 230 @ 4400 245 @ 4000 RPM
Engine: Front X Rear ___ Drive: FWD ___ RWD X 4WD-FT X 4WD-PT ___
Exhaust ECS (eg. EGR, MFI, TC, CAC): 2WUOC, 2HO2S(2), TWC, SFI,
(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.*	DPA Or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
CA-100	BE1L31 BE1L32 BE1L33 BR1L61 BR1L62	A4	5500	SEE ATTACHMENT	56040369AB	--	52103344AA
CA-200	BR6L61 BR6L62		5500 5750				
CA-300	BE1L31 BE1L32 BE1L33 BR1L61 BR1L62		5500 5750 5500		56040411AB		
CA-400	BR6L61 BR6L62		5500				

* Denotes ALVW test weights

Date Issued: 06/14/99
Revisions: ___

2000
YCRXA0360H31

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW ETW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	LOADED VEHICLE WEIGHT COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	COLD CO ELECTRIC DYNO COEFFICIENTS TARGET A (LINE 1 IS 20 DEG COEFFS,LINE 2 IS 50 DEG WHEN NEEDED)	B	C	SET A	B	C	ADJUSTED LOADED VEHICLE WGT ALVW ETW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
BE1L31	ELF	DGT	RW Y	6400	C	5250	STD	00	TR8	TZA		14.75	14.1	35	35	61.92		0.04324				5500	14.98	14.5	35	35
																56.29		0.03931								
							OPT	00	TYU	TZA		14.87	13.9	35	35	55.79		0.04522					15.25	14.0	35	35
																50.72		0.04111								
							OPT	00	TYU	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
							OPT	00	TYV	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
BE1L31	EML	DGT	RW Y	6400	C	5250	STD	00	TR8	TZA		14.75	14.1	35	35	61.92		0.04324				5500	14.98	14.5	35	35
																56.29		0.03931								
							OPT	00	TYU	TZA		14.87	13.9	35	35	55.79		0.04522					15.25	14.0	35	35
																50.72		0.04111								
							OPT	00	TYU	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
							OPT	00	TYV	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
BE1L32	ELF	DGT	RW Y	6400	C	5500	STD	00	TR8	TZA		15.27	14.3	35	35	64.03		0.04324				5500	14.98	14.5	35	35
																58.21		0.03931								
							OPT	00	TYU	TZA		15.41	14.1	35	35	57.66		0.04522					15.25	14.0	35	35
																52.42		0.04111								
							OPT	00	TYU	TZH		16.06	13.8	35	35	56.65		0.04281					15.67	13.9	35	35
																51.50		0.03892								
							OPT	00	TYV	TZH		16.06	13.8	35	35	56.65		0.04281					15.67	13.9	35	35
																51.50		0.03892								
BE1L32	EML	DGT	RW Y	6400	C	5500	STD	00	TR8	TZA		15.27	14.3	35	35	64.03		0.04324				6000	16.32	14.5	35	35
																58.21		0.03931								
							OPT	00	TYU	TZA		15.41	14.1	35	35	57.66		0.04522					16.62	14.1	35	35
																52.42		0.04111								
							OPT	00	TYU	TZH		16.06	13.8	35	35	56.65		0.04281					17.08	13.9	35	35
																51.50		0.03892								
							OPT	00	TYV	TZH		16.06	13.8	35	35	56.65		0.04281					17.08	13.9	35	35
																51.50		0.03892								
BE1L33	ELF	DGT	RW Y	6400	C	5250	STD	00	TR8	TZA		14.75	14.1	35	35	61.92		0.04324				5500	14.98	14.5	35	35
																56.29		0.03931								
							OPT	00	TYU	TZA		14.87	13.9	35	35	55.79		0.04522					15.25	14.0	35	35
																50.72		0.04111								
							OPT	00	TYU	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
							OPT	00	TYV	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
BE1L33	EML	DGT	RW Y	6400	C	5250	STD	00	TR8	TZA		14.75	14.1	35	35	61.92		0.04324				5500	14.98	14.5	35	35
																56.29		0.03931								
							OPT	00	TYU	TZA		14.87	13.9	35	35	55.79		0.04522					15.25	14.0	35	35
																50.72		0.04111								

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TJ08 - 400 /

Report Date: 06/05/99
Time: 06:45:04

2000
YCRXA0360H31

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	HKT TYPE	LVW ETW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	LOADED VEHICLE WEIGHT: COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	COLD CO ELECTRIC DYNO COEFFICIENTS (LINE 1 IS 20 DEG COEFFS, LINE 2 IS 50 DEG WHEN NEEDED): TARGET A	B	C	SET A	B	C	ADJUSTED LOADED VEHICLE WGT: ALVW ETW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
							OPT	00	TYU	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
							OPT	00	TYV	TZH		15.50	13.6	35	35	54.81		0.04281					15.67	13.9	35	35
																49.83		0.03892								
BR1L61	ELF	DGT	RW Y	6400	C	4750	STD	00	TR8	TZA		13.71	14.4	35	35	57.15		0.04324				5500	14.98	14.5	35	35
																51.95		0.03931								
							OPT	00	TYU	TZA		13.78	14.3	35	35	51.56		0.04522					15.25	14.0	35	35
																46.87		0.04111								
							OPT	00	TYU	TZH		14.38	13.9	35	35	50.66		0.04281					15.67	13.9	35	35
																46.05		0.03892								
							OPT	00	TYV	TZH		14.38	13.9	35	35	50.66		0.04281					15.67	13.9	35	35
																46.05		0.03892								
BR1L61	EML	DGT	RW Y	6400	C	4750	STD	00	TR8	TZA		13.71	14.4	35	35	57.15		0.04324				5500	14.98	14.5	35	35
																51.95		0.03931								
							OPT	00	TXP	TZA		12.74	14.5	35	35	57.07		0.04906					14.23	12.6	35	35
																51.88		0.04460								
							OPT	00	TYU	TZA		13.78	14.3	35	35	51.56		0.04522					15.25	14.0	35	35
																46.87		0.04111								
							OPT	00	TYU	TZH		14.38	13.9	35	35	50.66		0.04281					15.67	13.9	35	35
																46.05		0.03892								
							OPT	00	TYV	TZH		14.38	13.9	35	35	50.66		0.04281					15.67	13.9	35	35
																46.05		0.03892								
BR1L62	ELF	DGT	RW Y	6400	C	5000	STD	00	TR8	TZA		14.34	14.5	35	35	58.28		0.04324				5500	14.98	14.5	35	35
																52.98		0.03931								
							OPT	00	TYU	TZA		14.42	14.4	35	35	52.56		0.04522					15.25	14.0	35	35
																47.78		0.04111								
							OPT	00	TYU	TZH		15.04	14.0	35	35	51.63		0.04281					15.67	13.9	35	35
																46.94		0.03892								
							OPT	00	TYV	TZH		15.04	14.0	35	35	51.63		0.04281					15.67	13.9	35	35
																46.94		0.03892								
BR1L62	EML	DGT	RW Y	6400	C	5000	STD	00	TR8	TZA		14.34	14.5	35	35	58.28		0.04324				5500	14.98	14.5	35	35
																52.98		0.03931								
							OPT	00	TYU	TZA		14.42	14.4	35	35	52.56		0.04522					15.25	14.0	35	35
																47.78		0.04111								
							OPT	00	TYU	TZH		15.04	14.0	35	35	51.63		0.04281					15.67	13.9	35	35
																46.94		0.03892								
							OPT	00	TYV	TZH		15.04	14.0	35	35	51.63		0.04281					15.67	13.9	35	35
																46.94		0.03892								
BR6L61	ELF	DGT	4W Y	6400	C	5250	STD	00	TR8	TZA		13.12	16.9	35	35	63.80		0.05154				5500	13.16	15.8	35	35
																58.00		0.04685								
							OPT	00	TXW	TZA		13.28	16.2	35	35	67.65		0.04902					13.28	15.0	35	35
																61.50		0.04456								
							OPT	00	TYL	TZA		12.39	17.4	35	35	75.08		0.05183					13.03	15.5	35	35
																68.25		0.04712								

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TJ08 - 401 /

Report Date: 06/05/99
Time: 06:45:04

2000
YCRXA0360H31

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	HKT TYPE	LVW ETW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	LOADED VEHICLE WEIGHT COAST DOWN TIME	*DYNO HP	TIRE PRES F	R	COLD CO ELECTRIC DYNO COEFFICIENTS TARGET A (LINE 1 IS 20 DEG COEFFS,LINE 2 IS 50 DEG WHEN NEEDED)	B	C	SET A	B	C	ADJUSTED LOADED VEHICLE WGT ALVW ETW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	R
							OPT	00	TYU	TZA		13.43	16.3	35	35	57.83		0.05212					13.51	15.1	35	35
																52.57		0.04738								
							OPT	00	TYU	TZH		13.75	16.0	35	35	61.37		0.04879					13.79	14.9	35	35
																55.79		0.04435								
							OPT	00	TYV	TZH		13.75	16.0	35	35	61.37		0.04879					13.79	14.9	35	35
																55.79		0.04435								
							OPT	00	TYX	TZA		12.72	15.8	35	35	68.87		0.05209					12.73	14.2	35	35
																62.61		0.04735								
							OPT	00	TYZ	TZA		12.72	15.8	35	35	68.87		0.05209					12.73	14.2	35	35
																62.61		0.04735								
BR6L61	EML	DGT	4W	Y 6400	C	5250	STD	00	TRB	TZA		13.12	16.9	35	35	63.80		0.05154				5500	13.16	15.8	35	35
																58.00		0.04685								
							OPT	00	TXW	TZA		13.28	16.2	35	35	67.65		0.04902					13.28	15.0	35	35
																61.50		0.04456								
							OPT	00	TYL	TZA		12.39	17.4	35	35	75.08		0.05183					13.03	15.5	35	35
																68.25		0.04712								
							OPT	00	TYU	TZA		13.43	16.3	35	35	57.83		0.05212					13.51	15.1	35	35
																52.57		0.04738								
							OPT	00	TYU	TZH		13.75	16.0	35	35	61.37		0.04879					13.79	14.9	35	35
																55.79		0.04435								
							OPT	00	TYV	TZH		13.75	16.0	35	35	61.37		0.04879					13.79	14.9	35	35
																55.79		0.04435								
							OPT	00	TYX	TZA		12.72	15.8	35	35	68.87		0.05209					12.73	14.2	35	35
																62.61		0.04735								
							OPT	00	TYZ	TZA		12.72	15.8	35	35	68.87		0.05209					12.73	14.2	35	35
																62.61		0.04735								
BR6L62	ELF	DGT	4W	Y 6400	C	5500	STD	00	TRB	TZA		13.64	17.0	35	35	65.40		0.05154				6000	14.30	16.2	35	35
																59.45		0.04685								
							OPT	00	TXN	TZA		12.88	17.4	35	35	75.74		0.05226					13.46	16.5	35	35
																68.85		0.04751								
							OPT	00	TXW	TZA		13.79	16.3	35	35	69.32		0.04902					14.42	15.5	35	35
																63.02		0.04456								
							OPT	00	TYL	TZA		12.87	17.5	35	35	76.80		0.05183					14.16	15.9	35	35
																69.82		0.04712								
							OPT	00	TYU	TZA		13.96	16.4	35	35	59.27		0.05212					14.68	15.6	35	35
																53.88		0.04738								
							OPT	00	TYU	TZH		14.29	16.1	35	35	62.89		0.04879					14.98	15.4	35	35
																57.17		0.04435								
							OPT	00	TYV	TZH		14.29	16.1	35	35	62.89		0.04879					14.98	15.4	35	35
																57.17		0.04435								
							OPT	00	TYX	TZA		13.21	16.0	35	35	70.59		0.05209					13.83	14.8	35	35
																64.14		0.04735								
							OPT	00	TYZ	TZA		13.21	16.0	35	35	70.59		0.05209					13.83	14.8	35	35
																64.17		0.04735								

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TJ08 - 402 /

Report Date: 06/05/99
Time: 06:45:04

Attachment to SDS Pg. 3 of 7
of Executive Order # A-9-464

2000
YCRXA0360H31

Chrysler Corporation
Family Tire Usage

MODEL	ENG	TRANS	A C	GVW	MKT TYPE	LVW ETW	TIRE DESCRIPTION USE	YR	COD	MFG	OPT	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R	TARGET (LINE 1 IS 20 DEG COEFFS,LINE 2 IS 50 DEG WHEN NEEDED)	COLD CO ELECTRIC DYNO COEFFICIENTS A	B	C	SET A	B	C	ALVW ETW	COAST DOWN TIME	*DYNO HP	TIRE PRES F	TIRE PRES R
BR6L62	ENL	DGT	4W Y	6400	C	5500	STD	00	TR8	TZA		13.64	17.0	35	35	65.40			0.05154				5500	13.16	15.8	35	35
																59.45			0.04685								
							OPT	00	TXN	TZA		12.88	17.4	35	35	75.74			0.05226					13.46	16.5	35	35
																68.85			0.04751								
							OPT	00	TXW	TZA		13.79	16.3	35	35	69.32			0.04902					13.28	15.0	35	35
																63.02			0.04456								
							OPT	00	TYL	TZA		12.87	17.5	35	35	76.80			0.05183					13.03	15.5	35	35
																69.82			0.04712								
							OPT	00	TYU	TZA		13.96	16.4	35	35	59.27			0.05212					13.51	15.1	35	35
																53.88			0.04738								
							OPT	00	TYU	TZH		14.29	16.1	35	35	62.89			0.04879					13.79	14.9	35	35
																57.17			0.04435								
							OPT	00	TYV	TZH		14.29	16.1	35	35	62.89			0.04879					13.79	14.9	35	35
																57.17			0.04435								
							OPT	00	TYX	TZA		13.21	16.0	35	35	70.59			0.05209					12.73	14.2	35	35
																64.17			0.04735								
							OPT	00	TYZ	TZA		13.21	16.0	35	35	70.59			0.05209					12.73	14.2	35	35
																64.17			0.04735								

LOADED VEHICLE WEIGHT

ADJUSTED LOADED VEHICLE WGT

* - For DYNO HP = 0.00
Ref To FRONTAL AREA

/ 10. - TJ08 - 403 /

Report Date: 06/05/99
Time: 06:45:04

Attachment to SDS Pg. 4 of 7
of Executive Order # A-9-464

2000
YCRXA0360H31

Chrysler Corporation
FAMILY TIRE DESCRIPTION

TIRE DESCRIPTION YR	COD	MFG	OPT	NAME	SIZE	RPM	CONSTRUCTION COD	TREAD MATERIAL	PLY	SW	SIDEWALL MATERIAL	PLY	OVERLAY MATERIAL	PLY	TREAD DEPTH (IN.) X 1/32
00	TRB	TZA		WRANGLER APC	P225/75R16-XL	716	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	12
00	TXN	TZA		WRANGLER ATS (A/T)	LT275/70R17 C	647	SBR	2-Steel/3-Polyester	5	OWL	Polyester	3	None	0	18
00	TXP	TZA		EAGLE RSA (A/S)	P275/60R17	697	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	Nylon	2	11
00	TXW	TZA		WRANGLER RTS (A/T)	P265/75R16	668	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	14
00	TYL	TZA		WRANGLER RT/S (A/T)	LT245/75R16-C	679	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	16
00	TYU	TZA		WRANGLER APC	P245/75R16	689	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	12
00	TYU	TZH		LTX A/S	P245/75R16	691	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	10
00	TYV	TZH		LTX A/S	P245/75R16	691	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	10
00	TYX	TZA		WRANGLER RTS (A/S)	P245/75R16	692	SBR	2-Steel/2-Polyester	4	BSW	Polyester	2	None	0	13
00	TYZ	TZA		WRANGLER RTS (A/S)	P245/75R16	692	SBR	2-Steel/2-Polyester	4	OWL	Polyester	2	None	0	13

Report Date: 06/05/99
Time: 06:45:04

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER

Engine Family: YCRXA0360H31
Evaporative Fam: YCRXE0174G3H

Certificate #:

Model ID	Car Line	California Sales
BE1L31	Ram 1500 Pickup 2WD	YES
BE1L32	Ram 1500 Pickup 2WD	YES
BE1L33	Ram 1500 Pickup 2WD	YES
BR1L61	Ram 1500 Pickup 2WD	YES
BR6L61	Ram 1500 Pickup 4WD	YES

Model Codes
BE 8 L 34

-- 1st digit: 3=Club Cab
2nd digit: 1=139" wb w/2 Doors
2=155" wb w/2 Doors
3=139" wb w/4 Doors
4=155" wb w/4 Doors

----- Price Class
L=Covers all trim levels

------- Model:
1=1500 6=1500 4X4
2=2500 7=2500 4X4
3=3500 8=3500 4X4

---------- Body Code:
Ram Club Cab

Model Codes
BR 2 L 62

-- 1st digit: 6=Regular Cab
2nd digit: 1=119" or 139" wb
2=135" or 155" wb
3=139" wb Chassis Cab
4=163" wb Chassis Cab
5=135" wb Chassis Cab

----- Price Class
L=Covers all trim levels

------- Model:
1=1500 6=1500 4X4
2=2500 7=2500 4X4
3=3500 8=3500 4X4

---------- Body Code:
Ram Pickup
Ram Club Cab
Ram Chassis Cab

Report Date: 06/15/99

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER

Engine Family: YCRXA0360H31
Evaporative Fam: YCRXE0174G4H

Certificate #:

Model ID	Car Line	California Sales
BE1L32	Ram 1500 Pickup 2WD	YES
BR1L62	Ram 1500 Pickup 2WD	YES
BR6L62	Ram 1500 Pickup 4WD	YES

Model Codes
BE 8 L 34

--- 1st digit: 3=Club Cab
2nd digit:
1=139" wb w/2 Doors
2=155" wb w/2 Doors
3=139" wb w/4 Doors
4=155" wb w/4 Doors

------ Price Class
L=Covers all trim levels

-------- Model:
1=1500 6=1500 4X4
2=2500 7=2500 4X4
3=3500 8=3500 4X4

---------- Body Code:
Ram Club Cab

Model Codes
BR 2 L 62

-- 1st digit: 6=Regular Cab
2nd digit:
1=119" or 139" wb
2=135" or 155" wb
3=139" wb Chassis Cab
4=163" wb Chassis Cab
5=135" wb Chassis Cab

----- Price Class
L=Covers all trim levels
C=Chassis Cab

------- Model:
1=1500 6=1500 4X4
2=2500 7=2500 4X4
3=3500 8=3500 4X4

---------- Body Code:
Ram Pickup
Ram Club Cab
Ram Chassis Cab

Report Date: 06/15/99