State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-259-79
Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YSKXT2.49LHA Displacement: 2.5 Liters (152 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter
Dual Warm Up Three Way Catalytic Converters
Dual Heated Oxygen Sensors
Heated Oxygen Sensor
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
0-3750	50,000	0.075	3.4	0.2	0.015	10.0
	100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for NMOG reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	CO	NOx	HCHO	CO (20°F)
0-3750	50,000	0.055	1.9	0.2	0.001	4.9
	100,000	0.069	2.7	0.2	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 1st day of July 1999.

R. B. Summerfield, Chief
Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: SUZUKI MOTOR CORP Exh Eng Fam: YSKXT2.49LHA EVAP Fam: YSKXE00892JA
All Engine Codes in Eng Fam: CA_49S_50S__X__ ORVR: YES_____NO__X__
Exh Std: Tier 0 ___ Tier 1_TLEV _____ LEV_X_ULEV ____ZEV____; US EPA____NLEV (All States)____
EVAP Std :50K __ Useful Life with R/L__X__ In Use Exh Std: FULL In Use__X__ Alt In Use_____
Veh Class(es): PC___LDT1_X_LDT2 __ MDV1 __ MDV2____ MDV3 ____ MDV4 ____MDV5 ___
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5)
Fuel Type (s): Dedicated__X__Flex-Fuel _____ Dual-Fuel _____ Bi-Fuel __ Gasoline__X__Diesel _____
CNG_____ LNG _____ LPG _____ M85 ____ Other (specify) _____
Emiss Test Fuel (s): Indo ___ Ph2__X__CNG ____ LPG _____ M85_____ Other (specify)_____
Diesel: 13CCR 2282 _____ 40CFR 86.113-90 ____ 40CFR 86.113-94 _____
Service Accum: Std AMA _____ Mod AMA _____ Mfr ADP__X__Other (specify)_____
EVAP Emission Test Procedures: California_____Federal__X__
NMOG Test Procedure: N/A _____ Std __X__ Equiv _____ R/L Test Proc: SHED _____ Pt Source __X__
Hybrid: Type A _____ B _____ C _____, APU Cycle (e.g. Otto, Diesel, Turbine) _____
Engine configuration:__V6__Displacement: 2.5 Liters or 152 cubic inches
Valves per Cylinder: __4__Rated HP__155__@__6,500__RPM
Engine: Front __X__ Mid_____Rear _____ Drive: FWD _____RWD__X__4WD-FT_____4WD-PT__X__
Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR
(per SAE J1930 SEP95)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (re: p.21.00)	Trans Type	ETW	RLHP	Ignition Part No. (ECM/PCM)	EGR System Part No.	Catalytic Converter Part No.
BTLMM (50ST)	Grand VITARA	M5	3500	14.0	33920-67D42	18111-77E00	14250-65D20 (Under) 14110-67D00 (Ex-R) 14110-67D10 (Ex-L)
BTLMB (50ST)	Grand VITARA	A4	3500	14.0	33920-67D52		

Date Issued: April 28, 1999
Revised:

Application Processed by: _____ Date _____ Reviewed by: _____ Date: _____