California Environ	mental Protection Agency OURCES BOARD	FORD MOTOR COMPANY	EXECUTIVE ORDER A-010-1103 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

Full

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

*		•	*					*						
*		*	*											
*		*	*		*									
1		1	3.0		Ford Escape 2WD									
EVA No.		ECS No.	ENGIN SIZE (L		VEHICLE MAKES & MODELS			ECT TO SFTP E <u>UNDERLINED</u>		REVIATIONS:				
4		*		4		*			dia	diagnostic prefix 2=parallel (2) suffix=series				
3		*		3	3 *					TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board				
2		*				*		ĂIF	AIR MFI/SFI= multiport fuel injection/sequential MFI					
1	3FM	IXR011	5BBE	1	2TWC, TWC, 2	2HO2S(2)	, EGR, SFI, C	AF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed					
No.		AMILY (EVAF)									cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S			
200	3	3FM)	(T03.01F	7	LDT: 0-3,750 pounds LV	W		LEV		100K / 100K	Gasoline (Indolene)			
MOD YEA		TEST	r groui		VEHICLE TYPE C=passenger car; LDT=light-dut IDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	loaded	CATEGOR) vehicle; T	EMISSION STAND (LEV=low emini- LEV= transitional LEV LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF= 1.00 AVERAGE [g/mi] CH4 RAF = *			NMOG or															
CER	T S	STD	NMOG NMHC		IHC	NMHC STD [g/mi]	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
0.05	3 0	0.062	CERT		RT		CC) [g/mi]	N	Ox [g/m	i]	НСНО	[mg/m	i]	PM [g/	g/mi]	Hwy NO)x [g/mi]	
0.03			[g/mi]	g/mi] [g/mi]		[9,]	CERT	STD	CER	T S	STD	CERT	ST	DC	ERT	STD	CERT	STD	
	Sec.	@ 50K	0.030		*	0.075	0.3	3.4	0.05	5	0.2 0.5		15		* *		0.03	0.3	
		@ UL	0.040		*	0.090	0.4	4.2	0.1		0.3	1	18 *		*	*	0.1	0.4	
	@ 50°	'F & 4K	*		*	*	*	*	*		*	*			*	*	*	*	
	@ 20°F &		LEV) or 50K (Tier 1, TLEV) (C				NMHC+NOx [g/mi] C (composite) (co				NMHC+NOx [g/mi] [US06]				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
						CERT	STD	CERT	STD	CER	TS	STD C	ERT	STD	CERT	STD	CERT	STD	
CERT	1.8		124	SF	TP 1	*	*	*	*	0.08		.14	4.1	8.0	0.07	0.20	0.3	2.7	
STD	10.0	14/1 14/1		SF	TP 2	*	*	*	*	*		*	•	*	*	*	*	*	
	E	VAPOR	ATIVE F	AMILY 1		EVAPORATIVE FAMILY 2					EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			LY 4	
@ UL	3-D	2-[) F	<u>81 0</u>	RVR	3-D	2-D	RL	ORVR	3-D	2.	D F	RF (ORVR	3-D	2-D	RL	ORVR	
CERT	1.0	0.9	ə 0.	01 C	0.10	*	*	*	*	*		•	*	*	*	*	*	*	
STD	2.0	2.5	5 0.	05 0).20	*	*	*	*	*			*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>JO</u>^{*TH*} day of June 2002.

Allen Igons, Chief Mobile Source Operations Division