| California Environmental Protection Agency AIR RESOURCES BOARD | DAIMLERCHRYSLER CORPORATION | EXECUTIVE ORDER A-009-0812 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles |
|---|---|---|

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | TEST GROUP | VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) | EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV) | EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles) | FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) |
|---|---|---|---|---|---|
| 2008 | 8CRXB0144M81 | PC; LDT 0 – 3750 # LVW and < 6000 # GVW | LEV II ULEV | 120K / 150K | Gasoline |

| No. | EVAPORATIVE FAMILY (EVAF) | No. | SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS) | * = not applicable |
|---|---|---|---|---|
| 1 | 8CRXR0112GHA | 1 | TWC, HO2S(2), SFI, OBD (P) | |
| 2 | * | 2 | * | |
| 3 | * | 3 | * | |
| 4 | * | 4 | * | |

OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series

| EVAF No. | ECS No. | ENGINE SIZE (L) | VEHICLE MAKES & MODELS | VEHICLES SUBJECT TO SFTP STANDARDS ARE UNDERLINED |
|---|---|---|---|---|
| 1 | 1 | 2.0 | DODGE: (PC) CALIBER; JEEP : (LDT) COMPASS 2WD, PATRIOT 2WD | |
| 1 | 1 | 2.4 | DODGE: (PC) CALIBER, CALIBER AWD; JEEP : (LDT) COMPASS 2WD, PATRIOT 2WD, COMPASS 4WD, PATRIOT 4WD | |
| * | * | * | * | |
| * | * | * | * | |

ABBREVIATIONS:

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| NMOG FLEET AVERAGE [g/mi] CERT PC/LDT1 | NMOG FLEET AVERAGE [g/mi] STD PC/LDT1 | NMOG @ RAF = * CH4 RAF = * NMOG CERT [g/mi] | NMOG @ RAF = * CH4 RAF = * NMHC CERT [g/mi] | NMOG or NMHC STD [g/mi] |
|---|---|---|---|---|
| 0.045 | 0.040 | | | |
| | @ 50K | 0.022 | * | 0.040 |
| | @ UL | 0.022 | * | 0.055 |
| | @ 50°F & 4K | * | * | * |

CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure

| | CO [g/mi] CERT | CO [g/mi] STD | NOx [g/mi] CERT | NOx [g/mi] STD | HCHO [mg/mi] CERT | HCHO [mg/mi] STD | PM [g/mi] CERT | PM [g/mi] STD | Hwy NOx [g/mi] CERT | Hwy NOx [g/mi] STD |
|---|---|---|---|---|---|---|---|---|---|---|
| @ 50K | 0.6 | 1.7 | 0.02 | 0.05 | * | 8 | * | * | 0.003 | 0.07 |
| @ UL | 0.6 | 2.1 | 0.02 | 0.07 | * | 11 | * | 0.01 | 0.003 | 0.09 |
| @ 50°F & 4K | * | * | * | * | * | * | * | * | * | * |

| CO [g/mi] @ 20°F & 50K | | SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV) | NMHC+NOx [g/mi] (composite) CERT | NMHC+NOx [g/mi] (composite) STD | CO [g/mi] (composite) CERT | CO [g/mi] (composite) STD | NMHC+NOx [g/mi] [US06] CERT | NMHC+NOx [g/mi] [US06] STD | CO [g/mi] [US06] CERT | CO [g/mi] [US06] STD | NMHC+NOx [g/mi] [SC03] CERT | NMHC+NOx [g/mi] [SC03] STD | CO [g/mi] [SC03] CERT | CO [g/mi] [SC03] STD |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CERT | 2.8 | SFTP 1 | * | * | * | * | 0.08 | 0.14 | 5.7 | 8.0 | 0.07 | 0.20 | 1.8 | 2.7 |
| STD | 10.0 | SFTP 2 | * | * | * | * | * | * | * | * | * | * | * | * |

| @ UL | EVAPORATIVE FAMILY 1 3-D | EVAPORATIVE FAMILY 1 2-D | EVAPORATIVE FAMILY 1 RL | EVAPORATIVE FAMILY 1 ORVR | EVAPORATIVE FAMILY 2 3-D | EVAPORATIVE FAMILY 2 2-D | EVAPORATIVE FAMILY 2 RL | EVAPORATIVE FAMILY 2 ORVR | EVAPORATIVE FAMILY 3 3-D | EVAPORATIVE FAMILY 3 2-D | EVAPORATIVE FAMILY 3 RL | EVAPORATIVE FAMILY 3 ORVR | EVAPORATIVE FAMILY 4 3-D | EVAPORATIVE FAMILY 4 2-D | EVAPORATIVE FAMILY 4 RL | EVAPORATIVE FAMILY 4 ORVR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CERT | 0.46 | 0.51 | 0.000 | 0.08 | * | * | * | * | * | * | * | * | * | * | * | * |
| STD | 0.50 | 0.65 | 0.05 | 0.20 | * | * | * | * | * | * | * | * | * | * | * | * |

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.
The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 27th day of April 2007.

Annette Hebert, Chief
Mobile Source Operations Division