California Environmental Protection Agency		EXECUTIVE ORDER A-006-1454			
	GENERAL MOTORS CORPORATION	New Passenger Cars, Light-Duty Trucks			
AIR RESOURCES BOARD	•	and Medium-Duty Vehicles			

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TES	T GRO	JP		VEHICLE TYPE PC=passenger car; LDT=light-duty IDV=medium-duty vehicle; LVW=l vehicle weight; GVW=gross VI	STAND (LEV=low a transitional	UST EMISSION ARD CATEGORY mission vehicle; TLE LEV; ULEV=ultra LE EV=super ULEV;		EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE {CNG/LNG=compressed/ liquefled natural gas; LPG=flquefled petroleum gas]					
200	2008 8GMXT03.6151					LDT 3,751-5750 pounds LV (<6,000 pounds GVW and >6 pounds GVW)	"LEV I" LEV			120K / 150K	Gasoline (Tier 2 Unleaded)					
No.		APOR/		14.612	No.	SPECIAL FEAT EMISSION CONTROL		S (ECS)	* = not applicable		DC/TWC=oxidizing/3-way ca WU= warm-up cat. 025/H02	L ADSTWC=adsorbing TWC S=oxygen sensor/heated O25				
1	8GI	MXR01	38813		1	2TWC, 21	HO2S(2),	SFI, OBD (F	11	AFS/HAFS=air-fuel ratio sens	sor/heated AFS EGR=exhaust					
2	8G)	MXR01	97962	B	2		*		11	AIR MFI/SF= multiport fu	secondary air injection/pulsed el injection/sequential MFI					
3	8G)	MXR01	97972	l	3		4			TBI= throttle body injection CAC=charps air cooler_OBI	TC/SC=turbo /super charger ) (F) / (P)=full /partial on-board					
4		*			4	diagnostic prefix 2=parallel (2) suffix=series						(2) suffix=series				
EVA No.		ECS No.	ENG			VEHICLE MAKES & MODELS			CT TO SFTP	AB	BREVIATIONS:					
1		1	3.6	1		Saturn: VUE FWD, VUE AWD										
2		1	3.6			GMC: Acadia AWD, Acadia FWD; Bulck: Enclave AWD, Enclave FWD; Saturn: Outlook AWD, Outlook FWD										
3		1	3,6			GMC:Acadia AWD, Acadia FWD; Bulck; Enclave AWD, Enclave FWD; Saturn: Outlook AWD, Outlook FWD										
*		•	•			•										

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF= ' AVERAGE [g/mi] CH4 RAF = '					NMOG or	CH4=methane NMCG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of http://www.nbc/source.com/charbon and the second and the sec										
CERT	5	TD	NMOG NMHC			mg=millig		mile K=10	000 miles	F=dep	rees F	ahrenheit	SFTP=sup	plemental fed	feral test p	ocedure
0.047	0.0	0.050 CE		CERT			[g/mi]		x [g/mi]			mg/mī	PM (		Hwy NO	
0.047			[g/mi]	[g/mi]		CERT	\$TD	CERT	STI	DCE	RT	STD	CERT	STD	CERT	STD
		§ 50K	0.081	•	0.075	1.1	3.4	0.03	0.0	5	*	15	•	•	0.01	0.07
	1. T	@ UL	0.061	*	0.090	1.1	4.2	0.03	0.0	7	•	18	•	0.01	0.01	0.09
<b>7</b>	@ 50°F	8.4K	•	•	•	•		•	•		*	*	•	•	•	*
	CO [g/mi] s		@ 4K (SULI	EV, ULEV, In 1, TLEV)	NMHC+NC (comp		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] (\$C03]		CO [g/mi] [\$C03]	
50		SFTP 2 •	UL (Tier	I, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RTST	D CER	T STD	CERT	STD
CERT	3.1	nt. 1	SI SI	TP @ 4K		*	•	*	0.10	0.25	1.	.6 10.	5 0.22	0.27	2.8	3.5
STD	12.5	г.ч.т. т	SI SI	TP @ UL	•		•	+	•	+		•	*	+	*	•
@ UL	EV	APORA	TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2 EVAPORA					PORATI	DRATIVE FAMILY 3			EVAPORATIVE FAMILY 4		LY 4
	3-0	2-D	RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL	. ORV	R 3-D	2-D	RL	ORVR
CERT	0.32	0,46	0.00	0,04	0.34	0.50	0.00	0.08	0.34	0.50	0.0	0 0.08	•	•	•	•
STD	0,65	0.85	0.05	0.20	0.90	1.15	0.05	0.20	0,90	1.15	0.0	5 0.20	•	*	•	•

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of February 2007.

Annette Hebert, Chief Mobile Source Operations Division