FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1653-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

rsuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

DCIOVV.	1 TOGGOTOTT VCTTOR	23 Shan be in an material ret	specia the same as thos	C TOT WITHO	or ocitin			
MODE! YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN-	IEDIATE USE LIANCE	FUEL TYPE
2012	CFMXD06.771C	MDV: 10001-14000# GVW	"LEV II" Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Diesel
. 7			ULEV) .	120K *		*	*	
No.		SPECIAL FEATURES	EVAPORATIVE					EMENT (L)
1	OC,SCR-U,PTOX, NO	XS, DFI, EGRC, TC, CAC, OBD(P)	!	-			
*		*	*				6	.7
*		*	*		-			

*("=N/A or full in-use;A/E=exh. / evap. intermediate in-use)

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. mission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High—titude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer. independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.



FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1653-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have eight deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$175 per vehicle for the fourth through eighth deficiencies in the listed test group that is produced and delivered for sale in California. On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that guarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2012 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification. effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-010-1653 dated July 21, 2011.

Executed at El Monte, California on this 26th day of January 2012.

Annette Hebert, Chief

Mobile Source Operations Division

ourener

FORD MOTOR COMPANY

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

					CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; or HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+									
CERT	STD	NMOG	NMHC	NMHC STD		hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg· mi=mile: K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure								ıram
		CERT	CERT	[g/mi]	CO	g/mi]	NOx	[g/mi]	HCHO	[mg/mi]	PM [g/mi]	Hwy NO	x [g/mi]
,		[g/mi]	[g/mi]	[g/iii]	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
	@ 50K	*	*	*	. *	* .	*	*	*	*	*	*	*	*
	@ UL	*	0.056	0.167	0.6	7.3	0.25	0.4	3.9	21.	0.01	0.06	0.03	0.8
	@ 50°F & 4K	*	*	*	*	*	*	*	*	*	*	*	*	*
	ž	SHALL TENS		NMHC+NC)x [a/mi]	CO [q/	/mil	NMHC+N	Ox	CO [a/mi]	NMI	-IC+NOx	CO	a/mil

CO [g/mi] @ 20°F & 50K				Ox [g/mi] oosite)	CO [+NOx [US06]	[US	g/mi] :06]		+NOx [SC03]	[S0]	
			CERT	STD	CERT	STD	CERT	STD	CERT	□□ÿ	CERT	STD	CERT	STD
CERT	*	SFTP @ * miles	*	*	*	*	*	*	*	*	*	*	*	*
STD	*	SFTP @ * miles	*	*	*	. *	*	*	*	*	*	*	*	*

Evaporative Family		al + Hot Soak est) @ UL		al + Hot Soak est) @ UL	Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
*	*	*	* .	*	*	*	*	*	
*	*	*	*	*	*	*	*	*	
*	*	. **	*	*	*	*	*	*	
*	*	*	*	*	*	*	*	*	

* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U/SCR-N= selective catalytic reduction-vrea/ammonia; NH3OC=SCR-U/SCR-N ammonia slip catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor;)02S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; NOXS= NOX sensor; RDQS=reductant quality sensor; EGR=exhaust gas recirculation; CGRC=cooled EGR; AIR=secondary air injection; PAIR=pulsed AIR; SFI/MFI= sequentia/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)(B)=full/partial/both on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol ("15%"gasoline) Fuel;

2012 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or A/E=exi	IEDIATE JSE JANCE full in-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
FORD	F450 PICKUP 4WD DIESEL DRW	*	1	6.7	*	*	*	Partial
FORD	F350 2WD BED DELETE DIESEL DRW	; *	. 1	6.7	*	*	*	Partial
FORD	F350 4WD BED DELETE DIESEL DRW	*	1	6.7	*	*	*	Partial
FORD	F350 2WD BED DELETE DIESEL	*	1	6.7	*	*	*	Partial
FORD	F350 4WD BED DELETE DIESEL	*	1	6.7	*	*	. *	Partial
FORD	F350 PICKUP 2WD DIESEL DRW	*	1	6.7	*	*	*	Partial
FORD	F350 PICKUP 4WD DIESEL DRW	*.	1	6.7	*	*	*	Partial
FORD	F350 PICKUP 2WD DIESEL	*	1	6.7	*	*	*	Partial
FORD	F350 PICKUP 4WD DIESEL	*	1	6.7	*	*	*	Partial