Californ	ia Environme	ntal Protection	Agency
AIR	RESO	URCES	BOARD

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST	r grol	JΡ			assenger car; LDT=light-duty truck; medium-duty vehicle; LVW=loaded				EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
201	13 DADXJ03.03UF					Passenger Car, "LEV II" Ultra Low Emiss DT: GVW< 6000 lbs 0-3750 lbs LVW Vehicle (LEV II ULEV)					120K / 150K Gasoline (Tier 2 Unleaded)				
No.		APORA AILY (E		$W_{\rm H}$	No.	SPECIAL FEAT		S (ECS)	* = not applicable	W	U= warm-up cat. 02S/HO2	t. ADSTWC=adsorbing TWC S=oxygen sensor/heated O2S			
1	DAD	XR014	10B8A	1	1	2TWC, 2HO2S(2)	sor/heated AFS EGR=exhaust secondary air injection/pulsed								
2	DAD	XR015	55D4A		2		*			AIR MFI/SFI= multiport fuel injection/sequential MFI TBI=					
3		•		1	3		•		П	C/SC=turbo /super charger	CAC=charge air cooler OBD				
4		•					*		– (F) / (P)=full /partial on-board diagnostic prefix 2≂parallel (2) suffix=series						
EVAI No.		ECS No	ENGI SIZE			VEHICLE MAKES & MODELS			ECT TO SFTP	ABB					
1		1	3.0			(PC) Audi: S4, S5, S5 Cabriole									
2		1	3.0			(PC) Audi: A8, A8 LWB									
*		*	*			•									
•		*	*												

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *			NMOG or	nitrogen	HCHO=fo	rmaidehyd	e PM≓pa	rticulate m	natter R	AF=reactiv	bon CO=ca ity adjustme =on-board re	nt factor	2/3 D [g/test	=2/3 day				
CERT	PC	STD	NMOG	NMHC	NMHC STD	mg=milli	gram mit	=mile K=	1000 miles	F=deg	grees Fa	hrenheit	SFTP=supp	lemental fee	deral test pr	ocedure		
0.024	0	035	CERT [g/mi]			CERT [g/mi]	[g/mi]		) [g/mi]		Dx [g/mi]			[mg/mi]	PM [g		Hwy NO	
				[g/m]		CERT	STD	CER	T ST	DCI	ERT	STD	CERT	STD	CERT	STD		
		@ 50K	0.020	•	0.040	0.9	1.7	0.03	0.0	5	•	8	•	•	0.02	0.07		
	5 S S S S S	@ UL	0.025	•	0.055	1.6	2.1	0.04	0.0	)7	*	11	•	0.01	0.03	0.09		
	@ 50°	F & 4K	0.034	*	0.080	0.8	1.7	0.02	0.0	05	•	16	•	*	*	*		
@ 20°F& LE		1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)		NMHC+N (comp			[g/mi] posite)		C+NOx [US06]		O [g/mi] [US06]		IC+NOx [SC03]		[g/mi] 203]			
			= @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CER	T ST	CERT	STD	CERT	STD		
CERT	2.0	2	SF	TP @ 4K		*	•	*	0.06	0.14	1.3	8.0	0.05	0.20	0.7	2.7		
STD	10.0		SF	TP @ UL	•	*	*	*	*	*		*	*		*	•		
a	Ē١	VAPOR/	TIVE FAM	ILY 1	EVA	APORATIVE FAMILY 2 EVAPOR				PORATI	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
@ UL  -	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR		
CERT	0.44	0.46	0.002	0.01	0.33	0.42	0.000	0.03	*	*	*	•	*	*	*	*		
STD	0.50	0.65	0.05	0.20	0.50	0.65	0.05	0.20	*	*	*	*	*	*		*		

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding

## California Environmental Protection Agency AIR RESOURCES BOARD

the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of April 2012.

Annette Hebert, Chief
Mobile Source Operations Division